



SOFTWARE SECURITY INFORMATION

FCC ID: W2Z-01000016

IC : 7736B-01000016

Pursuant to:

FCC Part 15E 15.407(I) and KDB 594280 D02 UNII Device Security v01r03 / IC RSS-247 issue 2 article 6.4(4).

The information within this section is to show compliance against the SW Security Requirements laid out within KDB 594280 D02 U-NII Device Security v01r03. The information below describes how to maintain the overall security measures and systems so that only:

1. **Authenticated software is loaded and operating on the device.**
2. **The device is not easily modified to operate with RF parameters outside of the authorization.**

SOFTWARE SECURITY DESCRIPTION		
	Requirement	Answer
General Description	1. Describe how any software/firmware updates for elements that can affect the device's RF parameters will be obtained, downloaded, validated and installed. For software that is accessed through manufacturer's website or device's management system, describe the different levels of security as appropriate.	There is no downloadable software provided by the manufacturer that can modify critical radio transmitter parameters. All critical parameters are programmed in OTP memory at the factory and cannot be modified or overridden by third parties.
	2. Describe the RF parameters that are modified by any software/firmware without any hardware changes. Are these parameters in some way limited such that any other software/firmware changes will not allow the device to exceed the authorized RF characteristics?	There are no rf parameters that can be modified. All rf parameters are programmed in OTP memory at the factory and cannot be modified or overridden by third parties.
	3. Describe in detail the authentication protocols that are in place to ensure that the source of the RF-related software/firmware is valid. Describe in detail how the RF-related software is protected against modification.	The firmware is programmed at the factory and cannot be modified by third parties.
	4. Describe in detail any encryption methods used to support the use of legitimate RF-related software/firmware.	The firmware is programmed at the factory and cannot be modified by third parties therefore no encryption is necessary.
	5. For a device that can be configured as a master and client (with active or passive scanning), explain how the device ensures compliance for each mode? In particular if the device acts as master in some band of operation and client in another; how is compliance ensured in each band of operation?	This device has no master mode.



	Requirement	Answer
Third Party Access Control	1. Explain if any third parties have the capability to operate a U.S./Canada - sold device on any other regulatory domain, frequencies, or in any manner that may allow the device to operate in violation of the device's authorization if activated in the U.S./Canada.	Third parties do not the capability to operate in any manner that is violation of the certification.
	2. Describe, if the device permits third-party software or firmware installation, what mechanisms are provided by the manufacturer to permit integration of such functions while ensuring that the RF parameters of the device cannot be operated outside its authorization for operation in the U.S./Canada. In the description include what controls and/or agreements are in place with providers of third-party functionality to ensure the devices' underlying RF parameters are unchanged and how the manufacturer verifies the functionality.	Third parties do not the capability to operate in any manner that is violation of the certification.
	3. For Certified Transmitter modular devices, describe how the module grantee ensures that host manufacturers fully comply with these software security requirements for U-NII devices. If the module is controlled through driver software loaded in the host, describe how the drivers are controlled and managed such that the modular transmitter RF parameters are not modified outside the grant of authorization.	There are no rf parameters that can be modified. All rf parameters are programmed in OTP memory at the factory and cannot be modified or overridden by third parties. The module is not controlled by driver software on the host and cannot override critical rf parameters stored in module OTP memory.

This section is required for devices which have a "User Interface" (UI) to configure the device in a manner that may impact the operational parameter. The operation description must address if the device supports any of the country code configurations or peer-peer mode communications discussed in KDB 594280 D01 v02r01

SOFTWARE CONFIGURATION DESCRIPTION		
	Requirement	Answer
ER CONFIGURATION GUIDE	1. Describe the user configurations permitted through the UI. If different levels of access are permitted for professional installers, system integrators or end-users, describe the differences.	No UI provided.
	a) What parameters are viewable and configurable by different parties?	No UI provided.
	b) What parameters are accessible or modifiable by the professional installer or system integrators?	None.



(1) Are the parameters in some way limited, so that the installers will not enter parameters that exceed those authorized?	The module micro-code reads the parameters from the module OTP memory. These parameters cannot be modified or overridden by sw drivers.
(2) What controls exist that the user cannot operate the device outside its authorization in the U.S./Canada?	Default setting is set in the factory and no UI is Provided for modification.
c) What parameters are accessible or modifiable by the end-user?	None.
(1) Are the parameters in some way limited, so that the user or installers will not enter parameters that exceed those authorized?	The module micro-code reads the parameters from the module OTP memory. These parameters cannot be modified or overridden by sw drivers.
(2) What controls exist so that the user cannot operate the device outside its authorization in the U.S./Canada?	Default setting is set in the factory and no UI is Provided for modification.
d) Is the country code factory set? Can it be changed in the UI?	There is a UI for professional installers to change the country code.
(1) If it can be changed, what controls exist to ensure that the device can only operate within its authorization in the U.S./Canada?	Since this device works only with clients and passive scanning, there is no problem if the country code on the master side is set appropriately.
e) What are the default parameters when the device is restarted?	Always U.S./Canada compliant
2. Can the radio be configured in bridge or mesh mode? If yes, an attestation may be required. Further information is available in KDB Publication 905462 D02.	No.
3. For a device that can be configured as a master and client (with active or passive scanning), if this is user configurable, describe what controls exist, within the UI, to ensure compliance for each mode. If the device acts as a master in some bands and client in others, how is this configured to ensure compliance?	This device has no master mode.
4. For a device that can be configured as different types of access points, such as point-to-point or point-to-multipoint, and use different types of antennas, describe what controls exist to ensure compliance with applicable limits and the proper antenna is used for each mode of operation. (See Section 15.407(a)).	This device cannot be configured as a different type of access point. It has one type of antenna.

Name and surname of applicant (or authorized representative): Fuji Film Corporation / Kazuaki Inoue

Date: July 3, 2024

Signature: *Kazuaki Inoue*