

RF Exposure Evaluation Report

Product Name : HYBRID INSTANT CAMERA

Model No. : FI019

FCC ID : W2Z-03000009

Applicant : Fuji Film Corporation

Address : 7-3, AKASAKA 9-CHOME, MINATO-KU, Tokyo
107-0052, Japan

Date of Receipt : Mar. 18, 2021

Date of Declaration : Jun. 03, 2021

Report No. : 2130789R-E3082100014

Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Issued Date: Jun. 03, 2021
 Report No.: 2130789R-E3082100014



Product Name	HYBRID INSTANT CAMERA	
Applicant	Fuji Film Corporation	
Address	7-3, AKASAKA 9-CHOME, MINATO-KU, Tokyo 107-0052, Japan	
Manufacturer	ABILITY ENTERPRISE CO., LTD.	
Model No.	FI019	
FCC ID.	W2Z-03000009	
Trade Name	FUJIFILM	
Applicable Standard	KDB 447498 D01 v06	<input type="checkbox"/> Minimum test separation distance \geq 20 cm <input checked="" type="checkbox"/> For low power devices
Test Result	Complied	

Documented By : Jinn Chen
 (Senior Adm. Specialist / Jinn Chen)

Tested By : wenLee
 (Supervisor / Wen Lee)

Approved By : Tim Sung
 (Manager / Tim Sung)

Revision History

Report No.	Version	Description	Issued Date
2130789R-E3082100014	V1.0	Initial issue of report.	Jun. 03, 2021

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	HYBRID INSTANT CAMERA
Trade Name	FUJIFILM
Model No.	FI019
FCC ID.	W2Z-03000009
Frequency Range	2402-2480MHz
Channel Number	V3.0+HS, V2.1+EDR:79 V4.2:40
Type of Modulation	V3.0+HS, V2.1+EDR: GFSK(1Mbps) / π /4DQPSK(2Mbps) / 8DPSK(3Mbps) V4.2: GFSK(1Mbps)
Channel Control	Auto
Antenna Type	Print on PCB Antenna
Antenna Gain	Refer to the table "Antenna List"

1.2. Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	LYNwave	KC36A00	Print on PCB Antenna	2.3dBi for 2.4 GHz

2. RF Exposure Evaluation

2.1. Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

2.2. Measurement Result:

According to KDB Publication 447498 D01, section 4.3.1, per the calculations of item 1 (Power(mW)/separation (mm)*sqrt(f(GHz)≤3.0), SAR is required as shown in the table below where calculated values are greater than 3.0:

Operation frequency = 2450MHz and antenna separation distance = 10mm

Body SAR Test Exclusion Threshold = 10mW

Frequency Band (MHz)	Maximum Peak output power Antenna Gain: 2.3 dBi			SAR Test Exclusion Threshold	Calculated Threshold Value (≤3.0 SAR is not required)
	Conducted (dBm)	EIRP (dBm)	EIRP (mW)	(mW)	
2441	8.67	10.8	12.02	19	1.878

Note1: The SAR/MPE measurement is not necessary.

Note2: The maximum peak output power is refer to report No.: 2130789R-E3032110108 from the DEKRA.