

Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: <u>W2Z-03000015</u>

Item	Items to be covered by Single modular transmitters. Answer from applicant						
1.	The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly.	The module has shielded. Case to cover all the Needed items.					
2.	The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal.	The module has mechanism to control the Part 15 requirements.					
3.	The module must contain power supply regulation on the module	Internal regulator in module chipset					
4.	The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b).	Yes, the module contains PCB antenna with 1.363dBi gain.					
5.	The module must demonstrate compliance in a stand-alone configuration.	The module was tested in a stand-alone configuration via a USB extender.					
6.	The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (see KDB Publication 784748).	The module has fix label displaying FCC ID in the manual and package due to the extremely small dimension of EUT.					
7.	The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee.	This module has user's manual and is compliant with all applicable FCC rules. Detail instructions for maintaining compliance are given in the manual.					
8.	The module must comply with RF exposure requirements.	Yes, this module comply with RF exposure requirements.					



Ite	ms to be covered by Split modular transmitters.	Answer from applicant
1.	The modular transmitter must comply with all requirements of a single modular transmitter except for items (1) & (5) of the above single modular approval requirements.	
2.	Only the radio front end must be shielded. The physical crystal and tuning capacitors may be located external to the shielded radio elements. The interface between the split sections of the modular system must be digital with a minimum signalling amplitude of 150 mV peak-to-peak.	
3.	Control information and other data may be exchanged between the transmitter control elements and radio front end.	
4.	The sections of a split modular transmitter must be tested installed in a host device(s) similar to that which is representative of the platform(s) intended for use.	
5.	Manufacturers must ensure that only transmitter control elements and radio front end components that have been approved together are capable of operating together. The transmitter module must not operate unless it has verified that the installed transmitter control elements and radio front end have been authorized together. Manufacturers may use means including, but not limited to, coding in hardware and electronic signatures in software to meet these requirements, and must describe the methods in their application for equipment authorization.	

Note: A limited modular approval (LMA) may be granted for single or split modular transmitters that comply partially with the requirements above.

Name and surname of applicant (or <u>authorized</u> representative): Takao Ozaki

Date: 05-12-2023 Signature: Takao Ozaki



Revision Record Sheet:

Revision	Section number	Page number	Date	Remark(s)	issued by
5		1	28-12-2022	History sheet added	WJJ

Issued/modified by Function

: Willem Jan Jong

: Team Lead

Revision

: 5

Date

: 28-12-2022

Verified by

Function

: Axel Gase : Quality Manager

Date

: 28-12-2022

Released by

: Axel Gase

Function

: Manager Quality Assurance

Date of release:

: 28-12-2022