



**Modular Approval Request FCC** (KDB 996369 D01 & Part 15.212)

FCC ID: W34UMRR9D98

<i>Items to be covered by <b>Single modular transmitters.</b></i>	<i>Answer from applicant</i>
1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly.	RF circuitry is shielded. (See internal Photo)
2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal.	No data inputs available for radar application Transmission follows predefined schemes, which can be switched by parameter, but not configured
3. The module must contain power supply regulation on the module	Radar unit contains voltage regulator, applicable voltages 8-32V
4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b).	Integrated patch antenna
5. The module must demonstrate compliance in a stand-alone configuration.	FCC Approval of 9D already passed (FCC ID: W34UMRRD98)
6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (see KDB Publication 784748).	Radar unit already has FCC label (See label Photo). <b>Customer to place a label on outside of new system. The description can be found in the integration guide</b>
7. The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee.	See integration guide.
8. The module must comply with RF exposure requirements.	FCC approval of 9D already satisfies that (FCC ID: W34UMRRD98)

<b>Items to be covered by <i>Split modular transmitters</i>.</b>	<b>Answer from applicant</b>
1. The modular transmitter must comply with all requirements of a single modular transmitter except for items (1) & (5) of the above single modular approval requirements.	
2. Only the radio front end must be shielded. The physical crystal and tuning capacitors may be located external to the shielded radio elements. The interface between the split sections of the modular system must be digital with a minimum signalling amplitude of 150 mV peak-to-peak.	
3. Control information and other data may be exchanged between the transmitter control elements and radio front end.	
4. The sections of a split modular transmitter must be tested installed in a host device(s) similar to that which is representative of the platform(s) intended for use.	
5. Manufacturers must ensure that only transmitter control elements and radio front end components that have been approved together are capable of operating together. The transmitter module must not operate unless it has verified that the installed transmitter control elements and radio front end have been authorized together. Manufacturers may use means including, but not limited to, coding in hardware and electronic signatures in software to meet these requirements, and must describe the methods in their application for equipment authorization.	

Note: A limited modular approval (LMA) may be granted for *single* or *split* modular transmitters that comply partially with the requirements above.

**Name and surname of applicant (or authorized representative): Dr.-Ing. Ralph Mende**

**Date: 23.04.2024**

**Signature:**





Revision Record Sheet:

Revision	Section number	Page number	Date	Remark(s)	issued by
5		1	28-12-2022	History sheet added	WJJ

Issued/modified by : Willem Jan Jong  
Function : Team Lead  
Revision : 5  
Date : 28-12-2022

Verified by : Axel Gase  
Function : Quality Manager  
Date : 28-12-2022

Released by : Axel Gase  
Function : Manager Quality Assurance  
Date of release: : 28-12-2022