

SafeWorks, LLC

SafeWorks Pendant

Report No. SPID0004

Report Prepared By



www.nwemc.com
1-888-EMI-CERT

© 2009 Northwest EMC, Inc

EMC Test Report



22975 NW Evergreen Parkway
Suite 400
Hillsboro, Oregon 97124

Certificate of Test
Last Date of Test: April 2, 2009
SafeWorks, LLC
Model: SafeWorks Pendant

Emissions			
Test Description	Specification	Test Method	Pass/Fail
Spurious Radiated Emissions	FCC 15.249:2009	ANSI C63.4:2003	Pass
Field Strength of Fundamental	FCC 15.249:2009	ANSI C63.4:2003	Pass
AC Powerline Conducted Emissions	FCC 15.207:2009	ANSI C63.4:2003	Pass

Modifications made to the product

See the Modifications section of this report

Test Facility

The measurement facility used to collect the data is located at:

Northwest EMC, Inc.
22975 NW Evergreen Parkway, Suite 400
Hillsboro, OR 97124

Phone: (503) 844-4066 Fax: 844-3826

This site has been fully described in a report filed with and accepted by the FCC (Federal Communications Commission) and Industry Canada (Site filing #2834D-1).

Approved By:

Tim O'Shea, Minneapolis Lab Manager



NVLAP Lab Code: 200630-0

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government of the United States of America.

Product compliance is the responsibility of the client, therefore the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. This Report may only be duplicated in its entirety. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test.

Revision Number	Description	Date	Page Number
00	None		

FCC: Accredited by NVLAP for performance of FCC radio, digital, and ISM device testing. Our Open Area Test Sites, certification chambers, and conducted measurement facilities have been fully described in reports filed with the FCC and accepted by the FCC in letters maintained in our files. Northwest EMC has been accredited by ANSI to ISO / IEC Guide 65 as a product certifier. We have been designated by the FCC as a Telecommunications Certification Body (TCB). This allows Northwest EMC to certify transmitters to FCC specifications in accordance with 47 CFR 2.960 and 2.962.



NVLAP: Northwest EMC, Inc. is accredited under the United States Department of Commerce, National Institute of Standards and Technology, and National Voluntary Laboratory Accreditation Program for satisfactory compliance with the requirements of ISO/IEC 17025 for Testing Laboratories. The NVLAP accreditation encompasses Electromagnetic Compatibility Testing in accordance with the European Union EMC Directive 2004/108/EC, and ANSI C63.4. Additionally, Northwest EMC is accredited by NVLAP to perform radio testing in accordance with the European Union R&TTE Directive 1999/5/EEC, the requirements of FCC, and the RSS radio standards for Industry Canada.



NVLAP LAB CODE 200629-0
NVLAP LAB CODE 200630-0
NVLAP LAB CODE 200676-0
NVLAP LAB CODE 200761-0

Industry Canada: Accredited by NVLAP for performance of Industry Canada RSS and ICES testing. Our Open Area Test Sites and certification chambers comply with RSS-Gen, Issue 2 and have been filed with Industry Canada and accepted. Northwest EMC has been accredited by ANSI to ISO / IEC Guide 65 as a product certifier. We have been designated by NIST and recognized by Industry Canada as a Certification Body (CB) per the APEC Mutual Recognition Arrangement (MRA). This allows Northwest EMC to certify transmitters to Industry Canada technical requirements. (Site Filing Numbers - Hillsboro: 2834D-1, 2834D-2, Sultan: 2834C-1, Irvine: 2834B-1, 2834B-2)



CAB: Designated by NIST and validated by the European Commission as a Conformity Assessment Body (CAB) to conduct tests and approve products to the EMC directive and transmitters to the R&TTE directive, as described in the U.S. - EU Mutual Recognition Agreement.



NEMKO: Assessed and accredited by NEMKO (Norwegian testing and certification body) for European emissions and immunity testing. As a result of NEMKO's laboratory assessment, they will accept test results from Northwest EMC, Inc. for product certification (Authorization No. ELA 119).



Australia/New Zealand: The National Association of Testing Authorities (NATA), Australia has been appointed by the ACA as an accreditation body to accredit test laboratories and competent bodies for EMC standards. Accredited test reports or assessments by competent bodies must carry the NATA logo. Test reports made by an overseas laboratory that has been accredited for the relevant standards by an overseas accreditation body that has a Mutual Recognition Agreement (MRA) with NATA are also accepted as technical grounds for product conformity. The report should be endorsed with the respective logo of the accreditation body (NVLAP).



VCCI: Accepted as an Associate Member to the VCCI, Acceptance No. 564. Conducted and radiated measurement facilities have been registered in accordance with Regulations for Voluntary Control Measures, Article 8. (Registration Numbers. - Hillsboro: C-1071, R-1025, C-2687, T-289, and R-2318, Irvine: R-1943, C-2766, and T-298, Sultan: R-871, C-1784, and T-294).



BSMI: Northwest EMC has been designated by NIST and validated by C-Taipei (BSMI) as a CAB to conduct tests as described in the APEC Mutual Recognition Agreement (US0017). License No.SL2-IN-E-1017.



GOST: Northwest EMC, Inc. has been assessed and accredited by the Russian Certification bodies Certinform VNIINMASH, CERTINFO, SAMTES, and Federal CHEC, to perform EMC and Hygienic testing for Information Technology Products. As a result of their laboratory assessment, they will accept test results from Northwest EMC, Inc. for product certification




KCC: Northwest EMC, Inc is a CAB designated by MRA partners and recognized by Korea. (Assigned Lab Numbers: Hillsboro: US0017, Irvine: US0158, Sultan: US0157)



SCOPE

For details on the Scopes of our Accreditations, please visit:
<http://www.nwemc.com/accreditations/>



**California – Orange County Facility
Labs OC01 – OC13**

41 Tesla Ave. Irvine, CA 92618
(888) 364-2378 Fax: (503) 844-3826



**Oregon – Evergreen Facility
Labs EV01 – EV11**

22975 NW Evergreen Pkwy. Suite 400 Hillsboro, OR 97124
(503) 844-4066 Fax: (503) 844-3826



**Washington – Sultan Facility
Labs SU01 – SU07**

14128 339th Ave. SE Sultan, WA 98294
(888) 364-2378

Party Requesting the Test

Company Name:	SafeWorks, LLC
Address:	365 Upland Drive
City, State, Zip:	Tukwila, WA 98188
Test Requested By:	Gavin Brickell
Model:	SafeWorks Pendant
First Date of Test:	February 20, 2009
Last Date of Test:	April 2, 2009
Receipt Date of Samples:	February 2, 2009
Equipment Design Stage:	Preproduction
Equipment Condition:	No Damage

Information Provided by the Party Requesting the Test**Functional Description of the EUT (Equipment Under Test):**

Operator wears a pendant that only transmits. It has no receive capability.

Testing Objective:

Seeking to demonstrate compliance of the pendant under FCC 15.249 for operation in the 915 MHz Band.

EUT Photo

CONFIGURATION 1 SPID0004

EUT				
Description	Manufacturer	Model/Part Number	Serial Number	
SafeWorks Pendant	SafeWorks, LLC	SafeWorks Pendant	None	

Peripherals in test setup boundary				
Description	Manufacturer	Model/Part Number	Serial Number	
Power Adapter	Cincon Electronics Co., LTD.	TR10R075	TR10R075-ASUE-11A13 0731	

Cables					
Cable Type	Shield	Length (m)	Ferrite	Connection 1	Connection 2
Power	PA	1.8m	PA (Yes)	SafeWorks Pendant	Power Adapter
PA = Cable is permanently attached to the device. Shielding and/or presence of ferrite may be unknown.					

CONFIGURATION 2 SPID0004

EUT				
Description	Manufacturer	Model/Part Number	Serial Number	
SafeWorks Pendant	SafeWorks, LLC	Safeworks Pendant	None	

Equipment modifications					
Item	Date	Test	Modification	Note	Disposition of EUT
1	2/20/2009	Field Strength of Fundamental	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
2	2/24/2009	Spurious Radiated Emissions	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
3	4/2/2009	AC Powerline Conducted Emissions	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	Scheduled testing was completed.

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

MODES OF OPERATION

Tx

MODE USED FOR FINAL DATA

Tx

POWER SETTINGS INVESTIGATED

Battery

120VAC/60Hz

POWER SETTINGS USED FOR FINAL DATA

Battery

120VAC/60Hz

FREQUENCY RANGE INVESTIGATED

Start Frequency 902MHz Stop Frequency 928MHz

SAMPLE CALCULATIONS

Radiated Emissions: Field Strength = Measured Level + Antenna Factor + Cable Factor - Amplifier Gain + Distance Adjustment Factor + External Attenuation

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Spectrum Analyzer	Agilent	E44440A	AFA	11/14/2008	12
EV01 Cables		Bilog Cables	EVA	5/19/2008	13
Antenna, Biconilog	EMCO	3141	AXE	1/15/2008	24

MEASUREMENT BANDWIDTHS

	Frequency Range	Peak Data	Quasi-Peak Data	Average Data
	(MHz)	(kHz)	(kHz)	(kHz)
	0.01 - 0.15	1.0	0.2	0.2
	0.15 - 30.0	10.0	9.0	9.0
	30.0 - 1000	100.0	120.0	120.0
	Above 1000	1000.0	N/A	1000.0


Measurements were made using the bandwidths and detectors specified. No video filter was used.


MEASUREMENT UNCERTAINTY



Measurement uncertainty is used to reflect the accuracy of the measured result as compared with its "true" or theoretically correct value. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4. In the case of transient tests our test equipment has been demonstrated by calibration to provide at least a 95% confidence that it complies with the test specification requirements. The measurement uncertainty for any test is available upon request.

TEST DESCRIPTION

The antennas to be used with the EUT were tested. The EUT was transmitting while set at the channel available. While scanning, emissions from the EUT were maximized by rotating the EUT, adjusting the measurement antenna height and polarization, and manipulating the EUT antenna in 3 orthogonal planes (per ANSI C63.4:2003).

Field Strength of Fundamental												PSA 2007.07.21 EMI 2008.7.3	
EMC						Work Order: SPID0004 Date: 02/20/09							
EUT: SafeWorks Pendant			Serial Number: None			Customer: SafeWorks, LLC			Attendees: None			Temperature: 22	
Project: None			Tested by: Jennifer Herrett			Power: 120VAC/60Hz						Humidity: 29%	
TEST SPECIFICATIONS						Test Method						Barometric Pres.: 30.23	
FCC 15.249:2009						ANSI C63.4:2003						Job Site: EV01	
TEST PARAMETERS													
Antenna Height(s) (m)			1 - 4			Test Distance (m)			3				
COMMENTS													
None													
EUT OPERATING MODES													
Tx													
DEVIATIONS FROM TEST STANDARD													
No deviations.													
Run #	5		Configuration #	1		Signature							
Results	Pass		<i>Jennifer Herrett</i>										
													
Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Azimuth (degrees)	Height (meters)	Distance (meters)	External Attenuation (dB)	Polarity	Detector	Distance Adjustment (dB)	Adjusted dBuV/m	Spec. Limit dBuV/m	Compared to Spec. (dB)	Comments
914.973	51.7	33.3	277.0	1.0	0.0	0.0	H-Bilog	QP	3.0	85.0	94.0	-9.0	EUT on side (power port up)
914.974	50.4	33.3	274.0	1.0	0.0	0.0	H-Bilog	QP	3.0	83.7	94.0	-10.3	EUT horizontal (buttons down)
914.926	49.7	33.3	193.0	1.0	0.0	0.0	H-Bilog	QP	3.0	83.0	94.0	-11.0	EUT vertical
914.975	47.8	33.3	147.0	1.0	0.0	0.0	V-Bilog	QP	3.0	81.1	94.0	-12.9	EUT vertical
914.974	45.0	33.3	110.0	1.0	0.0	0.0	V-Bilog	QP	3.0	78.3	94.0	-15.7	EUT horizontal (buttons down)
914.979	42.6	33.3	182.0	1.2	0.0	0.0	V-Bilog	QP	3.0	75.9	94.0	-18.1	EUT on side (power port up)

Field Strength of Fundamental												PSA 2007.07.21	EMI 2008.7.3																																																																																																	
EMC						Work Order: SPID0004																																																																																																								
EUT: SafeWorks Pendant						Date: 02/20/09																																																																																																								
Serial Number: None			Customer: SafeWorks, LLC			Temperature: 22																																																																																																								
Attendees: None			Project: None			Humidity: 29%																																																																																																								
Tested by: Jennifer Herrett			Power: Battery			Barometric Pres.: 30.23																																																																																																								
TEST SPECIFICATIONS						Test Method																																																																																																								
FCC 15.249:2009						ANSI C63.4:2003																																																																																																								
TEST PARAMETERS																																																																																																														
Antenna Height(s) (m)			1 - 4			Test Distance (m)			3																																																																																																					
COMMENTS																																																																																																														
None																																																																																																														
EUT OPERATING MODES																																																																																																														
Tx																																																																																																														
DEVIATIONS FROM TEST STANDARD																																																																																																														
No deviations.																																																																																																														
Run #	6																																																																																																													
Configuration #	2																																																																																																													
Results	Pass																																																																																																													
Signature																																																																																																														
 <p>The graph shows field strength in dBuV/m on the y-axis (0.0 to 120.0) versus frequency in MHz on the x-axis (902.000 to 927.000). A blue line represents the test data, which is constant at approximately 93 dBuV/m. Three green diamond markers are plotted at approximately 916.5 MHz, showing values around 80, 83, and 85 dBuV/m. The graph has a grid background.</p>																																																																																																														
<table border="1"> <thead> <tr> <th>Freq (MHz)</th> <th>Amplitude (dBuV)</th> <th>Factor (dB)</th> <th>Azimuth (degrees)</th> <th>Height (meters)</th> <th>Distance (meters)</th> <th>External Attenuation (dB)</th> <th>Polarity</th> <th>Detector</th> <th>Distance Adjustment (dB)</th> <th>Adjusted dBuV/m</th> <th>Spec. Limit dBuV/m</th> <th>Compared to Spec. (dB)</th> <th>Comments</th> </tr> </thead> <tbody> <tr> <td>914.979</td> <td>52.0</td> <td>33.3</td> <td>116.0</td> <td>1.0</td> <td>3.0</td> <td>0.0</td> <td>H-Bilog</td> <td>QP</td> <td>0.0</td> <td>85.3</td> <td>94.0</td> <td>-8.7</td> <td>EUT horizontal (buttons down)</td> </tr> <tr> <td>914.979</td> <td>52.0</td> <td>33.3</td> <td>168.0</td> <td>1.0</td> <td>3.0</td> <td>0.0</td> <td>H-Bilog</td> <td>QP</td> <td>0.0</td> <td>85.3</td> <td>94.0</td> <td>-8.7</td> <td>EUT on side (power port up)</td> </tr> <tr> <td>914.976</td> <td>50.1</td> <td>33.3</td> <td>91.0</td> <td>1.3</td> <td>3.0</td> <td>0.0</td> <td>V-Bilog</td> <td>QP</td> <td>0.0</td> <td>83.4</td> <td>94.0</td> <td>-10.6</td> <td>EUT vertical</td> </tr> <tr> <td>914.976</td> <td>46.8</td> <td>33.3</td> <td>26.0</td> <td>1.7</td> <td>3.0</td> <td>0.0</td> <td>V-Bilog</td> <td>QP</td> <td>0.0</td> <td>80.1</td> <td>94.0</td> <td>-13.9</td> <td>EUT horizontal (buttons down)</td> </tr> <tr> <td>914.979</td> <td>43.8</td> <td>33.3</td> <td>162.0</td> <td>1.3</td> <td>3.0</td> <td>0.0</td> <td>V-Bilog</td> <td>QP</td> <td>0.0</td> <td>77.1</td> <td>94.0</td> <td>-16.9</td> <td>EUT on side (power port up)</td> </tr> <tr> <td>914.929</td> <td>43.2</td> <td>33.3</td> <td>209.0</td> <td>1.0</td> <td>3.0</td> <td>0.0</td> <td>H-Bilog</td> <td>QP</td> <td>0.0</td> <td>76.5</td> <td>94.0</td> <td>-17.5</td> <td>EUT vertical</td> </tr> </tbody> </table>													Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Azimuth (degrees)	Height (meters)	Distance (meters)	External Attenuation (dB)	Polarity	Detector	Distance Adjustment (dB)	Adjusted dBuV/m	Spec. Limit dBuV/m	Compared to Spec. (dB)	Comments	914.979	52.0	33.3	116.0	1.0	3.0	0.0	H-Bilog	QP	0.0	85.3	94.0	-8.7	EUT horizontal (buttons down)	914.979	52.0	33.3	168.0	1.0	3.0	0.0	H-Bilog	QP	0.0	85.3	94.0	-8.7	EUT on side (power port up)	914.976	50.1	33.3	91.0	1.3	3.0	0.0	V-Bilog	QP	0.0	83.4	94.0	-10.6	EUT vertical	914.976	46.8	33.3	26.0	1.7	3.0	0.0	V-Bilog	QP	0.0	80.1	94.0	-13.9	EUT horizontal (buttons down)	914.979	43.8	33.3	162.0	1.3	3.0	0.0	V-Bilog	QP	0.0	77.1	94.0	-16.9	EUT on side (power port up)	914.929	43.2	33.3	209.0	1.0	3.0	0.0	H-Bilog	QP	0.0	76.5	94.0	-17.5	EUT vertical
Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Azimuth (degrees)	Height (meters)	Distance (meters)	External Attenuation (dB)	Polarity	Detector	Distance Adjustment (dB)	Adjusted dBuV/m	Spec. Limit dBuV/m	Compared to Spec. (dB)	Comments																																																																																																	
914.979	52.0	33.3	116.0	1.0	3.0	0.0	H-Bilog	QP	0.0	85.3	94.0	-8.7	EUT horizontal (buttons down)																																																																																																	
914.979	52.0	33.3	168.0	1.0	3.0	0.0	H-Bilog	QP	0.0	85.3	94.0	-8.7	EUT on side (power port up)																																																																																																	
914.976	50.1	33.3	91.0	1.3	3.0	0.0	V-Bilog	QP	0.0	83.4	94.0	-10.6	EUT vertical																																																																																																	
914.976	46.8	33.3	26.0	1.7	3.0	0.0	V-Bilog	QP	0.0	80.1	94.0	-13.9	EUT horizontal (buttons down)																																																																																																	
914.979	43.8	33.3	162.0	1.3	3.0	0.0	V-Bilog	QP	0.0	77.1	94.0	-16.9	EUT on side (power port up)																																																																																																	
914.929	43.2	33.3	209.0	1.0	3.0	0.0	H-Bilog	QP	0.0	76.5	94.0	-17.5	EUT vertical																																																																																																	











Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

MODES OF OPERATION

Running per operating instructions. AC adapter attached.

Running per operating instructions

MODE USED FOR FINAL DATA

Running per operating instructions. AC adapter attached.

POWER SETTINGS INVESTIGATED

120VAC/60Hz

POWER SETTINGS USED FOR FINAL DATA

120VAC/60Hz

FREQUENCY RANGE INVESTIGATED

Start Frequency 30MHz Stop Frequency 12500MHz

CLOCKS AND OSCILLATORS

915MHz

SAMPLE CALCULATIONS

Radiated Emissions: Field Strength = Measured Level + Antenna Factor + Cable Factor - Amplifier Gain + Distance Adjustment Factor + External Attenuation

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Spectrum Analyzer	Agilent	E4446A	AAY	12/11/2008	13
EV12 Cables		Standard Gain Horn Cables	EVU	5/14/2008	13
Pre-Amplifier	Miteq	AMF-6F-08001200-30-10P	AVH	5/14/2008	13
Antenna, Horn	ETS	3160.07	AHZ	10/14/2008	24
EV12 Cables		Double Ridge Horn Cables	EVT	6/17/2008	13
Pre-Amplifier	Miteq	AMF-3D00100800-32-13P	AVF	6/17/2008	13
Antenna, Horn	ETS	3115	AIB	8/25/2008	24
EV12 Cables		Bilog Cables	EVS	6/17/2008	13
Pre-Amplifier	Miteq	AM-1616-1000	AVM	6/17/2008	13
Antenna, Biconilog	EMCO	3141	AXG	11/4/2008	13

MEASUREMENT BANDWIDTHS

	Frequency Range	Peak Data	Quasi-Peak Data	Average Data
	(MHz)	(kHz)	(kHz)	(kHz)
	0.01 - 0.15	1.0	0.2	0.2
	0.15 - 30.0	10.0	9.0	9.0
	30.0 - 1000	100.0	120.0	120.0
	Above 1000	1000.0	N/A	1000.0

Measurements were made using the bandwidths and detectors specified. No video filter was used.


MEASUREMENT UNCERTAINTY


Measurement uncertainty is used to reflect the accuracy of the measured result as compared with its "true" or theoretically correct value. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4. In the case of transient tests our test equipment has been demonstrated by calibration to provide at least a 95% confidence that it complies with the test specification requirements. The measurement uncertainty for any test is available upon request.

TEST DESCRIPTION

Using the mode of operation and configuration noted within this report, a final radiated emissions test was performed. The frequency range investigated (scanned), is also noted in this report. Radiated emissions measurements were made at the EUT azimuth and antenna height such that the maximum radiated emissions level will be detected. This requires the use of a turntable and an antenna positioner. The preferred method of a continuous azimuth search is utilized for frequency scans of the EUT field strength with both polarities of the measuring antenna. A calibrated, linearly polarized antenna was positioned at the specified distance from the periphery of the EUT.


Tests were made with the antenna positioned in both the horizontal and vertical planes of polarization. The antenna was varied in height above the conducting ground plane to obtain the maximum signal strength. Though specified in the report, the measurement distance shall be 3 meters or 10 meters. At any measurement distance, the antenna height was varied from 1 meter to 4 meters. These height scans apply for both horizontal and vertical polarization, except that for vertical polarization the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the antenna clears the ground surface by at least 25 cm.

SURIOUS RADIATED EMISSIONS DATA SHEET												PSA 2007.07.21	EMI 2008.7.3
EUT: SafeWorks Pendant						Work Order: SPID0004							
Serial Number: None						Date: 02/24/09							
Customer: SafeWorks, LLC						Temperature: 21.3 °C							
Attendees: None						Humidity: 38%							
Project: None						Barometric Pres.: 1013.0mb							
Tested by: Dan Haas			Power: 120VAC/60Hz			Job Site: EV12							
TEST SPECIFICATIONS												Test Method	
FCC 15.249:2009						ANSI C63.4:2003							
TEST PARAMETERS													
Antenna Height(s) (m)			1 - 4			Test Distance (m)			3				
COMMENTS													
See notes for EUT orientation.													
EUT OPERATING MODES													
Running per operating instructions													
DEVIATIONS FROM TEST STANDARD													
No deviations.													
Run #	1											Signature 	
Configuration #	1												
Results	Pass												
													
Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Azimuth (degrees)	Height (meters)	Distance (meters)	External Attenuation (dB)	Polarity	Detector	Distance Adjustment (dB)	Adjusted dBuV/m	Spec. Limit dBuV/m	Compared to Spec. (dB)	Comments
47.139	42.7	-5.1	19.0	1.0	3.0	0.0	V-Bilog	QP	0.0	37.6	40.0	-2.4	AC adapter connected, EUT vertical.
46.578	40.3	-4.9	40.0	1.0	3.0	0.0	V-Bilog	QP	0.0	35.4	40.0	-4.6	AC adapter connected, EUT vertical.
30.026	31.7	2.8	12.0	1.0	3.0	0.0	V-Bilog	QP	0.0	34.5	40.0	-5.5	AC adapter connected, EUT vertical.
47.886	38.4	-5.3	41.0	1.0	3.0	0.0	V-Bilog	QP	0.0	33.1	40.0	-6.9	AC adapter connected, EUT vertical.
78.488	40.8	-7.9	98.0	1.2	3.0	0.0	V-Bilog	QP	0.0	32.9	40.0	-7.1	AC adapter connected, EUT vertical.
77.401	40.8	-8.0	121.0	1.5	3.0	0.0	V-Bilog	QP	0.0	32.8	40.0	-7.2	AC adapter connected, EUT vertical.
79.608	39.9	-7.8	43.0	1.6	3.0	0.0	V-Bilog	QP	0.0	32.1	40.0	-7.9	AC adapter connected, EUT vertical.
879.415	24.7	12.6	285.0	3.2	3.0	0.0	V-Bilog	QP	0.0	37.3	46.0	-8.7	AC adapter connected, EUT vertical.
879.401	24.6	12.6	192.0	1.2	3.0	0.0	H-Bilog	QP	0.0	37.2	46.0	-8.8	AC adapter connected, EUT vertical.
681.244	27.5	9.6	192.0	1.8	3.0	0.0	V-Bilog	QP	0.0	37.1	46.0	-8.9	AC adapter connected, EUT vertical.
681.241	27.4	9.6	315.0	3.4	3.0	0.0	H-Bilog	QP	0.0	37.0	46.0	-9.0	AC adapter connected, EUT vertical.
869.860	24.5	11.9	266.0	1.5	3.0	0.0	H-Bilog	QP	0.0	36.4	46.0	-9.6	AC adapter connected, EUT vertical.
869.853	24.4	11.9	126.0	1.8	3.0	0.0	V-Bilog	QP	0.0	36.3	46.0	-9.7	AC adapter connected, EUT vertical.
940.220	20.9	13.2	184.0	1.2	3.0	0.0	H-Bilog	QP	0.0	34.1	46.0	-11.9	AC adapter connected, EUT vertical.
940.235	20.9	13.2	67.0	1.8	3.0	0.0	V-Bilog	QP	0.0	34.1	46.0	-11.9	AC adapter connected, EUT vertical.
890.823	20.0	12.9	292.0	3.5	3.0	0.0	V-Bilog	QP	0.0	32.9	46.0	-13.1	AC adapter connected, EUT vertical.
890.821	19.2	12.9	346.0	1.7	3.0	0.0	H-Bilog	QP	0.0	32.1	46.0	-13.9	AC adapter connected, EUT vertical.
929.616	18.1	13.2	132.0	2.0	3.0	0.0	H-Bilog	QP	0.0	31.3	46.0	-14.7	AC adapter connected, EUT vertical.
877.078	18.1	12.4	246.0	3.0	3.0	0.0	H-Bilog	QP	0.0	30.5	46.0	-15.5	AC adapter connected, EUT vertical.
877.006	17.6	12.4	271.0	1.7	3.0	0.0	V-Bilog	QP	0.0	30.0	46.0	-16.0	AC adapter connected, EUT vertical.



SPURIOUS RADIATED EMISSIONS DATA SHEET												PSA 2007.07.21 EMI 2008.7.3	
EUT: SafeWorks Pendant						Work Order: SPID0004							
Serial Number: None			Customer: SafeWorks, LLC			Date: 02/24/09							
Attendees: None			Project: None			Temperature: 21.3 °C							
Tested by: Dan Haas			Power: 120VAC/60Hz			Humidity: 38%							
TEST SPECIFICATIONS						Job Site: EV12							
FCC 15.249:2009						Test Method: ANSI C63.4:2003							
TEST PARAMETERS													
Antenna Height(s) (m)			1 - 4			Test Distance (m)			3				
COMMENTS													
See notes for EUT orientation.													
EUT OPERATING MODES													
Running per operating instructions													
DEVIATIONS FROM TEST STANDARD													
No deviations.													
Run #	2												
Configuration #	1												
Results	Pass												
													
Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Azimuth (degrees)	Height (meters)	Distance (meters)	External Attenuation (dB)	Polarity	Detector	Distance Adjustment (dB)	Adjusted dBuV/m	Spec. Limit dBuV/m	Compared to Spec. (dB)	Comments
5489.251	58.7	9.1	161.0	1.8	3.0	0.0	H-Horn	PK	0.0	67.8	74.0	-6.2	AC adapter connected, EUT on its side.
5490.346	57.0	9.1	237.0	1.8	3.0	0.0	H-Horn	PK	0.0	66.1	74.0	-7.9	AC adapter connected, EUT horizontal.
5489.596	55.0	9.1	146.0	1.2	3.0	0.0	H-Horn	PK	0.0	64.1	74.0	-9.9	AC adapter connected, EUT vertical.
7320.063	48.8	14.1	165.0	1.2	3.0	0.0	H-Horn	PK	0.0	62.9	74.0	-11.1	AC adapter connected, EUT vertical.
5489.953	53.6	9.1	120.0	1.4	3.0	0.0	V-Horn	PK	0.0	62.7	74.0	-11.3	AC adapter connected, EUT vertical.
5489.888	53.4	9.1	153.0	1.3	3.0	0.0	V-Horn	PK	0.0	62.5	74.0	-11.5	AC adapter connected, EUT on its side.
7318.933	47.7	14.1	131.0	1.4	3.0	0.0	H-Horn	PK	0.0	61.8	74.0	-12.2	AC adapter connected, EUT on its side.
7319.766	26.7	14.1	165.0	1.2	3.0	0.0	H-Horn	AV	0.0	40.8	54.0	-13.2	AC adapter connected, EUT vertical.
7319.189	26.6	14.1	215.0	1.2	3.0	0.0	V-Horn	AV	0.0	40.7	54.0	-13.3	AC adapter connected, EUT vertical.
7319.958	26.2	14.1	302.0	1.1	3.0	0.0	V-Horn	AV	0.0	40.3	54.0	-13.7	AC adapter connected, EUT horizontal.
7319.848	45.9	14.1	215.0	1.2	3.0	0.0	V-Horn	PK	0.0	60.0	74.0	-14.0	AC adapter connected, EUT vertical.
7320.248	25.9	14.1	109.0	1.7	3.0	0.0	V-Horn	AV	0.0	40.0	54.0	-14.0	AC adapter connected, EUT on its side.
7318.738	25.8	14.1	131.0	1.4	3.0	0.0	H-Horn	AV	0.0	39.9	54.0	-14.1	AC adapter connected, EUT on its side.
7318.893	25.7	14.1	0.0	1.7	3.0	0.0	H-Horn	AV	0.0	39.8	54.0	-14.2	AC adapter connected, EUT horizontal.
7318.868	45.7	14.1	302.0	1.1	3.0	0.0	V-Horn	PK	0.0	59.8	74.0	-14.2	AC adapter connected, EUT horizontal.
5489.823	49.9	9.1	0.0	1.9	3.0	0.0	V-Horn	PK	0.0	59.0	74.0	-15.0	AC adapter connected, EUT horizontal.
5490.891	28.0	9.1	161.0	1.8	3.0	0.0	H-Horn	AV	0.0	37.1	54.0	-16.9	AC adapter connected, EUT on its side.
7318.368	42.0	14.1	109.0	1.7	3.0	0.0	V-Horn	PK	0.0	56.1	74.0	-17.9	AC adapter connected, EUT on its side.
6404.215	24.6	11.1	164.0	1.9	3.0	0.0	V-Horn	AV	0.0	35.7	54.0	-18.3	AC adapter connected, EUT vertical.
6405.761	24.6	11.1	342.0	1.2	3.0	0.0	H-Horn	AV	0.0	35.7	54.0	-18.3	AC adapter connected, EUT vertical.


NORTHWEST PSA 2007.07.21
EMC EMI 2008.7.3
SPURIOUS RADIATED EMISSIONS DATA SHEET

EUT: SafeWorks Pendant	Work Order: SPID0004
Serial Number: None	Date: 02/24/09
Customer: SafeWorks, LLC	Temperature: 21.3 °C
Attendees: None	Humidity: 38%
Project: None	Barometric Pres.: 1013.0mb
Tested by: Dan Haas	Power: 120VAC/60Hz
Job Site: EV12	
TEST SPECIFICATIONS	
Test Method	
FCC 15.249:2009	
ANSI C63.4:2003	
TEST PARAMETERS	
Antenna Height(s) (m)	1 - 4
Test Distance (m)	3
COMMENTS	
See notes for EUT orientation.	
EUT OPERATING MODES	
Running per operating instructions. AC adapter attached.	
DEVIATIONS FROM TEST STANDARD	
No deviations.	
Run #	3
Configuration #	1
Results	Pass
Signature 	



Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Azimuth (degrees)	Height (meters)	Distance (meters)	External Attenuation (dB)	Polarity	Detector	Distance Adjustment (dB)	Adjusted dBuV/m	Spec. Limit dBuV/m	Compared to Spec. (dB)
9149.654	46.3	-11.0	233.0	1.0	3.0	0.0	H-Horn	AV	0.0	35.3	54.0	-18.7
9149.180	61.9	-11.0	118.0	1.1	3.0	0.0	H-Horn	PK	0.0	50.9	74.0	-23.1
9149.305	61.7	-11.0	45.0	1.3	3.0	0.0	V-Horn	PK	0.0	50.7	74.0	-23.3
9149.151	41.6	-11.0	89.0	1.3	3.0	0.0	V-Horn	AV	0.0	30.6	54.0	-23.4
9149.405	60.8	-11.0	211.0	1.0	3.0	0.0	V-Horn	PK	0.0	49.8	74.0	-24.2
9150.260	60.8	-11.0	302.0	1.0	3.0	0.0	H-Horn	PK	0.0	49.8	74.0	-24.2
10980.090	40.9	-11.5	312.0	1.0	3.0	0.0	V-Horn	AV	0.0	29.4	54.0	-24.6
10979.090	60.9	-11.5	162.0	1.3	3.0	0.0	V-Horn	PK	0.0	49.4	74.0	-24.6
10978.140	60.8	-11.5	152.0	1.0	3.0	0.0	H-Horn	PK	0.0	49.3	74.0	-24.7
9149.541	39.8	-11.0	118.0	1.1	3.0	0.0	H-Horn	AV	0.0	28.8	54.0	-25.2
10979.800	39.0	-11.5	214.0	1.0	3.0	0.0	V-Horn	AV	0.0	27.5	54.0	-26.5
9149.833	37.5	-11.0	45.0	1.3	3.0	0.0	V-Horn	AV	0.0	26.5	54.0	-27.5
9148.659	37.2	-11.0	302.0	1.0	3.0	0.0	H-Horn	AV	0.0	26.2	54.0	-27.8
9149.531	37.2	-11.0	211.0	1.0	3.0	0.0	V-Horn	AV	0.0	26.2	54.0	-27.8
10979.330	37.3	-11.5	152.0	1.0	3.0	0.0	H-Horn	AV	0.0	25.8	54.0	-28.2
10979.710	37.3	-11.5	162.0	1.3	3.0	0.0	V-Horn	AV	0.0	25.8	54.0	-28.2
9148.355	56.8	-11.0	233.0	1.0	3.0	0.0	H-Horn	PK	0.0	45.8	74.0	-28.2
10978.180	37.1	-11.5	105.0	1.0	3.0	0.0	H-Horn	AV	0.0	25.6	54.0	-28.4
10979.180	37.0	-11.5	194.0	1.0	3.0	0.0	H-Horn	AV	0.0	25.5	54.0	-28.5
9148.045	55.3	-11.0	89.0	1.3	3.0	0.0	V-Horn	PK	0.0	44.3	74.0	-29.7
10978.300	55.2	-11.5	312.0	1.0	3.0	0.0	V-Horn	PK	0.0	43.7	74.0	-30.3
10978.030	55.0	-11.5	194.0	1.0	3.0	0.0	H-Horn	PK	0.0	43.5	74.0	-30.5
10979.780	54.6	-11.5	214.0	1.0	3.0	0.0	V-Horn	PK	0.0	43.1	74.0	-30.9
10980.590	54.6	-11.5	105.0	1.0	3.0	0.0	H-Horn	PK	0.0	43.1	74.0	-30.9





Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

MODES OF OPERATION

Transmitting

POWER SETTINGS INVESTIGATED

120VAC/60Hz

CONFIGURATIONS INVESTIGATED

SPID0004 - 1

SAMPLE CALCULATIONS

Conducted Emissions: Adjusted Level = Measured Level + Transducer Factor + Cable Attenuation Factor + External Attenuator

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Receiver	Rohde & Schwarz	ESCI	ARH	8/28/2008	24 mo
High Pass Filter	T.T.E.	7766	HFG	2/23/2009	13 mo
Attenuator	Coaxicom	66702 2910-20	ATO	6/30/2008	13 mo
EV07 Cables		Conducted Cables	EVG	5/2/2008	13 mo
LISN	Solar	9252-50-R-24-BNC	LIR	2/4/2009	13 mo

MEASUREMENT BANDWIDTHS

	Frequency Range	Peak Data	Quasi-Peak Data	Average Data
	(MHz)	(kHz)	(kHz)	(kHz)
0.01 - 0.15	1.0	0.2	0.2	
0.15 - 30.0	10.0	9.0	9.0	
30.0 - 1000	100.0	120.0	120.0	
Above 1000	1000.0	N/A	1000.0	

Measurements were made using the bandwidths and detectors specified. No video filter was used.

MEASUREMENT UNCERTAINTY


Measurement uncertainty is used to reflect the accuracy of the measured result as compared with its "true" or theoretically correct value. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4-2. In the case of transient tests our test equipment has been demonstrated by calibration to provide at least a 95% confidence that it complies with the test specification requirements. The measurement uncertainty for any test is available upon request.

TEST DESCRIPTION


Using the mode of operation and configuration noted within this report, conducted emissions tests were performed. The frequency range investigated (scanned), is also noted in this report. Conducted power line measurements are made, unless otherwise specified, over the frequency range from 150 kHz to 30 MHz to determine the line-to-ground radio-noise voltage that is conducted from the EUT power-input terminals that are directly (or indirectly via separate transformer or power supplies) connected to a public power network. Equipment is tested with power cords that are normally used or that have electrical or shielding characteristics that are the same as those cords normally used. Typically those measurements are made using a LISN (Line Impedance Stabilization Network), the 50ohm measuring port is terminated by a 50ohm EMI meter or a 50ohm resistive load. All 50ohm measuring ports of the LISN are terminated by 50ohm.

Work Order:	SPID0004	Date:	04/02/09	<i>Rod Peloquin</i>	
Project:	None	Temperature:	21.7 °C		
Job Site:	EV07	Humidity:	37.3		
Serial Number:	None	Barometric Pres.:	1017.6mb	Tested by:	Rod Peloquin
EUT:	SafeWorks Pendant				
Configuration:	1 - SafeWorks Pendant Basic Configuration - With Power Adapter				
Customer:	SafeWorks, LLC				
Attendees:	None				
EUT Power:	120VAC/60Hz				
Operating Mode:	Transmitting				
Deviations:	No deviations.				
Comments:	None				
Test Specifications		Class B		Test Method	
FCC 15.207:2009				ANSI C63.4:2003	
RSS-Gen:2007				RSS-Gen :2007	
Run #	5	Line:	High Line	Ext. Attenuation:	20
				Results	Pass

Peak Data - vs - Quasi Peak Limit



Peak Data - vs - Average Limit



Peak Data - vs - Quasi Peak Limit


Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Adjusted (dBuV)	Spec. Limit (dBuV)	Compared to Spec. (dB)
0.408	22.8	20.9	43.7	57.7	-13.9
4.088	17.8	20.6	38.4	56.0	-17.6
1.904	17.4	20.6	38.0	56.0	-18.0
4.128	16.9	20.6	37.5	56.0	-18.5
2.176	16.7	20.6	37.3	56.0	-18.7
3.904	16.6	20.6	37.2	56.0	-18.8
4.040	16.5	20.6	37.1	56.0	-18.9
3.992	16.5	20.6	37.1	56.0	-18.9
3.944	16.5	20.6	37.1	56.0	-18.9
0.636	16.3	20.8	37.1	56.0	-18.9
4.224	16.3	20.6	36.9	56.0	-19.1
0.725	16.1	20.8	36.9	56.0	-19.1
4.176	16.2	20.6	36.8	56.0	-19.2
4.264	16.2	20.6	36.8	56.0	-19.2
0.770	16.1	20.7	36.8	56.0	-19.2
1.992	16.2	20.6	36.8	56.0	-19.2
4.312	16.1	20.6	36.7	56.0	-19.3
2.680	16.1	20.6	36.7	56.0	-19.3
2.128	16.1	20.6	36.7	56.0	-19.3
1.808	15.9	20.6	36.5	56.0	-19.5

Peak Data - vs - Average Limit


Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Adjusted (dBuV)	Spec. Limit (dBuV)	Compared to Spec. (dB)
0.408	22.8	20.9	43.7	47.7	-3.9
4.088	17.8	20.6	38.4	46.0	-7.6
1.904	17.4	20.6	38.0	46.0	-8.0
4.128	16.9	20.6	37.5	46.0	-8.5
2.176	16.7	20.6	37.3	46.0	-8.7
3.904	16.6	20.6	37.2	46.0	-8.8
4.040	16.5	20.6	37.1	46.0	-8.9
3.992	16.5	20.6	37.1	46.0	-8.9
3.944	16.5	20.6	37.1	46.0	-8.9
0.636	16.3	20.8	37.1	46.0	-8.9
4.224	16.3	20.6	36.9	46.0	-9.1
0.725	16.1	20.8	36.9	46.0	-9.1
4.176	16.2	20.6	36.8	46.0	-9.2
4.264	16.2	20.6	36.8	46.0	-9.2
0.770	16.1	20.7	36.8	46.0	-9.2
1.992	16.2	20.6	36.8	46.0	-9.2
4.312	16.1	20.6	36.7	46.0	-9.3
2.680	16.1	20.6	36.7	46.0	-9.3
2.128	16.1	20.6	36.7	46.0	-9.3
1.808	15.9	20.6	36.5	46.0	-9.5

Work Order:	SPID0004	Date:	04/02/09	<i>Rod Peloquin</i>
Project:	None	Temperature:	21.7 °C	
Job Site:	EV07	Humidity:	37.3	
Serial Number:	None	Barometric Pres.:	1017.6mb	Tested by: Rod Peloquin
EUT:	SafeWorks Pendant			
Configuration:	1 - SafeWorks Pendant Basic Configuration - With Power Adapter			
Customer:	SafeWorks, LLC			
Attendees:	None			
EUT Power:	120VAC/60Hz			
Operating Mode:	Transmitting			
Deviations:	No deviations.			
Comments:	None			
Test Specifications		Class B		Test Method
FCC 15.207:2009				ANSI C63.4:2003
RSS-Gen:2007				RSS-Gen :2007
Run #	6	Line:	Neutral	Ext. Attenuation:
				20
				Results
				Pass

Peak Data - vs - Quasi Peak Limit



Peak Data - vs - Average Limit



Peak Data - vs - Quasi Peak Limit

Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Adjusted (dBuV)	Spec. Limit (dBuV)	Compared to Spec. (dB)
2.584	16.7	20.6	37.3	56.0	-18.7
4.176	16.4	20.6	37.0	56.0	-19.0
2.176	16.1	20.6	36.7	56.0	-19.3
4.088	16.0	20.6	36.6	56.0	-19.4
2.448	16.0	20.6	36.6	56.0	-19.4
2.496	16.0	20.6	36.6	56.0	-19.4
0.906	15.9	20.6	36.5	56.0	-19.5
0.818	15.8	20.7	36.5	56.0	-19.5
4.136	15.8	20.6	36.4	56.0	-19.6
0.862	15.7	20.7	36.4	56.0	-19.6
0.682	15.5	20.8	36.3	56.0	-19.7
4.040	15.6	20.6	36.2	56.0	-19.8
0.636	15.4	20.8	36.2	56.0	-19.8
2.544	15.6	20.6	36.2	56.0	-19.8
3.944	15.5	20.6	36.1	56.0	-19.9
3.856	15.5	20.6	36.1	56.0	-19.9
2.264	15.5	20.6	36.1	56.0	-19.9
4.448	15.3	20.6	35.9	56.0	-20.1
4.312	15.3	20.6	35.9	56.0	-20.1
2.360	15.3	20.6	35.9	56.0	-20.1

Peak Data - vs - Average Limit

Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Adjusted (dBuV)	Spec. Limit (dBuV)	Compared to Spec. (dB)
2.584	16.7	20.6	37.3	46.0	-8.7
4.176	16.4	20.6	37.0	46.0	-9.0
2.176	16.1	20.6	36.7	46.0	-9.3
4.088	16.0	20.6	36.6	46.0	-9.4
2.448	16.0	20.6	36.6	46.0	-9.4
2.496	16.0	20.6	36.6	46.0	-9.4
0.906	15.9	20.6	36.5	46.0	-9.5
0.818	15.8	20.7	36.5	46.0	-9.5
4.136	15.8	20.6	36.4	46.0	-9.6
0.862	15.7	20.7	36.4	46.0	-9.6
0.682	15.5	20.8	36.3	46.0	-9.7
4.040	15.6	20.6	36.2	46.0	-9.8
0.636	15.4	20.8	36.2	46.0	-9.8
2.544	15.6	20.6	36.2	46.0	-9.8
3.944	15.5	20.6	36.1	46.0	-9.9
3.856	15.5	20.6	36.1	46.0	-9.9
2.264	15.5	20.6	36.1	46.0	-9.9
4.448	15.3	20.6	35.9	46.0	-10.1
4.312	15.3	20.6	35.9	46.0	-10.1
2.360	15.3	20.6	35.9	46.0	-10.1

