

MPE ENGINEERING ANALYSIS

This analysis was performed as part of FCC certification requirements for Coulomb Technologies Inc modules, according to the requirements of FCC Part 1.1310, and OET Bulletin 65 “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields”

Zigbee Module (FCC ID: W38-17-001002-01) and GSM/GPRS Module (FCC ID: W38-17-001004-01) will be built into a Coulomb Host, two Hosts will be mounted back to back that allow Zigbee and GSM/GPRS modules transmit simultaneously.

According to §1.1310 and §2.1091 (Mobile Devices) RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minute) |
|--|-------------------------------|-------------------------------|-------------------------------------|-------------------------|
| Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | f/1500 | 30 |
| 1500-100,000 | / | / | 1.0 | 30 |

Note: f = frequency in MHz, * = Plane-wave equivalent power density

The MPE calculations were performed based on FCC OET-65 with the following formula:

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna



| Radio/FCC ID | Freq. (MHz) | MPE Limit (mW/cm ²) | Output Power (mW) | Duty Cycle | Antenna Gain (dBi) | Antenna Gain (Number) | Power Density at 20 cm | % of MPE at 20 cm | MPE Distance in cm |
|---|--------------|---------------------------------|-------------------|------------|--------------------|-----------------------|------------------------|-------------------|--------------------|
| Zigbee FCC ID: W38-17-001002-01 | 2405 | 1.0 | 72 | 100% | 1.09 | 1.29 | 0.02 | 1.8% | 2.71 |
| GSM/GPRS Modem FCC ID: W38-17-001004-01 | 824 | 0.549 | 1514 | 24% | 3.0 | 2.0 | 0.14 | 26.3% | 10.25 |
| | 1850 | 1.0 | 978 | 24% | 1.4 | 1.38 | 0.06 | 6.4% | 5.08 |
| Zigbee Radio Co-located with GSM/GPRS Radio | | | | | | | | | |
| Zigbee with GSM/GPRS Modem | 2405 824 | | | | | | | 28.1% | 10.6 |
| | 2405 1850 | | | | | | | 8.2% | 5.76 |

The MPE calculations in the spreadsheet above demonstrates that the combination of the Zigbee module (FCC ID: W38-17-001002-01) with the GSM/GPRS modem (FCC ID: W38-17-001004-01) defined meets the MPE requirement stated in FCC Part 1.1310 at the 20 cm distance required for mobile exposure conditions.