



Test Report

Date : 2019-02-27
No. : HM18120052

Page 1 of 33

Applicant: Gatekeeper Systems (HK) Ltd.
36/F, Tower 2, Times Square, 1 Matheson Street, Causeway Bay,
Hong Kong

Manufacturer: Gatekeeper Systems (HK) Ltd.
36/F, Tower 2, Times Square, 1 Matheson Street, Causeway Bay,
Hong Kong

Description of Sample(s): Product: Carttronics CRFII
Brand Name: Gatekeeper Systems
Model Number: CRFII
FCC ID: W3Z-CRFII

Date Sample(s) Received: 2018-12-20

Date Tested: 2019-01-05 to 2019-01-20

Investigation Requested: Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2017 and ANSI C63.10:2013 for FCC Certification.

Conclusion(s): The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Remark(s): ---




CHEUNG Chi, Kenneth
Authorized Signatory

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2019-02-27
No. : HM18120052

Page 2 of 33

CONTENT:

Cover	Page 1 of 33	
Content	Page 2 of 33	
<u>1.0</u>	<u>General Details</u>	
1.1	Equipment Under Test [EUT] Description of EUT operation	Page 3 of 33
1.2	Description of EUT Operation	
1.3	Date of Order	Page 3 of 33
1.4	Submitted Sample	Page 3 of 33
1.5	Test Duration	Page 3 of 33
1.6	Country of Origin	Page 3 of 33
<u>2.0</u>	<u>Technical Details</u>	
2.1	Investigations Requested	Page 4 of 33
2.2	Test Standards and Results Summary	Page 4 of 33
<u>3.0</u>	<u>Test Results</u>	
3.1	Emission	Page 5-27 of 33
<u>Appendix A</u>		
	List of Measurement Equipment	Page 28 of 33
<u>Appendix B</u>		
	Photographs	Page 29-33of 33

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2019-02-27
No. : HM18120052

Page 3 of 33

1.0 General Details

1.1 Equipment Under Test [EUT]

Description of Sample(s)

Product: Carttronics CRFII
Manufacturer: Gatekeeper Systems (HK) Ltd.
36/F, Tower 2, Times Square, 1 Matheson Street, Causeway Bay, Hong Kong
Brand Name: Gatekeeper Systems
Model Number: CRFII
Rating: 100-240V a.c, 0.5A

1.2 Description of EUT Operation

The Equipment Under Test (EUT) is transmitter of Gatekeeper Systems (HK) Ltd., which is 2.4GHz transceiver.

The CRFII Operational mode transmissions are modulated at O-QPSK &FSK. The EUT was tested under test mode which was set in maximum output power and transmit continuously.

1.3 Date of Order

2018-12-20

1.4 Submitted Sample(s):

2 Samples

1.5 Test Duration

2019-01-05 to 2019-01-20

1.6 Country of Origin

China

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2019-02-27
No. : HM18120052

Page 4 of 33

2.0 Technical Details

2.1 Investigations Requested

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2017 Regulations and ANSI C63.10:2013 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION Results Summary					
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result	
				Pass	Fail
Field Strength of Fundamental & Harmonics Emissions	FCC 47CFR 15.249	ANSI C63.10:2013	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>
AC power-line conducted emissions	FCC 47CFR 15.207	ANSI C63.10:2013	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emissions	FCC 47CFR 15.209	ANSI C63.10:2013	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Note: N/A - Not Applicable

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2019-02-27
No. : HM18120052

Page 5 of 33

3.0 Test Results

3.1 Emission

3.1.1 Field Strength of Fundamental & Harmonics Emissions

Test Requirement:	FCC 47CFR 15.249
Test Method:	ANSI C63.10:2013
Test Date:	2019-02-28
Mode of Operation:	1. Tx Mode : CC2430 2. Tx Mode : CC2500

Test Method:

For emission measurements at or below 1 GHz, the sample was placed 0.8m above the ground plane of semi-anechoic Chamber*. For emission measurements above 1 GHz, the sample was placed 1.5m above the ground plane of semi-anechoic Chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. In the frequency range of 9kHz to 30MHz, The center of the loop antenna shall be 1 meter above the ground and rotated loop axis for maximum reading. The emissions worst-case are shown in Test Results of the following pages.

Remark: 3 orthogonal axis apply to hand-held device only.

*: Semi-anechoic chamber located on the G/F of The Hong Kong Standards and Testing Centre Ltd.
FCC Test Firm Registration Number 723883
Designation Number HK0001

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report


Date : 2019-02-27
No. : HM18120052

Page 6 of 33

Spectrum Analyzer Setting:

9KHz – 30MHz (Pk & Av)	RBW: 10kHz VBW: 30kHz Sweep: Auto Span: Fully capture the emissions being measured Trace: Max. hold
30MHz – 1GHz (QP)	RBW: 120kHz VBW: 120kHz Sweep: Auto Span: Fully capture the emissions being measured Trace: Max. hold
Above 1GHz (Pk & Av)	RBW: 3MHz VBW: 3MHz Sweep: Auto Span: Fully capture the emissions being measured Trace: Max. hold

Test Setup:



- Absorbers placed on top of the ground plane are for measurements above 1000MHz only.
- Measurements between 30MHz to 1000MHz made with Bi-log antennas, above 1000MHz horn antennas are used, 9kHz to 30MHz loop antennas are used.
- For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report


Date : 2019-02-27
 No. : HM18120052

Page 7 of 33

Limits for Field Strength of Fundamental & Harmonics Emissions [FCC 47CFR 15.249]:

Fundamental frequency [MHz]	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

Result of TX mode : CC2430 (Lowest Channel), (Above 1GHz): Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2019-02-27
 No. : HM18120052

Page 8 of 33

Field Strength of Fundamental and Harmonics Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2405.0	58.1	27.9	105.7	192,752.5	500,000	Vertical
* 4810.0	12.1	32.1	40.3	103.5	5,000	Vertical
7215.0	3.1	38.6	47.4	234.4	5,000	Vertical
9620.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12025.0					5,000	Vertical
14430.0					5,000	Vertical
16835.0					5,000	Vertical
* 19240.0					5,000	Vertical
21645.0					5,000	Vertical
24050.0					5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2405.0	46.9	27.9	76.9	6,998.4	50,000	Vertical
* 4810.0	2.3	32.1	34.3	51.9	500	Vertical
7215.0	-1.2	38.6	35.3	58.2	500	Vertical
9620.0	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12025.0					500	Vertical
14430.0					500	Vertical
16835.0					500	Vertical
* 19240.0					500	Vertical
21645.0					500	Vertical
24050.0					500	Vertical

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report


Date : 2019-02-27
No. : HM18120052

Page 9 of 33

Result of TX mode: CC2430 (Middle Channel), (Above 1GHz): Pass



Att 0 dB	Det	MA/CA Trd	HORN
INPUT 1	ResBW	1 MHz	
	Meas T	100 ms Unit	dB μ V/m





Test Report

Date : 2019-02-27
 No. : HM18120052

Page 10 of 33

Result of TX mode : CC2430 (Middle Channel), (Above 1GHz): Pass

Field Strength of Fundamental and Harmonics Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2445.0	57.4	27.9	104.9	175,792.4	500,000	Vertical
* 4890.0	9.9	32.1	41.3	116.1	5,000	Vertical
* 7335.0	2.8	38.6	46.2	204.2	5,000	Vertical
9780.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12225.0					5,000	Vertical
14670.0					5,000	Vertical
17115.0					5,000	Vertical
* 19560.0					5,000	Vertical
22005.0					5,000	Vertical
24450.0					5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2440.0	45.1	27.9	73.0	4,466.8	50,000	Vertical
* 4880.0	2.4	32.1	34.5	53.1	500	Vertical
* 7320.0	-1.4	38.6	37.2	72.4	500	Vertical
9760.0	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12200.0					500	Vertical
14640.0					500	Vertical
17080.0					500	Vertical
* 19520.0					500	Vertical
21960.0					500	Vertical
24400.0					500	Vertical

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2019-02-27
No. : HM18120052

Page 11 of 33


Result of TX mode : CC2430 (Highest Channel), (Above 1GHz): Pass



Att 0 dB

INPUT 1

Det	MA/CA Trd	HORN
ResBW	1 MHz	
Meas T	100 ms Unit	dB μ V/m



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2019-02-27
 No. : HM18120052

Page 12 of 33

Result of TX mode: CC2430 (Highest Channel), (Above 1GHz): Pass

Field Strength of Fundamental and Harmonics Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2480.0	57.9	27.9	105.3	184,077.2	500,000	Vertical
* 4960.0	11.1	32.1	46.3	206.5	5,000	Vertical
* 7440.0	2.1	38.6	49.2	288.4	5,000	Vertical
9920.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12400.0					5,000	Vertical
14880.0					5,000	Vertical
17360.0					5,000	Vertical
* 19840.0					5,000	Vertical
22320.0					5,000	Vertical
24800.0					5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2480.0	45.7	27.9	76.8	6,918.3	50,000	Vertical
* 4960.0	3.2	32.1	33.7	48.4	500	Vertical
* 7440.0	-0.8	38.6	37.2	72.4	500	Vertical
9920.0	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12400.0					500	Vertical
14880.0					500	Vertical
17360.0					500	Vertical
* 19840.0					500	Vertical
22320.0					500	Vertical
24800.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2019-02-27
No. : HM18120052

Page 13 of 33


Result of TX mode:CC2500, (Above 1GHz): Pass



Att 0 dB

INPUT 1

Det	MA/CA Trd	HORN
ResBW	1 MHz	
Meas T	100 ms Unit	dB μ V/m



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report


Date : 2019-02-27
 No. : HM18120052

Page 15 of 33

Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	20dB Bandwidth [MHz]
2405.0	2.70

TX mode : CC2430 Lowest Channel






Test Report

Date : 2019-02-27
No. : HM18120052

Page 16 of 33

Frequency Range [MHz]	20dB Bandwidth [MHz]
2445.0	2.53

TX mode : CC2430 Middle Channel



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2019-02-27
No. : HM18120052

Page 17 of 33

Frequency Range [MHz]	20dB Bandwidth [MHz]
2480.0	2.65

TX mode : CC2430 Highest Channel



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2019-02-27
No. : HM18120052

Page 18 of 33

Frequency Range [MHz]	20dB Bandwidth [MHz]
2433.0	0.637

TX mode: CC2500



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report


Date : 2019-02-27
 No. : HM18120052

Page 19 of 33

Band Edge Measurement:

TX mode : CC2430

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2400MHz – Lowest Fundamental	43.7



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
 For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report


Date : 2019-02-27
 No. : HM18120052

Page 20 of 33

Band Edge Measurement:

TX mode: CC2430

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Highest Fundamental – 2483.5MHz	30.7



Result of TX mode: CC2430, Band-edge measurement: PASS

Field Strength of Fundamental and Harmonics Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2399.8	28.6	27.9	56.5	668.3	5,000	Vertical
2483.8	22.9	27.9	50.8	346.7	5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2399.8	3.4	27.9	31.3	36.7	500	Vertical
2483.8	2.8	27.9	30.7	34.3	500	Vertical



Test Report

Date : 2019-02-27
 No. : HM18120052


Page 21 of 33

Band Edge Measurement:

TX mode: CC2500

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2400MHz – Lowest Fundamental	37.3

Band Edge Compliance Measurement



Marker	Frequency	Δ Frequency	Time	Δ Time	Amplitude	Δ Amplitude	Phase	Δ Phase	Distance	Δ Distance	Spectrum	Δ Spectrum
MR	2.4330875 GHz		0.0000 s		0.00 dBm		0.0000 °		0.000 m		77.3 dBuV/m	
M1	2.399525 GHz	-33.5625 MHz	-47.43 zs	-47.43 zs	106.99 dBm	106.99 dBm	0.0000 °	0.0000 °	0.000 m	0.000 m	37.3 dBuV/m	-40.0 dB

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
 For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report

Date : 2019-02-27
 No. : HM18120052


Page 22 of 33

Band Edge Measurement:

TX mode CC2500

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Highest Fundamental – 2483.5MHz	42.3

Band Edge Compliance Measurement



Result of TX mode CC2500, Band-edge measurement: PASS

Field Strength of Fundamental and Harmonics Emissions Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2399.6	9.4	27.9	37.3	73.3	5,000	Vertical
2483.6	7.1	27.9	35.0	56.2	5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions Average Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2399.6	1.3	27.9	29.2	28.8	500	Vertical
2483.6	1.2	27.9	29.1	28.5	500	Vertical



Test Report

Date : 2019-02-27
No. : HM18120052

Page 23 of 33

Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [μ V/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Remarks: Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate in the table below is the worst case rate with respect to the specific test item.
Investigation has been done on all the possible configurations for searching the worst cases.

Result of TX mode: CC2430, (9kHz – 30MHz): PASS

Emissions detected are more than 20 dB below the FCC Limits

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2019-02-27
 No. : HM18120052

Page 24 of 33

Result of TX mode: CC2430, (30MHz – 1GHz): PASS



Field Strength of Fundamental and Harmonics Emissions						
Quasi-Peak Value						
Frequency MHz	Measured Level @3m dBµV/m	Correction Factor dBµV/m	Field Strength dBµV/m	Field Strength µV/m	Limit @3m µV/m	E-Field Polarity
48.3	0.9	7.5	8.4	2.6	100	Vertical
103.8	0.8	8.4	9.2	2.9	150	Vertical
210.7	1.2	10.5	11.7	3.8	150	Vertical
431.6	3.2	18.2	21.4	11.7	200	Vertical
557.8	0.4	21.2	21.6	12.0	200	Vertical
612.3	1.1	21.1	22.2	12.9	200	Horizontal

Remarks: Tx mode was tested in both CC2430 & CC2500, CC2500 was the worst case found in Tx mode.



Test Report

Date : 2019-02-27
No. : HM18120052

Page 25 of 33

Result of Receiver mode, (9kHz – 30MHz): N/A

Result of Receiver mode, (30MHz – 1GHz): N/A

Result of Receiver mode, (1GHz – 18GHz): N/A

Remarks:

No additional spurious emissions found between lowest internal used/generated frequency and 30 MHz
Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty	:	(9kHz – 30MHz):	2.4dB
		(30MHz – 18GHz):	5.0dB
		(18GHz - 26GHz):	5.24dB

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report

Date : 2019-02-27
No. : HM18120052

Page 26 of 33

3.1.2 Conducted Emissions (9kHz to 30MHz)

Test Requirement: FCC Part 15.207
Test Method: ANSI C63.10: 2013
Level: Table 1

Test Date(s): 2019-01-18

Mode of Operation: TX mode: CC2430


Test Method:

The test was performed in accordance with ANSI C63.10: 2013, with the following: an initial measurement was performed in peak and average detection mode on the live line, any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Test Procedure:

The test of EUT was conducted under on mode.

Test Setup:





Test Report

Date : 2019-02-27
 No. : HM18120052


Page 27 of 33

Limit for Conducted Emissions (FCC 47 CFR 15.207):

Frequency Range [MHz]	Quasi-Peak Limits [dB μ V]	Average [dB μ V]
0.15-0.5	79	66
0.5-30.0	73	60

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

Results of TX mode: CC2430- Live and Neutral: PASS



Remark:
 Calculated measurement uncertainty (150kHz – 30MHz): 3.25dB



Test Report

Date : 2019-02-27
No. : HM18120052

Page 28 of 33

Appendix A

LIST OF MEASUREMENT EQUIPMENT

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM215	MULTIDEVICE CONTROLLER	EMCO	2090	00024676	N/A	N/A
EM217	ELECTRIC POWERED TURNTABLE	EMCO	2088	00029144	N/A	N/A
EM218	ANECHOIC CHAMBER	ETS-LINDGREN	FACT-3	--	2018/04/24	2019/04/24
EM356	ANTENNA POSITIONING TOWER	ETS-LINDGREN	2171B	00150346	N/A	N/A
EM355	BICONILOG ANTENNA	ETS-LINDGREN	3143B	00201783	2017/03/15	2019/03/15
EM229	EMI TEST RECEIVER	R&S	ESIB40	100248	2018/06/01	2019/06/01
EM299	DOUBLE-RIDGED WAVEGUIDE HORN ANTENNA	ETS-LINDGREN	3115	00114120	2018/04/27	2020/04/27
EM300	PYRAMIDAL STANDARD GAIN HORN ANTENNA	ETS-LINDGREN	3160-09	00130130	2018/05/13	2020/05/13
EM353	LOOP ANTENNA	ETS_LINDGREN	6502	00206533	2018/03/16	2020/03/16

Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM232	LISN	SCHAFFNER	NNB41	04/100082	2018/03/03	2019/03/03
EM181	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESIB7	100072	2018/06/01	2019/06/01
EM179	IMPULSE LIMITER	ROHDE & SCHWARZ	ESH3-Z2	357- 8810.52/54	2019/01/11	2020/01/11
EM154	SHIELDING ROOM	SIEMENS MATSUSHITA COMPONENTS	N/A	803-740- 057-99A	2017/02/02	2022/02/02
N/A	MEASUREMENT AND EVALUATION SOFTWARE	ROHDE & SCHWARZ	ESIB-K1	V1.20	N/A	N/A

Remarks:

CM Corrective Maintenance
N/A Not Applicable or Not Available
TBD To Be Determined

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report

Date : 2019-02-27
No. : HM18120052

Page 29 of 33

Appendix B

Photographs of EUT


Front View of the product



Rear View of the product



Rear View of the product



Rear View of the product



Test Report

Date : 2019-02-27
No. : HM18120052

Page 30 of 33

Photographs of EUT


Inner View of the Product



Inner View of the Product



Inner View of the Product




Test Report

Date : 2019-02-27
No. : HM18120052

Page 31 of 33

Photographs of EUT

Measurement of Radiated Emission Test Set Up (9kHz to 30MHz)



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.


Test Report

Date : 2019-02-27
No. : HM18120052

Page 32 of 33

Photographs of EUT

Measurement of Radiated Emission Test Set Up (30MHz to 1000MHz)



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report

Date : 2019-02-27
No. : HM18120052

Page 33 of 33

Photographs of EUT

Measurement of Radiated Emission Test Set Up (Above 1000MHz)



***** End of Test Report *****

Conditions of Issuance of Test Reports

1. All samples and goods are accepted by The Hong Kong Standards & Testing Centre Limited (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The Company provides its services on the basis that such terms and conditions constitute express agreement between the Company and any person, firm or company requesting its services (the "Clients").
2. Any report issued by the Company as a result of this application for testing service (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to his customer, supplier or other persons directly concerned. Subject to clause 3, the Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall be at liberty to disclose the testing-related documents and/or files anytime to any third-party accreditation and/or recognition bodies for audit or other related purposes. No liabilities whatsoever shall attach to the Company's act of disclosure.
4. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
5. The results in Report apply only to the sample as received and do not apply to the bulk, unless the sampling has been carried out by the Company and is stated as such in the Report.
6. When a statement of conformity to a specification or standard is provided, the ILAC-G8 Guidance document (and/or IEC Guide 115 in the electrotechnical sector) will be adopted as a decision rule for the determination of conformity unless it is inherent in the requested specification or standard, or otherwise specified in the Report.
7. In the event of the improper use the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
8. Sample submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
9. The Company will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
10. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
11. Subject to the variable length of retention time for test data and report stored hereinto as to otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of this test report for a period of three years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after the retention period. Under no circumstances shall we be liable for damages of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.
12. Issuance records of the Report are available on the internet at www.stc.group. Further enquiry of validity or verification of the Reports should be addressed to the Company.