



## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 1 of 72

**Applicant:** Gatekeeper Systems (HK) Ltd.  
36/F, Tower 2, Times Square, 1 Matheson Street, Causeway Bay,  
Hong Kong

**Manufacturer:** Gatekeeper Systems (HK) Ltd.  
36/F, Tower 2, Times Square, 1 Matheson Street, Causeway Bay,  
Hong Kong

**Description of Sample(s):** Product: 2.4GHz Transmitter Module  
Brand Name: Gatekeeper Systems  
Model Number: D-9000A-SMT  
FCC ID: W3Z-D9000ASMT

**Date Sample(s) Received:** 2019-11-01

**Date Tested:** 2019-11-27 to 2019-12-02

**Investigation Requested:** Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2018 and ANSI C63.10:2013 for FCC Certification.

**Conclusion(s):** The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

**Remark(s):** ---

CHEUNG Chi, Kenneth  
Authorized Signatory



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.  
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 2 of 72

### CONTENT:

Cover	Page 1 of 72	
Content	Page 2 of 72	
<b><u>1.0</u></b>	<b><u>General Details</u></b>	
1.1	Equipment Under Test [EUT] Description of EUT operation	Page 3 of 72
1.2	Description of EUT Operation	
1.3	Date of Order	Page 3 of 72
1.4	Submitted Sample	Page 3 of 72
1.5	Test Duration	Page 3 of 72
1.6	Country of Origin	Page 3 of 72
<b><u>2.0</u></b>	<b><u>Technical Details</u></b>	
2.1	Investigations Requested	Page 4 of 72
2.2	Test Standards and Results Summary	Page 4 of 72
<b><u>3.0</u></b>	<b><u>Test Results</u></b>	
3.1	Emission	Page 5-66 of 72
<b><u>Appendix A</u></b>		
	List of Measurement Equipment	Page 67 of 72
<b><u>Appendix B</u></b>		
	Photographs	Page 68-72of 72



## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 3 of 72

### **1.0 General Details**

#### **1.1 Equipment Under Test [EUT] Description of Sample(s)**

Product: 2.4GHz Transmitter Module  
Manufacturer: Gatekeeper Systems (HK) Ltd.  
36/F, Tower 2, Times Square, 1 Matheson Street, Causeway Bay, Hong Kong  
Brand Name: Gatekeeper Systems  
Model Number: D-9000A-SMT  
Rating: 3.3VVd.c from DC power supply

#### **1.2 Description of EUT Operation**

The Equipment Under Test (EUT) is 2.4GHz RF Transmitter Module of Gatekeeper Systems (HK) Ltd., which is 2.4GHz transceiver.  
The D-9000A-SMT support 2 transmissions modes which are modulated at 500kHz MSK (Minimum Shift Keying) and 1MHz FSK (Frequency Shift Keying). There are two antenna ports supported by the EUT, port 0 is prepared for external antenna, port 1 is embedded with an integral antenna. Port 0 of the EUT was connected to reference antenna provided by the manufacturer during test. The EUT was tested under test mode which was set in maximum output power and transmit continuously.

#### **1.3 Date of Order**

2019-11-01

#### **1.4 Submitted Sample(s):**

1 Sample

#### **1.5 Test Duration**

2019-11-27 to 2019-12-02

#### **1.6 Country of Origin**

China



## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 4 of 72

### 2.0 Technical Details

#### 2.1 Investigations Requested

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2018 Regulations and ANSI C63.10:2013 for FCC Certification.

#### 2.2 Test Standards and Results Summary Tables

EMISSION Results Summary					
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result	
				Pass	Fail
Field Strength of Fundamental & Harmonics Emissions	FCC 47CFR 15.249	ANSI C63.10:2013	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>
AC power-line conducted emissions	FCC 47CFR 15.207	ANSI C63.10:2013	N/A	N/A	
Radiated Emissions	FCC 47CFR 15.209	ANSI C63.10:2013	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Antenna requirement	FCC 47CFR 15.203	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Note: N/A - Not Applicable

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 5 of 72

### **3.0 Test Results**

#### **3.1 Emission**

##### **3.1.1 Field Strength of Fundamental & Harmonics Emissions**

Test Requirement:	FCC 47CFR 15.249
Test Method:	ANSI C63.10:2013
Test Date:	2019-11-27
Mode of Operation:	<ol style="list-style-type: none"><li>1. Tx Mode: Port 0 (External Antenna), MSK mode</li><li>2. Tx Mode: Port 0 (External Antenna), FSK mode</li><li>3. Tx Mode: Port 1 (Integral Antenna), MSK mode</li><li>4. Tx Mode: Port 1 (Integral Antenna), FSK mode</li></ol>

#### **Test Method:**

For emission measurements at or below 1 GHz, the sample was placed 0.8m above the ground plane of semi-anechoic Chamber\*. For emission measurements above 1 GHz, the sample was placed 1.5m above the ground plane of semi-anechoic Chamber\*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. In the frequency range of 9kHz to 30MHz, The center of the loop antenna shall be 1 meter above the ground and rotated loop axis for maximum reading. The emissions worst-case are shown in Test Results of the following pages.

Remark: 3 orthogonal axis apply to hand-held device only.

\*: Semi-anechoic chamber located on the G/F of The Hong Kong Standards and Testing Centre Ltd.  
FCC Test Firm Registration Number 723883  
Designation Number HK0001

## Test Report


Date : 2019-12-23  
No. : HM19110001

Page 6 of 72

### Spectrum Analyzer Setting:

9KHz – 30MHz (Pk & Av)	RBW: 10kHz VBW: 30kHz Sweep: Auto Span: Fully capture the emissions being measured Trace: Max. hold
30MHz – 1GHz (QP)	RBW: 120kHz VBW: 120kHz Sweep: Auto Span: Fully capture the emissions being measured Trace: Max. hold
Above 1GHz (Pk & Av)	RBW: 3MHz VBW: 3MHz Sweep: Auto Span: Fully capture the emissions being measured Trace: Max. hold

### Test Setup:



- Absorbers placed on top of the ground plane are for measurements above 1000MHz only.
- Measurements between 30MHz to 1000MHz made with Bi-log antennas, above 1000MHz horn antennas are used, 9kHz to 30MHz loop antennas are used.
- For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.  
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 7 of 72

**Limits for Field Strength of Fundamental & Harmonics Emissions [FCC 47CFR 15.249]:**

Fundamental frequency [MHz]	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

**Result of Tx Mode: Port 0 (External Antenna), MSK mode (Lowest Channel), (Above 1GHz): Pass**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 8 of 72

**Result of Tx Mode: Port 0 (External Antenna), MSK mode (Lowest Channel):Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2401.3	68.7	27.9	96.6	67,608.3	500,000	Vertical
* 4802.6	19.2	32.1	51.3	367.3	5,000	Vertical
7203.9	2.1	38.6	40.7	108.4	5,000	Vertical
9605.2	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12006.5					5,000	Vertical
14407.8					5,000	Vertical
16809.1					5,000	Vertical
* 19210.4					5,000	Vertical
21611.7					5,000	Vertical
24013.0					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2401.3	57.9	27.9	85.8	19,498.4	50,000	Vertical
* 4802.6	5.4	32.1	37.5	75.0	500	Vertical
7203.9	-1.3	38.6	37.3	73.3	500	Vertical
9605.2	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12006.5					500	Vertical
14407.8					500	Vertical
16809.1					500	Vertical
* 19210.4					500	Vertical
21611.7					500	Vertical
24013.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.





## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 9 of 72

**Result of Tx Mode: Port 0 (External Antenna), MSK mode (Lowest Channel):Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2401.3	56.3	27.9	84.2	16,218.1	500,000	Horizontal
* 4802.6	16.9	32.1	49.0	281.8	5,000	Horizontal
7203.9	2.3	38.6	40.9	110.9	5,000	Horizontal
9605.2	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12006.5					5,000	Horizontal
14407.8					5,000	Horizontal
16809.1					5,000	Horizontal
* 19210.4					5,000	Horizontal
21611.7					5,000	Horizontal
24013.0					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2401.3	46.8	27.9	74.7	5,432.5	50,000	Horizontal
* 4802.6	3.6	32.1	35.7	61.0	500	Horizontal
7203.9	-1.4	38.6	37.2	72.4	500	Horizontal
9605.2	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12006.5					500	Horizontal
14407.8					500	Horizontal
16809.1					500	Horizontal
* 19210.4					500	Horizontal
21611.7					500	Horizontal
24013.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 10 of 72

Result of Tx Mode: Port 0 (External Antenna), MSK mode (Middle Channel), (Above 1GHz): Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 11 of 72

**Result of Tx Mode: Port 0 (External Antenna), MSK mode (Middle Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.2	68.4	27.9	96.3	65,313.1	500,000	Vertical
* 4882.4	18.9	32.1	51.0	354.8	5,000	Vertical
* 7323.6	1.9	38.6	40.5	105.9	5,000	Vertical
9764.8	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12206.1					5,000	Vertical
14647.3					5,000	Vertical
17088.5					5,000	Vertical
* 19529.7					5,000	Vertical
21970.9					5,000	Vertical
24412.1					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.2	58.6	27.9	86.5	21,134.9	50,000	Vertical
* 4882.4	4.6	32.1	36.7	68.4	500	Vertical
* 7323.6	-1.3	38.6	37.3	73.3	500	Vertical
9764.8	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12206.0					500	Vertical
14647.2					500	Vertical
17088.4					500	Vertical
* 19529.6					500	Vertical
21970.8					500	Vertical
24412.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 12 of 72

**Result of Tx Mode: Port 0 (External Antenna), MSK mode (Middle Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.2	56.3	27.9	84.2	16,218.1	500,000	Horizontal
* 4882.4	16.9	32.1	49.0	281.8	5,000	Horizontal
* 7323.6	1.8	38.6	40.4	104.7	5,000	Horizontal
9764.8	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12206.1					5,000	Horizontal
14647.3					5,000	Horizontal
17088.5					5,000	Horizontal
* 19529.7					5,000	Horizontal
21970.9					5,000	Horizontal
24412.1					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.2	46.7	27.9	74.6	5,370.3	50,000	Horizontal
* 4882.4	4.3	32.1	36.4	66.1	500	Horizontal
* 7323.6	-1.6	38.6	37.0	70.8	500	Horizontal
9764.8	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12206.0					500	Horizontal
14647.2					500	Horizontal
17088.4					500	Horizontal
* 19529.6					500	Horizontal
21970.8					500	Horizontal
24412.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 13 of 72

Result of Tx Mode: Port 0 (External Antenna), MSK mode (Highest Channel), (Above 1GHz): Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 14 of 72

**Result of Tx Mode: Port 0 (External Antenna), MSK mode ( (Highest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2481.1	68.7	27.9	96.6	67,608.3	500,000	Vertical
* 4962.2	18.9	32.1	51.0	354.8	5,000	Vertical
* 7443.4	1.7	38.6	40.3	103.5	5,000	Vertical
9924.5	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12405.6					5,000	Vertical
14886.7					5,000	Vertical
17367.8					5,000	Vertical
* 19849.0					5,000	Vertical
22330.1					5,000	Vertical
24811.2					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2481.1	57.6	27.9	85.5	18,836.5	50,000	Vertical
* 4962.2	5.1	32.1	37.2	72.4	500	Vertical
* 7443.3	-1.4	38.6	37.2	72.4	500	Vertical
9924.4	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12405.5					500	Vertical
14886.6					500	Vertical
17367.7					500	Vertical
* 19848.8					500	Vertical
22329.9					500	Vertical
24811.0					500	Vertical

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

**Date : 2019-12-23**  
**No. : HM19110001**

**Page 15 of 72**

**Result of Tx Mode: Port 0 (External Antenna), MSK mode ( (Highest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2481.1	57.9	27.9	85.8	19,498.4	500,000	Horizontal
* 4962.2	17.3	32.1	49.4	295.1	5,000	Horizontal
* 7443.4	2.1	38.6	40.7	108.4	5,000	Horizontal
9924.5	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12405.6					5,000	Horizontal
14886.7					5,000	Horizontal
17367.8					5,000	Horizontal
* 19849.0					5,000	Horizontal
22330.1					5,000	Horizontal
24811.2					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2481.1	45.6	27.9	73.5	4,731.5	50,000	Horizontal
* 4962.2	4.3	32.1	36.4	66.1	500	Horizontal
* 7443.3	-1.9	38.6	36.7	68.4	500	Horizontal
9924.4	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12405.5					500	Horizontal
14886.6					500	Horizontal
17367.7					500	Horizontal
* 19848.8					500	Horizontal
22329.9					500	Horizontal
24811.0					500	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 16 of 72

**Limits for Field Strength of Fundamental & Harmonics Emissions [FCC 47CFR 15.249]:**

Fundamental frequency [MHz]	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

**Result of Tx Mode: Port 0 (External Antenna), FSK mode (Lowest Channel), (Above 1GHz): Pass**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 17 of 72

**Result of Tx Mode: Port 0 (External Antenna), FSK (Lowest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2402.0	68.4	27.9	96.3	65,313.1	500,000	Vertical
* 4804.0	16.4	32.1	48.5	266.1	5,000	Vertical
7206.0	1.8	38.6	40.4	104.7	5,000	Vertical
9608.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12010.0					5,000	Vertical
14412.0					5,000	Vertical
16814.0					5,000	Vertical
* 19216.0					5,000	Vertical
21618.0					5,000	Vertical
24020.0					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2402.0	56.3	27.9	84.2	16,218.1	50,000	Vertical
* 4804.0	3.7	32.1	35.8	61.7	500	Vertical
7206.0	-1.3	38.6	37.3	73.3	500	Vertical
9608.0	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12010.0					500	Vertical
14412.0					500	Vertical
16814.0					500	Vertical
* 19216.0					500	Vertical
21618.0					500	Vertical
24020.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.



## Test Report

**Date : 2019-12-23**  
**No. : HM19110001**

**Page 18 of 72**

**Result of Tx Mode: Port 0 (External Antenna), FSK (Lowest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2402.0	61.4	27.9	89.3	29,174.3	500,000	Horizontal
* 4804.0	16.4	32.1	48.5	266.1	5,000	Horizontal
7206.0	1.8	38.6	40.4	104.7	5,000	Horizontal
9608.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12010.0					5,000	Horizontal
14412.0					5,000	Horizontal
16814.0					5,000	Horizontal
* 19216.0					5,000	Horizontal
21618.0					5,000	Horizontal
24020.0					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2402.0	50.4	27.9	78.3	8,222.4	50,000	Horizontal
* 4804.0	3.2	32.1	35.3	58.2	500	Horizontal
7206.0	-1.6	38.6	37.0	70.8	500	Horizontal
9608.0	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12010.0					500	Horizontal
14412.0					500	Horizontal
16814.0					500	Horizontal
* 19216.0					500	Horizontal
21618.0					500	Horizontal
24020.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 19 of 72

Result of Tx Mode: Port 0 (External Antenna), FSK mode (Middle Channel), (Above 1GHz): Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 20 of 72

**Result of Tx Mode: Port 0 (External Antenna), FSK mode (Middle Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.0	66.9	27.9	94.8	54,954.1	500,000	Vertical
* 4882.0	16.8	32.1	48.9	278.6	5,000	Vertical
* 7323.0	2.3	38.6	40.9	110.9	5,000	Vertical
9764.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12205.0					5,000	Vertical
14646.0					5,000	Vertical
17087.0					5,000	Vertical
* 19528.0					5,000	Vertical
21969.0					5,000	Vertical
24410.0					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.0	54.2	27.9	82.1	12,735.0	50,000	Vertical
* 4882.0	3.7	32.1	35.8	61.7	500	Vertical
* 7323.0	-1.8	38.6	36.8	69.2	500	Vertical
9764.0	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12205.0					500	Vertical
14646.0					500	Vertical
17087.0					500	Vertical
* 19528.0					500	Vertical
21969.0					500	Vertical
24410.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 21 of 72

**Result of Tx Mode: Port 0 (External Antenna), FSK mode (Middle Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.0	59.7	27.9	87.6	23,988.3	500,000	Horizontal
* 4882.0	15.8	32.1	47.9	248.3	5,000	Horizontal
* 7323.0	2.1	38.6	40.7	108.4	5,000	Horizontal
9764.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12205.0					5,000	Horizontal
14646.0					5,000	Horizontal
17087.0					5,000	Horizontal
* 19528.0					5,000	Horizontal
21969.0					5,000	Horizontal
24410.0					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.0	54.2	27.9	82.1	12,735.0	50,000	Horizontal
* 4882.0	3.7	32.1	35.8	61.7	500	Horizontal
* 7323.0	-1.9	38.6	36.7	68.4	500	Horizontal
9764.0	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12205.0					500	Horizontal
14646.0					500	Horizontal
17087.0					500	Horizontal
* 19528.0					500	Horizontal
21969.0					500	Horizontal
24410.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 22 of 72

Result of Tx Mode: Port 0 (External Antenna) FSK (Highest Channel), (Above 1GHz): Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 23 of 72

**Result of Tx Mode: Port 0 (External Antenna), FSK mode ( (Highest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2480.0	68.5	27.9	96.4	66,069.3	500,000	Vertical
* 4960.0	19.4	32.1	51.5	375.8	5,000	Vertical
* 7440.0	2.9	38.6	41.5	118.9	5,000	Vertical
9920.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12400.0					5,000	Vertical
14880.0					5,000	Vertical
17360.0					5,000	Vertical
* 19840.0					5,000	Vertical
22320.0					5,000	Vertical
24800.0					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2480.0	55.7	27.9	83.6	15,135.6	50,000	Vertical
* 4960.0	4.5	32.1	36.6	67.6	500	Vertical
* 7440.0	-1.8	38.6	36.8	69.2	500	Vertical
9920.0	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12400.0					500	Vertical
14880.0					500	Vertical
17360.0					500	Vertical
* 19840.0					500	Vertical
22320.0					500	Vertical
24800.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.



## Test Report

**Date : 2019-12-23**  
**No. : HM19110001**

**Page 24 of 72**

**Result of Tx Mode: Port 0 (External Antenna), FSK mode ( (Highest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2480.0	61.8	27.9	89.7	30,549.2	500,000	Horizontal
* 4960.0	14.3	32.1	46.4	208.9	5,000	Horizontal
* 7440.0	2.3	38.6	40.9	110.9	5,000	Horizontal
9920.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12400.0					5,000	Horizontal
14880.0					5,000	Horizontal
17360.0					5,000	Horizontal
* 19840.0					5,000	Horizontal
22320.0					5,000	Horizontal
24800.0					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2480.0	50.6	27.9	78.5	8,414.0	50,000	Horizontal
* 4960.0	3.9	32.1	36.0	63.1	500	Horizontal
* 7440.0	-1.5	38.6	37.1	71.6	500	Horizontal
9920.0	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12400.0					500	Horizontal
14880.0					500	Horizontal
17360.0					500	Horizontal
* 19840.0					500	Horizontal
22320.0					500	Horizontal
24800.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.






## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 25 of 72

Result of Tx Mode: Port 1 (Integral Antenna), MSK mode (Lowest Channel), (Above 1GHz): Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 26 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), MSK mode (Lowest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2401.3	62.3	27.9	90.2	32,359.4	500,000	Vertical
* 4802.6	12.4	32.1	44.5	167.9	5,000	Vertical
7203.9	1.4	38.6	40.0	100.0	5,000	Vertical
9605.2	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12006.5					5,000	Vertical
14407.8					5,000	Vertical
16809.1					5,000	Vertical
* 19210.4					5,000	Vertical
21611.7					5,000	Vertical
24013.0					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2401.3	50.9	27.9	78.8	8,709.6	50,000	Vertical
* 4802.6	1.3	32.1	33.4	46.8	500	Vertical
7203.9	-1.5	38.6	37.1	71.6	500	Vertical
9605.2	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12006.5					500	Vertical
14407.8					500	Vertical
16809.1					500	Vertical
* 19210.4					500	Vertical
21611.7					500	Vertical
24013.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 27 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), MSK mode (Lowest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2401.3	53.9	27.9	81.8	12,302.7	500,000	Horizontal
* 4802.6	11.3	32.1	43.4	147.9	5,000	Horizontal
7203.9	1.9	38.6	40.5	105.9	5,000	Horizontal
9605.2	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12006.5					5,000	Horizontal
14407.8					5,000	Horizontal
16809.1					5,000	Horizontal
* 19210.4					5,000	Horizontal
21611.7					5,000	Horizontal
24013.0					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2401.3	43.2	27.9	71.1	3,589.2	50,000	Horizontal
* 4802.6	1.5	32.1	33.6	47.9	500	Horizontal
7203.9	-1.8	38.6	36.8	69.2	500	Horizontal
9605.2	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12006.5					500	Horizontal
14407.8					500	Horizontal
16809.1					500	Horizontal
* 19210.4					500	Horizontal
21611.7					500	Horizontal
24013.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 28 of 72

Result of Tx Mode: Port 1 (Integral Antenna), MSK mode (Middle Channel), (Above 1GHz): Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 29 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), MSK mode (Middle Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.2	62.7	27.9	90.6	33,884.4	500,000	Vertical
* 4882.4	13.7	32.1	45.8	195.0	5,000	Vertical
* 7323.6	1.4	38.6	40.0	100.0	5,000	Vertical
9764.8	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12206.1					5,000	Vertical
14647.3					5,000	Vertical
17088.5					5,000	Vertical
* 19529.7					5,000	Vertical
21970.9					5,000	Vertical
24412.1					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.2	51.8	27.9	79.7	9,660.5	50,000	Vertical
* 4882.4	1.3	32.1	33.4	46.8	500	Vertical
* 7323.6	-2.1	38.6	36.5	66.8	500	Vertical
9764.8	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12206.0					500	Vertical
14647.2					500	Vertical
17088.4					500	Vertical
* 19529.6					500	Vertical
21970.8					500	Vertical
24412.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 30 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), MSK mode (Middle Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.2	51.2	27.9	79.1	9,015.7	500,000	Horizontal
* 4882.4	12.4	32.1	44.5	167.9	5,000	Horizontal
* 7323.6	1.6	38.6	40.2	102.3	5,000	Horizontal
9764.8	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12206.1					5,000	Horizontal
14647.3					5,000	Horizontal
17088.5					5,000	Horizontal
* 19529.7					5,000	Horizontal
21970.9					5,000	Horizontal
24412.1					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.2	42.1	27.9	70.0	3,162.3	50,000	Horizontal
* 4882.4	1.6	32.1	33.7	48.4	500	Horizontal
* 7323.6	-1.9	38.6	36.7	68.4	500	Horizontal
9764.8	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12206.0					500	Horizontal
14647.2					500	Horizontal
17088.4					500	Horizontal
* 19529.6					500	Horizontal
21970.8					500	Horizontal
24412.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 31 of 72

Result of Tx Mode: Port 1 (Integral Antenna), MSK mode), (Above 1GHz): Pass

10 dB/div Ref 96.99 dB $\mu$ V/m  
Log



Start 1.00 GHz  
#Res BW 1.0 MHz

#VBW 3.0 MHz

Stop 26.00 GHz  
Sweep 62.53 ms (1001 pts)

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

**Date : 2019-12-23**  
**No. : HM19110001**

**Page 32 of 72**

**Result of Tx Mode: Port 1 (Integral Antenna), MSK mode (Highest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2481.1	62.7	27.9	90.6	33,884.4	500,000	Vertical
* 4962.2	12.4	32.1	44.5	167.9	5,000	Vertical
* 7443.4	1.6	38.6	40.2	102.3	5,000	Vertical
9924.5	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12405.6					5,000	Vertical
14886.7					5,000	Vertical
17367.8					5,000	Vertical
* 19849.0					5,000	Vertical
22330.1					5,000	Vertical
24811.2					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2481.1	51.3	27.9	79.2	9,120.1	50,000	Vertical
* 4962.2	2.4	32.1	34.5	53.1	500	Vertical
* 7443.3	-1.8	38.6	36.8	69.2	500	Vertical
9924.4	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12405.5					500	Vertical
14886.6					500	Vertical
17367.7					500	Vertical
* 19848.8					500	Vertical
22329.9					500	Vertical
24811.0					500	Vertical

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 33 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), MSK mode (Highest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2481.1	53.9	27.9	81.8	12,302.7	500,000	Horizontal
* 4962.2	13.2	32.1	45.3	184.1	5,000	Horizontal
* 7443.4	2.1	38.6	40.7	108.4	5,000	Horizontal
9924.5	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12405.6					5,000	Horizontal
14886.7					5,000	Horizontal
17367.8					5,000	Horizontal
* 19849.0					5,000	Horizontal
22330.1					5,000	Horizontal
24811.2					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2481.1	43.1	27.9	71.0	3,548.1	50,000	Horizontal
* 4962.2	2.8	32.1	34.9	55.6	500	Horizontal
* 7443.3	-1.9	38.6	36.7	68.4	500	Horizontal
9924.4	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12405.5					500	Horizontal
14886.6					500	Horizontal
17367.7					500	Horizontal
* 19848.8					500	Horizontal
22329.9					500	Horizontal
24811.0					500	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 34 of 72

**Limits for Field Strength of Fundamental & Harmonics Emissions [FCC 47CFR 15.249]:**

Fundamental frequency [MHz]	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

**Result of Tx Mode: Port 1 (Integral Antenna), FSK mode (Lowest Channel), (Above 1GHz): Pass**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

**Date : 2019-12-23**  
**No. : HM19110001**

**Page 35 of 72**

**Result of Tx Mode: Port 1 (Integral Antenna), FSK mode (Lowest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2402.0	63.5	27.9	91.4	37,153.5	500,000	Vertical
* 4804.0	12.1	32.1	44.2	162.2	5,000	Vertical
7206.0	1.8	38.6	40.4	104.7	5,000	Vertical
9608.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12010.0					5,000	Vertical
14412.0					5,000	Vertical
16814.0					5,000	Vertical
* 19216.0					5,000	Vertical
21618.0					5,000	Vertical
24020.0					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2402.0	48.6	27.9	76.5	6,683.4	50,000	Vertical
* 4804.0	1.1	32.1	33.2	45.7	500	Vertical
7206.0	-1.7	38.6	36.9	70.0	500	Vertical
9608.0	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12010.0					500	Vertical
14412.0					500	Vertical
16814.0					500	Vertical
* 19216.0					500	Vertical
21618.0					500	Vertical
24020.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 36 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), FSK mode (Lowest Channel), (Above 1GHz): Pass**

Field Strength of Fundamental and Harmonics Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2402.0	53.9	27.9	81.8	12,302.7	500,000	Horizontal
* 4804.0	12.6	32.1	44.7	171.8	5,000	Horizontal
7206.0	2.3	38.6	40.9	110.9	5,000	Horizontal
9608.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12010.0					5,000	Horizontal
14412.0					5,000	Horizontal
16814.0					5,000	Horizontal
* 19216.0					5,000	Horizontal
21618.0					5,000	Horizontal
24020.0					5,000	Horizontal

Field Strength of Fundamental and Harmonics Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2402.0	43.7	27.9	71.6	3,801.9	50,000	Horizontal
* 4804.0	1.3	32.1	33.4	46.8	500	Horizontal
7206.0	-1.9	38.6	36.7	68.4	500	Horizontal
9608.0	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12010.0					500	Horizontal
14412.0					500	Horizontal
16814.0					500	Horizontal
* 19216.0					500	Horizontal
21618.0					500	Horizontal
24020.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 37 of 72

Result of Tx Mode: Port 1 (Integral Antenna), FSK mode (Middle Channel), (Above 1GHz): Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 38 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), FSK mode (Middle Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.0	61.8	27.9	89.7	30,549.2	500,000	Vertical
* 4882.0	12.3	32.1	44.4	166.0	5,000	Vertical
* 7323.0	2.1	38.6	40.7	108.4	5,000	Vertical
9764.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12205.0					5,000	Vertical
14646.0					5,000	Vertical
17087.0					5,000	Vertical
* 19528.0					5,000	Vertical
21969.0					5,000	Vertical
24410.0					5,000	Vertical

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.0	49.8	27.9	77.7	7,673.6	50,000	Vertical
* 4882.0	0.9	32.1	33.0	44.7	500	Vertical
* 7323.0	-1.5	38.6	37.1	71.6	500	Vertical
9764.0	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12205.0					500	Vertical
14646.0					500	Vertical
17087.0					500	Vertical
* 19528.0					500	Vertical
21969.0					500	Vertical
24410.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.



## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 39 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), FSK mode (Middle Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.0	52.1	27.9	80.0	10,000.0	500,000	Horizontal
* 4882.0	12.1	32.1	44.2	162.2	5,000	Horizontal
* 7323.0	2.4	38.6	41.0	112.2	5,000	Horizontal
9764.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12205.0					5,000	Horizontal
14646.0					5,000	Horizontal
17087.0					5,000	Horizontal
* 19528.0					5,000	Horizontal
21969.0					5,000	Horizontal
24410.0					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2441.0	41.9	27.9	69.8	3,090.3	50,000	Horizontal
* 4882.0	1.6	32.1	33.7	48.4	500	Horizontal
* 7323.0	-1.7	38.6	36.9	70.0	500	Horizontal
9764.0	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12205.0					500	Horizontal
14646.0					500	Horizontal
17087.0					500	Horizontal
* 19528.0					500	Horizontal
21969.0					500	Horizontal
24410.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 40 of 72

Result of Tx Mode: Port 1 (Integral Antenna), FSK mode (Highest Channel), (Above 1GHz): Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 41 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), FSK mode ( (Highest Channel), (Above 1GHz): Pass**

Field Strength of Fundamental and Harmonics Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2480.0	62.9	27.9	90.8	34,673.7	500,000	Vertical
* 4960.0	12.9	32.1	45.0	177.8	5,000	Vertical
* 7440.0	1.9	38.6	40.5	105.9	5,000	Vertical
9920.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Vertical
* 12400.0					5,000	Vertical
14880.0					5,000	Vertical
17360.0					5,000	Vertical
* 19840.0					5,000	Vertical
22320.0					5,000	Vertical
24800.0					5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2480.0	50.8	27.9	78.7	8,609.9	50,000	Vertical
* 4960.0	2.4	32.1	34.5	53.1	500	Vertical
* 7440.0	-1.9	38.6	36.7	68.4	500	Vertical
9920.0	Emissions detected are more than 20 dB below the FCC Limits				500	Vertical
* 12400.0					500	Vertical
14880.0					500	Vertical
17360.0					500	Vertical
* 19840.0					500	Vertical
22320.0					500	Vertical
24800.0					500	Vertical

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.



## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 42 of 72

**Result of Tx Mode: Port 1 (Integral Antenna), FSK mode ( (Highest Channel), (Above 1GHz): Pass**

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2480.0	53.5	27.9	81.4	11,749.0	500,000	Horizontal
* 4960.0	12.1	32.1	44.2	162.2	5,000	Horizontal
* 7440.0	2.0	38.6	40.6	107.2	5,000	Horizontal
9920.0	Emissions detected are more than 20 dB below the FCC Limits				5,000	Horizontal
* 12400.0					5,000	Horizontal
14880.0					5,000	Horizontal
17360.0					5,000	Horizontal
* 19840.0					5,000	Horizontal
22320.0					5,000	Horizontal
24800.0					5,000	Horizontal

<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2480.0	42.8	27.9	70.7	3,427.7	50,000	Horizontal
* 4960.0	2.3	32.1	34.4	52.5	500	Horizontal
* 7440.0	-1.9	38.6	36.7	68.4	500	Horizontal
9920.0	Emissions detected are more than 20 dB below the FCC Limits				500	Horizontal
* 12400.0					500	Horizontal
14880.0					500	Horizontal
17360.0					500	Horizontal
* 19840.0					500	Horizontal
22320.0					500	Horizontal
24800.0					500	Horizontal

Remarks: The fundamental frequency was not included in the pre-scan plot, a 2.4G notch filter was added prior to the Receiver, please refer the band-edge plot for the level of fundamental frequency.

**No additional spurious emissions found between lowest internal used/generated frequency and 30 MHz**

\*: Denotes restricted band of operation.

Measurements were made using a peak detector. Any emission less than 1000 MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 and the limits of FCC Rules Part 15 Section 15.209 were applied.

Calculated measurement uncertainty : 9kHz to 30MHz: 2.4dB  
30MHz to 18GHz: 5.0dB  
18GHz – 26.5Hz: 5.24dB

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
 No. : HM19110001


Page 43 of 72

Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	20dB Bandwidth [MHz]
2401.31	0.549

**Tx Mode: Port 0 (External Antenna), MSK mode (Lowest Channel)**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-8.34 dBm</b>
<b>549.11 kHz</b>		
<b>Transmit Freq Error</b>	<b>-64.564 kHz</b>	<b>OBW Power    99.00 %</b>
<b>x dB Bandwidth</b>	<b>548.6 kHz</b>	<b>x dB            -20.00 dB</b>



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 44 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2441.21	0.548

**Tx Mode: Port 0 (External Antenna), MSK mode (Middle Channel)**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-8.21 dBm</b>
<b>549.36 kHz</b>		
<b>Transmit Freq Error</b>	<b>-62.847 kHz</b>	<b>OBW Power</b>
<b>x dB Bandwidth</b>	<b>548.3 kHz</b>	<b>99.00 %</b>
	<b>x dB</b>	<b>-20.00 dB</b>



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 45 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2481.12	0.547

**Tx Mode: Port 0 (External Antenna), MSK mode Highest Channel**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-8.00 dBm</b>
<b>548.56 kHz</b>		
<b>Transmit Freq Error</b>	<b>-104.19 kHz</b>	<b>OBW Power</b>
<b>x dB Bandwidth</b>	<b>547.3 kHz</b>	<b>99.00 %</b>
	<b>x dB</b>	<b>-20.00 dB</b>



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 46 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2402.0	1.032

**Tx Mode: Port 0 (External Antenna), FSK mode (Lowest Channel)**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-6.06 dBm</b>
<b>1.0318 MHz</b>		
<b>Transmit Freq Error</b>	<b>-66.554 kHz</b>	<b>OBW Power</b>
<b>x dB Bandwidth</b>	<b>1.151 MHz</b>	<b>99.00 %</b>
	<b>x dB</b>	<b>-20.00 dB</b>



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 47 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2441.0	1.150

**Tx Mode: Port 0 (External Antenna), FSK mode (Middle Channel)**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>
<b>1.0326 MHz</b>	<b>-4.58 dBm</b>
<b>Transmit Freq Error</b>	<b>OBW Power</b>
-68.096 kHz	99.00 %
<b>x dB Bandwidth</b>	<b>x dB</b>
1.150 MHz	-20.00 dB



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 48 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2480.0	1.145

**Tx Mode: Port 0 (External Antenna), FSK mode Highest Channel**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-5.77 dBm</b>
<b>1.0326 MHz</b>		
<b>Transmit Freq Error</b>	<b>-69.290 kHz</b>	<b>OBW Power</b>
<b>x dB Bandwidth</b>	<b>1.145 MHz</b>	<b>99.00 %</b>
	<b>x dB</b>	<b>-20.00 dB</b>





## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 49 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2401.31	0.547

**Tx Mode: Port 1 (Integral Antenna), MSK mode (Lowest Channel)**

**20dB Bandwidth of Fundamental Emission**



Center 2.401 GHz Span 3 MHz  
 #Res BW 10 kHz #VBW 30 kHz Sweep 37.07 ms

<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-12.3 dBm</b>
<b>549.56 kHz</b>		
<b>Transmit Freq Error</b>	<b>-63.944 kHz</b>	<b>OBW Power</b>
		<b>99.00 %</b>
<b>x dB Bandwidth</b>	<b>547.0 kHz</b>	<b>x dB</b>
		<b>-20.00 dB</b>



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 50 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2441.21	0.548

**Tx Mode: Port 1 (Integral Antenna), MSK mode (Middle Channel)**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-12.2 dBm</b>
<b>551.12 kHz</b>		
<b>Transmit Freq Error</b>	<b>-61.981 kHz</b>	<b>OBW Power</b>
<b>x dB Bandwidth</b>	<b>548.0 kHz</b>	<b>99.00 %</b>
	<b>x dB</b>	<b>-20.00 dB</b>

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 51 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2481.12	0.548

**Tx Mode: Port 1 (Integral Antenna), MSK mode Highest Channel**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-11.9 dBm</b>
<b>549.23 kHz</b>		
<b>Transmit Freq Error</b>	<b>-104.32 kHz</b>	<b>OBW Power</b>
<b>x dB Bandwidth</b>	<b>547.6 kHz</b>	<b>99.00 %</b>
	<b>x dB</b>	<b>-20.00 dB</b>



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 52 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2402.0	1.15

**Tx Mode: Port 1 (Integral Antenna), FSK mode (Lowest Channel)**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-10.1 dBm</b>
<b>1.0324 MHz</b>		
<b>Transmit Freq Error</b>	<b>-66.781 kHz</b>	<b>OBW Power</b>
<b>x dB Bandwidth</b>	<b>1.151 MHz</b>	<b>99.00 %</b>
	<b>x dB</b>	<b>-20.00 dB</b>



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 53 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2441.0	1.150

**Tx Mode: Port 1 (Integral Antenna), FSK mode (Middle Channel)**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-5.97 dBm</b>
<b>1.0323 MHz</b>		
<b>Transmit Freq Error</b>	<b>-67.891 kHz</b>	<b>OBW Power</b>
<b>x dB Bandwidth</b>	<b>1.150 MHz</b>	<b>99.00 %</b>
	<b>x dB</b>	<b>-20.00 dB</b>



## Test Report


Date : 2019-12-23  
 No. : HM19110001

Page 54 of 72

Frequency Range [MHz]	20dB Bandwidth [MHz]
2480.0	1.15

**Tx Mode: Port 1 (Integral Antenna), FSK mode Highest Channel**

**20dB Bandwidth of Fundamental Emission**



<b>Occupied Bandwidth</b>	<b>Total Power</b>	<b>-9.68 dBm</b>
<b>1.0331 MHz</b>		
<b>Transmit Freq Error</b>	<b>-69.088 kHz</b>	<b>OBW Power</b>
<b>x dB Bandwidth</b>	<b>1.151 MHz</b>	<b>99.00 %</b>
	<b>x dB</b>	<b>-20.00 dB</b>



## Test Report

Date : 2019-12-23  
 No. : HM19110001


Page 55 of 72

**Band Edge Measurement:**

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2400MHz – Lowest Fundamental	41.6

**Tx Mode: Port 0 (External Antenna), MSK mode**

**Band Edge Compliance Measurement**



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.401 20 GHz	93.632 dBµV			
2	N	1	f	2.400 00 GHz	51.998 dBµV			
3	N	1	f	2.397 02 GHz	48.863 dBµV			
4								



## Test Report

Date : 2019-12-23  
 No. : HM19110001


Page 56 of 72

**Band Edge Measurement:**

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Highest Fundamental – 2483.5MHz	52.3

**Tx Mode: Port 0 (External Antenna), MSK mode**

**Band Edge Compliance Measurement**



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.480 92 GHz	94.541 dBμV			
2	N	1	f	2.483 50 GHz	42.208 dBμV			
3	N	1	f	2.484 85 GHz	49.797 dBμV			
4								

**Result of Tx Mode: Port 0 (External Antenna), MSK mode, Band-edge measurement: PASS**

Field Strength of Fundamental and Harmonics Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2389.5	23.3	27.9	51.2	363.1	5,000	Vertical
2487.7	27.5	27.9	55.4	588.8	5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2389.5	12.8	27.9	40.7	108.4	500	Vertical
2487.7	16.4	27.9	44.3	164.1	500	Vertical







## Test Report

Date : 2019-12-23  
 No. : HM19110001


Page 58 of 72

**Band Edge Measurement:**

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Highest Fundamental – 2483.5MHz	36.0

**Tx Mode: Port 0 (External Antenna), FSK mode**

**Band Edge Compliance Measurement**



Start 2.47000 GHz      Stop 2.50000 GHz  
 #Res BW 100 kHz      #VBW 300 kHz      Sweep 2.933 ms (1001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.479 69 GHz	97.222 dBμV/m			
2	N	1	f	2.483 50 GHz	52.743 dBμV/m			
3	N	1	f	2.487 22 GHz	44.892 dBμV/m			
4								

**Result of Tx Mode: Port 0 (External Antenna), FSK mode, Band-edge measurement: PASS**

Field Strength of Fundamental and Harmonics Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2389.5	23.3	27.9	51.2	363.1	5,000	Vertical
2487.7	27.5	27.9	55.4	588.8	5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2389.5	12.8	27.9	40.7	108.4	500	Vertical
2487.7	16.4	27.9	44.3	164.1	500	Vertical



## Test Report

Date : 2019-12-23  
 No. : HM19110001


Page 59 of 72

**Band Edge Measurement:**

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2400MHz – Lowest Fundamental	40.9

**Tx Mode: Port 1 (Internal Antenna), MSK mode**

**Band Edge Compliance Measurement**



Start 2.3000 GHz      Stop 2.41000 GHz  
 #Res BW 100 kHz      #VBW 300 kHz      Sweep 10.53 ms (1001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.401 09 GHz	90.133 dBµV			
2	N	1	f	2.400 00 GHz	49.225 dBµV			
3	N	1	f	2.397 02 GHz	45.194 dBµV			
4								



## Test Report

Date : 2019-12-23  
 No. : HM19110001


Page 60 of 72

**Band Edge Measurement:**

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Highest Fundamental – 2483.5MHz	52.1

**Tx Mode: Port 1 (Internal Antenna), MSK mode**

**Band Edge Compliance Measurement**



Start 2.47000 GHz      Stop 2.50000 GHz  
 #Res BW 100 kHz      #VBW 300 kHz      Sweep 2.933 ms (1001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.480 92 GHz	90.609 dBμV			
2	N	1	f	2.483 50 GHz	38.518 dBμV			
3	N	1	f	2.484 85 GHz	46.051 dBμV			
4								

**Result of Tx Mode: Port 1 (Internal Antenna), MSK mode, Band-edge measurement: PASS**

Field Strength of Fundamental and Harmonics Emissions Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2397.0	17.3	27.9	45.2	182.0	5,000	Vertical
2484.9	18.2	27.9	46.1	201.8	5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions Average Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
2389.5	8.3	27.9	36.2	64.6	500	Vertical
2484.9	9.7	27.9	37.6	75.9	500	Vertical

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.  
 For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23  
No. : HM19110001


Page 62 of 72

**Band Edge Measurement:**

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Highest Fundamental – 2483.5MHz	43.4

**Tx Mode: Port 1 (External Antenna), FSK mode**

**Band Edge Compliance Measurement**



Start 2.47000 GHz      Stop 2.50000 GHz  
#Res BW 100 kHz      #VBW 300 kHz      Sweep 2.933 ms (1001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.479 69 GHz	93.391 dBµV/m			
2	N	1	f	2.483 50 GHz	49.992 dBµV/m			
3	N	1	f	2.487 55 GHz	43.731 dBµV/m			
4								

**Result of Tx Mode: Port 1 (Internal Antenna), FSK mode, Band-edge measurement: PASS**

Field Strength of Fundamental and Harmonics Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBµV/m	Correction Factor dBµV/m	Field Strength dBµV/m	Field Strength µV/m	Limit @3m µV/m	E-Field Polarity
2397.6	20.7	27.9	48.6	269.2	5,000	Vertical
2487.6	15.8	27.9	43.7	153.1	5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBµV/m	Correction Factor dBµV/m	Field Strength dBµV/m	Field Strength µV/m	Limit @3m µV/m	E-Field Polarity
2389.5	8.9	27.9	36.8	69.2	500	Vertical
2487.7	6.8	27.9	34.7	54.3	500	Vertical



## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 63 of 72

### Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [ $\mu$ V/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Remarks: Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate in the table below is the worst case rate with respect to the specific test item.  
Investigation has been done on all the possible configurations for searching the worst cases.

### **Result of TX mode, (9kHz – 30MHz): PASS**

Emissions detected are more than 20 dB below the FCC Limits

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




## Test Report

Date : 2019-12-23  
 No. : HM19110001

Page 64 of 72

**Result of TX mode (30MHz – 1GHz): PASS**



<b>Field Strength of Fundamental and Harmonics Emissions</b>						
<b>Quasi-Peak Value</b>						
Frequency MHz	Measured Level @3m dBµV/m	Correction Factor dBµV/m	Field Strength dBµV/m	Field Strength µV/m	Limit @3m µV/m	E-Field Polarity
38.4	9.8	7.5	17.3	7.3	100	Horizontal
111.4	5.4	8.4	13.8	4.9	150	Horizontal
224.5	4.8	10.5	15.3	5.8	150	Horizontal
387.4	6.8	18.2	25.0	17.8	200	Horizontal
512.8	3.4	21.2	24.6	17.0	200	Horizontal
598.4	2.3	21.1	23.4	14.8	200	Horizontal
32.4	8.7	8.1	16.8	6.9	100	Vertical
90.3	6.3	8.9	15.2	5.8	150	Vertical





## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 65 of 72

Result of Receiver mode, (9kHz – 30MHz): N/A

Result of Receiver mode, (30MHz – 1GHz): N/A

Result of Receiver mode, (1GHz – 18GHz): N/A

Remarks:

No additional spurious emissions found between lowest internal used/generated frequency and 30 MHz  
Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty	:	(9kHz – 30MHz):	2.4dB
		(30MHz – 18GHz):	5.0dB
		(18GHz - 26GHz):	5.24dB

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2019-12-23

No. : HM19110001

Page 66 of 72

### 3.1.3 Antenna Requirement

Ambient temperature 21°C

Relative humidity 50%

**Test Requirements:** § 15.203

#### **Test Specification:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### **Test Results:**

There are 2 antennae, for port 0 which is mounted on the enclosure of the EUT, the antenna gain = 13dBi, for port 1, which is a PCB printed inverted F antenna, the antenna gain = 3.3dBi. There is no external antenna port. User is unable to remove or changed the Antenna.



## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 67 of 72

### Appendix A

#### LIST OF MEASUREMENT EQUIPMENT

##### Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM215	MULTIDEVICE CONTROLLER	EMCO	2090	00024676	N/A	N/A
EM217	ELECTRIC POWERED TURNTABLE	EMCO	2088	00029144	N/A	N/A
EM218	ANECHOIC CHAMBER	ETS-LINDGREN	FACT-3	--	2019/04/24	2020/04/24
EM356	ANTENNA POSITIONING TOWER	ETS-LINDGREN	2171B	00150346	N/A	N/A
EM355	BICONILOG ANTENNA	ETS-LINDGREN	3143B	00201783	2019/03/11	2021/03/11
EM229	EMI TEST RECEIVER	R&S	ESIB40	100248	2019/06/11	2020/06/11
EM299	DOUBLE-RIDGED WAVEGUIDE HORN ANTENNA	ETS-LINDGREN	3115	00114120	2018/04/27	2020/04/27
EM300	PYRAMIDAL STANDARD GAIN HORN ANTENNA	ETS-LINDGREN	3160-09	00130130	2018/05/13	2020/05/13
EM353	LOOP ANTENNA	ETS_LINDGREN	6502	00206533	2018/03/16	2020/03/16

##### Remarks:

CM Corrective Maintenance  
N/A Not Applicable or Not Available  
TBD To Be Determined

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.  
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 68 of 72


### Appendix B

#### Photographs of EUT

**Front View of the product**




**Rear View of the product**



**Rear View of the product**



**Rear View of the product**



## Test Report

Date : 2019-12-23  
No. : HM19110001


Page 69 of 72

### Photographs of EUT


**Inner View of the Product**



**PCB Front View of the Product**



**PCB Bottom View of the Product**




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 70 of 72

### Photographs of EUT

#### Measurement of Radiated Emission Test Set Up (9kHz to 30MHz)



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@stc.group](mailto:hkstc@stc.group) Website: [www.stc.group](http://www.stc.group)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.  
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 71 of 72

### Photographs of EUT

Measurement of Radiated Emission Test Set Up (30MHz to 1000MHz)



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@stc.group](mailto:hkstc@stc.group) Website: [www.stc.group](http://www.stc.group)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.


## Test Report

Date : 2019-12-23  
No. : HM19110001

Page 72 of 72

### Photographs of EUT

Measurement of Radiated Emission Test Set Up (Above 1000MHz)



\*\*\*\*\* End of Test Report \*\*\*\*\*

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@stc.group](mailto:hkstc@stc.group) Website: [www.stc.group](http://www.stc.group)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Conditions of Issuance of Test Reports

1. All samples and goods are accepted by The Hong Kong Standards & Testing Centre Limited (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The Company provides its services on the basis that such terms and conditions constitute express agreement between the Company and any person, firm or company requesting its services (the "Clients").
2. Any report issued by the Company as a result of this application for testing service (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to his customer, supplier or other persons directly concerned. Subject to clause 3, the Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall be at liberty to disclose the testing-related documents and/or files anytime to any third-party accreditation and/or recognition bodies for audit or other related purposes. No liabilities whatsoever shall attach to the Company's act of disclosure.
4. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
5. The results in Report apply only to the sample as received and do not apply to the bulk, unless the sampling has been carried out by the Company and is stated as such in the Report.
6. When a statement of conformity to a specification or standard is provided, the ILAC-G8 Guidance document (and/or IEC Guide 115 in the electrotechnical sector) will be adopted as a decision rule for the determination of conformity unless it is inherent in the requested specification or standard, or otherwise specified in the Report.
7. In the event of the improper use the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
8. Sample submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
9. The Company will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
10. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
11. Subject to the variable length of retention time for test data and report stored hereinto as to otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of this test report for a period of three years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after the retention period. Under no circumstances shall we be liable for damages of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.
12. Issuance records of the Report are available on the internet at [www.stc.group](http://www.stc.group). Further enquiry of validity or verification of the Reports should be addressed to the Company.