

CETECOM ICT Services is now

**CTC** | advanced  
member of RWTÜV group

## TEST REPORT

Test report no.: 1-1120/16-01-03-D



Deutsche  
Akkreditierungsstelle  
D-PL-12076-01-01

### Testing laboratory

#### CTC advanced GmbH

Untertuerkheimer Strasse 6 – 10  
66117 Saarbruecken / Germany  
Phone: + 49 681 5 98 - 0  
Fax: + 49 681 5 98 - 9075  
Internet: <http://www.ctcadvanced.com>  
e-mail: [mail@ctcadvanced.com](mailto:mail@ctcadvanced.com)

#### Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS). The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-01

### Applicant

#### Profoto AB

Landsvägen 57  
172 65 Sundbyberg / SWEDEN  
Phone: +46 (0) 84 47 53 00  
Fax: -/-  
Contact: Frederic Luthman  
e-mail: [fredric@hagelund.se](mailto:fredric@hagelund.se)  
Phone: +46 (0) 70 41 98 90 0

### Manufacturer

#### Profoto AB

Landsvägen 57  
172 65 Sundbyberg / SWEDEN

### Test standard/s

|                   |   |
|-------------------|---|
| 47 CFR Part 15    | Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices   |
| RSS - 247 Issue 2 | Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence - Exempt Local Area Network (LE-LAN) Devices                            |
| RSS - Gen Issue 4 | Spectrum Management and Telecommunications Radio Standards Specifications - General Requirements and Information for the Certification of Radio Apparatus |

For further applied test standards please refer to section 3 of this test report.

### Test Item

|                    |                                 |
|--------------------|---------------------------------|
| Kind of test item: | Proprietary module              |
| Model name:        | RMI6                            |
| FCC ID:            | W4G-RMI6                        |
| IC:                | 8167A-RMI6                      |
| Frequency:         | DTS band 2400 MHz to 2483.5 MHz |
| Technology tested: | Proprietary                     |
| Antenna:           | Integrated antenna              |
| Power supply:      | 3.0 V DC by two AA-batteries    |
| Temperature range: | -10°C to +55°C                  |



This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Test report authorized:

Marco Bertolino  
Lab Manager  
Radio Communications & EMC

### Test performed:

Mihail Dorongovskij  
Lab Manager  
Radio Communications & EMC

## 1 Table of contents

|         |   |    |
|---------|---|----|
| 1       | Table of contents.....  | 2  |
| 2       | General information .....                                     | 3  |
| 2.1     | Notes and disclaimer .....                                    | 3  |
| 2.2     | Application details .....                                     | 3  |
| 2.3     | Test laboratories sub-contracted .....                        | 3  |
| 3       | Test standard/s and references.....                           | 4  |
| 4       | Test environment .....  | 5  |
| 5       | Test item .....   | 5  |
| 5.1     | General description.....                                      | 5  |
| 5.2     | Additional information .....                                  | 5  |
| 6       | Description of the test setup .....                           | 6  |
| 6.1     | Shielded semi anechoic chamber .....                          | 7  |
| 6.2     | Shielded fully anechoic chamber .....                         | 8  |
| 6.3     | Radiated measurements > 18 GHz .....                          | 9  |
| 6.4     | Conducted measurements C.BER system .....                     | 10 |
| 6.5     | AC conducted .....  | 11 |
| 7       | Sequence of testing .....                                     | 12 |
| 7.1     | Sequence of testing radiated spurious 9 kHz to 30 MHz .....   | 12 |
| 7.2     | Sequence of testing radiated spurious 30 MHz to 1 GHz .....   | 13 |
| 7.3     | Sequence of testing radiated spurious 1 GHz to 18 GHz .....   | 14 |
| 7.4     | Sequence of testing radiated spurious above 18 GHz .....      | 15 |
| 8       | Measurement uncertainty.....                                  | 16 |
| 9       | Summary of measurement results .....                          | 17 |
| 10      | Additional comments.....                                      | 18 |
| 11      | Measurement results .....                                     | 19 |
| 11.1    | Antenna gain.....   | 19 |
| 11.2    | Carrier frequency separation .....                            | 20 |
| 11.3    | Number of hopping channels .....                              | 22 |
| 11.4    | Time of occupancy (dwell time).....                           | 24 |
| 11.5    | Spectrum bandwidth of a FHSS system.....                      | 28 |
| 11.6    | Maximum output power .....                                    | 32 |
| 11.7    | Detailed spurious emissions @ the band edge – conducted ..... | 35 |
| 11.8    | Band edge compliance radiated .....                           | 38 |
| 11.9    | Spurious emissions conducted .....                            | 41 |
| 11.10   | Spurious emissions radiated below 30 MHz .....                | 45 |
| 11.11   | Spurious emissions radiated 30 MHz to 1 GHz .....             | 48 |
| 11.12   | Spurious emissions radiated above 1 GHz .....                 | 53 |
| 11.13   | Spurious emissions conducted below 30 MHz (AC conducted)..... | 59 |
| 12      | Observations .....  | 62 |
| Annex A | Document history .....  | 63 |
| Annex B | Glossary .....  | 64 |
| Annex C | Accreditation Certificate .....                               | 65 |

## 2 General information

### 2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CTC advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTC advanced GmbH.

The testing service provided by CTC advanced GmbH has been rendered under the current "General Terms and Conditions for CTC advanced GmbH".

CTC advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CTC advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CTC advanced GmbH test report include or imply any product or service warranties from CTC advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CTC advanced GmbH.

All rights and remedies regarding vendor's products and services for which CTC advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by CTC advanced GmbH. In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

**This test report replaces the test report with the number 1-1120/16-01-03-C and dated 2017-09-25**

### 2.2 Application details

|                                    |            |
|------------------------------------|------------|
| Date of receipt of order:          | 2016-07-06 |
| Date of receipt of test item:      | 2017-03-22 |
| Start of test:                     | 2017-06-12 |
| End of test:                       | 2017-08-08 |
| Person(s) present during the test: | -/-        |

### 2.3 Test laboratories sub-contracted

None

### 3 Test standard/s and references

| Test standard     | Date          | Description   |
|-------------------|---------------|---|
| 47 CFR Part 15    | -/-           | Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices   |
| RSS - 247 Issue 2 | February 2017 | Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence - Exempt Local Area Network (LE-LAN) Devices                            |
| RSS - Gen Issue 4 | November 2014 | Spectrum Management and Telecommunications Radio Standards Specifications - General Requirements and Information for the Certification of Radio Apparatus |

| Guidance         | Version | Description   |
|------------------|---------|---|
| ANSI C63.4-2014  | -/-     | American national standard for methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz |
| ANSI C63.10-2013 | -/-     | American national standard of procedures for compliance testing of unlicensed wireless devices  |

## 4 Test environment

|                           |   |  |  |
|---------------------------|---|--|--|
| Temperature               | : | T <sub>nom</sub><br>T <sub>max</sub><br>T <sub>min</sub> | +22 °C during room temperature tests<br>No tests under extreme conditions required.<br>No tests under extreme conditions required.   |
| Relative humidity content | : |  | 50 %   |
| Barometric pressure       | : |  | 1021 hpa   |
| Power supply              | : | V <sub>nom</sub><br>V <sub>max</sub><br>V <sub>min</sub> | 3.0 V DC by two 1.5. V DC AA-batteries<br>No tests under extreme conditions required.<br>No tests under extreme conditions required. |

## 5 Test item

### 5.1 General description

|                            |   |  |
|----------------------------|---|--|
| Kind of test item          | : | Proprietary module   |
| Type identification        | : | RMI6   |
| HMN                        | : | -/-  |
| PMN                        | : | RMI6   |
| HVIN                       | : | PCD0142-0000   |
| FVIN                       | : | -/-  |
| S/N serial number          | : | Rad. 7A<br>Cond. 7B  |
| HW hardware status         | : | PCB 6179 rev B1  |
| SW software status         | : | RMI6ITD_CETECOM_C4   |
| Frequency band             | : | DTS band 2400 MHz to 2483.5 MHz<br>(lowest channel 2404.0 MHz; highest channel 2479.3 MHz) |
| Type of radio transmission | : | FHSS   |
| Use of frequency spectrum  | : |  |
| Type of modulation         | : | MSK  |
| Number of channels         | : | 22   |
| Antenna                    | : | Integrated antenna   |
| Power supply               | : | 3.0 V DC by two 1.5. V DC AA-batteries   |
| Temperature range          | : | -10°C to +55°C   |

### 5.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup- and EUT-photos are included in test report: 1-1120/16-01-01\_AnnexB  
1-1120/16-01-01\_AnnexD

## 6 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).


In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

**Agenda:** Kind of Calibration

|      |  |     |  |
|------|--|-----|--|
| k    | calibration / calibrated                   | EK  | limited calibration                                  |
| ne   | not required (k, ev, izw, zw not required) | zw  | cyclical maintenance (external cyclical maintenance) |
| ev   | periodic self verification                 | izw | internal cyclical maintenance                        |
| Ve   | long-term stability recognized             | g   | blocked for accredited testing                       |
| vkl! | Attention: extended calibration interval   |     |  |
| NK!  | Attention: not calibrated                  | *)  | next calibration ordered / currently in progress     |

## 6.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter

$$FS = UR + CL + AF$$

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


*Example calculation:*

$$FS [dB\mu V/m] = 12.35 [dB\mu V/m] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB\mu V/m] (35.69 \mu V/m)$$

### Equipment table:

| No. | Lab / Item | Equipment                                    | Type         | Manufact.    | Serial No. | INV. No Cetecom | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|--|--------------|--------------|------------|-----------------|---------------------|------------------|------------------|
| 1   | A          | Switch-Unit                                  | 3488A        | HP           | 2719A14505 | 300000368       | ev                  | -/-              | -/-              |
| 2   | A          | EMI Test Receiver                            | ESCI 3       | R&S          | 100083     | 300003312       | k                   | 01.02.2017       | 31.01.2018       |
| 3   | A          | Antenna Tower                                | Model 2175   | ETS-Lindgren | 64762      | 300003745       | izw                 | -/-              | -/-              |
| 4   | A          | Positioning Controller                       | Model 2090   | ETS-Lindgren | 64672      | 300003746       | izw                 | -/-              | -/-              |
| 5   | A          | Turntable Interface-Box                      | Model 105637 | ETS-Lindgren | 44583      | 300003747       | izw                 | -/-              | -/-              |
| 6   | A          | TRILOG Broadband Test-Antenna 30 MHz – 3 GHz | VULB9163     | Schwarzbeck  | 295        | 300003787       | k                   | 25.04.2016       | 25.04.2018       |

## 6.2 Shielded fully anechoic chamber



Measurement distance: horn antenna 3 meter; loop antenna 3 meter / 1 meter

$$FS = UR + CA + AF$$

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)

Example calculation:


$$FS \text{ [dB}\mu\text{V/m]} = 40.0 \text{ [dB}\mu\text{V/m]} + (-35.8) \text{ [dB]} + 32.9 \text{ [dB/m]} = 37.1 \text{ [dB}\mu\text{V/m]} \text{ (71.61 } \mu\text{V/m)}$$

### Equipment table:

| No. | Lab / Item | Equipment                                      | Type                            | Manufact.            | Serial No. | INV. No Cetecom | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|--|---------------------------------|----------------------|------------|-----------------|---------------------|------------------|------------------|
| 1   | A          | Double-Ridged Waveguide Horn Antenna 1-18.0GHz | 3115                            | EMCO                 | 9709-5290  | 300000212       | k                   | 13.08.2015       | 13.08.2017       |
| 2   | A,B,C      | Anechoic chamber                               | FAC 3/5m                        | MWB / TDK            | 87400/02   | 300000996       | ev                  | -/-              | -/-              |
| 3   | A,B,C      | Switch / Control Unit                          | 3488A                           | HP                   | *          | 300000199       | ne                  | -/-              | -/-              |
| 4   | C          | Active Loop Antenna 10 kHz to 30 MHz           | 6502                            | EMCO                 | 2210       | 300001015       | k                   | 20.05.2017       | 20.05.2019       |
| 5   | A          | Amplifier                                      | js42-00502650-28-5a             | Parzich GMBH         | 928979     | 300003143       | ne                  | -/-              | -/-              |
| 6   | A          | Band Reject filter                             | WRCG2400/2483-2375/2505-50/10SS | Wainwright           | 11         | 300003351       | ev                  | -/-              | -/-              |
| 7   | A          | Highpass Filter                                | WHKX7.0/18G-8SS                 | Wainwright           | 18         | 300003789       | ne                  | -/-              | -/-              |
| 8   | A,B,C      | 4U RF Switch Platform                          | L4491A                          | Agilent Technologies | MY50000037 | 300004509       | ne                  | -/-              | -/-              |
| 9   | A, B, C    | EMI Test Receiver 20Hz- 26,5GHz                | ESU26                           | R&S                  | 100037     | 300003555       | k                   | 31.01.2017       | 30.01.2018       |
| 10  | A, B       | TRILOG Broadband Test-Antenna 30 MHz – 3 GHz   | VULB9163                        | Schwarzbeck          | 371        | 30000           | vIKI!               | 29.10.2014       | 29.10.2017       |



### 6.3 Radiated measurements > 18 GHz



Measurement distance: horn antenna 50 cm

$$FS = UR + CA + AF$$

(FS-field strength; UR-voltage at the receiver; CA-loss signal path & distance correction; AF-antenna factor)


Example calculation:

$$FS [dB\mu V/m] = 40.0 [dB\mu V/m] + (-60.1) [dB] + 36.74 [dB/m] = 16.64 [dB\mu V/m] (6.79 \mu V/m)$$

#### Equipment table:

| No. | Lab / Item | Equipment                               | Type                | Manufacturer   | Serial No.       | INV. No.  | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|---|---------------------|----------------|------------------|-----------|---------------------|------------------|------------------|
| 1   | A          | Std. Gain Horn Antenna 18.0 to 26.5 GHz | 638                 | Narda          | -/-              | 300000486 | k                   | 10.09.2015       | 10.09.2017       |
| 2   | A          | Signal Analyzer 40 GHz                  | FSV40               | R&S            | 101042           | 300004517 | k                   | 27.01.2017       | 26.01.2018       |
| 3   | A          | Amplifier 2-40 GHz                      | JS32-02004000-57-5P | MITEQ          | 1777200          | 300004541 | ev                  | -/-              | -/-              |
| 4   | A          | RF-Cable                                | ST18/SMAm/SMAm/48   | Huber & Suhner | Batch no. 600918 | 400001182 | ev                  | -/-              | -/-              |
| 5   | A          | RF-Cable                                | ST18/SMAm/SMAm/48   | Huber & Suhner | Batch no. 127377 | 400001183 | ev                  | -/-              | -/-              |
| 6   | A          | DC-Blocker 0.1-40 GHz                   | 8141A               | Inmet          | -/-              | 400001185 | ev                  | -/-              | -/-              |

## 6.4 Conducted measurements C.BER system



OP = AV + CA  
 (OP-output power; AV-analyzer value; CA-loss signal path)


Example calculation:

OP [dBm] = 6.0 [dBm] + 11.7 [dB] = 17.7 [dBm] (58.88 mW)

**Equipment table:**

| No. | Lab / Item | Equipment             | Type               | Manufact.      | Serial No.       | INV. No Cetecom | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|-----------------------|--------------------|----------------|------------------|-----------------|---------------------|------------------|------------------|
| 1   | A          | Switch / Control Unit | 3488A              | HP             |                  | 300001691       | ne                  | -/-              | -/-              |
| 2   | A          | Signal Analyzer 30GHz | FSV30              | R&S            | 103170           | 300004855       | k                   | 30.01.2017       | 29.01.2019       |
| 3   | A          | Directional Coupler   | 101020010          | Krytar         | 70215            | 300002840       | ev                  | -/-              | -/-              |
| 4   | A          | DC-Blocker            | 8143               | Inmet Corp.    | none             | 300002842       | ne                  | -/-              | -/-              |
| 5   | A          | Powersplitter         | 6005-3             | Inmet Corp.    | none             | 300002841       | ev                  | -/-              | -/-              |
| 6   | A          | RF-Cable              | ST118/SMAm/SMAm/72 | Huber & Suhner | Batch no. 605505 | 400001187       | ev                  | -/-              | -/-              |
| 7   | A          | RF-Cable              | Sucoflex 104       | Huber & Suhner | 147636/4         | 400001188       | ev                  | -/-              | -/-              |

## 6.5 AC conducted



$$FS = UR + CF + VC$$

(FS-field strength; UR-voltage at the receiver; CR-loss of the cable and filter; VC-correction factor of the ISN)

*Example calculation:*

$$FS [dB\mu V/m] = 37.62 [dB\mu V/m] + 9.90 [dB] + 0.23 [dB] = 47.75 [dB\mu V/m] (244.06 \mu V/m)$$

### Equipment table:

| No. | Lab / Item | Equipment                                 | Type     | Manufacturer | Serial No. | INV. No.  | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|---|----------|--------------|------------|-----------|---------------------|------------------|------------------|
| 1   | A          | Two-line V-Network (LISN) 9 kHz to 30 MHz | ESH3-Z5  | R&S          | 893045/004 | 300000584 | k                   | 31.01.2017       | 30.01.2018       |
| 2   | A          | RF-Filter-section                         | 85420E   | HP           | 3427A00162 | 300002214 | k                   | 27.11.2006       | -/-              |
| 3   | A          | EM-Injection Clamp                        | FCC-203i | emv          | 232        | 300000626 | ev                  | 18.05.2001       | -/-              |
| 4   | A          | AC-Spannungsquelle variabel               | MV2616-V | EM-Test      | 0397-12    | 300003259 | k                   | 11.12.2015       | 11.12.2017       |
| 5   | A          | Hochpass 150 kHz                          | EZ-25    | R&S          | 100010     | 300003798 | ev                  | 08.04.2008       | -/-              |
| 6   | A          | Signal Analyser 40 GHz                    | FSV40    | R&S          | 101042     | 300004517 | k                   | 27.01.2017       | 26.01.2018       |

## 7 Sequence of testing

### 7.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

#### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

#### Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.5 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

#### Final measurement

- Identified emissions during the premeasurement are maximized by the software by rotating the turntable from 0° to 360°. In case of the 2-axis positioner is used the elevation axis is also rotated from 0° to 360°.
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

## 7.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

### Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position  $\pm 45^\circ$  and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

### 7.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

#### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

#### Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

#### Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

## 7.4 Sequence of testing radiated spurious above 18 GHz

### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

### Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

### Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

## 8 Measurement uncertainty

| Measurement uncertainty                                  |  |
|--|--|
| Test case  | Uncertainty                              |
| Antenna gain   | ± 3 dB                                   |
| Carrier frequency separation                             | ± 21.5 kHz                               |
| Number of hopping channels                               | -/-                                      |
| Time of occupancy  | -/-                                      |
| Spectrum bandwidth                                       | ± 21.5 kHz absolute; ± 15.0 kHz relative |
| Maximum output power                                     | ± 1 dB                                   |
| Detailed conducted spurious emissions @ the band edge    | ± 1 dB                                   |
| Band edge compliance radiated                            | ± 3 dB                                   |
| Spurious emissions conducted                             | ± 3 dB                                   |
| Spurious emissions radiated below 30 MHz                 | ± 3 dB                                   |
| Spurious emissions radiated 30 MHz to 1 GHz              | ± 3 dB                                   |
| Spurious emissions radiated 1 GHz to 12.75 GHz           | ± 3.7 dB                                 |
| Spurious emissions radiated above 12.75 GHz              | ± 4.5 dB                                 |
| Spurious emissions conducted below 30 MHz (AC conducted) | ± 2.6 dB                                 |



## 9 Summary of measurement results

|                                     |  |
|-------------------------------------|--|
| <input checked="" type="checkbox"/> | No deviations from the technical specifications were ascertained   |
| <input type="checkbox"/>            | There were deviations from the technical specifications ascertained  |
| <input type="checkbox"/>            | This test report is only a partial test report.<br>The content and verdict of the performed test cases are listed below. |

| TC Identifier | Description                       | Verdict    | Date       | Remark |
|---------------|-----------------------------------|------------|------------|--------|
| RF-Testing    | CFR Part 15<br>RSS – 247, Issue 2 | See table! | 2017-10-25 | -/-    |

| Test specification clause                             | Test case   | Temperature conditions | Power source voltages | Mode           | C                                   | NC                       | NA                       | NP                       | Remark |
|---|---|------------------------|-----------------------|----------------|-------------------------------------|--------------------------|--------------------------|--------------------------|--------|
| §15.247(b)(4)<br>RSS – 247 / 5.4 (2)                  | Antenna gain  | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.247(a)(1)<br>RSS – 247 / 5.1 (2)                  | Carrier frequency separation                            | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.247(a)(1)<br>RSS – 247 / 5.1 (4)                  | Number of hopping channels                              | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.247(a)(1) (iii)<br>RSS – 247 / 5.1 (4)            | Time of occupancy (dwell time)                          | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.247(a)(1)<br>RSS – 247 / 5.1 (1)                  | Spectrum bandwidth of a FHSS system bandwidth           | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.247(b)(1)<br>RSS – 247 / 5.4 (2)                  | Maximum output power                                    | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.247(d)<br>RSS – 247 / 5.5                         | Detailed spurious emissions @ the band edge – conducted | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.205<br>RSS – 247 / 5.5<br>RSS – Gen               | Band edge compliance radiated                           | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.247(d)<br>RSS – 247 / 5.5                         | Spurious emissions conducted                            | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.209(a)<br>RSS – Gen                               | Spurious emissions radiated below 30 MHz                | Nominal                | Nominal               | MSK            | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.247(d)<br>RSS – 247 / 5.5<br>§15.109<br>RSS – Gen | Spurious emissions radiated 30 MHz to 1 GHz             | Nominal                | Nominal               | MSK<br>RX mode | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.247(d)<br>RSS – 247 / 5.5<br>§15.109<br>RSS – Gen | Spurious emissions radiated above 1 GHz                 | Nominal                | Nominal               | MSK<br>RX mode | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |
| §15.107(a)<br>§15.207                                 | Conducted emissions below 30 MHz (AC conducted)         | Nominal                | Nominal               |                | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/-    |

**Note:** C = Compliant; NC = Not compliant; NA = Not applicable; NP = Not performed

## 10 Additional comments

Reference documents: promote\_air\_FHSS\_radiosystem\_rev\_A4  
Test report no. 1-1120/16-01-02

Special test descriptions: None

Configuration descriptions: **All TX measurements were performed with a power setting of 18 dBm, only measurements on highest channel were performed with 6 dBm power setting because else it was not compliant with the band edge limitations.**

Test mode:  Special software is used.  
EUT is transmitting pseudo random data by itself

Antennas and transmit operating modes:  Operating mode 1 (single antenna)

- Equipment with 1 antenna,
- Equipment with 2 diversity antennas operating in switched diversity mode by which at any moment in time only 1 antenna is used,
- Smart antenna system with 2 or more transmit/receive chains, but operating in a mode where only 1 transmit/receive chain is used)

## 11 Measurement results

### 11.1 Antenna gain

**Measurement:**

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

| Measurement parameters  |   |
|-------------------------|---|
| Detector                | Peak  |
| Sweep time              | Auto  |
| Resolution bandwidth    | 3 MHz   |
| Video bandwidth         | 3 MHz   |
| Span                    | 5 MHz   |
| Trace mode              | Max hold  |
| Test setup              | See sub clause 6.2 B (radiated)<br>See sub clause 6.4 A (conducted) |
| Measurement uncertainty | See sub clause 8  |

**Limits:**

| FCC   | IC |
|---|----|
| 6 dBi / > 6 dBi output power and power density reduction required |    |

**Results: Values taken from Test report no. 1-1120/16-01-02**

|            | lowest channel<br>2404 MHz | middle channel<br>2447 MHz | highest channel<br>2479.3 MHz |
|------------|----------------------------|----------------------------|-------------------------------|
| Gain [dBi] | -0.2                       | 0.0                        | 0.2                           |

## 11.2 Carrier frequency separation

### Description:

Measurement of the carrier frequency separation of a hopping system. The carrier frequency separation is constant for all modulation-modes. EUT in hopping mode.

| Measurement parameters  |                      |
|-------------------------|----------------------|
| Detector                | Peak                 |
| Sweep time              | Auto                 |
| Resolution bandwidth    | 100 kHz              |
| Video bandwidth         | 300 kHz              |
| Span                    | 4 MHz                |
| Trace mode              | Max hold             |
| Test setup              | See sub clause 6.4 A |
| Measurement uncertainty | See sub clause 8     |

### Limits:


| FCC   | IC |
|---|----|
| Carrier frequency separation  |    |
| Minimum 25 kHz or two-thirds of the 20 dB bandwidth of the hopping system whichever is greater. |    |

### Result:

|                              |         |
|------------------------------|---------|
| Carrier frequency separation | ~ 3 MHz |
|------------------------------|---------|

**Plot:**

**Plot 1:** Carrier frequency separation



### 11.3 Number of hopping channels

**Description:**

Measurement of the total number of used hopping channels. The number of hopping channels is constant for all modulation-modes. EUT in hopping mode.

| Measurement parameters  |  |
|-------------------------|--|
| Detector                | Peak   |
| Sweep time              | Auto   |
| Resolution bandwidth    | 500 kHz  |
| Video bandwidth         | 500 kHz  |
| Span                    | Plot 1: 2400 – 2445 MHz<br>Plot 2: 2445 – 2485 MHz |
| Trace mode              | Max hold   |
| Test setup              | See sub clause 6.4 A                               |
| Measurement uncertainty | See sub clause 8                                   |

**Limits:**


| FCC  | IC |
|--|----|
| Number of hopping channels                   |    |
| At least 15 non overlapping hopping channels |    |

**Result:**

|                            |    |
|----------------------------|----|
| Number of hopping channels | 22 |
|----------------------------|----|

**Plots:**

**Plot 1:** Number of hopping channels



**11.4 Time of occupancy (dwell time)**

| Measurement parameters     |                      |
|----------------------------|----------------------|
| Detector                   | Peak                 |
| Sweep time                 | 100 ms / 8.8 s       |
| Resolution bandwidth       | 300 kHz              |
| Video bandwidth            | 1 MHz                |
| Trace mode                 | Max hold             |
| Span                       | Zero span            |
| Additional EUT parameters: | Hopping on           |
| Test setup                 | See sub clause 6.4 A |
| Measurement uncertainty    | See sub clause 8     |

**Results:**

| <i>Channel frequency [MHz]</i> | <i>Measured pulse width [ms]</i> | Number of hops during observation time 8.8s | <i>Calculated staying time[ms]</i> |
|--------------------------------|----------------------------------|---|------------------------------------|
| 2404.0                         | 20.145                           | 19  | 382.8                              |
| 2427.0                         | 20.000                           | 18  | 360.0                              |
| 2479.3                         | 20.000                           | 19  | 380.0                              |


**Limits:**

| FCC   | IC |
|---|----|
| Time of occupancy (dwell time)  |    |
| The frequency hopping operation shall have an average time of occupancy on any frequency not exceeding 0.4 seconds within a duration in seconds equal to the number of hopping frequencies multiplied by 0.4. |    |




**Plots:**

**Plot 1: 2404 MHz, Zero span, pulse width**




Date: 8 AUG 2017 14:46:33

**Plot 2: 2427 MHz, Zero span, pulse width**




Date: 8 AUG 2017 14:47:05

Plot 3: 2479.3 MHz, Zero span, pulse width




Date: 8 AUG 2017 14:47:24

Plot 4: 2404 MHz, 8.8 s sweep




Date: 8 AUG 2017 14:47:49

Plot 5: 2427 MHz, 8.8 s sweep



Plot 6: 2479.3 MHz, 8.8 s sweep



### 11.5 Spectrum bandwidth of a FHSS system

**Description:**

Measurement of the 20dB bandwidth and 99% bandwidth of the modulated signal. The measurement is performed according to the "Measurement Guidelines" (DA 00-705, March 30, 2000). EUT in single channel mode.

| Measurement parameters  |                      |
|-------------------------|----------------------|
| Detector                | Peak                 |
| Sweep time              | Auto                 |
| Resolution bandwidth    | 30 kHz               |
| Video bandwidth         | 100 kHz              |
| Span                    | 3 MHz                |
| Trace mode              | Max hold             |
| Test setup              | See sub clause 6.4 A |
| Measurement uncertainty | See sub clause 8     |

**Limits:**

| FCC                                 | IC |
|-------------------------------------|----|
| Spectrum bandwidth of a FHSS system |    |
| < 4500 kHz                          |    |

**Results:**


| Frequency | 20 dB bandwidth [kHz] |            |            |
|-----------|-----------------------|------------|------------|
|           | 2404.0 MHz            | 2427.0 MHz | 2479.3 MHz |
|           | 1210                  | 1200       | 1200       |

**Results:**


| Frequency | 99 % bandwidth [kHz] |            |            |
|-----------|----------------------|------------|------------|
|           | 2404.0 MHz           | 2427.0 MHz | 2479.3 MHz |
|           | 1207                 | 1187       | 1167       |

**Plots:**


**Plot 1:** lowest channel – 2404.0 MHz



**Plot 2:** middle channel – 2427.0 MHz



**Plot 3:** highest channel – 2479.3 MHz



**11.6 Maximum output power**

**Description:**

Measurement of the maximum output power conducted and radiated. EUT in single channel mode. The measurement is performed according to the ANSI C63.10.

| Measurement parameters  |                      |
|-------------------------|----------------------|
| Detector                | Peak                 |
| Sweep time              | Auto                 |
| Resolution bandwidth    | 3 MHz                |
| Video bandwidth         | 10 MHz               |
| Span                    | 6 MHz                |
| Trace mode              | Max hold             |
| Test setup              | See sub clause 6.4 A |
| Measurement uncertainty | See sub clause 8     |

**Limits:**

| FCC  | IC |
|--|----|
| Maximum output power   |    |
| [Conducted: 0.125 W – antenna gain max. 6 dBi]<br>Systems using more than 75 hopping channels:<br>Conducted: 1.0 W – antenna gain max. 6 dBi |    |

**Results:**

| Frequency | Maximum output power conducted [dBm] |            |            |
|-----------|--------------------------------------|------------|------------|
|           | 2404.0 MHz                           | 2427.0 MHz | 2479.3 MHz |
|           | 19.1                                 | 18.7       | 8.1        |




**Plots:**

**Plot 1:** lowest channel – 2404.0 MHz



**Plot 2:** middle channel – 2427.0 MHz



**Plot 3:** highest channel – 2479.3 MHz



**11.7 Detailed spurious emissions @ the band edge – conducted**

**Description:**

Measurement of the conducted band edge compliance. EUT is measured at the lower and upper band edge in single channel and hopping mode. The measurement is repeated for all modulations.

| Measurement parameters  |  |
|-------------------------|--|
| Detector                | Peak   |
| Sweep time              | Auto   |
| Resolution bandwidth    | 100 kHz  |
| Video bandwidth         | 300 kHz / 500 kHz  |
| Span                    | Lower Band Edge: 2395 – 2405 MHz<br>Upper Band Edge: 2478 – 2489 MHz |
| Trace mode              | Max hold   |
| Test setup              | See sub clause 6.4 A   |
| Measurement uncertainty | See sub clause 8   |

**Limits:**


| FCC   | IC |
|---|----|
| In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. |    |

**Results:**


| Scenario                      | Spurious band edge conducted [dB] |
|-------------------------------|-----------------------------------|
| Lower band edge – hopping off | > 20 dB                           |
| Lower band edge – hopping on  | > 20 dB                           |
| Upper band edge – hopping off | > 20 dB                           |
| Upper band edge – hopping on  | > 20 dB                           |

**Plots:**

**Plot 1:** Lower band edge – hopping on




**Plot 2:** Upper band edge – hopping on



**Plot 3: Lower band edge – hopping off**



**Plot 4: Upper band edge – hopping off**



## 11.8 Band edge compliance radiated

### Description:

Measurement of the radiated band edge compliance. The EUT is turned in the position that results in the maximum level at the band edge. Then a sweep over the corresponding restricted band is performed. The EUT is set to single channel mode and the transmit frequency is 2404.0 MHz for the lower restricted band and frequency 2479.3 MHz for the upper restricted band. Measurement distance is 3m.

| Measurement parameters  |  |
|-------------------------|--|
| Detector                | Peak / RMS   |
| Sweep time              | Auto   |
| Resolution bandwidth    | 1 MHz  |
| Video bandwidth         | 3 MHz  |
| Span                    | Lower Band: 2370 – 2400 MHz<br>Upper Band: 2480 – 2500 MHz |
| Trace mode              | Max hold   |
| Test setup              | See sub clause 6.2 B                                       |
| Measurement uncertainty | See sub clause 8   |

### Limits:

| FCC  | IC |
|--|----|
| Band edge compliance radiated  |    |
| In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)). |    |
| 54 dBµV/m AVG<br>74 dBµV/m Peak  |    |

**Results:**

| Scenario              | Band edge compliance radiated [dBµV/m] |
|-----------------------|--|
| Modulation            | MSK                                    |
| Lower restricted band | 62.4 (peak)<br>48.6* (AVG)             |
| Upper restricted band | 65.9 (peak)<br>52.1* (AVG)             |

\*Average correction factor:

$$F = 20 * \log (\text{dwell time}^* / 100 \text{ ms})$$

\*with Txon time as dwell time!


The maximum dwell time (see Chapter 11.4) is 20.4 ms.

In a period of 100 ms, we have a maximum of 1 transmission and that implies a correction factor for spurious measurement emissions:


$$F = 20 * \log (1 * 20.4 / 100) = -13.8 \text{ dB}$$

**Plots:**

**Plot 1:** Lower band edge, vertical & horizontal polarization, 18 dBm power setting



**Plot 2:** Upper band edge, vertical & horizontal polarization, 6 dBm power setting





## 11.9 Spurious emissions conducted

### Description:

Measurement of the conducted spurious emissions in transmit mode. The EUT is set to single channel mode.

| Measurement parameters  |                      |
|-------------------------|----------------------|
| Detector                | Peak                 |
| Sweep time              | Auto                 |
| Resolution bandwidth    | 100 kHz              |
| Video bandwidth         | 300 kHz              |
| Span                    | 9 kHz to 25 GHz      |
| Trace mode              | Max hold             |
| Test setup              | See sub clause 6.4 A |
| Measurement uncertainty | See sub clause 8     |

### Limits:


| FCC   | IC |
|---|----|
| TX spurious emissions conducted   |    |
| <p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required</p> |    |

**Results:**


| TX spurious emissions conducted  |  |                             |                                   |  |                     |
|--|--|-----------------------------|-----------------------------------|--|---------------------|
| f [MHz]  |  | amplitude of emission [dBm] | limit max. allowed emission power | actual attenuation below frequency of operation [dB] | results             |
| 2404.0   |  | 18.9                        | 30 dBm                            |  | Operating frequency |
| All detected emissions are below the -20 dBc criteria. Please take a look at the plot! |  |                             | -20 dBc                           |  | compliant           |
|  |  |                             |                                   |  |                     |
|  |  |                             |                                   |  |                     |
| 2427.0   |  | 18.7                        | 30 dBm                            |  | Operating frequency |
| All detected emissions are below the -20 dBc criteria. Please take a look at the plot! |  |                             | -20 dBc                           |  | compliant           |
|  |  |                             |                                   |  |                     |
|  |  |                             |                                   |  |                     |
| 2479.3   |  | 7.9                         | 30 dBm                            |  | Operating frequency |
| All detected emissions are below the -20 dBc criteria. Please take a look at the plot! |  |                             | -20 dBc                           |  | compliant           |
|  |  |                             |                                   |  |                     |
|  |  |                             |                                   |  |                     |

**Plots:**


**Plot 1: lowest channel – 2404.0 MHz**



**Plot 2: middle channel – 2427.0 MHz**



**Plot 3:** highest channel – 2479.3 MHz



### 11.10 Spurious emissions radiated below 30 MHz

**Description:**

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The EUT is set to single channel mode. The limits are recalculated to a measurement distance of 3 m according the ANSI C63.10.

| Measurement parameters  |  |
|-------------------------|--|
| Detector                | Peak / Quasi peak                          |
| Sweep time              | Auto                                       |
| Resolution bandwidth    | F < 150 kHz: 200 Hz<br>F > 150 kHz: 9 kHz  |
| Video bandwidth         | F < 150 kHz: 1 kHz<br>F > 150 kHz: 100 kHz |
| Span                    | 9 kHz to 30 MHz                            |
| Trace mode              | Max hold                                   |
| Test setup              | See sub clause 6.2 C                       |
| Measurement uncertainty | See sub clause 8                           |

**Limits:**


| FCC   |                         | IC                   |
|---|-------------------------|----------------------|
| TX spurious emissions radiated below 30 MHz |                         |                      |
| Frequency (MHz)                             | Field strength (dBµV/m) | Measurement distance |
| 0.009 – 0.490                               | 2400/F(kHz)             | 300                  |
| 0.490 – 1.705                               | 24000/F(kHz)            | 30                   |
| 1.705 – 30.0                                | 30                      | 30                   |

**Results:**


| TX spurious emissions radiated below 30 MHz [dBµV/m]        |          |                |
|---|----------|----------------|
| F [MHz]   | Detector | Level [dBµV/m] |
| All detected emissions are more than 20 dB below the limit. |          |                |
|   |          |                |
|   |          |                |

**Plots:**


**Plot 1:** 9 kHz to 30 MHz, 2404.0 MHz, transmit mode



**Plot 2:** 9 kHz to 30 MHz, 2427.0 MHz, transmit mode



**Plot 3:** 9 kHz to 30 MHz, 2479.3 MHz, transmit mode



**11.11 Spurious emissions radiated 30 MHz to 1 GHz**

**Description:**

Measurement of the radiated spurious emissions in transmit mode. The EUT is set to single channel mode.

| Measurement parameters  |                      |
|-------------------------|----------------------|
| Detector                | Peak / Quasi Peak    |
| Sweep time              | Auto                 |
| Resolution bandwidth    | 3 x VBW              |
| Video bandwidth         | 120 kHz              |
| Span                    | 30 MHz to 1 GHz      |
| Trace mode              | Max hold             |
| Test setup              | See sub clause 6.1 A |
| Measurement uncertainty | See sub clause 8     |


**Limits:**

| FCC  | IC                      |                      |
|--|-------------------------|----------------------|
| TX spurious emissions radiated   |                         |                      |
| In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |                         |                      |
| §15.209  |                         |                      |
| Frequency (MHz)  | Field strength (dBµV/m) | Measurement distance |
| 30 – 88  | 30.0                    | 10                   |
| 88 – 216   | 33.5                    | 10                   |
| 216 – 960  | 36.0                    | 10                   |
| Above 960  | 54.0                    | 3                    |



**Plots:** Transmit mode


**Plot 1:** 30 MHz to 1 GHz, TX mode, 2404 MHz, vertical & horizontal polarization



**Final results:**

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 34.016700       | 13.25              | 30.00          | 16.75       | 1000.0          | 120.000         | 101.0       | V   | 171.0         | 13.7       |
| 39.856200       | 10.96              | 30.00          | 19.04       | 1000.0          | 120.000         | 170.0       | V   | 260.0         | 14.0       |
| 43.791750       | 10.40              | 30.00          | 19.60       | 1000.0          | 120.000         | 101.0       | V   | 261.0         | 13.9       |
| 683.165400      | 18.88              | 36.00          | 17.12       | 1000.0          | 120.000         | 170.0       | V   | 260.0         | 21.4       |
| 758.126400      | 20.15              | 36.00          | 15.85       | 1000.0          | 120.000         | 170.0       | V   | 170.0         | 22.7       |
| 894.773550      | 21.37              | 36.00          | 14.63       | 1000.0          | 120.000         | 101.0       | H   | 280.0         | 24.0       |


**Plot 2:** 30 MHz to 1 GHz, TX mode, 2427.0 MHz, vertical & horizontal polarization



**Final results:**

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 35.580750       | 10.91              | 30.00          | 19.09       | 1000.0          | 120.000         | 98.0        | H   | 328.0         | 13.8       |
| 41.956950       | 11.05              | 30.00          | 18.95       | 1000.0          | 120.000         | 101.0       | V   | 56.0          | 14.0       |
| 44.685900       | 10.68              | 30.00          | 19.32       | 1000.0          | 120.000         | 101.0       | V   | 186.0         | 13.9       |
| 691.431450      | 18.94              | 36.00          | 17.06       | 1000.0          | 120.000         | 98.0        | H   | 43.0          | 21.5       |
| 755.105400      | 19.99              | 36.00          | 16.01       | 1000.0          | 120.000         | 185.0       | H   | 93.0          | 22.7       |
| 891.076800      | 21.37              | 36.00          | 14.63       | 1000.0          | 120.000         | 185.0       | V   | 93.0          | 24.0       |

**Plot 3:** 30 MHz to 1 GHz, TX mode, 2479.3 MHz , vertical & horizontal polarization




**Final results:**

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 34.005300       | 13.57              | 30.00          | 16.43       | 1000.0          | 120.000         | 101.0       | V   | 268.0         | 13.7       |
| 46.222200       | 10.17              | 30.00          | 19.83       | 1000.0          | 120.000         | 101.0       | V   | 181.0         | 13.5       |
| 607.775400      | 18.24              | 36.00          | 17.76       | 1000.0          | 120.000         | 185.0       | V   | 165.0         | 20.8       |
| 722.888100      | 19.52              | 36.00          | 16.48       | 1000.0          | 120.000         | 185.0       | V   | 264.0         | 22.1       |
| 816.595650      | 20.38              | 36.00          | 15.62       | 1000.0          | 120.000         | 185.0       | V   | 143.0         | 23.0       |
| 957.847800      | 21.58              | 36.00          | 14.42       | 1000.0          | 120.000         | 101.0       | H   | 257.0         | 24.3       |

**Plots:** Receiver mode

**Plot 1:** 30 MHz to 1 GHz, RX / idle – mode, vertical & horizontal polarization



**Final results:**

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|------------|
| 36.036750       | 11.04              | 30.00          | 18.96       | 1000.0          | 120.000         | 98.0        | H   | 0.0           | 13.8       |
| 45.689550       | 10.51              | 30.00          | 19.49       | 1000.0          | 120.000         | 185.0       | H   | 353.0         | 13.7       |
| 590.370750      | 17.31              | 36.00          | 18.69       | 1000.0          | 120.000         | 185.0       | V   | 174.0         | 20.4       |
| 725.875800      | 19.54              | 36.00          | 16.46       | 1000.0          | 120.000         | 98.0        | V   | 121.0         | 22.1       |
| 836.488050      | 20.70              | 36.00          | 15.30       | 1000.0          | 120.000         | 100.0       | H   | 272.0         | 23.3       |
| 920.521500      | 21.57              | 36.00          | 14.43       | 1000.0          | 120.000         | 185.0       | H   | 109.0         | 24.2       |

**11.12 Spurious emissions radiated above 1 GHz**

**Description:**

Measurement of the radiated spurious emissions in transmit mode. The EUT is set to single channel mode.

| Measurement parameters  |   |
|-------------------------|---|
| Detector                | Peak / RMS  |
| Sweep time              | Auto  |
| Resolution bandwidth    | 1 MHz   |
| Video bandwidth         | 3 x RBW   |
| Span                    | 1 GHz to 26 GHz   |
| Trace mode              | Max hold  |
| Test setup              | See sub clause 6.2 A (1 GHz – 18 GHz)<br>See sub clause 6.3 A (18 GHz – 26 GHz) |
| Measurement uncertainty | See sub clause 8  |

**Limits:**

| FCC  | IC                      |                      |
|--|-------------------------|----------------------|
| TX spurious emissions radiated   |                         |                      |
| In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |                         |                      |
| §15.209  |                         |                      |
| Frequency (MHz)  | Field strength (dBµV/m) | Measurement distance |
| Above 960  | 54.0                    | 3                    |

**Results:** Transmitter mode

| TX spurious emissions radiated [dBµV/m] |          |                |            |          |                |            |          |                |
|---|----------|----------------|------------|----------|----------------|------------|----------|----------------|
| 2404.0 MHz                              |          |                | 2427.0 MHz |          |                | 2479.3 MHz |          |                |
| F [MHz]                                 | Detector | Level [dBµV/m] | F [MHz]    | Detector | Level [dBµV/m] | F [MHz]    | Detector | Level [dBµV/m] |
| 2247                                    | Peak     | 58.1           | 2271       | Peak     | 57.6           | 2323       | Peak     | 53.0           |
|   | AVG      | 53.6           |            | AVG      | 46.5           |            | AVG      | 43.7           |
| 4808                                    | Peak     | 62.9           | 4954       | Peak     | 60.7           | 4958       | Peak     | 61.3           |
|   | AVG      | 49.1**         |            | AVG      | 46.9**         |            | AVG      | 47.5**         |
| 7212                                    | Peak     | *              | 7280       | Peak     | 61.1           | 7437       | Peak     | 64.3           |
|   | AVG      |                |            | AVG      | 47.3**         |            | AVG      | 50.5**         |
| 9616                                    | Peak     | *              | 9706       | Peak     | *              | 9916       | Peak     | *              |
|   | AVG      |                |            | AVG      |                |            | AVG      |                |
| 12020                                   | Peak     | 59.4           | 12134      | Peak     | 55.7           | 12396      | Peak     | 62.6           |
|   | AVG      | 45.6**         |            | AVG      | 41.9**         |            | AVG      | 48.8**         |
|   | Peak     |                |            | Peak     |                |            | Peak     |                |
|   | AVG      |                |            | AVG      |                |            | AVG      |                |

\*Not rated because the emission frequency is not in a restricted band.

\*\*Average correction factor:

$$F = 20 * \log(\text{dwell time}^* / 100 \text{ ms})$$

\*with Txon time as dwell time!

The maximum dwell time (see Chapter 11.4) is 20.4 ms.

In a period of 100 ms, we have a maximum of 1 transmission and that implies a correction factor for spurious measurement emissions:

$$F = 20 * \log(1 * 20.4 / 100) = -13.8 \text{ dB}$$


**Results:** Receiver mode

| RX spurious emissions radiated [dBµV/m] |          |                |
|---|----------|----------------|
| F [MHz]                                 | Detector | Level [dBµV/m] |
| 4960                                    | Peak     | 51.0           |
|   | AVG      | 44.2           |

**Note:** The limit was recalculated with 20 dB / decade (Part 15.31) for all radiated spurious emissions 30 MHz to 1 GHz from 3 meter limit to a 10 meter distance. (40dB/decade for emissions < 30MHz)


**Plots:** Transmitter mode

**Plot 1:** 1 GHz to 18 GHz, TX mode, 2404.0 MHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

**Plot 2:** 18 GHz to 26 GHz, TX mode, 2404.0 MHz, vertical & horizontal polarization




**Plot 3:** 1 GHz to 18 GHz, TX mode, 2427.0 MHz, vertical & horizontal polarization



The carrier signal is notched with a 2.4 GHz band rejection filter.


**Plot 4:** 18 GHz to 26 GHz, TX mode, 2427.0 MHz, vertical & horizontal polarization



Date: 10.AUG.2017 09:55:56




**Plot 5:** 1 GHz to 18 GHz, TX mode, 2479.3 MHz, vertical & horizontal polarization



The carrier signal is notched with a 2.4 GHz band rejection filter.


**Plot 6:** 18 GHz to 26 GHz, TX mode, 2479.3 MHz, vertical & horizontal polarization




Date: 10.AUG.2017 09:57:02

**Plots:** Receiver mode

**Plot 1:** 1 GHz to 18 GHz, RX / idle – mode, vertical & horizontal polarization



**Plot 2:** 18 GHz to 26 GHz, RX / idle – mode, vertical & horizontal polarization



Date: 10.AUG.2017 09:57:46

**11.13 Spurious emissions conducted below 30 MHz (AC conducted)**

**Description:**

Measurement of the conducted spurious emissions in transmit mode below 30 MHz. The EUT is set to single channel mode and the transmit channel is channel 39. This measurement is representative for all channels and modes. If critical peaks are found channel 00 and channel 78 will be measured too. The measurement is performed in the mode with the highest output power. Both power lines, phase and neutral line, are measured. Found peaks are remeasured with average and quasi peak detection to show compliance to the limits.

| Measurement parameters  |  |
|-------------------------|--|
| Detector                | Peak - Quasi peak / average                |
| Sweep time              | Auto                                       |
| Resolution bandwidth    | F < 150 kHz: 200 Hz<br>F > 150 kHz: 9 kHz  |
| Video bandwidth         | F < 150 kHz: 1 kHz<br>F > 150 kHz: 100 kHz |
| Span                    | 9 kHz to 30 MHz                            |
| Trace mode              | Max hold                                   |
| Test setup              | See sub clause 6.5. A                      |
| Measurement uncertainty | See sub clause 8                           |

**Limits:**

| FCC                                      |                     | IC               |  |
|--|---------------------|------------------|--|
| TX spurious emissions conducted < 30 MHz |                     |                  |  |
| Frequency (MHz)                          | Quasi-peak (dBµV/m) | Average (dBµV/m) |  |
| 0.15 – 0.5                               | 66 to 56*           | 56 to 46*        |  |
| 0.5 – 5                                  | 56                  | 46               |  |
| 5 – 30.0                                 | 60                  | 50               |  |


\*Decreases with the logarithm of the frequency

**Results:**

| Spurious emissions conducted < 30 MHz [dBµV/m] |          |                |
|--|----------|----------------|
| F [MHz]  | Detector | Level [dBµV/m] |
| No emissions detected                          |          |                |
|  |          |                |
|  |          |                |

**Plots:**


**Plot 1:** 150 kHz to 30 MHz, phase line



**Final results:**

| Frequency<br>MHz | Quasi peak<br>level<br>dBµV | Margin<br>quasi peak<br>dB | Limit QP<br>dBµV | Average<br>level<br>dBµV | Margin<br>average<br>dB | Limit AV<br>dBµV |
|------------------|-----------------------------|----------------------------|------------------|--------------------------|-------------------------|------------------|
| 0.152919         | 36.26                       | 29.58                      | 65.840           | 29.48                    | 26.44                   | 55.917           |
| 0.513228         | 28.94                       | 27.06                      | 56.000           | 22.06                    | 23.94                   | 46.000           |
| 0.598676         | 28.83                       | 27.17                      | 56.000           | 21.98                    | 24.02                   | 46.000           |
| 0.754911         | 28.31                       | 27.69                      | 56.000           | 21.51                    | 24.49                   | 46.000           |
| 1.329878         | 27.66                       | 28.34                      | 56.000           | 20.83                    | 25.17                   | 46.000           |
| 1.407881         | 27.61                       | 28.39                      | 56.000           | 20.78                    | 25.22                   | 46.000           |
| 4.445538         | 27.37                       | 28.63                      | 56.000           | 20.44                    | 25.56                   | 46.000           |
| 4.908934         | 27.28                       | 28.72                      | 56.000           | 20.45                    | 25.55                   | 46.000           |
| 26.397614        | 28.71                       | 31.29                      | 60.000           | 21.87                    | 28.13                   | 50.000           |
| 26.504307        | 28.70                       | 31.30                      | 60.000           | 21.89                    | 28.11                   | 50.000           |
| 26.789251        | 28.82                       | 31.18                      | 60.000           | 21.87                    | 28.13                   | 50.000           |
| 26.853209        | 28.63                       | 31.37                      | 60.000           | 21.85                    | 28.15                   | 50.000           |

Plot 2: 150 kHz to 30 MHz, neutral line



Final results:

| Frequency<br>MHz | Quasi peak<br>level<br>dBµV | Margin<br>quasi peak<br>dB | Limit QP<br>dBµV | Average<br>level<br>dBµV | Margin<br>average<br>dB | Limit AV<br>dBµV |
|------------------|-----------------------------|----------------------------|------------------|--------------------------|-------------------------|------------------|
| 0.151722         | 36.36                       | 29.55                      | 65.905           | 29.45                    | 26.50                   | 55.951           |
| 0.467075         | 29.21                       | 27.35                      | 56.566           | 22.35                    | 24.59                   | 46.941           |
| 0.541767         | 28.75                       | 27.25                      | 56.000           | 21.90                    | 24.10                   | 46.000           |
| 0.633190         | 28.45                       | 27.55                      | 56.000           | 21.66                    | 24.34                   | 46.000           |
| 1.464873         | 27.62                       | 28.38                      | 56.000           | 20.76                    | 25.24                   | 46.000           |
| 1.623304         | 27.49                       | 28.51                      | 56.000           | 20.68                    | 25.32                   | 46.000           |
| 2.058110         | 27.46                       | 28.54                      | 56.000           | 20.55                    | 25.45                   | 46.000           |
| 3.451067         | 27.23                       | 28.77                      | 56.000           | 20.45                    | 25.55                   | 46.000           |
| 24.114746        | 28.58                       | 31.42                      | 60.000           | 21.78                    | 28.22                   | 50.000           |
| 24.625695        | 28.72                       | 31.28                      | 60.000           | 21.83                    | 28.17                   | 50.000           |
| 24.754864        | 28.60                       | 31.40                      | 60.000           | 21.98                    | 28.02                   | 50.000           |
| 24.787585        | 28.92                       | 31.08                      | 60.000           | 21.99                    | 28.01                   | 50.000           |

## 12 Observations

No observations except those reported with the single test cases have been made.

**Annex A Document history**

| Version | Applied changes                          | Date of release |
|---------|--|-----------------|
|         | Initial release                          | 2017-08-10      |
| A       | Model name, FCC ID and IC number changed | 2017-09-07      |
| B       | HVIN changed                             | 2017-09-12      |
| C       | Editorial changes                        | 2017-09-25      |
| D       | AC conducted results added               | 2017-10-25      |

**Annex B Glossary**

|                        |  |
|------------------------|--|
| <b>EUT</b>             | Equipment under test                               |
| <b>DUT</b>             | Device under test                                  |
| <b>UUT</b>             | Unit under test                                    |
| <b>GUE</b>             | GNSS User Equipment                                |
| <b>ETSI</b>            | European Telecommunications Standard Institute     |
| <b>EN</b>              | European Standard                                  |
| <b>FCC</b>             | Federal Communication Commission                   |
| <b>FCC ID</b>          | Company Identifier at FCC                          |
| <b>IC</b>              | Industry Canada                                    |
| <b>PMN</b>             | Product marketing name                             |
| <b>HMN</b>             | Host marketing name                                |
| <b>HVIN</b>            | Hardware version identification number             |
| <b>FVIN</b>            | Firmware version identification number             |
| <b>EMC</b>             | Electromagnetic Compatibility                      |
| <b>HW</b>              | Hardware   |
| <b>SW</b>              | Software   |
| <b>Inv. No.</b>        | Inventory number                                   |
| <b>S/N or SN</b>       | Serial number                                      |
| <b>C</b>               | Compliant  |
| <b>NC</b>              | Not compliant                                      |
| <b>NA</b>              | Not applicable                                     |
| <b>NP</b>              | Not performed                                      |
| <b>PP</b>              | Positive peak                                      |
| <b>QP</b>              | Quasi peak   |
| <b>AVG</b>             | Average  |
| <b>OC</b>              | Operating channel                                  |
| <b>OCW</b>             | Operating channel bandwidth                        |
| <b>OBW</b>             | Occupied bandwidth                                 |
| <b>OOB</b>             | Out of band  |
| <b>DFS</b>             | Dynamic frequency selection                        |
| <b>CAC</b>             | Channel availability check                         |
| <b>OP</b>              | Occupancy period                                   |
| <b>NOP</b>             | Non occupancy period                               |
| <b>DC</b>              | Duty cycle   |
| <b>PER</b>             | Packet error rate                                  |
| <b>CW</b>              | Clean wave   |
| <b>MC</b>              | Modulated carrier                                  |
| <b>WLAN</b>            | Wireless local area network                        |
| <b>RLAN</b>            | Radio local area network                           |
| <b>DSSS</b>            | Dynamic sequence spread spectrum                   |
| <b>OFDM</b>            | Orthogonal frequency division multiplexing         |
| <b>FHSS</b>            | Frequency hopping spread spectrum                  |
| <b>GNSS</b>            | Global Navigation Satellite System                 |
| <b>C/N<sub>0</sub></b> | Carrier to noise-density ratio, expressed in dB-Hz |



**Annex C Accreditation Certificate**

| first page  | last page  |  |  |  |
|---|--|--|--|--|
|  <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Beliehene gemäß § 8 Absatz 1 AkkStelleG i.V.m. § 1 Absatz 1 AkkStelleGBV<br/>                 Unterzeichnerin der Multilateralen Abkommen<br/>                 von EA, ILAC und IAF zur gegenseitigen Anerkennung</p> <p><b>Akkreditierung</b> </p> <p>Die Deutsche Akkreditierungsstelle GmbH bestätigt hiermit, dass das Prüflaboratorium</p> <p><b>CTC advanced GmbH</b><br/>                 Untertürkheimer Straße 6-10, 66117 Saarbrücken</p> <p>die Kompetenz nach DIN EN ISO/IEC 17025:2005 besitzt, Prüfungen in folgenden Bereichen durchzuführen:</p> <ul style="list-style-type: none"> <li>Funk</li> <li>Mobilfunk (GSM / DCS) + OTA</li> <li>Elektromagnetische Verträglichkeit (EMV)</li> <li>Produktsicherheit</li> <li>SAH / EMF</li> <li>Umwelt</li> <li>Smart Card Technology</li> <li>Bluetooth®</li> <li>Automotive</li> <li>Wi-Fi Services</li> <li>Kanadische Anforderungen</li> <li>US-Anforderungen</li> <li>Akustik</li> <li>Near Field Communication (NFC)</li> </ul> <p>Die Akkreditierungsurkunde gilt nur in Verbindung mit dem Bescheid vom 25.11.2016 mit der Akkreditierungsnummer D-PL-12076-01 und ist gültig bis 17.01.2018. Sie besteht aus diesem Deckblatt, der Rückseite des Deckblatts und der folgenden Anlage mit insgesamt 63 Seiten.</p> <p>Registrierungsnummer der Urkunde: D-PL-12076-01-01</p> <p>Frankfurt, 25.11.2016</p> <p><br/>                 Im Auftrag Dipl.-Ing. Ralf Egner<br/>                 Abteilungsleiter</p> <p><small>Siehe Hinweise auf der Rückseite</small></p> | <p>Deutsche Akkreditierungsstelle GmbH</p> <table border="0"> <tr> <td>Standort Berlin<br/>Spittelmarkt 10<br/>10117 Berlin</td> <td>Standort Frankfurt am Main<br/>Europa-Allee 52<br/>60327 Frankfurt am Main</td> <td>Standort Braunschweig<br/>Bundesallee 100<br/>38116 Braunschweig</td> </tr> </table> <p>Die auszugsweise Veröffentlichung der Akkreditierungsurkunde bedarf der vorherigen schriftlichen Zustimmung der Deutsche Akkreditierungsstelle GmbH (DAkKS). Ausgenommen davon ist die separate Weiterverbreitung des Deckblatts durch die umeitig genannte Konformitätsbewertungsstelle in unveränderter Form.</p> <p>Es darf nicht der Anschein erweckt werden, dass sich die Akkreditierung auch auf Bereiche erstreckt, die über den durch die DAkKS bestätigten Akkreditierungsbereich hinausgehen.</p> <p>Die Akkreditierung erfolgte gemäß des Gesetzes über die Akkreditierungsstelle (AkkStelleG) vom 31. Juli 2009 (BGBl. I S. 2625) sowie der Verordnung (EG) Nr. 765/2008 des Europäischen Parlaments und des Rates vom 9. Juli 2008 über die Vorschriften für die Akkreditierung und Marktüberwachung im Zusammenhang mit der Vermarktung von Produkten (Abi. L 218 vom 9. Juli 2008, S. 30). Die DAkKS ist Unterzeichnerin der Multilateralen Abkommen zur gegenseitigen Anerkennung der European co-operation for Accreditation (EA), des International Accreditation Forum (IAF) und der International Laboratory Accreditation Cooperation (ILAC). Die Unterzeichner dieser Abkommen erkennen ihre Akkreditierungen gegenseitig an.</p> <p>Der aktuelle Stand der Mitgliedschaft kann folgenden Webseiten entnommen werden:<br/>                 EA: <a href="http://www.european-accreditation.org">www.european-accreditation.org</a><br/>                 ILAC: <a href="http://www.ilac.org">www.ilac.org</a><br/>                 IAF: <a href="http://www.iaf.eu">www.iaf.eu</a></p> | Standort Berlin<br>Spittelmarkt 10<br>10117 Berlin             | Standort Frankfurt am Main<br>Europa-Allee 52<br>60327 Frankfurt am Main | Standort Braunschweig<br>Bundesallee 100<br>38116 Braunschweig |
| Standort Berlin<br>Spittelmarkt 10<br>10117 Berlin  | Standort Frankfurt am Main<br>Europa-Allee 52<br>60327 Frankfurt am Main   | Standort Braunschweig<br>Bundesallee 100<br>38116 Braunschweig |  |  |

**Note: The current certificate including annex is published on the website (link see below) of the Accreditation Body DAkKS or may be received by CTC advanced GmbH on request**

<http://www.dakks.de/as/ast/d/D-PL-12076-01-01.pdf>

<http://www.dakks.de/as/ast/d/D-PL-12076-01-02.pdf>