



Test Report

Product Name : Tire Pressure Monitoring System
 Model No. : W401
 FCC ID. : W55FRSFM1B2

Applicant : Oro Technology Co., LTD
 Address : 3F, No.32-1, 24th Road, Industrial Park, Taichung 408,
 Taiwan

Date of Receipt : 2011/12/19
 Issued Date : 2012/01/04
 Report No. : 11C351R-RFUSP41V01
 Report Version : V2.0

The test results relate only to the samples tested.
 The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.
 This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Test Report Certification

Issued Date : 2012/01/04

Report No. : 11C351R-RFUSP41V01



Product Name : Tire Pressure Monitoring System
 Applicant : Oro Technology Co., LTD
 Address : 3F, No.32-1, 24th Road, Industrial Park, Taichung 408,
 Taiwan
 Manufacturer : Oro Technology Co., LTD
 Model No. : W401
 FCC ID. : W55FRSFM1B2
 EUT Voltage : DC 3V
 Trade Name : ORO
 Applicable Standard : FCC 15 Subpart C Section 15.231(e): 2010
 Test Result : Complied

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By :

Sandy Chuang

(Sandy Chuang / Adm. Specialist)

Tested By :

Quale Tang

(Quale Tang / Engineer)

Approved By :

Roy Wang

(Roy Wang / Manager)

TABLE OF CONTENTS

Description	Page
1. General Information.....	4
1.1. EUT Description	4
1.2. Operation Description.....	5
1.3. Test Mode	6
1.4. Tested System Details	7
1.5. Configuration of tested System	7
1.6. EUT Exercise Software	7
1.7. Test Facility.....	8
2. Radiated Emission	9
2.1. Test Equipment.....	9
2.2. Test Setup	10
2.3. Limits	11
2.4. Test Procedure	12
2.5. Test Specification.....	12
2.6. Uncertainty	12
2.7. Test Result.....	13
2.8. Test Photo	18
3. Occupied Bandwidth.....	20
3.1. Test Equipment.....	20
3.2. Test Setup	20
3.3. Limits	20
3.4. Test Specification.....	20
3.5. Uncertainty	20
3.6. Test Result.....	21
4. Duty cycle.....	22
4.1. Test Equipment.....	22
4.2. Test Setup	22
4.3. Limits	22
4.4. Test Specification.....	22
4.5. Uncertainty	22
4.6. Test Result.....	23
5. Transmitter time.....	24
5.1. Test Equipment.....	24
5.2. Test Setup	24
5.3. Limits	24
5.4. Test Specification.....	24
5.5. Uncertainty	24
5.6. Test Result.....	25
Attachment.....	27
EUT Photograph.....	27

1. General Information

1.1. EUT Description

Product Name	Tire Pressure Monitoring System
Trade Name	ORO
Model No.	W401
Frequency Range	433.92 MHz
Antenna Gain	0dBi
Channel Number	1
Type of Modulation	FSK, ASK
Channel Control	Auto
Antenna Type	monopole antenna

Component	
Aluminum Value	4Set
Holder	1Set
Car Adapter	Oro Technology Co., LTD / P0PL00001 I/P: DC 9V~16V O/P: DC 8V/0.5A Cable In: Non-Shielded, 1.4m Cable Out: Non-Shielded, 1.4m

Working Frequency of Each Channel	
Channel	Frequency
001	433.92 MHz

Note:

1. This device is a Tire Pressure Monitoring System included a 433.92MHz transceiver function.
2. These tests are conducted on a sample for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.231.
3. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.
4. This device is a composite device in accordance with Part 15 regulations. The function receiving was measured and made a test report that the report number is 11C351R-RFUSP37V02 under Declaration of Conformity.

1.3. Test Mode

QuieTek verified the construction and function in typical operation. All the test modes are performed in normal operation and are defined as:

Pre-Test Mode	
TX	Mode 1: Transmit
Final Test Mode	
TX	Mode 1: Transmit


Emission	
Performed Item	
Conducted Emission	No
Radiated Emission	Yes
Occupied Bandwidth	Yes
Duty cycle	Yes
Transmitter time	Yes

1.4. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
N/A					

1.5. Configuration of tested System



1.6. EUT Exercise Software

1	Setup the EUT as shown in section 1.5.
2	The EUT will transmit automatically.
3	Verify that the EUT works properly.

1.7. Test Facility

Ambient conditions in the laboratory:

Items	Test Item	Required (IEC 68-1)	Actual
Temperature (°C)	FCC PART 15 C 15.231 Radiated Emission	15 - 35	22
Humidity (%RH)		25 - 75	55
Barometric pressure (mbar)		860 - 1060	950-1000
Temperature (°C)	FCC PART 15 C 15.231 Occupied Bandwidth	15 - 35	22
Humidity (%RH)		25 - 75	55
Barometric pressure (mbar)		860 - 1060	950-1000
Temperature (°C)	FCC PART 15 C 15.231 Duty Cycle	15 - 35	22
Humidity (%RH)		25 - 75	55
Barometric pressure (mbar)		860 - 1060	950-1000
Temperature (°C)	FCC PART 15 C 15.231 Transmitter Time	15 - 35	22
Humidity (%RH)		25 - 75	55
Barometric pressure (mbar)		860 - 1060	950-1000

Site Description: September 27, 2010 File on
 Federal Communications Commission
 Laboratory Division
 7435 Oakland Mills Road
 Columbia, MD 21046
 Registration Number: 365520
 Accredited by TAF
 Accreditation Number: 1313
 Effective through: December 27, 2013



Accredited by NVLAP
 NVLAP Lab Code: 200347-0
 Effective through: September 30, 2012



Site Name: Quietek Corporation

Site Address: No.75-1, Wang-Yeh Valley, Yung-Hsing,
 Chiung-Lin, Hsin-Chu County,
 Taiwan, R.O.C.
 TEL : 886-3-592-8858 / FAX : 886-3-592-8859
 E-Mail : service@quietek.com

2. Radiated Emission

2.1. Test Equipment

The following test equipments are used during the test:


Radiated Emission / CB1

Instrument	Manufacturer	Type No.	Serial No	Next Cal. Date
Bilog Antenna	SCHAFFNER	CBL6112B	2895	2012/08/14
Double Ridged Guide Horn Antenna	Schwarzback	BBHA 9120D	743	2012/02/24
Pre-Amplifier	MITEQ	AMF-4D-005180 -24-10P	888003	2012/12/05
Pre-Amplifier	QuieTek	AP-025C	CHM-0706049	2012/03/10
Spectrum Analyzer	Agilent	E4440A	MY46187335	2012/01/06
Coaxial Cable	Huber+Suhner AG	Sucoflex 102	25623/2	2012/03/21


Note: 1. All equipments that need to calibrate are with calibration period of 1 year.

2.2. Test Setup

Under 1GHz Test Setup:



Above 1GHz Test Setup:



2.3. Limits

➤ Fundamental and Harmonics Emission Limits

FCC Part 15 Subpart C Paragraph 15.231(e) Limits				
Fundamental Frequency MHz	Field Strength of Fundamental		Field Strength of Harmonics	
	uV/m	dBuV/m	uV/m	dBuV/m
40.66-40.70	1000	60	100	40
70-130	500	53.98	50	33,98
130-174	500-1500	53.98-63.52	50-150	33.98-43.52
174-260	1500	63.52	150	43.52
260-470	1500-5000	53.52-73.98	150-500	33.52-53.98
above 470	5000	73.98	500	53.98

- Remarks:
1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
 2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

➤ Spurious electric field strength limits

FCC Part 15 Subpart C Paragraph 15.209 Limits			
Frequency MHz	uV/m	dBuV/m	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	See Remark ¹	300
0.490-1.705	24000/F(kHz)	See Remark ¹	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

- Remarks :
1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
 2. In the Above Table, the tighter limit applies at the band edges.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

2.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

Radiated emission measurements below 1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB beamwidth of the antenna.

The worst radiated emission is measured on the Final Measurement.

The frequency range from 30MHz to 10th harmonics is checked.

2.5. Test Specification

According to FCC Part 15 Subpart C Paragraph 15.231(e): 2010

2.6. Uncertainty

± 3.8 dB below 1GHz

± 3.9 dB above 1GHz

2.7. Test Result

Product	Tire Pressure Monitoring System		
Test Item	Fundamental Radiated Emission		
Test Mode	Mode 1: Transmit		
Date of Test	2012/01/04	Test Site	CB1

Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Peak Measurement Level (dBuV/m)	Average Measurement Level (dBuV/m)	Average Limit (dBuV/m)
Horizontal					
433.920 (X-axis)	15.631	71.740	87.372	66.172	72.870
433.920 (Y-axis)	15.629	56.798	72.427	51.227	72.870
433.920 (Z-axis)	15.631	64.850	80.481	59.281	72.870
Vertical					
433.920 (X-axis)	15.631	59.380	75.012	53.812	72.870
433.920 (Y-axis)	15.630	68.252	83.882	62.682	72.870
433.920 (Z-axis)	15.631	64.441	80.072	58.872	72.870

Note1:

Peak Measurement Level = Reading Level + Correct Factor


Average Measurement Level = Peak Measurement Level + 20Log (Duty Cycle)

Duty Cycle=(Ton/(Ton+Toff)) = 8.7/100 = 0.087

20*Log(Duty Cycle) = -21.20

30MHz-1GHz Spurious :

Site : CB1	Time : 2011/12/20 - 15:00
Limit : NCC_3.4.2_H_433.92MHz_03M_PK	Margin : 6
Probe : CB1_FCC_EFS_30-1G-1_0901 - HORIZONTAL	Power : DC 3V
EUT : Tire Pressure Monitoring System	Note : 433.92MHz (X-axis)




	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	133.467	-12.568	27.469	14.901	-57.969	72.870	PEAK
2	181.158	-14.715	31.165	16.450	-56.420	72.870	PEAK
3	362.225	-8.462	22.267	13.806	-59.064	72.870	PEAK
4	550.567	-4.724	23.345	18.620	-54.250	72.870	PEAK
5	717.892	-3.705	22.967	19.262	-53.608	72.870	PEAK
6	* 868.020	-2.211	47.080	44.869	-28.001	72.870	PEAK

Note:

1. All Reading Levels are Peak value.
2. “ * ”, means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Site : CB1	Time : 2011/12/20 - 15:02
Limit : NCC_3.4.2_H_433.92MHz_03M_PK	Margin : 6
Probe : CB1_FCC_EFS_30-1G-1_0901 - VERTICAL	Power : DC 3V
EUT : Tire Pressure Monitoring System	Note : 433.92MHz (X-axis)




	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	133.467	-12.568	31.085	18.517	-54.353	72.870	PEAK
2	161.758	-14.003	34.934	20.931	-51.939	72.870	PEAK
3	181.158	-14.715	32.577	17.862	-55.008	72.870	PEAK
4	571.583	-4.556	23.027	18.470	-54.400	72.870	PEAK
5	720.317	-3.673	22.525	18.851	-54.019	72.870	PEAK
6	* 867.840	-2.212	45.080	42.868	-30.002	72.870	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Above 1GHz Spurious:

Site : CB1	Time : 2011/12/20 - 10:48
Limit : FCC_SpartC_15.231(e)_H_433.92MHz_03M_PK	Margin : 6
Probe : CB1_FCC_EFS_1-18G-1_0901 - HORIZONTAL	Power : DC 3V
EUT : Tire Pressure Monitoring System	Note : 433.92MHz (X-axis)




	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	1301.340	-8.558	67.550	58.992	-15.008	74.000	PEAK
2	* 1735.510	-7.764	75.540	67.776	-5.094	72.870	PEAK
3	2168.930	-5.619	64.830	59.211	-13.659	72.870	PEAK
4	2603.280	-4.328	66.940	62.612	-10.258	72.870	PEAK
5	3037.750	-3.049	64.140	61.091	-11.779	72.870	PEAK
6	3471.660	-1.669	59.160	57.491	-15.379	72.870	PEAK
7	3905.670	-0.478	51.400	50.922	-23.078	74.000	PEAK
8	4339.730	0.461	58.580	59.042	-14.958	74.000	PEAK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. “ * ”, means this data is the worst emission level.
4. Measurement Level = Reading Level + Correct Factor.
5. Average Measurement Level = Peak Measurement Level + 20Log (Duty Cycle)
 Duty Cycle=(Ton/(Ton+Toff)) = 8.8/100 = 0.088
 20*Log(Duty Cycle) = -21.11
5. The average measurement was not performed when the peak measured data under the limit of peak detection.

Site : CB1	Time : 2011/12/20 - 10:47
Limit : FCC_SpartC_15.231(e)_H_433.92MHz_03M_PK	Margin : 6
Probe : CB1_FCC_EFS_1-18G-1_0901 - VERTICAL	Power : DC 3V
EUT : Tire Pressure Monitoring System	Note : 433.92MHz (X-axis)



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	1301.560	-8.557	62.600	54.043	-19.957	74.000	PEAK
2	* 1735.210	-7.765	72.660	64.895	-7.975	72.870	PEAK
3	2169.400	-5.617	59.500	53.883	-18.987	72.870	PEAK
4	2603.810	-4.328	60.370	56.043	-16.827	72.870	PEAK
5	3037.100	-3.051	55.010	51.959	-20.911	72.870	PEAK
6	3472.460	-1.666	55.820	54.154	-18.716	72.870	PEAK
7	3906.380	-0.477	48.770	48.294	-25.706	74.000	PEAK
8	4339.608	0.461	59.320	59.781	-14.219	74.000	PEAK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. “ * ”, means this data is the worst emission level.
4. Measurement Level = Reading Level + Correct Factor.
5. Average Measurement Level = Peak Measurement Level + 20Log (Duty Cycle)
 $Duty\ Cycle = (Ton / (Ton + Toff)) = 8.8 / 100 = 0.088$
 $20 * Log(Duty\ Cycle) = -21.11$
5. The average measurement was not performed when the peak measured data under the limit of peak detection.

3. Occupied Bandwidth

3.1. Test Equipment


The following test equipments are used during the radiated emission tests:

Occupied Bandwidth / SR7

Instrument	Manufacturer	Model No.	Serial No	Next Cal. Date
Spectrum Analyzer	R&S	FSP	100561	2012/01/06

Note: 1. All equipments that need to calibrate are with calibration period of 1 year.

3.2. Test Setup



3.3. Limits

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

3.4. Test Specification

According to FCC Part 15 Subpart C Paragraph 15.231(e): 2010


3.5. Uncertainty

± 150Hz

3.6. Test Result

Product	Tire Pressure Monitoring System		
Test Item	Occupied Bandwidth		
Test Mode	Mode 1: Transmit		
Date of Test	2011/12/21	Test Site	SR7

Center Frequency	433.92 MHz
Allowable Bandwidth (70-900 MHz: 0.25%, Above 900MHz: 0.5%)	1084.8 KHz
Bandwidth at 20dB down (Max)	775KHz
Result	PASS



Date: 21.DEC.2011 11:35:56

4. Duty cycle

4.1. Test Equipment


The following test equipments are used during the radiated emission tests:

Duty cycle / SR7

Instrument	Manufacturer	Model No.	Serial No	Next Cal. Date
Spectrum Analyzer	R&S	FSP	100561	2012/01/06

Note: 1. All equipments that need to calibrate are with calibration period of 1 year.

4.2. Test Setup



4.3. Limits

N/A

4.4. Test Specification

According to FCC Part 15 Subpart C Paragraph 15.231(e): 2010


4.5. Uncertainty

± 25msec

4.6. Test Result

Product	Tire Pressure Monitoring System		
Test Item	Duty Cycle		
Test Mode	Mode 1: Transmit		
Date of Test	2011/12/21	Test Site	SR7

Center Frequency	433.92 MHz
Ton= 8.70ms	
Ton+Toff= 100ms	
Duty Cycle= 0.087/100%	8.70%



5. Transmitter time

5.1. Test Equipment


The following test equipments are used during the radiated emission tests:

Transmitter time / SR7

Instrument	Manufacturer	Model No.	Serial No	Next Cal. Date
Spectrum Analyzer	R&S	FSP	100561	2012/01/06

Note: 1. All equipments that need to calibrate are with calibration period of 1 year.

5.2. Test Setup



5.3. Limits

The duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

5.4. Test Specification

According to FCC Part 15 Subpart C Paragraph 15.231(e): 2010

5.5. Uncertainty

± 25msec

5.6. Test Result

Product	Tire Pressure Monitoring System		
Test Item	Transmitter time		
Test Mode	Mode 1: Transmit		
Date of Test	2011/12/21	Test Site	SR7

Frequency (MHz)	Transmitter time (ms.)		Silent period (sec.)	
	Measure value	Limit	Measure value	Limit
433.92	8.7	1000	30.32	10

Result	PASS
--------	------

Transmitter time in 100ms

