

Nemko-CCL, Inc.
1940 West Alexander Street
Salt Lake City, UT 84119
801-972-6146

Test Report

Certification

Test Of:
XAP-1040

FCC ID:
W59XAP1040

Test Specifications:
FCC PART 15, Subpart C

Test Report Serial No: 180885-2.1

Applicant:
Luxul Wireless
357 South 670 West, Suite 160
Lindon, UT 84042

Date of Test:
June 27 – 29, 2011 and July 5 & 6, 2011

Issue Date: August 1, 2011

CERTIFICATION OF ENGINEERING REPORT

This report has been prepared by Nemko-CCL, Inc. to document compliance of the device described below with the requirements of Federal Communications Commission (FCC) Part 15, Subpart C. This report may be reproduced in full, partial reproduction may only be made with the written consent of the laboratory. The results in this report apply only to the sample tested.

- Applicant: Luxul Wireless
- Manufacturer: Luxul Wireless
- Brand Name: Luxul
- Model Number: XAP-1040
- FCC ID Number: W59XAP1040

On this 1st day of August 2011, I, individually, and for Nemko-CCL, Inc., certify that the statements made in this engineering report are true, complete, and correct to the best of my knowledge, and are made in good faith.

Although NVLAP has recognized that the Nemko-CCL, Inc. EMC testing facilities are in good standing, this report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Nemko-CCL, Inc.



Tested by: Norman P. Hansen
EMC Technician

TABLE OF CONTENTS

| | PAGE |
|---|-------------|
| SECTION 1.0 CLIENT INFORMATION | 4 |
| SECTION 2.0 EQUIPMENT UNDER TEST (EUT)..... | 5 |
| SECTION 3.0 TEST SPECIFICATION, METHODS & PROCEDURES | 8 |
| SECTION 4.0 OPERATION OF EUT DURING TESTING..... | 14 |
| SECTION 5.0 SUMMARY OF TEST RESULTS | 15 |
| SECTION 6.0 MEASUREMENTS, EXAMINATIONS AND DERIVED RESULTS | 16 |
| APPENDIX 1 TEST PROCEDURES AND TEST EQUIPMENT..... | 66 |
| APPENDIX 2 PHOTOGRAPHS..... | 74 |
| APPENDIX 3 MANUFACTURER'S STATEMENT/ATTESTATION..... | 85 |

SECTION 1.0 CLIENT INFORMATION

1.1 Applicant:

Company Name: Luxul Wireless
357 South 670 West, Suite 160
Lindon, UT 84042

Contact Name: Vaughn Staheli
Title: V.P. Engineering

1.2 Manufacturer:

Company Name: Luxul Wireless
105 South 1380 West, Unit 1
Lindon, UT 84042

Contact Name: Vaughn Staheli
Title: V.P. Engineering

SECTION 2.0 EQUIPMENT UNDER TEST (EUT)**2.1 Identification of EUT:**

Brand Name: Luxul
 Model Number: XAP-1040
 Serial Number: SW1015820

2.2 Description of EUT:

The XAP-1040 is an 802.11bgn access point operating in the 2400 MHz to 2483.5 MHz band. The 802.11n transmission is a single antenna single chain with 20 or 40 MHz BW. The XAP-1040 is designed for outdoor use and fits into a weather tight, plastic housing that mounts to a wall, pole or other device. The XAP-1040 uses an embedded antenna. The XAP-1040 connects to a wired network and receives power over an Ethernet port. Power is provided by a Shenzhen Flypower Technology Co. Ltd. PS48IEIAY1000S power supply thru an Engenius EBU-101-01 POE injector.

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 1 | 2412 | 5 | 2432 | 9 | 2452 |
| 2 | 2417 | 6 | 2437 | 10 | 2457 |
| 3 | 2422 | 7 | 2442 | 11 | 2462 |
| 4 | 2427 | 8 | 2447 | | |

Testing was performed using available data rates and modulations at channels 1, 6, and 11 for 802.11b, 802.11g, and 802.11n (20 MHz BW) and at channels 3, 6, and 11 for 802.11n (40 MHz BW). Channels 1 and 2 as shown above are removed by software when operating at 802.11n (40 MHz BW).

This report covers the circuitry of the devices subject to FCC Part 15, Subpart C. The circuitry of the device subject to FCC Subpart B is covered in Nemko-CCL, Inc. report #180885-1.1.

2.3 EUT and Support Equipment:

The FCC ID numbers for all the EUT and support equipment used during the test are listed below:

| Brand Name Model Number Serial Number | FCC ID Number or Compliance | Description | Name of Interface Ports / Interface Cables |
|---|--------------------------------|------------------------|---|
| BN: Luxul MN: XAP-1040 (Note 1) SN: SW1015820 | W59XAP1040 | WiFi Signal Booster | See Section 2.4 |
| BN: Netgear MN: WG103 SN: 20B103540015A | PY30840097 | Access Point | Ethernet/Cat 5 cable w/RJ45 connectors (Note 2) RF/Coax cable (Note 2) |
| BN: Engenius MN: EBU-101-01 SN: None | DoC | POE Injector | Ethernet with Power/Cat 5 cable w/RJ45 connectors (Note 2) Ethernet/Cat 5 cable w/RJ45 connectors |
| BN: TRENDnet MN: TEG-S50TXE SN: None | DoC | 5 port LAN switch | Ethernet/Cat 5 cable w/RJ45 connectors |
| BN: Toshiba MN: Satellite SN: None | DoC | Laptop Computer | Ethernet/Cat 5 cable w/RJ45 connectors |

Note: (1) EUT
(2) Interface port connected to EUT (See Section 2.4)

The support equipment listed above was not modified in order to achieve compliance with this standard.

2.4 Interface Ports on EUT:

| Name of Ports | No. of Ports Fitted to EUT | Cable Descriptions/Length |
|---------------------|----------------------------|-------------------------------------|
| Ethernet with Power | 1 | Cat 5e with RJ45 connectors/1 meter |

2.5 Modification Incorporated/Special Accessories on EUT:

The following modifications were made to the EUT by the Client during testing to comply with the specification. This report is not complete without an accompanying signed attestation, included as Appendix 3, that the product will have all of the documented modifications incorporated into the product when manufactured and placed on the market.

1. C1 and C25 were changed to 15000 pF capacitors.
2. The XAP-1040 Heatsink was replaced with the XAP-1010 Heatsink.
3. A Steward 28A2025-0A2 ferrite was placed on the Ethernet cable at the EUT port of the power injector.
4. Operation at channels 1 and 2 was removed by software when operating in 802.11n (40 MHz BW).
5. To comply with the requirements of 15.247(d) at the band edges, the transmit power for the individual channels was set as shown in the table below.

| Channel | Transmitter Power Setting (dBm) | | |
|---------|---------------------------------|-----------------------------|---------------------|
| | 802.11b | 802.11g/802.11n (20 MHz BW) | 802.11n (40 MHz BW) |
| 1 | 15.5 | 11.0 | Not Available |
| 2 | 20.0 | 20.0 | Not Available |
| 3 | 20.0 | 20.0 | 6.5 |
| 4 | 20.0 | 20.0 | 8.5 |
| 5 | 20.0 | 20.0 | 10.0 |
| 6 | 20.0 | 20.0 | 11.5 |
| 7 | 20.0 | 20.0 | 13.5 |
| 8 | 20.0 | 20.0 | 12.0 |
| 9 | 20.0 | 20.0 | 10.0 |
| 10 | 20.0 | 20.0 | 6.5 |
| 11 | 16.0 | 15.0 | 3.5 |

SECTION 3.0 TEST SPECIFICATION, METHODS & PROCEDURES

3.1 Test Specification:

Title: FCC PART 15, Subpart C (47 CFR 15)
15.203, 15.207, and 15.247

Limits and methods of measurement of radio interference characteristics of radio frequency devices.

Purpose of Test: The tests were performed to demonstrate initial compliance.

3.2 Methods & Procedures:

3.2.1 §15.203 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

3.2.2 §15.207 Conducted Limits

(a) Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

| Frequency of Emission (MHz) | Conducted Limit (dBμV) | |
|-----------------------------|------------------------|-----------|
| | Quasi-peak | Average |
| 0.15 – 0.5* | 66 to 56* | 56 to 46* |
| 0.5 – 5 | 56 | 46 |
| 5 - 30 | 60 | 50 |

*Decreases with the logarithm of the frequency.

3.2.3 §15.247 Operation within the bands 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz

(a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400 – 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(i) For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

(ii) Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any

channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 non-overlapping channels are used.

(2) Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

(b) The maximum peak output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

(2) For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725 - 5850 MHz bands: 1 watt. As an alternative to a peak power measurement, compliance with the Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

(iii) Fixed, point-to-point operation, as used in paragraphs (b)(4)(i) and (b)(4)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

(2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400-2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:

(i) Different information must be transmitted to each receiver.

(ii) If the transmitter employs an antenna system that emits multiple directional beams but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna /antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:

(A) The directional gain shall be calculated as the sum of $10 \log$ (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

(B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient

evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.

(iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.

(iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

(f) For the purposes of this section, hybrid systems are those that employ a combination of both frequency hopping and digital modulation techniques. The frequency hopping operation of the hybrid system, with the direct sequence or digital modulation operation turned off, shall have an average time of occupancy on any frequency not to exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4. The digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

(i) Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Note: Spread spectrum systems are sharing these bands on a noninterference basis with systems supporting critical Government requirements that have been allocated the usage of these bands, secondary only to ISM equipment operated under the provisions of Part 18 of this Chapter. Many of these Government systems are airborne radiolocation systems that emit a high EIRP which can cause interference to other users. Also, investigations of the effect of spread spectrum interference to U. S. Government operations in the 902-928 MHz band may require a future decrease in the power limits allowed for spread spectrum operation.

3.2.3 Test Procedure

The conducted disturbance at mains ports and radiated disturbance testing was performed according to the procedures in ANSI C63.4: 2003. Testing was performed at Nemko-CCL, Inc.'s Wanship open area test site #2, located at 29145 Old Lincoln Highway, Wanship, UT. This site has been fully described in a report submitted to the FCC, and was accepted in a letter dated March 11, 2009 (90504).

Nemko-CCL, Inc. is accredited by National Voluntary Laboratory Accreditation Program (NVLAP); NVLAP Lab Code: 100272-0, which is effective until September 30, 2011.

For radiated emission testing at 30 MHz or above that is performed at distances closer than the specified distance, an inverse proportionality factor of 20 dB per decade was used to normalize the measured data for determining compliance.

SECTION 4.0 OPERATION OF EUT DURING TESTING

4.1 Operating Environment:

Power Supply: 120 VAC at 60 Hz to POE Supply
 48 VDC to XAP-1040 from POE Supply

4.2 Operating Modes:

The transmitter was tested on three orthogonal axes while in a constant transmit mode at the desired frequency. 802.11b, 802.11g, 802.11n (20 MHz BW), and 802.11n (40 MHz BW) modes were tested at the available data rates to find worst-case emissions. The AC power to POE injector power supply was varied in accordance with FCC §15.31(e). The DC output remained constant and no change was seen in transmitter characteristics.

4.3 EUT Exercise Software:

Luxul Wireless software was used to exercise the transmitter.

SECTION 5.0 SUMMARY OF TEST RESULTS**5.1 FCC Part 15, Subpart C****5.1.1 Summary of Tests:**

| Section | Environmental Phenomena | Frequency Range (MHz) | Result |
|----------------|--------------------------------------|------------------------------|----------------|
| 15.203 | Antenna Requirements | Structural requirement | Complied |
| 15.207 | Conducted Disturbance at Mains Ports | 0.15 to 30 | Complied |
| 15.247(a) | Bandwidth Requirement | 2400 – 2483.5 | Complied |
| 15.247(b) | Peak Output Power | 2400 – 2483.5 | Complied |
| 15.247(c) | Antenna Conducted Spurious Emissions | 30 - 25000 | Complied |
| 15.247(c) | Radiated Spurious Emissions | 30 - 25000 | Complied |
| 15.247(d) | Peak Power Spectral Density | 2400 – 2483.5 | Complied |
| 15.247(e) | Reserved Paragraph | N/A | Not Applicable |
| 15.247(f) | Hybrid System Requirements | 2400 – 2483.5 | Not Applicable |
| 15.247(g) | Frequency Hopping Channel Usage | 2400 – 2438.5 | Not Applicable |
| 15.247(h) | Frequency Hopping Intelligence | 2400 – 2483.5 | Not Applicable |

5.2 Result

In the configuration tested, the EUT complied with the requirements of the specification.

SECTION 6.0 MEASUREMENTS, EXAMINATIONS AND DERIVED RESULTS**6.1 General Comments:**

This section contains the test results only. Details of the test methods used and a list of the test equipment used during the measurements can be found in Appendix 1 of this report.

6.2 Test Results:**6.2.1 §15.203 Antenna Requirements**

The EUT uses an embedded 4 dBi directional antenna.

6.2.2 §15.207 Conducted Disturbance at the AC Mains Ports

| Frequency (MHz) | AC Mains Lead | Detector | Measured Level (dBμV) | Limit (dBμV) | Margin (dB) |
|-----------------|---------------|---------------------|-----------------------|--------------|-------------|
| 0.18 | Hot Lead | Peak (Note 1) | 49.6 | 54.3 | -4.7 |
| 0.40 | Hot Lead | Quasi-Peak (Note 2) | 44.7 | 57.9 | -13.2 |
| 0.40 | Hot Lead | Average (Note 2) | 38.1 | 47.9 | -9.8 |
| 0.56 | Hot Lead | Peak (Note 1) | 39.3 | 46.0 | -6.7 |
| 1.10 | Hot Lead | Peak (Note 1) | 39.7 | 46.0 | -6.3 |
| 3.40 | Hot Lead | Peak (Note 1) | 41.3 | 46.0 | -4.7 |
| 4.41 | Hot Lead | Peak (Note 1) | 41.9 | 46.0 | -4.1 |
| 0.20 | Neutral Lead | Peak (Note 1) | 45.7 | 53.6 | -7.9 |
| 0.36 | Neutral Lead | Quasi-Peak (Note 1) | 45.4 | 48.7 | -3.3 |
| 1.18 | Neutral Lead | Peak (Note 1) | 40.2 | 46.0 | -5.8 |
| 1.91 | Neutral Lead | Peak (Note 1) | 41.2 | 46.0 | -4.8 |
| 2.90 | Neutral Lead | Peak (Note 1) | 40.7 | 46.0 | -5.3 |
| 3.27 | Neutral Lead | Peak (Note 1) | 41.3 | 46.0 | -4.7 |
| 4.35 | Neutral Lead | Peak (Note 1) | 41.1 | 46.0 | -4.9 |

| Frequency (MHz) | AC Mains Lead | Detector | Measured Level (dBμV) | Limit (dBμV) | Margin (dB) |
|--|---------------|----------|-----------------------|--------------|-------------|
| Note 1: The reference detector used for the measurements was Quasi-Peak or Peak and the data was compared to the average limit; therefore, the EUT was deemed to meet both the average and quasi-peak limits. Note 2: The reference detector used for the measurements was quasi-peak and average and the data was compared to the respective limits. | | | | | |

RESULT

In the configuration tested, the EUT complied with the specification by 3.3 dB.


6.2.3 §15.247(a)(2) Emission 6 dB Bandwidth

| Frequency (MHz) | 802.11b (MHz) | 802.11g & 802.11n (20 MHz BW) (MHz) | 802.11n (40 MHz BW) (MHz) |
|-----------------|---------------|-------------------------------------|---------------------------|
| 2412 | 12.15 | 16.38 | ----- |
| 2422 | ----- | ----- | 36.45 |
| 2437 | 12.25 | 16.44 | 36.40 |
| 2462 | 12.05 | 16.47 | 36.10 |

RESULT


In the configuration tested, the 6 dB bandwidth was greater than 500 kHz; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots below).

Channel 1 Emission 6 dB Bandwidth – 802.11b




| Mkr | Trace | X-Axis | Value | Notes |
|-------|---------|-------------|----------|-------|
| 1 ▽ | Trace A | 2.4144 GHz | 9.36 dBm | |
| 2-1 ▽ | Trace A | -8.6000 MHz | -5.88 dB | |
| 3-2 ▽ | Trace A | 12.1500 MHz | -0.44 dB | |

Channel 6 Emission 6 dB Bandwidth – 802.11b




| Mkr | Trace | X-Axis | Value | Notes |
|-------|---------|-------------|-----------|-------|
| 1 ▽ | Trace A | 2.4395 GHz | 13.67 dBm | |
| 2-1 ▽ | Trace A | -8.5500 MHz | -5.86 dB | |
| 3-2 ▽ | Trace A | 12.2500 MHz | 0.09 dB | |

Channel 11 Emission 6 dB Bandwidth – 802.011b




| Mkr | Trace | X-Axis | Value | Notes |
|-------|---------|-------------|----------|-------|
| 1 ▽ | Trace A | 2.4606 GHz | 9.58 dBm | |
| 2-1 ▽ | Trace A | -4.6500 MHz | -6.00 dB | |
| 3-2 ▽ | Trace A | 12.0500 MHz | 0.97 dB | |

Channel 1 Emission 6 dB Bandwidth – 802.11gn




| Mkr | Trace | X-Axis | Value | Notes |
|-------|---------|--------------|-----------|-------|
| 1 ▽ | Trace A | 2.4193 GHz | 11.04 dBm | |
| 2-1 ▽ | Trace A | -15.6600 MHz | -6.16 dB | |
| 3-2 ▽ | Trace A | 16.3800 MHz | 0.28 dB | |

Channel 6 Emission 6 dB Bandwidth – 802.11gn




| Mkr | Trace | X-Axis | Value | Notes |
|-------|---------|-------------|-----------|-------|
| 1 ▾ | Trace A | 2.4305 GHz | 10.76 dBm | |
| 2-1 ▾ | Trace A | -1.9200 MHz | -6.80 dB | |
| 3-2 ▾ | Trace A | 16.4400 MHz | 0.11 dB | |

Channel 11 Emission 6 dB Bandwidth – 802.11gn




| Mkr | Trace | X-Axis | Value | Notes |
|-------|---------|--------------|----------|-------|
| 1 ▽ | Trace A | 2.4643 GHz | 9.70 dBm | |
| 2-1 ▽ | Trace A | -10.7400 MHz | -6.33 dB | |
| 3-2 ▽ | Trace A | 16.4700 MHz | 0.73 dB | |

Channel 3 Emission 6 dB Bandwidth – 802.11n




| Mkr | Trace | X-Axis | Value | Notes |
|-------|---------|--------------|-----------|-------|
| 1 ▽ | Trace A | 2.4331 GHz | -4.96 dBm | |
| 2-1 ▽ | Trace A | -29.4500 MHz | -5.60 dB | |
| 3-2 ▽ | Trace A | 36.4500 MHz | -1.64 dB | |

Channel 6 Emission 6 dB Bandwidth – 802.11n



| Mkr | Trace | X-Axis | Value | Notes |
|-------|---------|-------------|-----------|-------|
| 1 ▽ | Trace A | 2.4256 GHz | -0.09 dBm | |
| 2-1 ▽ | Trace A | -6.9000 MHz | -5.42 dB | |
| 3-2 ▽ | Trace A | 36.4000 MHz | -1.29 dB | |

Channel 11 Emission 6 dB Bandwidth – 802.11n



| Mkr | Trace | X-Axis | Value | Notes |
|-------|---------|--------------|------------|-------|
| 1 ▾ | Trace A | 2.4569 GHz | -11.05 dBm | |
| 2-1 ▾ | Trace A | -13.2000 MHz | -5.38 dB | |
| 3-2 ▾ | Trace A | 36.1000 MHz | -0.25 dB | |

6.2.4 §15.247(b)(3) Peak Output Power

The maximum peak RF Conducted output power measured for this device was 29.82 dBm or 959.40 mW. The limit is 30 dBm or 1 Watt when using antennas with 6 dBi or less gain


The maximum RBW of the spectrum analyzer was not larger than the bandwidth of the signal to be measured; therefore, the method described in Power Output Option 2, Method #1 of the attachment to FCC Public Notice DA000705 was used to measure and sum the power, as allowed in §15.247(b)(3).

| Frequency (MHz) | 802.11b | | 802.11g & 802.11n (20 MHz BW) | | 802.11n (40 MHz BW) | |
|--------------------|---------|--------|----------------------------------|--------|---------------------|--------|
| | dBm | mW | dBm | mW | dBm | mW |
| 2412 | 25.1 | 323.59 | 22.14 | 163.68 | ----- | ----- |
| 2422 | ----- | ----- | ----- | ----- | 16.51 | 44.77 |
| 2437 | 29.62 | 916.22 | 29.82 | 959.40 | 20.65 | 116.14 |
| 2462 | 26.05 | 402.72 | 24.81 | 302.69 | 10.01 | 10.02 |

RESULT

In the configuration tested, the RF peak output power was less than 1 Watt; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots below).


Channel 1 Output Power – 802.11b



Trace A

| Measurement Parameter | Value |
|-----------------------|-----------|
| Channel power | 25.10 dBm |


Channel 6 Output Power – 802.11b



Trace A

| Measurement Parameter | Value |
|-----------------------|-----------|
| Channel power | 29.62 dBm |


Channel 11 Output Power – 802.11b



Trace A

| Measurement Parameter | Value |
|-----------------------|-----------|
| Channel power | 26.05 dBm |


Channel 1 Output Power – 802.11gn



Trace A

| Measurement Parameter | Value |
|-----------------------|-----------|
| Channel power | 22.14 dBm |


Channel 6 Output Power – 802.11gn



Trace A

| Measurement Parameter | Value |
|-----------------------|-----------|
| Channel power | 29.82 dBm |


Channel 11 Output Power – 802.11gn



Trace A

| Measurement Parameter | Value |
|-----------------------|-----------|
| Channel power | 24.81 dBm |


Channel 1 Output Power – 802.11n



Trace A

| Measurement Parameter | Value |
|-----------------------|-----------|
| Channel power | 16.51 dBm |


Channel 6 Output Power – 802.11n



Trace A

| Measurement Parameter | Value |
|-----------------------|-----------|
| Channel power | 20.65 dBm |

Channel 11 Output Power – 802.11n



Trace A

| Measurement Parameter | Value |
|-----------------------|-----------|
| Channel power | 10.01 dBm |

6.2.5 §15.247(c) Spurious Emissions**6.2.5.1 Conducted Spurious Emissions**

The frequency range from 8 MHz to the tenth harmonic of the highest fundamental frequency was investigated to measure any antenna-conducted emissions. The tables show the measurement data from spurious emissions noted across the frequency range when transmitting at the lowest frequency, middle frequency, and upper frequency. Shown below are plots with the EUT tuned to the upper and lower channels. These demonstrate compliance with the provisions of this section at the band edges.

The emissions must be attenuated 30 dB below the highest power level measured within the authorized band as measured with a 100 kHz RBW since §15.247(b)(3) was used in determining the output power. The highest level when operating at 802.11b was 14.6 dBm; therefore, the criteria is $14.6 - 30.0 = -15.4$ dBm. The highest level when operating at 802.11g or 802.11n (20 MHz BW) was 7.0 dBm; therefore, the criteria is $7.0 - 30.0 = -23.0$ dBm. . The highest level when operating at 802.11n (40 MHz BW) was 1.1 dBm; therefore, the criteria is $1.1 - 30.0 = -28.9$ dBm.

RESULT

Conducted spurious emissions were attenuated 20 dB or more from the fundamental; therefore, the EUT complies with the specification.

Transmitting at 2412 MHz – 802.11b

| Frequency (MHz) | Corrected Level (dBm) | Criteria (dBm) |
|-----------------|-----------------------|----------------|
| 4824 | -32.6 | -15.4 |
| 7236 | -61.4 | -15.4 |
| 9648 | -63.6 | -15.4 |
| 12060 | -63.4 | -15.4 |
| 14472 | -62.3 | -15.4 |
| 16884 | -62.5 | -15.4 |
| 19296 | -61.3 | -15.4 |
| 21708 | -62.0 | -15.4 |
| 24120 | -61.5 | -15.4 |

Transmitting at 2437 MHz – 802.11b

| Frequency (MHz) | Corrected Level (dBm) | Criteria (dBm) |
|-----------------|-----------------------|----------------|
| 4874 | -25.9 | -15.4 |
| 7311 | -50.0 | -15.4 |
| 9748 | -43.8 | -15.4 |
| 12185 | -61.1 | -15.4 |
| 14662 | -62.8 | -15.4 |
| 17059 | -62.7 | -15.4 |
| 19496 | -62.4 | -15.4 |
| 21993 | -62.4 | -15.4 |
| 24370 | -60.8 | -15.4 |

Transmitting at 2462 MHz – 802.11b

| Frequency (MHz) | Corrected Level (dBm) | Criteria (dBm) |
|-----------------|-----------------------|----------------|
| 4924 | -39.4 | -15.4 |
| 7386 | -55.1 | -15.4 |
| 9848 | -50.9 | -15.4 |
| 12310 | -62.8 | -15.4 |
| 14772 | -62.4 | -15.4 |
| 17234 | -65.6 | -15.4 |
| 19696 | -62.9 | -15.4 |
| 22158 | -62.1 | -15.4 |
| 24620 | -60.6 | -15.4 |

Transmitting at 2412 MHz – 802.11gn

| Frequency (MHz) | Corrected Level (dBm) | Criteria (dBm) |
|-----------------|-----------------------|----------------|
| 4824 | -48.5 | -23.0 |
| 7236 | -64.2 | -23.0 |
| 9648 | -64.6 | -23.0 |
| 12060 | -63.9 | -23.0 |
| 14472 | -63.2 | -23.0 |
| 16884 | -63.7 | -23.0 |
| 19296 | -63.3 | -23.0 |
| 21708 | -62.7 | -23.0 |
| 24120 | -62.0 | -23.0 |

Transmitting at 2437 MHz – 802.11gn

| Frequency (MHz) | Corrected Level (dBm) | Criteria (dBm) |
|-----------------|-----------------------|----------------|
| 4874 | -47.1 | -23.0 |
| 7311 | -47.3 | -23.0 |
| 9748 | -53.4 | -23.0 |
| 12185 | -63.1 | -23.0 |
| 14662 | -64.0 | -23.0 |
| 17059 | -63.4 | -23.0 |
| 19496 | -62.6 | -23.0 |
| 21993 | -61.7 | -23.0 |
| 24370 | -60.7 | -23.0 |

Transmitting at 2462 MHz – 802.11gn

| Frequency (MHz) | Corrected Level (dBm) | Criteria (dBm) |
|-----------------|-----------------------|----------------|
| 4924 | -53.8 | -23.0 |
| 7386 | -61.6 | -23.0 |
| 9848 | -63.3 | -23.0 |
| 12310 | -64.4 | -23.0 |
| 14772 | -63.1 | -23.0 |
| 17234 | -63.2 | -23.0 |
| 19696 | -63.3 | -23.0 |
| 22158 | -63.0 | -23.0 |
| 24620 | -62.3 | -23.0 |

Transmitting at 2422 MHz – 802.11n

| Frequency (MHz) | Corrected Level (dBm) | Criteria (dBm) |
|-----------------|-----------------------|----------------|
| 4844 | -59.0 | -28.9 |
| 7266 | -61.0 | -28.9 |
| 96.88 | -61.2 | -28.9 |
| 12110 | -60.3 | -28.9 |
| 14532 | -59.4 | -28.9 |
| 16954 | -59.2 | -28.9 |
| 19376 | -58.6 | -28.9 |
| 21798 | -59.6 | -28.9 |
| 24220 | -58.4 | -28.9 |


Transmitting at 2437 MHz – 802.11n

| Frequency (MHz) | Corrected Level (dBm) | Criteria (dBm) |
|-----------------|-----------------------|----------------|
| 4874 | -52.7 | -28.9 |
| 7311 | -61.1 | -28.9 |
| 9748 | -61.6 | -28.9 |
| 12185 | -60.2 | -28.9 |
| 14662 | -60.0 | -28.9 |
| 17059 | -59.3 | -28.9 |
| 19496 | -60.0 | -28.9 |
| 21993 | -59.2 | -28.9 |
| 24370 | -58.0 | -28.9 |


Transmitting at 2462 MHz – 802.11n

| Frequency (MHz) | Corrected Level (dBm) | Criteria (dBm) |
|-----------------|-----------------------|----------------|
| 4924 | -60.3 | -28.9 |
| 7386 | -61.2 | -28.9 |
| 9848 | -61.5 | -28.9 |
| 12310 | -61.2 | -28.9 |
| 14772 | -60.4 | -28.9 |
| 17234 | -60.4 | -28.9 |
| 19696 | -60.0 | -28.9 |
| 22158 | -59.3 | -28.9 |
| 24620 | -58.2 | -28.9 |


Channel 1 Band Edge – 802.11b




Channel 11 Band Edge – 802.11b




Channel 1 Band Edge – 802.11gn




Channel 11 Band Edge – 802.11gn



Channel 3 Band Edge – 802.11n



Channel 11 Band Edge – 802.11n



6.2.5.2 Radiated Emissions in the Restricted Bands of §15.205

The frequency range from 30 MHz to 25 GHz was investigated to measure any radiated emissions in the restricted bands. The following tables show measurements of any emission that fell into the restricted bands of §15.205. The tables show the worst-case emission measured from the XAP-1040. For frequencies above 12.5 GHz, a measurement distance of 1 meter was used. The noise floor was a minimum of 6 dB below the limit. The emissions in the restricted bands must meet the limits specified in §15.209. Tabular data for each of the spurious emissions is shown below for each of the units. Plots of the band edges are also shown.

For frequencies below 1000 MHz RBW = 100 kHz and VBW = 300 kHz, For frequencies above 1000 MHz RBW = 1 Mhz and VBW = 3 MHz.

AVERAGE FACTOR

There was not an average factor applied.

RESULT

All emissions in the restricted bands of §15.205 met the limits specified in §15.209; therefore, the EUT complies with the specification.

Transmitting at 2412 MHz – 802.11b

| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dBμV) | Correction Factor (dB) | Field Strength (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------|------------------------|-------------------------|----------------|-------------|
| 4824.0 | Peak | Vertical | 11.6 | 37.7 | 49.3 | 74.0 | -24.7 |
| 4824.0 | Average | Vertical | 9.1 | 37.7 | 46.8 | 54.0 | -7.2 |
| 4824.0 | Peak | Horizontal | 7.5 | 37.7 | 45.2 | 74.0 | -28.8 |
| 4824.0 | Average | Horizontal | 2.5 | 37.7 | 40.2 | 54.0 | -13.8 |
| 7236.0 | Peak | Vertical | 2.2 | 42.1 | 44.3 | 74.0 | -29.7 |
| 7236.0 | Average | Vertical | -8.2 | 42.1 | 33.9 | 54.0 | -20.1 |
| 7236.0 | Peak | Horizontal | 3.1 | 42.1 | 45.2 | 74.0 | -28.8 |
| 7236.0 | Average | Horizontal | -7.2 | 42.1 | 34.9 | 54.0 | -19.1 |
| 12060.0 | Peak | Vertical | 2.2 | 47.2 | 49.4 | 74.0 | -24.6 |
| 12060.0 | Average | Vertical | -7.2 | 47.2 | 40.0 | 54.0 | -14.0 |
| 12060.0 | Peak | Horizontal | 3.2 | 47.2 | 50.4 | 74.0 | -23.6 |
| 12060.0 | Average | Horizontal | -6.2 | 47.2 | 41.0 | 54.0 | -13.0 |

Transmitting at 2437 MHz – 802.11b


| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dBμV) | Correction Factor (dB) | Field Strength (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------|------------------------|-------------------------|----------------|-------------|
| 4874.0 | Peak | Vertical | 10.0 | 37.8 | 47.8 | 74.0 | -26.2 |
| 4874.0 | Average | Vertical | 6.7 | 37.8 | 44.5 | 54.0 | -9.5 |
| 4874.0 | Peak | Horizontal | 15.1 | 37.8 | 52.9 | 74.0 | -21.1 |
| 4874.0 | Average | Horizontal | 13.7 | 37.8 | 51.5 | 54.0 | -2.5 |

| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dB μ V) | Correction Factor (dB) | Field Strength (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------------|------------------------|-------------------------------|----------------------|-------------|
| 7311.0 | Peak | Vertical | 7.7 | 42.3 | 50.0 | 74.0 | -24.0 |
| 7311.0 | Average | Vertical | 0.5 | 42.3 | 42.8 | 54.0 | -11.2 |
| 7311.0 | Peak | Horizontal | 6.8 | 42.3 | 49.1 | 74.0 | -24.9 |
| 7311.0 | Average | Horizontal | -2.8 | 42.3 | 39.5 | 54.0 | -14.5 |
| 12185.0 | Peak | Vertical | 10.0 | 47.1 | 57.1 | 74.0 | -16.9 |
| 12185.0 | Average | Vertical | 1.8 | 47.1 | 48.9 | 54.0 | -5.1 |
| 12185.0 | Peak | Horizontal | 2.6 | 47.1 | 49.7 | 74.0 | -24.3 |
| 12185.0 | Average | Horizontal | -6.3 | 47.1 | 40.8 | 54.0 | -13.2 |


Transmitting at 2462 MHz – 802.11b

| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dB μ V) | Correction Factor (dB) | Field Strength (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------------|------------------------|-------------------------------|----------------------|-------------|
| 4924.0 | Peak | Vertical | 19.7 | 37.9 | 57.6 | 74.0 | -16.4 |
| 4924.0 | Average | Vertical | 10.4 | 37.9 | 48.3 | 54.0 | -5.7 |
| 4924.0 | Peak | Horizontal | 15.3 | 37.9 | 53.2 | 74.0 | -20.8 |
| 4924.0 | Average | Horizontal | 7.1 | 37.9 | 45.0 | 54.0 | -9.0 |
| 7386.0 | Peak | Vertical | 7.7 | 42.5 | 50.2 | 74.0 | -23.8 |
| 7386.0 | Average | Vertical | -1.4 | 42.5 | 41.1 | 54.0 | -12.9 |
| 7386.0 | Peak | Horizontal | 7.0 | 42.5 | 49.5 | 74.0 | -24.5 |
| 7386.0 | Average | Horizontal | -2.5 | 42.5 | 40.0 | 54.0 | -14.0 |
| 12310.0 | Peak | Vertical | 8.6 | 47.0 | 55.6 | 74.0 | -18.4 |
| 12310.0 | Average | Vertical | 0.6 | 47.0 | 47.6 | 54.0 | -6.4 |
| 12310.0 | Peak | Horizontal | 6.9 | 47.0 | 53.9 | 74.0 | -20.1 |
| 12310.0 | Average | Horizontal | -1.9 | 47.0 | 45.1 | 54.0 | -8.9 |

No other emissions were seen in the restricted bands. Noise floor was greater than 6 dB below the limit. At frequencies above 12.5 GHz, a 1 meter measurement distance was used.



Date: 28.JUN.2011 14:00:15



Date: 28.JUN.2011 13:48:49

Transmitting at 2412 MHz – 802.11 gn

| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dBµV) | Correction Factor (dB) | Field Strength (dBµV/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------|------------------------|-------------------------|----------------|-------------|
| 4824.0 | Peak | Vertical | 4.6 | 37.7 | 42.3 | 74.0 | -31.7 |
| 4824.0 | Average | Vertical | -4.3 | 37.7 | 33.4 | 54.0 | -20.6 |
| 4824.0 | Peak | Horizontal | 3.8 | 37.7 | 41.5 | 74.0 | -32.5 |
| 4824.0 | Average | Horizontal | -6.0 | 37.7 | 31.7 | 54.0 | -22.3 |
| 7236.0 | Peak | Vertical | 1.1 | 42.1 | 43.2 | 74.0 | -30.8 |
| 7236.0 | Average | Vertical | -10.4 | 42.1 | 31.7 | 54.0 | -22.3 |
| 7236.0 | Peak | Horizontal | 1.1 | 42.1 | 43.2 | 74.0 | -30.8 |
| 7236.0 | Average | Horizontal | -10.4 | 42.1 | 31.7 | 54.0 | -22.3 |
| 12060.0 | Peak | Vertical | -1.2 | 47.2 | 46.0 | 74.0 | -28.0 |
| 12060.0 | Average | Vertical | -10.5 | 47.2 | 36.7 | 54.0 | -17.3 |
| 12060.0 | Peak | Horizontal | -1.2 | 47.2 | 46.0 | 74.0 | -28.0 |
| 12060.0 | Average | Horizontal | -11.4 | 47.2 | 35.8 | 54.0 | -18.2 |


Transmitting at 2437 MHz – 802.11 gn

| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dBµV) | Correction Factor (dB) | Field Strength (dBµV/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------|------------------------|-------------------------|----------------|-------------|
| 4874.0 | Peak | Vertical | 16.9 | 37.8 | 54.7 | 74.0 | -19.3 |
| 4874.0 | Average | Vertical | 6.3 | 37.8 | 44.1 | 54.0 | -9.9 |
| 4874.0 | Peak | Horizontal | 13.8 | 37.8 | 51.6 | 74.0 | -22.4 |
| 4874.0 | Average | Horizontal | 3.6 | 37.8 | 41.4 | 54.0 | -12.6 |
| 7311.0 | Peak | Vertical | 6.4 | 42.3 | 48.7 | 74.0 | -25.3 |
| 7311.0 | Average | Vertical | -3.9 | 42.3 | 38.4 | 54.0 | -15.6 |
| 7311.0 | Peak | Horizontal | 7.9 | 42.3 | 50.2 | 74.0 | -23.8 |
| 7311.0 | Average | Horizontal | -1.8 | 42.3 | 40.5 | 54.0 | -13.5 |
| 12185.0 | Peak | Vertical | 8.2 | 47.1 | 55.3 | 74.0 | -18.7 |
| 12185.0 | Average | Vertical | -2.4 | 47.1 | 44.7 | 54.0 | -9.3 |
| 12185.0 | Peak | Horizontal | 8.7 | 47.1 | 55.8 | 74.0 | -18.2 |
| 12185.0 | Average | Horizontal | -6.6 | 47.1 | 40.5 | 54.0 | -13.5 |


Transmitting at 2462 MHz – 802.11gn

| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dB μ V) | Correction Factor (dB) | Field Strength (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------------|------------------------|-------------------------------|----------------------|-------------|
| 4924.0 | Peak | Vertical | 16.2 | 37.9 | 54.1 | 74.0 | -19.9 |
| 4924.0 | Average | Vertical | 6.0 | 37.9 | 43.9 | 54.0 | -10.1 |
| 4924.0 | Peak | Horizontal | 12.1 | 37.9 | 50.0 | 74.0 | -24.0 |
| 4924.0 | Average | Horizontal | 2.2 | 37.9 | 40.1 | 54.0 | -13.9 |
| 7386.0 | Peak | Vertical | 5.4 | 42.5 | 47.9 | 74.0 | -26.1 |
| 7386.0 | Average | Vertical | -5.2 | 42.5 | 37.3 | 54.0 | -16.7 |
| 7386.0 | Peak | Horizontal | 8.1 | 42.5 | 50.6 | 74.0 | -23.4 |
| 7386.0 | Average | Horizontal | -3.0 | 42.5 | 39.5 | 54.0 | -14.5 |
| 12310.0 | Peak | Vertical | 6.4 | 47.0 | 53.4 | 74.0 | -20.6 |
| 12310.0 | Average | Vertical | -3.2 | 47.0 | 43.8 | 54.0 | -10.2 |
| 12310.0 | Peak | Horizontal | 3.4 | 47.0 | 50.4 | 74.0 | -23.6 |
| 12310.0 | Average | Horizontal | -7.1 | 47.0 | 39.9 | 54.0 | -14.1 |

No other emissions were seen in the restricted bands. Noise floor was greater than 6 dB below the limit. At frequencies above 12.5 GHz, a 1 meter measurement distance was used.



Date: 28.JUN.2011 14:55:22



Date: 28.JUN.2011 14:53:06

Transmitting at 2422 MHz – 802.11n

| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dBµV) | Correction Factor (dB) | Field Strength (dBµV/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------|------------------------|-------------------------|----------------|-------------|
| 4844.0 | Peak | Vertical | 3.0 | 37.8 | 40.8 | 74.0 | -33.2 |
| 4844.0 | Average | Vertical | -4.4 | 37.8 | 33.4 | 54.0 | -20.6 |
| 4844.0 | Peak | Horizontal | 4.1 | 37.8 | 41.9 | 74.0 | -32.1 |
| 4844.0 | Average | Horizontal | -2.1 | 37.8 | 35.7 | 54.0 | -18.3 |
| 7266.0 | Peak | Vertical | 1.8 | 42.2 | 44.0 | 74.0 | -30.0 |
| 7266.0 | Average | Vertical | -10.2 | 42.2 | 32.0 | 54.0 | -22.0 |
| 7266.0 | Peak | Horizontal | 1.1 | 42.2 | 43.3 | 74.0 | -30.7 |
| 7266.0 | Average | Horizontal | -10.3 | 42.2 | 31.9 | 54.0 | -22.1 |
| 12110.0 | Peak | Vertical | -1.1 | 47.1 | 46.0 | 74.0 | -28.0 |
| 12110.0 | Average | Vertical | -12.7 | 47.1 | 34.4 | 54.0 | -19.6 |
| 12110.0 | Peak | Horizontal | -0.7 | 47.1 | 46.4 | 74.0 | -27.6 |
| 12110.0 | Average | Horizontal | -12.7 | 47.1 | 34.4 | 54.0 | -19.6 |


Transmitting at 2437 MHz – 802.11n

| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dBµV) | Correction Factor (dB) | Field Strength (dBµV/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------|------------------------|-------------------------|----------------|-------------|
| 4874.0 | Peak | Vertical | 5.5 | 37.8 | 43.3 | 74.0 | -30.7 |
| 4874.0 | Average | Vertical | -6.0 | 37.8 | 31.8 | 54.0 | -22.2 |
| 4874.0 | Peak | Horizontal | 1.5 | 37.8 | 39.3 | 74.0 | -34.7 |
| 4874.0 | Average | Horizontal | -4.9 | 37.8 | 32.9 | 54.0 | -21.1 |
| 7311.0 | Peak | Vertical | 1.1 | 42.3 | 43.4 | 74.0 | -30.6 |
| 7311.0 | Average | Vertical | -10.3 | 42.3 | 32.0 | 54.0 | -22.0 |
| 7311.0 | Peak | Horizontal | 1.0 | 42.3 | 43.3 | 74.0 | -30.7 |
| 7311.0 | Average | Horizontal | -10.6 | 42.3 | 31.7 | 54.0 | -22.3 |
| 12185.0 | Peak | Vertical | -1.8 | 47.1 | 45.3 | 74.0 | -28.7 |
| 12185.0 | Average | Vertical | -13.1 | 47.1 | 34.0 | 54.0 | -20.0 |
| 12185.0 | Peak | Horizontal | -1.1 | 47.1 | 46.0 | 74.0 | -28.0 |
| 12185.0 | Average | Horizontal | -13.1 | 47.1 | 34.0 | 54.0 | -20.0 |


Transmitting at 2462 MHz – 802.11n

| Frequency (MHz) | Detection Mode | Antenna Polarity | Receiver Reading (dB μ V) | Correction Factor (dB) | Field Strength (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------|------------------|-------------------------------|------------------------|-------------------------------|----------------------|-------------|
| 4924.0 | Peak | Vertical | 2.5 | 37.9 | 40.4 | 74.0 | -33.6 |
| 4924.0 | Average | Vertical | -9.2 | 37.9 | 28.7 | 54.0 | -25.3 |
| 4924.0 | Peak | Horizontal | 0.5 | 37.9 | 38.4 | 74.0 | -35.6 |
| 4924.0 | Average | Horizontal | -6.1 | 37.9 | 31.8 | 54.0 | -22.2 |
| 7386.0 | Peak | Vertical | 0.7 | 42.5 | 43.2 | 74.0 | -30.8 |
| 7386.0 | Average | Vertical | -11.0 | 42.5 | 31.5 | 54.0 | -22.5 |
| 7386.0 | Peak | Horizontal | 0.4 | 42.5 | 42.9 | 74.0 | -31.1 |
| 7386.0 | Average | Horizontal | -10.9 | 42.5 | 31.6 | 54.0 | -22.4 |
| 12310.0 | Peak | Vertical | -1.6 | 47.0 | 45.4 | 74.0 | -28.6 |
| 12310.0 | Average | Vertical | -12.7 | 47.0 | 34.3 | 54.0 | -19.7 |
| 12310.0 | Peak | Horizontal | -3.3 | 47.0 | 43.7 | 74.0 | -30.3 |
| 12310.0 | Average | Horizontal | -13.0 | 47.0 | 34.0 | 54.0 | -20.0 |

No other emissions were seen in the restricted bands. Noise floor was greater than 6 dB below the limit. At frequencies above 12.5 GHz, a 1 meter measurement distance was used.



Date: 28.JUN.2011 15:58:59



Date: 28.JUN.2011 16:04:43

6.2.6 §15.247(d) Peak Power Spectral Density


The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. Since the method described in Power Output Option 2, Method #1 of the attachment to FCC Public Notice DA000705 was used to measure and sum the power, the method in PSD Option 2 of the attachment to FCC Public Notice DA000705 was used to measure the 3 kHz power spectral density of the emission. The result of this testing is summarized in the table below.

| Frequency (MHz) | 802.11b (dBm) | 802.11g & 802.11n (20 MHz BW) (dBm) | 802.11n (40 MHz BW) (dBm) |
|--------------------|------------------|---|---------------------------------|
| 2412 | -4.99 | -12.37 | ----- |
| 2422 | ----- | ----- | -16.26 |
| 2437 | 2.65 | -1.41 | -13.89 |
| 2462 | -4.18 | -13.44 | -23.43 |

RESULT


The maximum peak power spectral density was 2.65 dBm. The EUT complies with the specification by 5.35 dB.

Lowest channel – 802.11b



| Mkr | Trace | X-Axis | Value | Notes |
|-----|---------|------------|-----------|-------|
| 1 ▽ | Trace A | 2.4122 GHz | -4.99 dBm | |

Middle channel – 802.11b



Start: 2.4363 GHz

Stop: 2.4378 GHz

Res BW: 3 kHz

Vid BW: 10 kHz

Sweep: 340.00 ms


6/29/2011 2:48:52 PM

Atten: 35 dB

ESU-40

| Mkr | Trace | X-Axis | Value | Notes |
|-----|---------|------------|----------|-------|
| 1 ▽ | Trace A | 2.4376 GHz | 2.65 dBm | |

Upper channel – 802.11b



Start: 2.4613 GHz

Stop: 2.4628 GHz

Res BW: 3 kHz

Vid BW: 10 kHz

Sweep: 340.00 ms


6/29/2011 2:51:39 PM

Atten: 35 dB

ESU-40

| Mkr | Trace | X-Axis | Value | Notes |
|-----|---------|------------|-----------|-------|
| 1 ▽ | Trace A | 2.4624 GHz | -4.18 dBm | |

Lower channel – 802.11gn



Start: 2.4111 GHz

Stop: 2.4126 GHz

Res BW: 3 kHz

Vid BW: 10 kHz

Sweep: 340.00 ms


6/29/2011 2:57:11 PM

Atten: 35 dB

ESU-40


| Mkr | Trace | X-Axis | Value | Notes |
|-----|---------|------------|------------|-------|
| 1 ▽ | Trace A | 2.4112 GHz | -12.37 dBm | |

Middle channel – 802.11gn




| Mkr | Trace | X-Axis | Value | Notes |
|-----|---------|------------|-----------|-------|
| 1 ▽ | Trace A | 2.4362 GHz | -0.41 dBm | |

Upper channel – 802.11gn




| Mkr | Trace | X-Axis | Value | Notes |
|-----|---------|------------|------------|-------|
| 1 ▽ | Trace A | 2.4623 GHz | -13.44 dBm | |

Lower channel – 802.11n



| Mkr | Trace | X-Axis | Value | Notes |
|-----|---------|------------|------------|-------|
| 1 ▽ | Trace A | 2.4206 GHz | -26.25 dBm | |

Middle channel – 802.11n



Start: 2.4374 GHz

Stop: 2.4389 GHz

Res BW: 3 kHz

Vid BW: 10 kHz

Sweep: 340.00 ms


6/29/2011 3:02:58 PM

Atten: 35 dB

ESU-40

| Mkr | Trace | X-Axis | Value | Notes |
|-----|---------|------------|------------|-------|
| 1 ▽ | Trace A | 2.4378 GHz | -13.89 dBm | |

Upper channel – 802.11n



| Mkr | Trace | X-Axis | Value | Notes |
|-----|---------|------------|------------|-------|
| 1 ▽ | Trace A | 2.4628 GHz | -23.43 dBm | |

APPENDIX 1 TEST PROCEDURES AND TEST EQUIPMENT**§15.207 Conducted Disturbance at the AC Mains**

The conducted disturbance at mains ports from the EUT was measured using a spectrum analyzer with a quasi-peak adapter for peak, quasi-peak and average readings. The quasi-peak adapter uses a bandwidth of 9 kHz, with the spectrum analyzer's resolution bandwidth set at 100 kHz, for readings in the 150 kHz to 30 MHz frequency ranges.

The conducted disturbance at mains ports measurements are performed in a screen room using a (50 Ω /50 μ H) Line Impedance Stabilization Network (LISN).

Where mains flexible power cords are longer than 1 m, the excess cable is folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.

Where the EUT is a collection of equipment with each device having its own power cord, the point of connection for the LISN is determined from the following rules:

- a) Each power cord, which is terminated in a mains supply plug, shall be tested separately.
- b) Power cords, which are not specified by the manufacturer to be connected via a host unit, shall be tested separately.
- c) Power cords which are specified by the manufacturer to be connected via a host unit or other power supplying equipment shall be connected to that host unit and the power cords of that host unit connected to the LISN and tested.
- d) Where a special connection is specified, the necessary hardware to effect the connection is supplied by the manufacturer for the testing purpose.
- e) When testing equipment with multiple mains cords, those cords not under test are connected to an artificial mains network (AMN) different than the AMN used for the mains cord under test.


For AC mains port testing the desktop EUT are placed on a non-conducting table at least 0.8 meters from the metallic floor. The equipment is placed a minimum of 40 cm from all walls. Floor standing equipment is placed directly on the earth grounded floor.

| Type of Equipment | Manufacturer | Model Number | Serial Number | Date of Last Calibration |
|--------------------------------|-----------------|---------------------|---------------|--------------------------|
| Wanship Open Area Test Site #2 | Nemko-CCL, Inc. | N/A | N/A | 11/15/2010 |
| Test Software | Nemko-CCL, Inc. | Conducted Emissions | Revision 1.2 | N/A |
| Spectrum Analyzer | Hewlett Packard | 8566B | 2230A01711 | 01/05/2011 |
| Quasi-Peak Detector | Hewlett Packard | 85650A | 2043A00137 | 01/05/2011 |

| Type of Equipment | Manufacturer | Model Number | Serial Number | Date of Last Calibration |
|--------------------------------------|-----------------|--------------|---------------|--------------------------|
| LISN | EMCO | 3825/2 | 9305-2099 | 03/07/2011 |
| Conductance Cable Wanship Site #2 | Nemko-CCL, Inc. | Cable J | N/A | 12/21/2010 |
| Transient Limiter | Hewlett Packard | 11947A | 3107A02266 | 12/21/2010 |

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Conducted Emissions Test Setup



§15.247(a)(2) Emission Bandwidth

The EUT was connected to the spectrum analyzer using an attenuator via the antenna output port as shown in the block diagram below.

The measurements were performed on three channels, as per 47 CFR 15.31(m), one near the bottom of the spectrum, one near the middle of the spectrum and one near the top of the spectrum.


The spectrum analyzer’s resolution bandwidth and video bandwidth were set as follows:

RBW = 100 kHz
 VBW = 300 kHz

| Type of Equipment | Manufacturer | Model Number | Serial Number |
|----------------------------|-----------------|--------------|---------------|
| Spectrum Analyzer | Hewlett Packard | 8566B | 2230A01711 |
| Quasi-Peak Detector | Hewlett Packard | 85650A | 2043A00137 |
| Spectrum Analyzer/Receiver | Rohde & Schwarz | 1302.6005.40 | 100064 |
| Low Loss Cable (1 dB) | N/A | N/A | N/A |

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Test Configuration Block Diagram



§15.247(b)(3) Peak Output Power

The EUT was connected to the spectrum analyzer using an attenuator via the antenna output port as shown in the block diagram below.

The measurements were performed on three channels, as per 47 CFR 15.31(m), one near the bottom of the spectrum, one near the middle of the spectrum and one near the top of the spectrum.

The spectrum analyzer’s resolution bandwidth and video bandwidth were set as follows:


RBW = 1 MHz

VBW = >1 MHz

| Type of Equipment | Manufacturer | Model Number | Serial Number |
|----------------------------|-----------------|--------------|---------------|
| Spectrum Analyzer | Hewlett Packard | 8566B | 2230A01711 |
| Quasi-Peak Detector | Hewlett Packard | 85650A | 2043A00137 |
| Spectrum Analyzer/Receiver | Rohde & Schwarz | 1302.6005.40 | 100064 |
| Low Loss Cable (1 dB) | N/A | N/A | N/A |

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Test Configuration Block Diagram



§15.247(c) Conducted Spurious Emissions

The EUT was connected to the spectrum analyzer using an attenuator via the antenna output port as shown in the block diagram below.

The measurements were performed on three channels, as per 47 CFR 15.31(m), one near the bottom of the spectrum, one near the middle of the spectrum and one near the top of the spectrum.


The spectrum analyzer’s resolution bandwidth and video bandwidth were set as follows:

RBW = 100 kHz
 VBW = 300 kHz

| Type of Equipment | Manufacturer | Model Number | Serial Number |
|----------------------------|-----------------|--------------|---------------|
| Spectrum Analyzer | Hewlett Packard | 8566B | 2230A01711 |
| Quasi-Peak Detector | Hewlett Packard | 85650A | 2043A00137 |
| Spectrum Analyzer/Receiver | Rohde & Schwarz | 1302.6005.40 | 100064 |
| Low Loss Cable (1 dB) | N/A | N/A | N/A |

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Test Configuration Block Diagram



§15.247(c) Radiated Spurious Emissions in the Restricted Bands

The radiated emissions from the intentional radiator were measured using a spectrum analyzer with a quasi-peak adapter for peak and quasi-peak readings. An amplifier and preamplifier were used to increase the sensitivity of the measuring instrumentation. The quasi-peak adapter uses a bandwidth of 120 kHz, with the spectrum analyzer's resolution bandwidth set at 1 MHz, for readings in the 30 to 1000 MHz frequency ranges. For peak emissions above 1000 MHz the spectrum analyzer's resolution bandwidth was set to 1 MHz and the video bandwidth was set to 3 MHz. For average emissions above 1000 MHz the spectrum analyzer's resolution bandwidth was set to 1 MHz and the average detector of the analyzer was used.

A biconilog antenna was used to measure the frequency range of 30 to 1000 MHz and a Double Ridge Guide Horn antenna was used to measure the frequency range of 1 GHz to 18 GHz, and a Pyramidal Horn antenna was used to measure the frequency range of 18 GHz to 25 GHz, at a distance of 3 meters and 1 meter from the EUT. The readings obtained by the antenna are correlated to the levels obtained with a tuned dipole antenna by adding antenna factors.

The configuration of the intentional radiator was varied to find the maximum radiated emission. The intentional radiator was connected to the peripherals listed in Section 2.4 via the interconnecting cables listed in Section 2.5. These interconnecting cables were manipulated manually by a technician to obtain worst case radiated emissions. The intentional radiator was rotated 360 degrees, and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission. Where there are multiple interface ports all of the same type, cables are either placed on all of the ports or cables added to these ports until the emissions do not increase by more than 2 dB.


Desktop intentional radiators are measured on a non-conducting table 80 centimeters above the ground plane. The table is placed on a turntable which is level with the ground plane. The turntable has slip rings, which supply AC power to the intentional radiator. For equipment normally placed on floors, the equipment shall be placed directly on the turntable.

| Type of Equipment | Manufacturer | Model Number | Serial Number | Date of Last Calibration |
|--------------------------------|-----------------|--------------------|---------------|--------------------------|
| Wanship Open Area Test Site #2 | Nemko-CCL, Inc. | N/A | N/A | 11/15/2010 |
| Test Software | Nemko-CCL, Inc. | Radiated Emissions | Revision 1.3 | N/A |
| Spectrum Analyzer/Receiver | Rohde & Schwarz | 1302.6005.40 | 100064 | 07/30/2010 |
| Spectrum Analyzer | Hewlett Packard | 8566B | 2230A01711 | 01/05/2011 |
| Quasi-Peak Detector | Hewlett Packard | 85650A | 2043A00137 | 01/05/2011 |

| Type of Equipment | Manufacturer | Model Number | Serial Number | Date of Last Calibration |
|--|-----------------|------------------------|---------------|--------------------------|
| Biconilog Antenna | EMCO | 3142 | 9601-1008 | 10/15/2010 |
| Double Ridged Guide Antenna | EMCO | 3115 | 9604-4779 | 03/10/2011 |
| High Frequency Amplifier | Miteq | AFS4-01002650-35-10P-4 | 1637474 | 05/25/2011 |
| 6' High Frequency Cable | Microcoax | UFB197C-0-0720-000000 | 1296 | 05/10/2011 |
| 20' High Frequency Cable | Microcoax | UFB197C-1-3120-000000 | 1297 | 05/10//2011 |
| 3 Meter Radiated Emissions Cable Wanship Site #2 | Microcoax | UFB205A-0-4700-000000 | 1295 | 05/10/2011 |
| Pre/Power-Amplifier | Hewlett Packard | 8447F | 3113A05161 | 08/25/2010 |
| 6 dB Attenuator | Hewlett Packard | 8491A | 32835 | 12/21/2010 |

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Radiated Emissions Test Setup



§15.247(d) Peak Power Spectral Density

The EUT was connected to the spectrum analyzer using an attenuator via the antenna output port as shown in the block diagram below.

The measurements were performed on three channels, as per 47 CFR 15.31(m), one near the bottom of the spectrum, one near the middle of the spectrum and one near the top of the spectrum.


The spectrum analyzer’s resolution bandwidth and video bandwidth were set as follows:

RBW = 3 kHz
 VBW = 10 kHz

| Type of Equipment | Manufacturer | Model Number | Serial Number |
|----------------------------|-----------------|--------------|---------------|
| Spectrum Analyzer | Hewlett Packard | 8566B | 2230A01711 |
| Quasi-Peak Detector | Hewlett Packard | 85650A | 2043A00137 |
| Spectrum Analyzer/Receiver | Rohde & Schwarz | 1302.6005.40 | 100064 |
| Low Loss Cable (1 dB) | N/A | N/A | N/A |

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Test Configuration Block Diagram




APPENDIX 2 PHOTOGRAPHS

Photograph 1 – Front View Worst-Case Radiated Emissions Configuration



Photograph 2 – Back View Worst-Case Radiated Emissions Configuration



Photograph 3 – Front View Worst-Case Conducted Emissions Configuration




Photograph 4 – Back View Worst-Case Radiated Emissions Configuration




Photograph 5 – Front View of the EUT




Photograph 6 – Back View of the EUT



Photograph 7 – Rear Cover Removed Showing Antenna Mounting and Coax




Photograph 8 – View of the Antenna




Photograph 9 – View of the Component Side of the PCB with RF Shielding in Place



Photograph 10 - View of the Components Under the RF Shielding



Photograph 11 – View of the Trace Side of the PCB




APPENDIX 3 MANUFACTURER'S STATEMENT/ATTESTATION

The manufacturer or responsible party for the equipment tested hereby affirms:

- a) That he/she has reviewed and concurs that the tests shown in this report are reflective of the operational characteristics of the device for which certification is sought;
- b) That the device in this test report will be representative of production units;
- c) That the product will have all of the documented modifications incorporated into the product when manufactured and placed on the market;
- d) That all changes in hardware and software/firmware to the subject device will be reviewed.
- e) That any changes impacting the attributes, functionality or operational characteristics documented in this report will be communicated to the body responsible for approving or certifying the subject equipment.

Vaughn Staheli

Printed name of official



Signature of official

8 Aug 2011

Date

NOTE—This affirmation must be signed by the responsible party before it is submitted to a regulatory body for approval.