



FCC Radio Test Report

FCC ID: W59XWR600

This report concerns (check one): Original Grant Class II Change

Issued Date : Feb. 20, 2014
Project No. : 1401C155
Equipment : Daul Band Wireless 600N Router
Model Name : XWR-600
Applicant : Luxul Wireless
Address : 14203 Minuteman Drive, Suite 201,
Draper, UT USA

Tested by: Neutron Engineering Inc. EMC Laboratory
Date of Receipt: Jan. 22, 2014
Date of Test: Jan. 22, 2014 ~ Feb. 19, 2014

Testing Engineer : David Mao
(David Mao)

Technical Manager : Leo Hung
(Leo Hung)

Authorized Signatory : Steven Lu
(Steven Lu)

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia,
Dalang Town, Dong Guan, China.

TEL: 0769-8318-3000

FAX: 0769-8319-6000



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (NML) of R.O.C., or National Institute of Standards and Technology (NIST) of U.S.A.

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



Table of Contents	Page
1 . CERTIFICATION	7
2 . SUMMARY OF TEST RESULTS	8
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
3 . GENERAL INFORMATION	10
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	12
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	13
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	14
3.5 DESCRIPTION OF SUPPORT UNITS	15
4 . EMC EMISSION TEST	16
4.1 CONDUCTED EMISSION MEASUREMENT	16
4.1.1 POWER LINE CONDUCTED EMISSION	16
4.1.2 TEST PROCEDURE	16
4.1.3 DEVIATION FROM TEST STANDARD	16
4.1.4 TEST SETUP	17
4.1.5 EUT OPERATING CONDITIONS	17
4.1.6 EUT TEST CONDITIONS	17
4.1.7 TEST RESULTS	17
4.2 RADIATED EMISSION MEASUREMENT	20
4.2.1 RADIATED EMISSION LIMITS	20
4.2.2 TEST PROCEDURE	21
4.2.3 DEVIATION FROM TEST STANDARD	21
4.2.4 TEST SETUP	21
4.2.5 EUT OPERATING CONDITIONS	22
4.2.6 EUT TEST CONDITIONS	22
Test Voltage: 120V/60Hz	22
4.2.7 TEST RESULTS (9K~ 30MHz)	23
4.2.8 TEST RESULTS-BETWEEN 30MHZ - 1000MHZ	24
4.2.9 TEST RESULTS - ABOVE 1000MHZ	31
5 . 26dB SPECTRUM BANDWIDTH	51
5.1 APPLIED PROCEDURES / LIMIT	51
5.1.1 TEST PROCEDURE	51
5.1.2 DEVIATION FROM STANDARD	51
5.1.3 TEST SETUP	51
5.1.4 EUT OPERATION CONDITIONS	51
5.1.5 EUT TEST CONDITIONS	51
5.1.6 TEST RESULTS	52



Table of Contents	Page
6 . MAXIMUM CONDUCTED OUTPUT POWER	62
6.1 APPLIED PROCEDURES / LIMIT	62
6.1.1 TEST PROCEDURE	62
6.1.2 DEVIATION FROM STANDARD	63
6.1.3 TEST SETUP	63
6.1.4 EUT OPERATION CONDITIONS	63
6.1.5 EUT TEST CONDITIONS	63
6.1.6 TEST RESULTS	64
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	67
7.1 APPLIED PROCEDURES / LIMIT	67
7.1.1 TEST PROCEDURE	67
7.1.2 DEVIATION FROM STANDARD	67
7.1.3 TEST SETUP	67
7.1.4 EUT OPERATION CONDITIONS	67
7.1.5 EUT TEST CONDITIONS	67
7.1.6 TEST RESULTS	68
8 . POWER SPECTRAL DENSITY TEST	73
8.1 APPLIED PROCEDURES / LIMIT	73
8.1.1 TEST PROCEDURE	73
8.1.2 DEVIATION FROM STANDARD	73
8.1.3 TEST SETUP	73
8.1.4 EUT OPERATION CONDITIONS	73
8.1.5 EUT TEST CONDITIONS	73
9 . PEAK EXCURSION MEASUREMENT	86
9.1 APPLIED PROCEDURES / LIMIT	86
9.1.1 TEST PROCEDURE	86
9.1.2 DEVIATION FROM STANDARD	86
9.1.3 TEST SETUP	86
9.1.4 EUT OPERATION CONDITIONS	86
9.1.5 EUT TEST CONDITIONS	86
9.1.6 TEST RESULTS	87
10 . FREQUENCY STABILITY MEASUREMENT	97
10.1 APPLIED PROCEDURES / LIMIT	97
10.1.1 TEST PROCEDURE	97
10.1.2 DEVIATION FROM STANDARD	97
10.1.3 TEST SETUP	97
10.1.4 EUT OPERATION CONDITIONS	97
10.1.5 EUT TEST CONDITIONS	97
10.1.6 TEST RESULTS	98
11 . MEASUREMENT INSTRUMENTS LIST	99



Table of Contents

Page

12. EUT TEST PHOTO

101



REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
NEI-FCCP-1-1401C155	Original Issue.	Feb. 20, 2014



1. CERTIFICATION

Equipment : Daul Band Wireless 600N Router
Brand Name : Luxul Xen™
Model Name : XWR-600
Applicant : Luxul Wireless
Date of Test : Jan. 22, 2014 ~ Feb. 19, 2014
Test Item : ENGINEERING SAMPLE
Standard(s) : FCC Part15, Subpart E(15.407) / ANSI C63.4 : 2009;
FCC KDB 789033 D01 General UNII Test Procedures v01r03 .

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-2-1401C155) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part15, Subpart E			
Standard(s) Section	Test Item	Judgment	Remark
FCC			
15.207	AC Power Line Conducted Emissions	PASS	
15.407(a)	26dB Spectrum Bandwidth	PASS	
15.407(a)	Maximum Conducted Output Power	PASS	
15.407(a)	Power Spectral Density	PASS	
15.407(a)	Peak Excursion	PASS	
15.407(a)	Radiated Emissions	PASS	
15.407(b)	Band Edge Emissions	PASS	
15.407(g)	Frequency Stability	PASS	
15.203	Antenna Requirements	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this test report.



2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792
 Neutron's test firm number for FCC: 319330

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95%**.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
DG-CB03	CISPR	9KHz~30MHz	V	3.79	
		9KHz~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Daul Band Wireless 600N Router	
Brand Name	Luxul Xen™	
Model Name	XWR-600	
Mode Different	N/A	
Product Description	Operation Frequency	Band 1:5150MHz~5250MHz
	Modulation Type	OFDM
	Bit Rate of Transmitter	11a:6/ 9/12/18/24/36/48/54Mbps 11n:300Mbps
	Output Power (Max.)-Band 1	802.11a:15.26dBm 802.11N20:15.45 dBm 802.11N40:15.28 dBm
Power Source	DC voltage supplied from AC/DC adapter. Manufacturer: SHENZHEN HEWEISHUN NETWORK TECHNOLOGY CO., LTD Model: TEA12U-12100	
Power Rating	I/P: AC 100-240V~50/60Hz 0.3A O/P: DC 12V 1A	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2. Channel List:

802.11a/n20 MHz		802.11n 40MHz	
Band 1			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190
40	5200	46	5230
44	5220		
48	5240		

3. Antenna Specification:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1	LUXUL	Q5095	Dipole	N/A	6.06	TX/RX
2	LUXUL	Q5096	Dipole	N/A	6.06	TX/RX

Note:

(1) The EUT incorporates a MIMO function. Physically, the EUT provides two completed two transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, **Direction gain = G_{ANT}** , that is Directional gain=6.06.

4.

Operating Mode TX Mode	1TX	2TX
	802.11a	V (ANT 1 or ANT 2)
802.11n(20MHz)	-	V (ANT 1 + ANT 2)
802.11n(40MHz)	-	V (ANT 1 + ANT 2)



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Test Mode	Description
Mode 1	TX A Mode / CH36, CH40, CH48(Band 1)
Mode 2	TX N20 Mode / CH36, CH40, CH48(Band 1)
Mode 3	TX N40 Mode / CH38, CH46 (Band 1)
Mode 4	TX Mode

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 4	TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX A Mode / CH36, CH40, CH48(Band 1)
Mode 2	TX N20 Mode / CH36, CH40, CH48(Band 1)
Mode 3	TX N40 Mode / CH38, CH46 (Band 1)

Note: For Radiated Below 1G test, the 802.11a mode is found to be the worst case and recorded.



3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product

Test software version	MTool_2.0.0.3		
Frequency	5180 MHz	5200MHz	5240 MHz
A Mode	67	76	59
N20 Mode	66	65	64
Frequency	5190 MHz	5230MHz	
N40 Mode	52	66	




3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted TX Mode:



Radiated TX Mode:





3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID/IC	Series No.	Note
E-1	Notebook	HP	HP NB 331	DOC	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	10m	RJ45 Cable



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: 120V/60Hz

4.1.7 TEST RESULTS


Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 'Note'. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a "*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.



Test Mode : TX Mode

Line




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1970	44.51	9.65	54.16	63.74	-9.58	peak	
2	0.1970	32.54	9.65	42.19	53.74	-11.55	AVG	
3	0.2594	42.08	9.66	51.74	61.45	-9.71	peak	
4	0.2594	31.71	9.66	41.37	51.45	-10.08	AVG	
5	0.3844	34.66	9.68	44.34	58.18	-13.84	peak	
6	2.0758	36.32	9.84	46.16	56.00	-9.84	peak	
7	2.0758	26.37	9.84	36.21	46.00	-9.79	AVG	
8	2.5367	36.33	9.86	46.19	56.00	-9.81	peak	
9 *	2.5367	27.10	9.86	36.96	46.00	-9.04	AVG	
10	17.2227	37.56	10.30	47.86	60.00	-12.14	peak	



Test Mode : TX Mode

Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1930	37.87	9.71	47.58	63.91	-16.33	peak	
2		0.2633	48.21	9.72	57.93	61.33	-3.40	peak	
3	*	0.2633	38.70	9.72	48.42	51.33	-2.91	AVG	
4		0.4586	36.95	9.74	46.69	56.72	-10.03	peak	
5		0.4586	28.41	9.74	38.15	46.72	-8.57	AVG	
6		0.9234	33.82	9.77	43.59	56.00	-12.41	peak	
7		1.6891	34.46	9.84	44.30	56.00	-11.70	peak	
8		1.6891	24.36	9.84	34.20	46.00	-11.80	AVG	
9		2.9078	36.29	9.89	46.18	56.00	-9.82	peak	
10		2.9078	27.76	9.89	37.65	46.00	-8.35	AVG	



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.

LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

Frequencies (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBµV/m)
5150~5250	-27	68.3
5250~5350	-27	68.3
5470~5725	-27	68.3
5725~5825	-27	68.3
	-17	78.3

NOTE: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

4.2.2 TEST PROCEDURE


- a. The measuring distance of at 1.5m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


Radiated Emission Test Set-Up Frequency 30 - 1000MHz



Radiated Emission Test Set-Up Frequency Above 1 GHz



Radiated emissions below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 EUT TEST CONDITIONS

- Temperature: 25°C
- Relative Humidity: 55%
- Test Voltage: 120V/60Hz



4.2.7 TEST RESULTS (9K~ 30MHz)

Test Mode : TX Mode

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0094	0°	16.86	23.27	40.13	128.18	-88.05	AV
0.0094	0°	19.52	23.27	42.79	148.18	-105.39	PK
0.0142	0°	18.89	23.27	42.16	124.56	-82.40	AV
0.0144	0°	20.54	23.27	43.81	144.56	-100.75	PK
0.0245	0°	16.19	24.02	40.21	119.82	-79.62	AV
0.0247	0°	19.75	24.02	43.77	139.82	-96.06	PK
0.0333	0°	18.16	23.46	41.62	117.16	-75.54	AV
0.0335	0°	20.41	23.46	43.87	137.16	-93.29	PK
0.4210	0°	18.64	19.99	38.63	95.12	-56.49	AVG
0.4230	0°	21.91	19.99	41.90	115.12	-73.22	PK
1.5270	0°	18.82	19.55	38.37	63.93	-25.56	QP

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0092	90°	18.03	24.30	42.33	128.30	-85.97	AVG
0.0093	90°	20.46	24.30	44.76	148.30	-103.54	PK
0.0235	90°	17.55	24.08	41.63	120.18	-78.55	AVG
0.0237	90°	20.33	24.08	44.41	140.18	-95.77	PK
0.0316	90°	18.43	23.57	42.00	117.61	-75.62	AVG
0.0318	90°	20.67	23.57	44.24	137.61	-93.38	PK
0.0427	90°	17.85	22.86	40.71	115.00	-74.28	AVG
0.0429	90°	20.39	22.86	43.25	135.00	-91.74	PK
0.2360	90°	17.45	20.43	37.88	100.15	-62.27	AVG
0.2390	90°	20.72	20.43	41.15	120.15	-79.00	PK
1.6760	90°	18.63	19.53	38.16	63.12	-24.96	QP

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.



4.2.8 TEST RESULTS-BETWEEN 30MHZ - 1000MHZ


Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz ◦
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz ◦
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table ◦



Test Mode : Band 1/TX A Mode 5180MHz

Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	42.6100	47.22	-14.39	32.83	40.00	-7.17	peak	
2	125.0600	50.18	-13.61	36.57	43.50	-6.93	peak	
3	199.7500	51.09	-15.18	35.91	43.50	-7.59	peak	
4	250.1900	48.11	-14.97	33.14	46.00	-12.86	peak	
5	375.3200	43.19	-10.66	32.53	46.00	-13.47	peak	
6 *	624.6100	45.99	-6.86	39.13	46.00	-6.87	peak	



Test Mode : Band 1/TX A Mode 5180MHz

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		243.4000	49.07	-14.87	34.20	46.00	-11.80	peak	
2		375.3200	45.64	-10.66	34.98	46.00	-11.02	peak	
3		500.4500	44.09	-10.31	33.78	46.00	-12.22	peak	
4		624.6100	45.69	-6.86	38.83	46.00	-7.17	peak	
5		749.7400	38.44	-4.91	33.53	46.00	-12.47	peak	
6	*	874.8700	44.11	-2.48	41.63	46.00	-4.37	peak	



Test Mode : Band 1/TX A Mode 5200MHz

Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	42.6100	48.22	-14.39	33.83	40.00	-6.17	peak	
2	125.0600	50.18	-13.61	36.57	43.50	-6.93	peak	
3	199.7500	51.09	-15.18	35.91	43.50	-7.59	peak	
4	250.1900	51.11	-14.97	36.14	46.00	-9.86	peak	
5	375.3200	44.69	-10.66	34.03	46.00	-11.97	peak	
6 *	624.6100	47.99	-6.86	41.13	46.00	-4.87	peak	



Test Mode : Band 1/TX A Mode 5200MHz

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		113.4200	44.53	-14.45	30.08	43.50	-13.42	peak	
2		243.4000	49.57	-14.87	34.70	46.00	-11.30	peak	
3		375.3200	47.14	-10.66	36.48	46.00	-9.52	peak	
4		500.4500	44.09	-10.31	33.78	46.00	-12.22	peak	
5		624.6100	44.69	-6.86	37.83	46.00	-8.17	peak	
6	*	874.8700	44.11	-2.48	41.63	46.00	-4.37	peak	



Test Mode : Band 1/TX A Mode 5240MHz

Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	42.6100	47.22	-14.39	32.83	40.00	-7.17	peak	
2	95.9600	49.91	-17.07	32.84	43.50	-10.66	peak	
3	125.0600	50.18	-13.61	36.57	43.50	-6.93	peak	
4	199.7500	50.09	-15.18	34.91	43.50	-8.59	peak	
5	375.3200	45.19	-10.66	34.53	46.00	-11.47	peak	
6 *	624.6100	45.99	-6.86	39.13	46.00	-6.87	peak	



Test Mode : Band 1/TX A Mode 5240MHz

Horizontal



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	240.4900	49.79	-14.83	34.96	46.00	-11.04	peak	
2	375.3200	46.64	-10.66	35.98	46.00	-10.02	peak	
3	500.4500	44.59	-10.31	34.28	46.00	-11.72	peak	
4	624.6100	45.19	-6.86	38.33	46.00	-7.67	peak	
5	749.7400	40.44	-4.91	35.53	46.00	-10.47	peak	
6 *	874.8700	43.61	-2.48	41.13	46.00	-4.87	peak	



4.2.9 TEST RESULTS - ABOVE 1000MHZ

Remark:

- (1) Spectrum Setting : 30MHz – 1000MHz , RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 40GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated AV in column of 『Note 』 . Peak denotes that the Peak reading compliance with the AV Limits and then AV Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.



Test Mode : Band 1/ TX A Mode 5180MHz

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5150.00	V	19.20	8.63	42.72	61.92	51.35	-42.85	-53.42	68.30	54.00	-27.00	-41.30	X/E
5180.30	V	61.04	53.51	42.80	103.84	96.31	-0.93	-8.46					X/F
10359.04	V	44.05	33.24	16.02	60.07	49.26	-44.70	-55.51	68.30	54.00	-27.00	-41.30	X/H

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5150.00	H	10.25	0.98	42.72	52.97	43.70	-51.80	-61.07	68.30	54.00	-27.00	-41.30	X/E
5181.00	H	51.05	53.27	42.80	93.85	96.07	-10.92	-8.70					X/F
10358.62	H	42.04	32.15	16.02	58.06	48.17	-46.71	-56.60	68.30	54.00	-27.00	-41.30	X/H

Test Mode : Band 1/ TX A Mode 5200MHz

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5199.40	V	61.97	54.44	42.84	104.81	97.28	0.04	-7.49					X/F
10399.04	V	43.47	32.90	15.97	59.44	48.87	-45.33	-55.90	68.30	54.00	-27.00	-41.30	X/H

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5200.60	H	50.40	42.36	42.84	93.24	85.20	-11.53	-19.57					X/F
10401.62	H	41.10	31.47	15.96	57.06	47.43	-47.71	-57.34	68.30	54.00	-27.00	-41.30	X/H



Test Mode : Band 1/ TX A Mode 5240MHz

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5239.90	V	63.34	55.05	42.94	106.28	97.99	1.51	-6.78					X/F
10480.31	V	44.51	34.42	15.85	60.36	50.27	-44.41	-54.50	68.30	54.00	-27.00	-41.30	X/H

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5238.60	H	53.04	46.48	42.94	95.98	89.42	-8.79	-15.35					X/F
10479.56	H	42.31	32.41	15.86	58.17	48.27	-46.60	-56.50	68.30	54.00	-27.00	-41.30	X/H





Orthogonal Axis:X
Band 1/CH36(Above 1000 MHz, Vertical)







Orthogonal Axis:X
Band 1/CH36(Above 1000 MHz, Horizontal)







Orthogonal Axis:X
Band 1/CH40(Above 1000 MHz, Vertical)







Orthogonal Axis:X
Band 1/CH40(Above 1000 MHz, Horizontal)







Orthogonal Axis:X
Band 1/CH48(Above 1000 MHz, Vertical)





Orthogonal Axis:X
Band 1/CH48(Above 1000 MHz, Horizontal)





Test Mode : Band 1/ TX N20 Mode 5180MHz

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5150.00	V	17.13	8.25	42.72	59.85	50.97	-44.92	-53.80	68.30	54.00	-27.00	-41.30	X/E
5180.80	V	61.96	53.08	42.80	104.76	95.88	-0.01	-8.89					X/F
10359.47	V	41.47	31.69	16.03	57.50	47.72	-47.27	-57.05	68.30	54.00	-27.00	-41.30	X/H

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5150.00	H	8.74	1.61	42.72	51.46	44.33	-53.31	-60.44	68.30	54.00	-27.00	-41.30	X/E
5179.20	H	53.38	44.13	42.80	96.18	86.93	-8.59	-17.84					X/F
10361.13	H	40.98	30.74	16.02	57.00	46.76	-47.77	-58.01	68.30	54.00	-27.00	-41.30	X/H

Test Mode : Band 1/ TX N20 Mode 5200MHz

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5193.70	V	61.42	53.23	42.83	104.25	96.06	-0.52	-8.71					X/F
10398.94	V	42.96	32.13	15.97	58.93	48.10	-45.84	-56.67	68.30	54.00	-27.00	-41.30	X/H

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5201.00	H	51.83	42.94	42.84	94.67	85.78	-10.10	-18.99					X/F
10401.97	H	40.34	31.12	15.96	56.30	47.08	-48.47	-57.69	68.30	54.00	-27.00	-41.30	X/H



Test Mode : Band 1/ TX N20 Mode 5240MHz

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5246.90	V	62.07	52.96	42.96	105.03	95.92	0.26	-8.85					X/F
10480.78	V	42.70	32.76	15.85	58.55	48.61	-46.22	-56.16	68.30	54.00	-27.00	-41.30	X/H

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5241.00	H	55.03	45.30	42.94	97.97	88.24	-6.80	-16.53					X/F
10480.79	H	40.39	30.87	15.85	56.24	46.72	-48.53	-58.05	68.30	54.00	-27.00	-41.30	X/H





Orthogonal Axis: X
Band 1/CH36(Above 1000 MHz, Vertical)







Orthogonal Axis:X
Band 1/CH36(Above 1000 MHz, Horizontal)







Orthogonal Axis:X
Band 1/CH40(Above 1000 MHz, Vertical)







Orthogonal Axis:X
Band 1/CH40(Above 1000 MHz, Horizontal)







Orthogonal Axis:X
Band 1/CH48(Above 1000 MHz, Vertical)





Orthogonal Axis:X
Band 1/CH48(Above 1000 MHz, Horizontal)





Test Mode : Band 1/ TX N40 Mode 5190MHz

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5150.00	V	20.83	9.36	42.72	63.55	52.08	-41.22	-52.69	68.30	54.00	-27.00	-41.30	X/E
5187.20	V	57.82	46.81	42.81	100.63	89.62	-4.14	-15.15					X/F
10380.97	V	40.86	30.83	16.00	56.86	46.83	-47.91	-57.94	68.30	54.00	-27.00	-41.30	X/H

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5150.00	H	12.72	1.15	42.72	55.44	43.87	-49.33	-60.90	68.30	54.00	-27.00	-41.30	X/E
5191.00	H	46.92	36.18	42.82	89.74	79.00	-15.03	-25.77					X/F
10381.62	H	40.12	30.41	15.99	56.11	46.40	-48.66	-58.37	68.30	54.00	-27.00	-41.30	X/H



Test Mode : Band 1/ TX N40 Mode 5230MHz

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5231.60	V	61.35	51.06	42.92	104.27	93.98	-0.50	-10.79					X/F
10461.96	V	40.36	32.14	15.88	56.24	48.02	-48.53	-56.75	68.30	54.00	-27.00	-41.30	X/H

Freq. (MHz)	Ant.Pd. H/V	Reading		Ant./CF CF(dB)	Act.(dBuV/m)		Act.(dBm)		Limit(dBuV/m)		Limit(dBm)		Note
		Peak (dBuV)	AV (dBuV)		Peak	AV	Peak	AV	Peak	AV	Peak	AV	
5232.20	H	49.86	39.76	42.92	92.78	82.68	-11.99	-22.09					X/F
10458.36	H	42.10	30.41	15.87	57.97	46.28	-46.80	-58.49	68.30	54.00	-27.00	-41.30	X/H





Orthogonal Axis: X
Band 1/CH38(Above 1000 MHz, Vertical)







Orthogonal Axis: X
Band 1/CH38(Above 1000 MHz, Horizontal)







Orthogonal Axis:X
Band 1/CH46(Above 1000 MHz, Vertical)





Orthogonal Axis: X
Band 1/CH46(Above 1000 MHz, Horizontal)





5. 26dB SPECTRUM BANDWIDTH

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Limit	Frequency Range (MHz)	Result
26 dB Bandwidth	-----	5150MHz~5250	PASS

5.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

b.


Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RB	300 kHz
VB	1000 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

c. Measured the spectrum width with power higher than 26dB below carrier

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


5.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: 120V/60Hz



5.1.6 TEST RESULTS


Test Mode : Band 1/TX A Mode_CH36/40/48



Date: 27.JAN.2014 10:57:13




CH40



Date: 27.JAN.2014 11:09:02

CH48




Date: 27.JAN.2014 12:47:24



Test Mode : Band 1/TXN20 Mode_CH36/40/48-ANT 1


CH36



Date: 27.JAN.2014 13:04:09




CH40



Date: 27.JAN.2014 13:17:56

CH48




Date: 27.JAN.2014 13:14:10



Test Mode : Band 1/TXN20 Mode_CH36/40/48-ANT 2


CH36



Date: 27.JAN.2014 13:03:31




CH40



Date: 27.JAN.2014 13:17:23


CH48



Date: 27.JAN.2014 13:11:20




Test Mode : Band 1/TX N40 Mode_CH38/46-ANT 1



Date: 27.JAN.2014 13:54:17




CH46



Date: 27.JAN.2014 14:00:13




Test Mode : Band 1/TX N40 Mode_CH38/46-ANT 2



Date: 27.JAN.2014 13:53:56



CH46



Date: 27.JAN.2014 13:59:49



6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Frequency Range (MHz)	Limit	Result
Conducted Output Power	5150 - 5250	not exceed the lesser of 50 mW (17dBm) or 4 dBm + 10log B,	PASS

Note: where “B” is the 26 dB emissions bandwidth in MHz.

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	= 1 MHz.
VBW	≥ 3 MHz.
Detector	RMS
Trace	Max Hold
Sweep Time	auto

- b. Test was performed in accordance with method of KDB 789033 D01.



6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: 120V/60Hz



6.1.6 TEST RESULTS

Test Mode :Band 1/TX A Mode				
Test Channel	Frequency (MHz)	Conducted Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH36	5180	15.04	17.00	0.0501
CH40	5200	15.26	17.00	0.0501
CH48	5240	14.91	17.00	0.0501



Test Mode :Band 1/TX N20 Mode-ANT 1

Test Channel	Frequency (MHz)	Conducted Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH36	5180	12.57	17.00	0.0501
CH40	5200	12.36	17.00	0.0501
CH48	5240	12.58	17.00	0.0501

Test Mode :Band 1/TX N20 Mode-ANT 2

Test Channel	Frequency (MHz)	Conducted Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH36	5180	12.31	17.00	0.0501
CH40	5200	12.24	17.00	0.0501
CH48	5240	12.18	17.00	0.0501

Test Mode :Band 1/TX N20 Mode-Total

Test Channel	Frequency (MHz)	Conducted Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH36	5180	15.45	17.00	0.0501
CH40	5200	15.31	17.00	0.0501
CH48	5240	15.39	17.00	0.0501



Test Mode : Band 1/TX N40 Mode-ANT 1				
Test Channel	Frequency (MHz)	Conducted Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH38	5190	10.96	17.00	0.0501
CH46	5230	12.31	17.00	0.0501

Test Mode : Band 1/TX N40 Mode-ANT 2				
Test Channel	Frequency (MHz)	Conducted Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH38	5190	10.71	17.00	0.0501
CH46	5230	12.23	17.00	0.0501

Test Mode : Band 1/TX N40 Mode-Total				
Test Channel	Frequency (MHz)	Conducted Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH38	5190	13.85	17.00	0.0501
CH46	5230	15.28	17.00	0.0501



7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Limit	Frequency Range (MHz)	Result
Antenna conducted Spurious Emission	-27 dBm/1MHz	5150 – 5250	PASS

7.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

b.

Spectrum Parameter	Setting
Attenuation	Auto
RB	1000 kHz
VB	1000 kHz
Trace	Max Hold
Sweep Time	Auto

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 EUT TEST CONDITIONS


Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: 120V/60Hz



7.1.6 TEST RESULTS


Test Mode : Band 1/TX A Mode

TX mode CH36



Date: 27.JAN.2014 12:56:35

TX mode CH48




Date: 27.JAN.2014 12:54:01




Test Mode : Band 1/TX N20 Mode-ANT 2

TX mode CH36



Date: 27.JAN.2014 13:01:14

TX mode CH48




Date: 27.JAN.2014 13:09:17




Test Mode : Band 1/TX N40 Mode-ANT 1

TX mode CH38



Date: 27.JAN.2014 14:09:20

TX mode CH46




Date: 27.JAN.2014 14:07:03




Test Mode : Band 1/TX N40 Mode-ANT 2

TX mode CH38



Date: 27.JAN.2014 14:11:55

TX mode CH46



Date: 27.JAN.2014 14:06:51



8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Limit	Frequency Range (MHz)	Result
Power Spectral Density	4 dBm	5150 - 5250	PASS

8.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

b.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	= 1 MHz.
VB	≥ 3 MHz.
Detector	RMS
Trace	Max Hold
Sweep Time	Auto

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


8.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: 120V/60Hz



8.1.6 TEST RESULTS


Test Mode : Band 1/TX A Mode_CH36/40/48



Date: 27.JAN.2014 10:48:17




CH40



Date: 27.JAN.2014 11:09:57


CH48



Date: 27.JAN.2014 11:16:18




Test Mode : Band 1/TX N20 Mode_CH13/40/48-ANT 1



Date: 27.JAN.2014 13:32:23




CH40



Date: 27.JAN.2014 13:20:06


CH48



Date: 27.JAN.2014 13:38:34




Test Mode : Band 1/TX N20 Mode_CH13/40/48-ANT 2



Date: 19.JAN.2014 00:12:31




CH40



Date: 27.JAN.2014 13:19:58

CH48




Date: 27.JAN.2014 13:38:24



Test Mode : Band 1/TX N20 Mode-Total			
Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH36	5180	2.02	4.00
CH40	5200	3.34	4.00
CH48	5240	3.97	4.00




CH46



Date: 27.JAN.2014 13:58:42



CH46



Date: 27.JAN.2014 13:58:24



Test Mode : Band 1/TX N40 Mode-Total			
Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH38	5190	-2.72	4.00
CH46	5230	-1.72	4.00



9. PEAK EXCURSION MEASUREMENT

9.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Limit	Frequency Range (MHz)	Result
Peak Excursion Measurement	13 dB	5150 - 5250	PASS

9.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

b.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz (Peak Trace) / 1000 kHz (Average Trace)
VB	3000 kHz (Peak Trace) / 3000 kHz (Average Trace)
Detector	Peak (Peak Trace) / RMS (Average Trace)
Trace	Max Hold
Sweep Time	60s


c. Peak Trace: Set RBW = 1 MHz, VBW ≥ 3 MHz with peak detector and maxhold settings.

d. Average Trace: set RBW = 1 MHz, VBW = 3 MHz with RMS detector and trace average across 100 traces in power averaging mode.

9.1.2 DEVIATION FROM STANDARD

No deviation.

9.1.3 TEST SETUP



9.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

9.1.5 EUT TEST CONDITIONS

Temperature: 25°C
 Relative Humidity: 55%
 Test Voltage: 120V/60Hz




CH40



Date: 27.JAN.2014 11:12:15


CH48



Date: 27.JAN.2014 11:15:32




Test Mode :Band 1/TX N20 Mode_CH36/40/48-ANT 1



Date: 27.JAN.2014 13:31:51




CH40



Date: 27.JAN.2014 13:21:43


CH48



Date: 27.JAN.2014 13:38:03




Test Mode :Band 1/TX N20 Mode_CH36/40/48-ANT 2



Date: 27.JAN.2014 13:31:31




CH40



Date: 27.JAN.2014 13:21:01

CH48




Date: 27.JAN.2014 13:37:49



Test Mode :Band 1/TX N40 Mode_CH38/46-ANT 1


CH38



Date: 27.JAN.2014 13:55:35



CH46




Date: 27.JAN.2014 13:57:00



Test Mode :Band 1/TX N40 Mode_CH38/46-ANT 2


CH38



Date: 27.JAN.2014 13:55:21



CH46



Date: 27.JAN.2014 13:57:16



10. FREQUENCY STABILITY MEASUREMENT

10.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E 15.407(g)			
Test Item	Limit	Frequency Range (MHz)	Result
Frequency Stability	specified in the user's manual	5150 – 5250	PASS

10.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

b.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RB	10 kHz
VB	10 kHz
Sweep Time	Auto

c. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value.

d. user manual temperature is -30°C~50°C.

10.1.2 DEVIATION FROM STANDARD

No deviation.

10.1.3 TEST SETUP



10.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

10.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: 120V/60Hz



10.1.6 TEST RESULTS

Test Mode :	Band 1
--------------------	---------------

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5180
132	5180.012500
120	5179.985000
118	5179.984000
Max. Deviation (MHz)	0.016000
Max. Deviation (ppm)	3.09

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)
(°C)	5180
0	5179.973000
10	5179.976000
20	5179.974000
30	5179.975000
40	5179.977000
Max. Deviation (MHz)	0.027000
Max. Deviation (ppm)	5.21



11. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	Apr. 25, 2014
2	LISN	R&S	ENV216	100087	Nov.15, 2014
3	Test Cable	N/A	C_17	N/A	Mar.15, 2014
4	EMI TEST RECEIVER	R&S	ESCS30	826547/022	Apr. 25, 2014
5	50Ω Terminator	SHX	TF2-3G-A	08122902	Apr. 25, 2014

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Apr. 25, 2014
2	Amplifier	HP	8447D	2944A09673	Apr. 25, 2014
3	Test Receiver	R&S	ESCI	100382	Apr. 25, 2014
4	Test Cable	N/A	C-01_CB03	N/A	Jul. 02, 2014
5	Antenna	ETS	3115	00075789	Apr. 25, 2014
6	Amplifier	Agilent	8449B	3008A02274	Apr. 25, 2014
7	Spectrum	Agilent	E4408B	US39240143	Nov.15, 2014
8	Test Cable	HUBER+SUHNER	C-45	N/A	Apr. 30, 2014
9	Controller	CT	SC100	N/A	N/A
10	Horn Antenna	EMCO	3115	9605-4803	Apr. 25, 2014
11	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Apr. 25, 2014
12	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Oct. 22, 2014

26dB Spectrum Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.15, 2014

Maximum Conducted Output Power Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.15, 2014



Antenna Conducted Spurious Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.15, 2014

Power Spectral Density Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.15, 2014

Peak Excursion Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.15, 2014

Frequency Stability Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.15, 2014
2	Precision Oven Tester	HOLINK	H-T-1F-D	BA03101701	May.25.2014

Remark: "N/A" denotes no model name, serial no. or calibration specified.
 All calibration period of equipment list is one year.



12. EUT TEST PHOTO

Conducted Measurement Photos






**Radiated Measurement Photos
9K~30MHz**





**Radiated Measurement Photos
30~1000MHz**





**Radiated Measurement Photos
Above 1000MHz**

