



FCC TEST REPORT (15.247)

REPORT NO.: RF121031C14A
MODEL NO.: SBG6782-HH
(Refer to item 3.1 for more details)
FCC ID: W5HSBG6782HH
RECEIVED: Nov. 26, 2012
TESTED: Dec. 04 ~ Dec. 10, 2012
ISSUED: Dec. 12, 2012

APPLICANT: GENERAL INSTRUMENT OF TAIWAN, LTD.

ADDRESS: 1, Lane 232 , Pao Chiao Road , Shin Dian,
Taipei, Taiwan 231 , R.O.C

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	5
1. CERTIFICATION.....	6
2. SUMMARY OF TEST RESULTS	7
2.1 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION.....	8
3.1 GENERAL DESCRIPTION OF EUT.....	8
3.2 DESCRIPTION OF TEST MODES.....	10
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	11
3.3 DESCRIPTION OF SUPPORT UNITS.....	15
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST.....	16
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	17
4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND).....	18
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	18
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	18
4.1.2 TEST INSTRUMENTS	19
4.1.3 TEST PROCEDURES.....	20
4.1.4 DEVIATION FROM TEST STANDARD	20
4.1.5 TEST SETUP	21
4.1.6 EUT OPERATING CONDITIONS.....	21
4.1.7 TEST RESULTS	22
4.2 CONDUCTED EMISSION MEASUREMENT.....	35
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	35
4.2.2 TEST INSTRUMENTS	35
4.2.3 TEST PROCEDURES.....	36
4.2.4 DEVIATION FROM TEST STANDARD	36
4.2.5 TEST SETUP	36
4.2.6 EUT OPERATING CONDITIONS.....	36
4.2.7 TEST RESULTS	37
4.3 6dB BANDWIDTH MEASUREMENT	39
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	39
4.3.2 TEST SETUP	39
4.3.3 TEST INSTRUMENTS	39
4.3.4 TEST PROCEDURE	39
4.3.5 DEVIATION FROM TEST STANDARD	39
4.3.6 EUT OPERATING CONDITIONS.....	39
4.3.7 TEST RESULTS	40
4.4 CONDUCTED OUTPUT POWER	41
4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....	41
4.4.2 TEST SETUP	41
4.4.3 TEST INSTRUMENTS	41
4.4.4 TEST PROCEDURES.....	41
4.4.5 DEVIATION FROM TEST STANDARD	42
4.4.6 EUT OPERATING CONDITIONS.....	42
4.4.7 TEST RESULTS	43
4.5 POWER SPECTRAL DENSITY MEASUREMENT.....	44
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	44
4.5.2 TEST SETUP	44
4.5.3 TEST INSTRUMENTS	44



4.5.4	TEST PROCEDURE	44
4.5.5	DEVIATION FROM TEST STANDARD	44
4.5.6	EUT OPERATING CONDITION	44
4.5.7	TEST RESULTS	45
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	47
4.6.1	LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT	47
4.6.2	TEST SETUP	47
4.6.3	TEST INSTRUMENTS	47
4.6.4	TEST PROCEDURE	47
4.6.5	DEVIATION FROM TEST STANDARD	48
4.6.6	EUT OPERATING CONDITION	48
4.6.7	TEST RESULTS	48
4.6.8	TEST RESULTS	49
5.	TEST TYPES AND RESULTS (FOR 5.0GHz BAND)	53
5.1	RADIATED EMISSION MEASUREMENT	53
5.1.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	53
5.1.2	TEST INSTRUMENTS	54
5.1.3	TEST PROCEDURES	54
5.1.4	DEVIATION FROM TEST STANDARD	54
5.1.5	TEST SETUP	54
5.1.6	EUT OPERATING CONDITIONS	54
5.1.7	TEST RESULTS	55
5.2	CONDUCTED EMISSION MEASUREMENT	64
5.2.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	64
5.2.2	TEST INSTRUMENTS.....	64
5.2.3	TEST PROCEDURES	64
5.2.4	DEVIATION FROM TEST STANDARD	64
5.2.5	TEST SETUP	64
5.2.6	EUT OPERATING CONDITIONS	64
5.2.7	TEST RESULTS	65
5.3	6dB BANDWIDTH MEASUREMENT	67
5.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	67
5.3.2	TEST SETUP	67
5.3.3	TEST INSTRUMENTS	67
5.3.4	TEST PROCEDURE	67
5.3.5	DEVIATION FROM TEST STANDARD	67
5.3.6	EUT OPERATING CONDITIONS	67
5.3.7	TEST RESULTS	68
5.4	CONDUCTED OUTPUT POWER	69
5.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	69
5.4.2	TEST SETUP	69
5.4.3	INSTRUMENTS.....	69
5.4.4	TEST PROCEDURES	69
5.4.5	DEVIATION FROM TEST STANDARD	69
5.4.6	EUT OPERATING CONDITIONS	69
5.4.7	TEST RESULTS	70
5.5	POWER SPECTRAL DENSITY MEASUREMENT	71
5.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	71
5.5.2	TEST SETUP	71
5.5.3	TEST INSTRUMENTS	71
5.5.4	TEST PROCEDURE	71



5.5.5	DEVIATION FROM TEST STANDARD	71
5.5.6	EUT OPERATING CONDITION	71
5.5.7	TEST RESULTS	72
5.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	73
5.6.1	LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT	73
5.6.2	TEST SETUP	73
5.6.3	TEST INSTRUMENTS	73
5.6.4	TEST PROCEDURE	73
5.6.5	DEVIATION FROM TEST STANDARD	73
5.6.6	EUT OPERATING CONDITION	73
5.6.7	TEST RESULTS	73
6.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	77
7.	INFORMATION ON THE TESTING LABORATORIES	78
8.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	79



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF121031C14A	Original release	Dec. 12, 2012



A D T

1. CERTIFICATION

PRODUCT: Wireless Gateway
MODEL NO.: SBG6782-HH (Refer to item 3.1 for more details)
BRAND: Motorola
APPLICANT: GENERAL INSTRUMENT OF TAIWAN, LTD.
TESTED: Dec. 04 ~ Dec. 10, 2012
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Part 15, Subpart C (Section 15.247)**
ANSI C63.10-2009

The above equipment (model: SBG6782-HH) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Celine Chou , **DATE** : Dec. 12, 2012
Celine Chou / Specialist

APPROVED BY : Ken Liu , **DATE** : Dec. 12, 2012
Ken Liu / Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -11.02dB at 0.36094MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -0.1dB at 2483.50MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is IPEX not a standard connector.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.19 dB
	200MHz ~1000MHz	3.21 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Wireless Gateway
MODEL NO.	SBG6782-HH (Refer to note for more details)
POWER SUPPLY	100-240Vac
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 450.0Mbps
OPERATING FREQUENCY	2.4GHz: 2412 ~ 2462MHz 5.0GHz: 5745 ~ 5825MHz
NUMBER OF CHANNEL	2.4GHz: 11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz) 5.0GHz: 5 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz)
OUTPUT POWER	574.182mW for 2412 ~ 2462MHz 704.947mW for 5745 ~ 5825MHz
ANTENNA TYPE	2.4GHz: Printed antenna with 4.4dBi gain 5.0GHz: Printed antenna with 3.5dBi gain
ANTENNA CONNECTOR	IPEX
DATA CABLE	1.8m non-shielded RJ45 cable w/o core 1.5m non-shielded Diagnostic cable w/o core
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	2.0m non-shielded power cable w/o core

NOTE:

- All models are listed as below.

EUT	Model	Difference
1	SBG6782-HH	without Diagnostic & USB port
2	SBG6782U-HH	with USB port
3	SBG6782U-HH Diagnostic	with Diagnostic & USB port

*The model: SBG6782-HH was chosen for the final test and presented in the test report.



A D T

2. The EUT incorporates a MIMO function. Physically, the EUT provides three completed transmitters and three receivers.

MODULATION MODE	TX FUNCTION
802.11b	1TX
802.11g	1TX
802.11a	1TX
802.11n (20MHz)	3TX
802.11n (40MHz)	3TX

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 DESCRIPTION OF TEST MODES

FOR 2.4GHz:

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

FOR 5.0GHz (5745 ~ 5825MHz):

5 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
151	5755MHz	159	5795MHz

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

FOR 2.4GHz:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE \geq 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where RE \geq 1G: Radiated Emission above 1GHz RE<1G: Radiated Emission below 1GHz
 PLC: Power Line Conducted Emission APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
-	802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	1 to 11	6	OFDM	BPSK	7.2

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	1 to 11	6	OFDM	BPSK	7.2

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	7.2
-	802.11n (40MHz)	3 to 9	3, 9	OFDM	BPSK	15.0

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
-	802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE _≥ 1G	24deg. C, 67%RH	120Vac, 60Hz	Chris Lin
RE _{<} 1G	24deg. C, 64%RH	120Vac, 60Hz	Martin Lee
PLC	26deg. C, 62%RH	120Vac, 60Hz	Cedric Wu
APCM	25deg. C, 60%RH	120Vac, 60Hz	Frank Liu

FOR 5.0GHz (5745 ~ 5825MHz):

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6.0
-	802.11n (20MHz)	149 to 165	149, 157, 165	OFDM	BPSK	7.2
-	802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	15.0

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (40MHz)	151 to 159	159	OFDM	BPSK	15.0

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (40MHz)	151 to 159	159	OFDM	BPSK	15.0

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	149 to 165	149, 165	OFDM	BPSK	6.0
-	802.11n (20MHz)	149 to 165	149, 165	OFDM	BPSK	7.2
-	802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	15.0

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6.0
-	802.11n (20MHz)	149 to 165	149, 157, 165	OFDM	BPSK	7.2
-	802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	15.0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE \geq 1G	24deg. C, 67%RH	120Vac, 60Hz	Match Tsui
RE $<$ 1G	24deg. C, 64%RH	120Vac, 60Hz	Martin Lee
PLC	26deg. C, 62%RH	120Vac, 60Hz	Cedric Wu
APCM	25deg. C, 60%RH	120Vac, 60Hz	Frank Liu

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	E5420	33MJMQ1	NA
2	USB FLASH DRIVE	Transcend	V85	538455 4481	NA
3	USB FLASH DRIVE	Transcend	V85	538455 4490	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	10m non-shielded RJ45 cable.
2	NA
3	NA

NOTE:

1. All power cords of the above support units are non shielded (1.8m).
2. Item 1 acted as communication partner to transfer data.

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v02

662911 D01 Multiple Transmitter Output v01 r02

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100212	Aug. 06, 2012	Aug. 05, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Feb. 03, 2012	Feb. 02, 2013
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Apr. 06, 2012	Apr. 05, 2013
HORN Antenna SCHWARZBECK	9120D	209	Sep. 03, 2012	Sep. 02, 2013
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 11, 2012	Jul. 10, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent	8447D	2944A10633	Oct. 25, 2012	Oct. 24, 2013
Preamplifier Agilent	8449B	3008A01964	Oct. 25, 2012	Oct. 24, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250723/4	Aug. 28, 2012	Aug. 27, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 106	12738/6+309224/ 4	Aug. 28, 2012	Aug. 27, 2013
Software ADT.	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA	NA
Turn Table ADT.	TT100	TT93021703	NA	NA
Turn Table Controller ADT.	SC100	SC93021703	NA	NA
26GHz ~ 40GHz Amplifier	EM26400	815221	Oct. 25, 2012	Oct. 24, 2013
High Speed Peak Power Meter	ML2495A	0842014	Apr. 28, 2012	Apr. 27, 2013
Power Sensor	MA2411B	0738404	Apr. 28, 2012	Apr. 27, 2013

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in HwaYa Chamber 3.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The FCC Site Registration No. is 988962.
6. The IC Site Registration No. is IC 7450F-3.

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 100kHz and video bandwidth is 300kHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Placed the EUT on the testing table.
- Prepared Notebook to act as communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and run a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".
- The necessary accessories enable the system in full functions.

4.1.7 TEST RESULTS

802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.6 PK	74.0	-18.4	1.02 H	310	24.80	30.80
2	2390.00	45.3 AV	54.0	-8.7	1.02 H	310	14.50	30.80
3	*2412.00	106.9 PK			1.02 H	310	76.00	30.90
4	*2412.00	102.8 AV			1.02 H	310	71.90	30.90
5	4824.00	44.8 PK	74.0	-29.2	1.20 H	187	7.80	37.00
6	4824.00	40.4 AV	54.0	-13.6	1.20 H	187	3.40	37.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.0 PK	74.0	-10.0	1.42 V	360	33.20	30.80
2	2390.00	53.7 AV	54.0	-0.3	1.42 V	360	22.90	30.80
3	*2412.00	115.6 PK			1.39 V	360	84.70	30.90
4	*2412.00	111.7 AV			1.39 V	360	80.80	30.90
5	4824.00	52.2 PK	74.0	-21.8	1.43 V	27	15.20	37.00
6	4824.00	47.5 AV	54.0	-6.5	1.43 V	27	10.50	37.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2357.00	55.6 PK	74.0	-18.4	1.10 H	300	24.90	30.70
2	2357.00	43.8 AV	54.0	-10.2	1.10 H	300	13.10	30.70
3	*2437.00	107.9 PK			1.03 H	300	76.90	31.00
4	*2437.00	103.9 AV			1.03 H	300	72.90	31.00
5	#3249.00	60.7 PK	87.9	-27.2	1.10 H	188	27.70	33.00
6	#3249.00	54.6 AV	83.9	-29.3	1.10 H	188	21.60	33.00
7	4874.00	45.1 PK	74.0	-28.9	1.19 H	179	8.00	37.10
8	4874.00	40.8 AV	54.0	-13.2	1.19 H	179	3.70	37.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2357.00	63.4 PK	74.0	-10.6	1.18 V	26	32.70	30.70
2	2357.00	51.7 AV	54.0	-2.3	1.18 V	26	21.00	30.70
3	*2437.00	116.6 PK			1.13 V	33	85.60	31.00
4	*2437.00	112.5 AV			1.13 V	33	81.50	31.00
5	#3249.00	68.8 PK	96.6	-27.8	1.00 V	360	35.80	33.00
6	#3249.00	62.9 AV	92.5	-29.6	1.00 V	360	29.90	33.00
7	4874.00	53.7 PK	74.0	-20.3	1.02 V	34	16.60	37.10
8	4874.00	49.8 AV	54.0	-4.2	1.02 V	34	12.70	37.10

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.2 PK			1.05 H	330	75.10	31.10
2	*2462.00	102.4 AV			1.05 H	330	71.30	31.10
3	2483.50	54.6 PK	74.0	-19.4	1.05 H	330	23.40	31.20
4	2483.50	43.5 AV	54.0	-10.5	1.05 H	330	12.30	31.20
5	#3282.00	60.6 PK	86.2	-25.6	1.21 H	187	27.60	33.00
6	#3282.00	53.5 AV	82.4	-28.9	1.21 H	187	20.50	33.00
7	4924.00	44.5 PK	74.0	-29.5	1.15 H	210	7.30	37.20
8	4924.00	40.5 AV	54.0	-13.5	1.15 H	210	3.30	37.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	115.0 PK			1.11 V	360	83.90	31.10
2	*2462.00	111.1 AV			1.11 V	360	80.00	31.10
3	2483.50	62.5 PK	74.0	-11.5	1.12 V	360	31.30	31.20
4	2483.50	51.3 AV	54.0	-2.7	1.12 V	360	20.10	31.20
5	#3282.00	67.5 PK	95.0	-27.5	1.00 V	0	34.50	33.00
6	#3282.00	61.1 AV	91.1	-30.0	1.00 V	0	28.10	33.00
7	4924.00	53.5 PK	74.0	-20.5	1.14 V	36	16.30	37.20
8	4924.00	49.2 AV	54.0	-4.8	1.14 V	36	12.00	37.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.

802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.8 PK	74.0	-13.2	1.03 H	300	30.00	30.80
2	2390.00	44.9 AV	54.0	-9.1	1.03 H	300	14.10	30.80
3	*2412.00	105.0 PK			1.03 H	300	74.10	30.90
4	*2412.00	92.4 AV			1.03 H	300	61.50	30.90
5	#3216.00	61.4 PK	85.0	-23.6	1.20 H	187	28.50	32.90
6	#3216.00	56.4 AV	72.4	-16.0	1.20 H	187	23.50	32.90
7	4824.00	50.4 PK	74.0	-23.6	1.20 H	360	13.40	37.00
8	4824.00	32.4 AV	54.0	-21.6	1.20 H	360	-4.60	37.00

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.2 PK	74.0	-4.8	1.15 V	77	38.40	30.80
2	2390.00	53.2 AV	54.0	-0.8	1.15 V	77	22.40	30.80
3	*2412.00	112.5 PK			1.18 V	13	81.60	30.90
4	*2412.00	101.1 AV			1.18 V	13	70.20	30.90
5	#3216.00	68.8 PK	92.5	-23.7	1.21 V	360	35.90	32.90
6	#3216.00	64.3 AV	81.1	-16.8	1.21 V	360	31.40	32.90
7	4824.00	52.4 PK	74.0	-21.6	1.20 V	360	15.40	37.00
8	4824.00	34.2 AV	54.0	-19.8	1.20 V	360	-2.80	37.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. "#": The radiated frequency is out the restricted band.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2357.00	55.4 PK	74.0	-18.6	1.01 H	298	24.70	30.70
2	2357.00	42.9 AV	54.0	-11.1	1.01 H	298	12.20	30.70
3	*2437.00	110.2 PK			1.01 H	298	79.20	31.00
4	*2437.00	97.3 AV			1.01 H	298	66.30	31.00
5	4874.00	50.8 PK	74.0	-23.2	1.00 H	360	13.70	37.10
6	4874.00	32.9 AV	54.0	-21.1	1.00 H	360	-4.20	37.10
7	7311.00	45.7 PK	74.0	-28.3	1.00 H	188	2.10	43.60
8	7311.00	33.6 AV	54.0	-20.4	1.00 H	188	-10.00	43.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2357.00	63.5 PK	74.0	-10.5	1.17 V	360	32.80	30.70
2	2357.00	51.2 AV	54.0	-2.8	1.17 V	360	20.50	30.70
3	*2437.00	118.9 PK			1.11 V	33	87.90	31.00
4	*2437.00	106.0 AV			1.11 V	33	75.00	31.00
5	4874.00	53.0 PK	74.0	-21.0	1.17 V	344	15.90	37.10
6	4874.00	35.4 AV	54.0	-18.6	1.17 V	344	-1.70	37.10
7	7311.00	50.8 PK	74.0	-23.2	1.14 V	163	7.20	43.60
8	7311.00	38.1 AV	54.0	-15.9	1.14 V	163	-5.50	43.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.5 PK			1.04 H	314	71.40	31.10
2	*2462.00	92.3 AV			1.04 H	314	61.20	31.10
3	2483.50	58.3 PK	74.0	-15.7	1.04 H	314	27.10	31.20
4	2483.50	45.0 AV	54.0	-9.0	1.04 H	314	13.80	31.20
5	4924.00	50.6 PK	74.0	-23.4	1.00 H	360	13.40	37.20
6	4924.00	32.9 AV	54.0	-21.1	1.00 H	360	-4.30	37.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.3 PK			1.35 V	33	80.20	31.10
2	*2462.00	100.9 AV			1.35 V	33	69.80	31.10
3	2483.50	66.7 PK	74.0	-7.3	1.10 V	360	35.50	31.20
4	2483.50	53.4 AV	54.0	-0.6	1.10 V	360	22.20	31.20
5	4924.00	53.1 PK	74.0	-20.9	1.21 V	178	15.90	37.20
6	4924.00	34.8 AV	54.0	-19.2	1.21 V	178	-2.40	37.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.5 PK	74.0	-7.5	1.16 H	326	35.70	30.80
2	2390.00	52.6 AV	54.0	-1.4	1.16 H	326	21.80	30.80
3	*2412.00	107.7 PK			1.08 H	146	76.80	30.90
4	*2412.00	98.8 AV			1.08 H	146	67.90	30.90
5	#3216.00	53.0 PK	87.7	-34.7	1.15 H	132	20.10	32.90
6	#3216.00	51.2 AV	78.8	-27.6	1.15 H	132	18.30	32.90
7	4824.00	46.3 PK	74.0	-27.7	1.32 H	45	9.30	37.00
8	4824.00	32.5 AV	54.0	-21.5	1.32 H	45	-4.50	37.00

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.3 PK	74.0	-7.7	1.41 V	36	35.50	30.80
2	2390.00	53.8 AV	54.0	-0.2	1.41 V	36	23.00	30.80
3	*2412.00	110.2 PK			1.41 V	360	79.30	30.90
4	*2412.00	101.5 AV			1.41 V	360	70.60	30.90
5	#3216.00	62.5 PK	90.2	-27.7	1.23 V	25	29.60	32.90
6	#3216.00	60.9 AV	81.5	-20.6	1.23 V	25	28.00	32.90
7	4824.00	45.8 PK	74.0	-28.2	1.00 V	25	8.80	37.00
8	4824.00	33.9 AV	54.0	-20.1	1.00 V	25	-3.10	37.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. "#":The radiated frequency is out the restricted band.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	114.4 PK			1.07 H	300	83.40	31.00
2	*2437.00	104.3 AV			1.07 H	300	73.30	31.00
3	#3249.00	53.4 PK	94.4	-41.0	1.24 H	189	20.40	33.00
4	#3249.00	51.6 AV	84.3	-32.7	1.24 H	189	18.60	33.00
5	4874.00	47.4 PK	74.0	-26.6	1.23 H	360	10.30	37.10
6	4874.00	35.4 AV	54.0	-18.6	1.23 H	360	-1.70	37.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	117.0 PK			1.31 V	61	86.00	31.00
2	*2437.00	107.0 AV			1.31 V	61	76.00	31.00
3	#3249.00	61.7 PK	97.0	-35.3	1.01 V	13	28.70	33.00
4	#3249.00	60.3 AV	87.0	-26.7	1.01 V	13	27.30	33.00
5	4874.00	54.1 PK	74.0	-19.9	1.32 V	254	17.00	37.10
6	4874.00	42.5 AV	54.0	-11.5	1.32 V	254	5.40	37.10

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.2 PK			1.02 H	153	77.10	31.10
2	*2462.00	90.1 AV			1.02 H	153	59.00	31.10
3	2483.50	65.1 PK	74.0	-8.9	1.02 H	153	33.90	31.20
4	2483.50	51.4 AV	54.0	-2.6	1.02 H	153	20.20	31.20
5	4924.00	46.5 PK	74.0	-27.5	1.19 H	300	9.30	37.20
6	4924.00	32.8 AV	54.0	-21.2	1.19 H	300	-4.40	37.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.1 PK			1.11 V	23	80.00	31.10
2	*2462.00	100.7 AV			1.11 V	23	69.60	31.10
3	2483.50	67.0 PK	74.0	-7.0	1.09 V	18	35.80	31.20
4	2483.50	53.9 AV	54.0	-0.1	1.09 V	18	22.70	31.20
5	4924.00	46.1 PK	74.0	-27.9	1.00 V	34	8.90	37.20
6	4924.00	34.3 AV	54.0	-19.7	1.00 V	34	-2.90	37.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.9 PK	74.0	-11.1	1.07 H	310	32.10	30.80
2	2390.00	51.8 AV	54.0	-2.2	1.07 H	310	21.00	30.80
3	*2422.00	101.4 PK			1.07 H	310	70.50	30.90
4	*2422.00	91.9 AV			1.07 H	310	61.00	30.90
5	#3229.00	54.3 PK	81.4	-27.1	1.00 H	10	21.30	33.00
6	#3229.00	53.7 AV	71.9	-18.2	1.00 H	10	20.70	33.00
7	4844.00	45.7 PK	74.0	-28.3	1.00 H	34	8.70	37.00
8	4844.00	33.0 AV	54.0	-21.0	1.00 H	34	-4.00	37.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.7 PK	74.0	-5.3	1.13 V	56	37.90	30.80
2	2390.00	53.7 AV	54.0	-0.3	1.13 V	56	22.90	30.80
3	*2422.00	103.8 PK			1.15 V	23	72.90	30.90
4	*2422.00	94.5 AV			1.15 V	23	63.60	30.90
5	#3229.00	62.4 PK	83.8	-21.4	1.00 V	37	29.40	33.00
6	#3229.00	61.6 AV	74.5	-12.9	1.00 V	37	28.60	33.00
7	4844.00	46.8 PK	74.0	-27.2	1.00 V	25	9.80	37.00
8	4844.00	34.2 AV	54.0	-19.8	1.00 V	25	-2.80	37.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. "#":The radiated frequency is out the restricted band.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.1 PK	74.0	-7.9	1.00 H	311	35.30	30.80
2	2390.00	51.2 AV	54.0	-2.8	1.00 H	311	20.40	30.80
3	*2437.00	108.6 PK			1.00 H	309	77.60	31.00
4	*2437.00	98.9 AV			1.00 H	309	67.90	31.00
5	2483.50	65.1 PK	74.0	-8.9	1.00 H	309	33.90	31.20
6	2483.50	48.9 AV	54.0	-5.1	1.00 H	309	17.70	31.20
7	#3249.00	52.2 PK	88.6	-36.4	1.04 H	340	19.20	33.00
8	#3249.00	50.7 AV	78.9	-28.2	1.04 H	340	17.70	33.00
9	4874.00	43.8 PK	74.0	-30.2	1.00 H	360	6.70	37.10
10	4874.00	32.6 AV	54.0	-21.4	1.00 H	360	-4.50	37.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.6 PK	74.0	-5.4	1.41 V	71	37.80	30.80
2	2390.00	53.5 AV	54.0	-0.5	1.41 V	71	22.70	30.80
3	*2437.00	111.3 PK			1.13 V	0	80.30	31.00
4	*2437.00	101.2 AV			1.13 V	0	70.20	31.00
5	2483.50	67.3 PK	74.0	-6.7	1.42 V	24	36.10	31.20
6	2483.50	51.0 AV	54.0	-3.0	1.42 V	24	19.80	31.20
7	#3249.00	60.1 PK	91.3	-31.2	1.00 V	54	27.10	33.00
8	#3249.00	58.9 AV	81.2	-22.3	1.00 V	54	25.90	33.00
9	4874.00	45.4 PK	74.0	-28.6	1.02 V	333	8.30	37.10
10	4874.00	35.3 AV	54.0	-18.7	1.02 V	333	-1.80	37.10

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 9	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	105.2 PK			1.07 H	301	74.10	31.10
2	*2452.00	95.5 AV			1.07 H	301	64.40	31.10
3	2483.50	67.1 PK	74.0	-6.9	1.07 H	301	35.90	31.20
4	2483.50	51.0 AV	54.0	-3.0	1.07 H	301	19.80	31.20
5	#3269.00	50.2 PK	85.2	-35.0	1.00 H	350	17.20	33.00
6	#3269.00	49.5 AV	75.5	-26.0	1.00 H	350	16.50	33.00
7	4904.00	45.4 PK	74.0	-28.6	1.00 H	10	8.20	37.20
8	4904.00	32.8 AV	54.0	-21.2	1.00 H	10	-4.40	37.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	107.7 PK			1.13 V	19	76.60	31.10
2	*2452.00	98.2 AV			1.13 V	19	67.10	31.10
3	2483.50	69.8 PK	74.0	-4.2	1.35 V	70	38.60	31.20
4	2483.50	53.4 AV	54.0	-0.6	1.35 V	70	22.20	31.20
5	#3269.00	58.2 PK	87.7	-29.5	1.00 V	62	25.20	33.00
6	#3269.00	57.8 AV	78.2	-20.4	1.00 V	62	24.80	33.00
7	4904.00	46.8 PK	74.0	-27.2	1.04 V	350	9.60	37.20
8	4904.00	34.5 AV	54.0	-19.5	1.04 V	350	-2.70	37.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”: The radiated frequency is out the restricted band.

BELOW 1GHz WORST-CASE DATA : 802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	125.17	38.2 QP	43.5	-5.3	1.50 H	245	25.90	12.30
2	269.05	41.1 QP	46.0	-4.9	1.00 H	209	27.30	13.80
3	480.97	38.9 QP	46.0	-7.1	2.00 H	85	19.40	19.50
4	624.85	35.5 QP	46.0	-10.5	2.00 H	245	13.20	22.30
5	751.23	42.1 QP	46.0	-3.9	1.00 H	174	17.70	24.40
6	875.67	40.2 QP	46.0	-5.8	2.00 H	298	13.70	26.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	125.17	38.8 QP	43.5	-4.7	1.00 V	218	26.50	12.30
2	179.61	36.3 QP	43.5	-7.2	1.00 V	188	23.70	12.60
3	269.05	41.3 QP	46.0	-4.7	2.00 V	7	27.50	13.80
4	480.97	44.2 QP	46.0	-1.8	1.00 V	210	24.70	19.50
5	500.42	44.0 QP	46.0	-2.0	1.00 V	177	24.00	20.00
6	875.67	40.1 QP	46.0	-5.9	1.50 V	318	13.60	26.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 09, 2012	Nov. 08, 2013
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 29, 2011	Dec. 28, 2012
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 30, 2011	Dec. 29, 2012
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 06, 2012	Jul. 05, 2013
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



- Note:** 1.Support units were connected to second LISN.
 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS


CONDUCTED WORST-CASE DATA : 802.11n (20MHz)

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18516	0.15	41.12	33.98	41.27	34.13	64.25	54.25	-22.98	-20.12
2	0.36094	0.17	38.43	37.52	38.60	37.69	58.71	48.71	-20.11	-11.02
3	0.51719	0.17	29.91	8.32	30.08	8.49	56.00	46.00	-25.92	-37.51
4	0.89609	0.19	28.06	22.95	28.25	23.14	56.00	46.00	-27.75	-22.86
5	4.23828	0.34	34.72	28.35	35.06	28.69	56.00	46.00	-20.94	-17.31
6	14.46484	0.52	35.05	30.47	35.57	30.99	60.00	50.00	-24.43	-19.01

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	0.13	30.89	8.12	31.02	8.25	65.18	55.18	-34.15	-46.92
2	0.31016	0.15	36.28	33.32	36.43	33.47	59.97	49.97	-23.54	-16.50
3	0.50938	0.17	25.67	10.67	25.84	10.84	56.00	46.00	-30.16	-35.16
4	1.21875	0.21	34.05	29.92	34.26	30.13	56.00	46.00	-21.74	-15.87
5	5.13281	0.37	34.05	28.17	34.42	28.54	60.00	50.00	-25.58	-21.46
6	8.54297	0.45	37.92	32.00	38.37	32.45	60.00	50.00	-21.63	-17.55

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.59	0.5	PASS
6	2437	8.15	0.5	PASS
11	2462	8.14	0.5	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.49	0.5	PASS
6	2437	16.39	0.5	PASS
11	2462	16.46	0.5	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2		
1	2412	17.71	17.72	17.68	0.5	PASS
6	2437	17.63	17.65	17.01	0.5	PASS
11	2462	17.68	17.70	17.07	0.5	PASS

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2		
3	2422	36.03	35.91	35.27	0.5	PASS
6	2437	36.45	35.94	36.49	0.5	PASS
9	2452	36.47	36.48	36.41	0.5	PASS

4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output v01r02 Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	186.638	22.71	30	PASS
6	2437	223.357	23.49	30	PASS
11	2462	247.742	23.94	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	46.452	16.67	30	PASS
6	2437	243.220	23.86	30	PASS
11	2462	73.961	18.69	30	PASS

802.11n (20MHz)

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER (dBm)			TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2				
1	2412	16.14	15.10	15.15	106.208	20.26	30	PASS
6	2437	23.06	22.87	22.51	574.182	27.59	30	PASS
11	2462	16.72	16.86	16.67	141.970	21.52	30	PASS

802.11n (40MHz)


CHAN.	CHAN. FREQ. (MHz)	PEAK POWER (dBm)			TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2				
3	2422	12.55	10.97	12.44	48.031	16.82	30	PASS
6	2437	19.74	19.83	19.66	282.820	24.52	30	PASS
9	2452	16.67	15.62	15.82	121.121	20.83	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- Set the RBW = 3 kHz, VBW = 10 kHz, Detector = peak.
- Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	3.43	8	PASS
6	2437	2.16	8	PASS
11	2462	1.90	8	PASS

802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-8.72	8	PASS
6	2437	-1.79	8	PASS
11	2462	-6.27	8	PASS

802.11n (20MHz)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=3) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-8.19	4.77	-3.42	4.83	PASS
	6	2437	-1.84	4.77	2.93	4.83	PASS
	11	2462	-8.28	4.77	-3.51	4.83	PASS
1	1	2412	-9.32	4.77	-4.55	4.83	PASS
	6	2437	-1.47	4.77	3.30	4.83	PASS
	11	2462	-8.81	4.77	-4.04	4.83	PASS
2	1	2412	-9.80	4.77	-5.03	4.83	PASS
	6	2437	-1.93	4.77	2.84	4.83	PASS
	11	2462	-6.22	4.77	-1.45	4.83	PASS

NOTE: Directional gain = 4.4dBi + 10log(3) = 9.17dBi > 6dBi , so the power density limit shall be reduced to 8-(9.17-6) = 4.83dBm.



802.11n (40MHz)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=3) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	3	2422	-13.36	4.77	-8.59	4.83	PASS
	6	2437	-8.11	4.77	-3.34	4.83	PASS
	9	2452	-11.21	4.77	-6.44	4.83	PASS
1	3	2422	-16.32	4.77	-11.55	4.83	PASS
	6	2437	-8.25	4.77	-3.48	4.83	PASS
	9	2452	-11.10	4.77	-6.33	4.83	PASS
2	3	2422	-15.11	4.77	-10.34	4.83	PASS
	6	2437	-5.92	4.77	-1.15	4.83	PASS
	9	2452	-8.74	4.77	-3.97	4.83	PASS


NOTE: Directional gain = 4.4dBi + 10log(3) = 9.17dBi > 6dBi , so the power density limit shall be reduced to 8-(9.17-6) = 4.83dBm.

4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS

The conducted emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit. Only worst data of each operating mode is presented.

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T


4.6.8 TEST RESULTS

802.11b


CH 1



CH 6



CH 11







A D T

802.11g


CH 1



CH 6



CH 11







A D T

802.11n (20MHz)


CH 1



CH 6



CH 11







A D T

802.11n (40MHz)


CH 3



CH 6



CH 9



5. TEST TYPES AND RESULTS (FOR 5.0GHz BAND)

5.1 RADIATED EMISSION MEASUREMENT

5.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

5.1.2 TEST INSTRUMENTS

Same as item 4.1.2.

5.1.3 TEST PROCEDURES

Same as item 4.1.3.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation.

5.1.5 TEST SETUP

Same as item 4.1.5.

5.1.6 EUT OPERATING CONDITIONS

Same as 4.1.6.



5.1.7 TEST RESULTS

802.11a

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 149	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3830.00	48.2 PK	74.0	-25.8	1.00 H	360	14.00	34.20
2	3830.00	43.1 AV	54.0	-10.9	1.00 H	360	8.90	34.20
3	#5725.00	85.1 PK	88.6	-3.5	1.10 H	106	46.40	38.70
4	#5725.00	66.3 AV	77.3	-11.0	1.10 H	106	27.60	38.70
5	*5745.00	118.6 PK			1.02 H	106	79.90	38.70
6	*5745.00	107.3 AV			1.02 H	106	68.60	38.70
7	11490.00	58.1 PK	74.0	-15.9	1.10 H	180	8.60	49.50
8	11490.00	45.7 AV	54.0	-8.3	1.10 H	180	-3.80	49.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3830.00	45.8 PK	74.0	-28.2	1.00 V	63	11.60	34.20
2	3830.00	36.3 AV	54.0	-17.7	1.00 V	63	2.10	34.20
3	#5725.00	84.7 PK	89.6	-4.9	1.17 V	265	46.00	38.70
4	#5725.00	67.2 AV	78.4	-11.2	1.17 V	265	28.50	38.70
5	*5745.00	119.6 PK			1.06 V	278	80.90	38.70
6	*5745.00	108.4 AV			1.06 V	278	69.70	38.70
7	11490.00	58.3 PK	74.0	-15.7	1.00 V	360	8.80	49.50
8	11490.00	45.7 AV	54.0	-8.3	1.00 V	360	-3.80	49.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. The limit value is defined as per 15.247.
7. "#":The radiated frequency is out the restricted band.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 157	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	119.0 PK			1.11 H	108	80.20	38.80
2	*5785.00	108.0 AV			1.11 H	108	69.20	38.80
3	11570.00	58.0 PK	74.0	-16.0	1.11 H	0	8.60	49.40
4	11570.00	45.4 AV	54.0	-8.6	1.11 H	0	-4.00	49.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	119.7 PK			1.17 V	264	80.90	38.80
2	*5785.00	108.5 AV			1.17 V	264	69.70	38.80
3	11570.00	58.3 PK	74.0	-15.7	1.17 V	360	8.90	49.40
4	11570.00	45.5 AV	54.0	-8.5	1.17 V	360	-3.90	49.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. The limit value is defined as per 15.247.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 165	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	117.4 PK			1.32 H	239	78.50	38.90
2	*5825.00	106.8 AV			1.32 H	239	67.90	38.90
3	#5850.00	49.6 PK	87.4	-37.8	1.32 H	239	10.70	38.90
4	#5850.00	38.2 AV	76.8	-38.6	1.32 H	239	-0.70	38.90
5	11650.00	57.7 PK	74.0	-16.3	1.20 H	180	8.40	49.30
6	11650.00	45.2 AV	54.0	-8.8	1.20 H	180	-4.10	49.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	119.2 PK			1.06 V	262	80.30	38.90
2	*5825.00	107.8 AV			1.06 V	262	68.90	38.90
3	#5850.00	49.8 PK	89.2	-39.4	1.06 V	262	10.90	38.90
4	#5850.00	38.2 AV	77.8	-39.6	1.06 V	262	-0.70	38.90
5	11650.00	58.3 PK	74.0	-15.7	1.10 V	360	9.00	49.30
6	11650.00	45.3 AV	54.0	-8.7	1.10 V	360	-4.00	49.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. The limit value is defined as per 15.247.
7. “#”:The radiated frequency is out the restricted band.



802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 149	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3830.00	48.3 PK	74.0	-25.7	1.00 H	19	14.10	34.20
2	3830.00	43.3 AV	54.0	-10.7	1.00 H	19	9.10	34.20
3	#5725.00	89.3 PK	90.5	-1.2	1.07 H	155	50.60	38.70
4	#5725.00	70.2 AV	80.7	-10.5	1.07 H	155	31.50	38.70
5	*5745.00	120.5 PK			1.02 H	105	81.80	38.70
6	*5745.00	110.7 AV			1.02 H	105	72.00	38.70
7	11490.00	59.8 PK	74.0	-14.2	1.00 H	180	10.30	49.50
8	11490.00	45.8 AV	54.0	-8.2	1.00 H	180	-3.70	49.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3830.00	45.6 PK	74.0	-28.4	1.03 V	100	11.40	34.20
2	3830.00	37.5 AV	54.0	-16.5	1.03 V	100	3.30	34.20
3	#5725.00	88.0 PK	90.4	-2.4	1.10 V	287	49.30	38.70
4	#5725.00	69.4 AV	80.6	-11.2	1.10 V	287	30.70	38.70
5	*5745.00	120.4 PK			1.10 V	278	81.70	38.70
6	*5745.00	110.6 AV			1.10 V	278	71.90	38.70
7	11490.00	59.9 PK	74.0	-14.1	1.00 V	320	10.40	49.50
8	11490.00	45.9 AV	54.0	-8.1	1.00 V	320	-3.60	49.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.
7. "#": The radiated frequency is out the restricted band.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 157	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	119.2 PK			1.10 H	182	80.40	38.80
2	*5785.00	108.9 AV			1.10 H	182	70.10	38.80
3	11570.00	59.5 PK	74.0	-14.5	1.10 H	360	10.10	49.40
4	11570.00	45.5 AV	54.0	-8.5	1.10 H	360	-3.90	49.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	119.8 PK			1.11 V	283	81.00	38.80
2	*5785.00	109.4 AV			1.11 V	283	70.60	38.80
3	11570.00	59.7 PK	74.0	-14.3	1.10 V	0	10.30	49.40
4	11570.00	45.6 AV	54.0	-8.4	1.10 V	0	-3.80	49.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. The limit value is defined as per 15.247.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 165	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	119.8 PK			1.09 H	154	80.90	38.90
2	*5825.00	109.6 AV			1.09 H	154	70.70	38.90
3	#5850.00	49.2 PK	89.8	-40.6	1.09 H	154	10.30	38.90
4	#5850.00	38.0 AV	79.6	-41.6	1.09 H	154	-0.90	38.90
5	11650.00	59.6 PK	74.0	-14.4	1.07 H	180	10.30	49.30
6	11650.00	45.2 AV	54.0	-8.8	1.07 H	180	-4.10	49.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	120.1 PK			1.09 V	280	81.20	38.90
2	*5825.00	110.3 AV			1.09 V	280	71.40	38.90
3	#5850.00	49.8 PK	90.1	-40.3	1.09 V	360	10.90	38.90
4	#5850.00	38.3 AV	80.3	-42.0	1.09 V	360	-0.60	38.90
5	11650.00	59.7 PK	74.0	-14.3	1.10 V	10	10.40	49.30
6	11650.00	45.4 AV	54.0	-8.6	1.10 V	10	-3.90	49.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. The limit value is defined as per 15.247.
7. “#”:The radiated frequency is out the restricted band.

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 151	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3836.60	48.6 PK	74.0	-25.4	1.00 H	360	14.40	34.20
2	3836.60	43.4 AV	54.0	-10.6	1.00 H	360	9.20	34.20
3	#5722.00	87.1 PK	88.0	-0.9	1.00 H	100	48.40	38.70
4	#5722.00	72.9 AV	78.4	-5.5	1.00 H	100	34.20	38.70
5	*5755.00	118.0 PK			1.01 H	109	79.30	38.70
6	*5755.00	108.4 AV			1.01 H	109	69.70	38.70
7	11510.00	58.7 PK	74.0	-15.3	1.00 H	0	9.20	49.50
8	11510.00	45.8 AV	54.0	-8.2	1.00 H	0	-3.70	49.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3836.60	45.9 PK	74.0	-28.1	1.02 V	88	11.70	34.20
2	3836.60	37.3 AV	54.0	-16.7	1.02 V	88	3.10	34.20
3	#5723.00	87.5 PK	88.7	-1.2	1.02 V	275	48.80	38.70
4	#5723.00	75.1 AV	79.2	-4.1	1.02 V	275	36.40	38.70
5	*5755.00	118.7 PK			1.08 V	276	80.00	38.70
6	*5755.00	109.2 AV			1.08 V	276	70.50	38.70
7	11510.00	59.0 PK	74.0	-15.0	1.05 V	0	9.50	49.50
8	11510.00	45.9 AV	54.0	-8.1	1.05 V	0	-3.60	49.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.
7. "#":The radiated frequency is out the restricted band.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 159	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 67%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	117.4 PK			1.00 H	100	78.60	38.80
2	*5795.00	108.8 AV			1.00 H	100	70.00	38.80
3	#5850.00	66.5 PK	87.4	-20.9	1.00 H	100	27.60	38.90
4	#5850.00	52.9 AV	78.8	-25.9	1.00 H	100	14.00	38.90
5	11590.00	58.2 PK	74.0	-15.8	1.08 H	180	8.80	49.40
6	11590.00	45.3 AV	54.0	-8.7	1.08 H	180	-4.10	49.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	118.0 PK			1.17 V	276	79.20	38.80
2	*5795.00	109.1 AV			1.17 V	276	70.30	38.80
3	#5850.00	67.5 PK	88.0	-20.5	1.17 V	276	28.60	38.90
4	#5850.00	53.5 AV	79.1	-25.6	1.17 V	276	14.60	38.90
5	11590.00	58.5 PK	74.0	-15.5	1.10 V	360	9.10	49.40
6	11590.00	45.5 AV	54.0	-8.5	1.10 V	360	-3.90	49.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. The limit value is defined as per 15.247.
7. “#”:The radiated frequency is out the restricted band.

BELOW 1GHz WORST-CASE DATA : 802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 159	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Martin Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	125.17	37.7 QP	43.5	-5.8	1.49 H	252	25.40	12.30
2	269.05	41.1 QP	46.0	-4.9	1.00 H	211	27.30	13.80
3	479.03	38.5 QP	46.0	-7.5	1.99 H	73	19.10	19.40
4	624.85	35.5 QP	46.0	-10.5	1.00 H	226	13.20	22.30
5	751.23	42.0 QP	46.0	-4.0	1.00 H	183	17.60	24.40
6	875.67	40.2 QP	46.0	-5.8	1.99 H	289	13.70	26.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	125.17	37.5 QP	43.5	-6.0	1.50 V	235	25.20	12.30
2	269.05	40.9 QP	46.0	-5.1	1.50 V	5	27.10	13.80
3	479.03	43.7 QP	46.0	-2.3	1.00 V	201	24.30	19.40
4	500.42	43.8 QP	46.0	-2.2	1.00 V	168	23.80	20.00
5	751.23	37.9 QP	46.0	-8.1	1.50 V	214	13.50	24.40
6	875.67	40.2 QP	46.0	-5.8	1.00 V	94	13.70	26.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

5.2 CONDUCTED EMISSION MEASUREMENT

5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

5.2.2 TEST INSTRUMENTS

Same as item 4.2.2.

5.2.3 TEST PROCEDURES

Same as item 4.2.3.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation.

5.2.5 TEST SETUP

Same as item 4.2.5.

5.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

5.2.7 TEST RESULTS


CONDUCTED WORST-CASE DATA : 802.11n (40MHz)

PHASE	Line 1	6dB BANDWIDTH	9kHz
--------------	--------	----------------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18516	0.15	39.06	18.16	39.21	18.31	64.25	54.25	-25.04	-35.94
2	0.27109	0.16	37.47	19.45	37.63	19.61	61.08	51.08	-23.46	-31.48
3	0.38828	0.17	32.77	15.45	32.94	15.62	58.10	48.10	-25.16	-32.48
4	0.96641	0.19	31.19	24.25	31.38	24.44	56.00	46.00	-24.62	-21.56
5	2.52344	0.28	32.31	23.35	32.59	23.63	56.00	46.00	-23.41	-22.37
6	8.43359	0.41	36.49	31.16	36.90	31.57	60.00	50.00	-23.10	-18.43

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.19297	0.14	39.03	23.57	39.17	23.71	63.91
2	0.25547	0.15	36.01	27.24	36.16	27.39	61.58	51.58	-25.42	-24.19
3	0.40000	0.16	35.03	25.57	35.19	25.73	57.85	47.85	-22.66	-22.12
4	0.60703	0.17	33.33	27.94	33.50	28.11	56.00	46.00	-22.50	-17.89
5	8.68750	0.45	37.48	31.04	37.93	31.49	60.00	50.00	-22.07	-18.51
6	16.24609	0.63	33.45	28.24	34.08	28.87	60.00	50.00	-25.92	-21.13

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

5.3.2 TEST SETUP

Same as item 4.3.2.

5.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.3.4 TEST PROCEDURE

Same as item 4.3.4.

5.3.5 DEVIATION FROM TEST STANDARD

No deviation.

5.3.6 EUT OPERATING CONDITIONS

Same as item 4.3.6.

5.3.7 TEST RESULTS

802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	16.48	0.5	PASS
157	5785	16.49	0.5	PASS
165	5825	16.45	0.5	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2		
149	5745	17.63	17.69	17.62	0.5	PASS
157	5785	17.67	17.71	17.62	0.5	PASS
165	5825	17.69	17.71	17.67	0.5	PASS

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2		
151	5755	35.84	36.44	36.17	0.5	PASS
159	5795	36.42	36.47	36.43	0.5	PASS

5.4 CONDUCTED OUTPUT POWER

5.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 5725 –5850 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output v01r02 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $NANT \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;

Array Gain = $5 \log(NANT/NSS)$ dB or 3 dB, whichever is less for 20-MHz channel widths with $NANT \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(NANT/NSS)$ dB.

5.4.2 TEST SETUP

Same as Item 4.4.2.

5.4.3 INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.4.4 TEST PROCEDURES

Same as Item 4.4.4.

5.4.5 DEVIATION FROM TEST STANDARD

No deviation.

5.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



5.4.7 TEST RESULTS

802.11a

CHAN.	CHAN. FREQ. (MHz)	TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
149	5745	289.068	24.61	30	PASS
157	5785	262.422	24.19	30	PASS
165	5825	243.781	23.87	30	PASS

802.11n (20MHz)

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER (dBm)			TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2				
149	5745	24.01	23.44	23.30	686.364	28.37	30	PASS
157	5785	23.52	23.31	23.68	672.540	28.28	30	PASS
165	5825	23.13	22.93	22.73	589.424	27.70	30	PASS

802.11n (40MHz)

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER (dBm)			TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2				
151	5755	23.56	23.58	23.55	681.484	28.33	30	PASS
159	5795	23.45	23.46	24.18	704.947	28.48	30	PASS

5.5 POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.5.2 TEST SETUP

Same as item 4.5.2.

5.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.5.4 TEST PROCEDURE.

Same as item 4.5.4.

5.5.5 DEVIATION FROM TEST STANDARD

No deviation.

5.5.6 EUT OPERATING CONDITION

Same as item 4.3.6.

5.5.7 TEST RESULTS

802.11a

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
149	5745	-0.27	8	PASS
157	5785	-0.34	8	PASS
165	5825	-1.60	8	PASS

802.11n (20MHz)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=3) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	149	5745	-0.95	4.77	3.82	5.73	PASS
	157	5785	-1.67	4.77	3.10	5.73	PASS
	165	5825	-2.42	4.77	2.35	5.73	PASS
1	149	5745	-1.16	4.77	3.61	5.73	PASS
	157	5785	-2.65	4.77	2.12	5.73	PASS
	165	5825	-1.61	4.77	3.16	5.73	PASS
2	149	5745	-0.95	4.77	3.82	5.73	PASS
	157	5785	-1.25	4.77	3.52	5.73	PASS
	165	5825	-2.19	4.77	2.58	5.73	PASS

NOTE: Directional gain = 3.5dBi + 10log(3) = 8.27dBi > 6dBi , so the power density limit shall be reduced to 8-(8.27-6) = 5.73dBm.

802.11n (40MHz)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=3) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	151	5755	-3.20	4.77	1.57	5.73	PASS
	159	5795	-3.84	4.77	0.93	5.73	PASS
1	151	5755	-4.06	4.77	0.71	5.73	PASS
	159	5795	-4.00	4.77	0.77	5.73	PASS
2	151	5755	-3.21	4.77	1.56	5.73	PASS
	159	5795	-3.32	4.77	1.45	5.73	PASS

NOTE: Directional gain = 3.5dBi + 10log(3) = 8.27dBi > 6dBi , so the power density limit shall be reduced to 8-(8.27-6) = 5.73dBm.

5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

5.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.6.2 TEST SETUP

Same as Item 4.6.2

5.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.6.4 TEST PROCEDURE

Same as Item 4.6.4

5.6.5 DEVIATION FROM TEST STANDARD

No deviation.

5.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

5.6.7 TEST RESULTS

The conducted emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit. Only worst data of each operating mode is presented.


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T

802.11a


CH 149



CH 157



CH 165









A D T

802.11n (20MHz)



CH 149



CH 157



CH 165







A D T

802.11n (40MHz)

CH 151



CH 159



6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

8. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---