



FCC TEST REPORT

REPORT NO.: RF120627C11B
MODEL NO.: RNX-N150PCe
FCC ID: W6RRNX-N150PCEV2
RECEIVED: Jun. 27, 2012
TESTED: Jul. 03 ~ Jul. 07, 2012 (For all tests except 6dB bandwidth and power spectral density)
May 31, 2013 (For 6dB bandwidth and power spectral density)
ISSUED: Jun. 03, 2013

APPLICANT: Rosewill Inc.
ADDRESS: 17708 Rowland Street, City of Industry, CA 91748, USA

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



A D T

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1. CERTIFICATION.....	5
2. SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION.....	7
3.1 GENERAL DESCRIPTION OF EUT.....	7
3.2 DESCRIPTION OF TEST MODES.....	8
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
3.3 DESCRIPTION OF SUPPORT UNITS.....	11
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST.....	11
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	12
4. TEST TYPES AND RESULTS	13
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT	13
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	13
4.1.2 TEST INSTRUMENTS.....	14
4.1.3 TEST PROCEDURES	16
4.1.4 DEVIATION FROM TEST STANDARD	16
4.1.5 TEST SETUP.....	17
4.1.6 EUT OPERATING CONDITIONS	17
4.1.7 TEST RESULTS	18
4.2 CONDUCTED EMISSION MEASUREMENT	31
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	31
4.2.2 TEST INSTRUMENTS.....	31
4.2.3 TEST PROCEDURES	32
4.2.4 DEVIATION FROM TEST STANDARD	32
4.2.5 TEST SETUP.....	32
4.2.6 EUT OPERATING CONDITIONS	32
4.2.7 TEST RESULTS	33
4.3 6dB BANDWIDTH MEASUREMENT	35
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	35
4.3.2 TEST SETUP.....	35
4.3.3 TEST INSTRUMENTS.....	35
4.3.4 TEST PROCEDURE.....	35
4.3.5 DEVIATION FROM TEST STANDARD	35
4.3.6 EUT OPERATING CONDITIONS.....	35
4.3.7 TEST RESULTS	36
4.4 CONDUCTED OUTPUT POWER	37
4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	37
4.4.2 TEST SETUP.....	37
4.4.3 TEST INSTRUMENTS.....	37
4.4.4 TEST PROCEDURES	37
4.4.5 DEVIATION FROM TEST STANDARD	37
4.4.6 EUT OPERATING CONDITIONS.....	37
4.4.7 TEST RESULTS	38
4.5 POWER SPECTRAL DENSITY MEASUREMENT.....	39
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	39
4.5.2 TEST SETUP.....	39



A D T

4.5.3	TEST INSTRUMENTS.....	39
4.5.4	TEST PROCEDURE.....	39
4.5.5	DEVIATION FROM TEST STANDARD	39
4.5.6	EUT OPERATING CONDITION	39
4.5.7	TEST RESULTS	40
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT	41
4.6.1	LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	41
4.6.2	TEST SETUP.....	41
4.6.3	TEST INSTRUMENTS.....	41
4.6.4	TEST PROCEDURE.....	41
4.6.5	DEVIATION FROM TEST STANDARD	42
4.6.6	EUT OPERATING CONDITION	42
4.6.7	TEST RESULTS	42
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	47
6.	INFORMATION ON THE TESTING LABORATORIES.....	48
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	49



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120627C11B	Original release	Jun. 03, 2013



1. CERTIFICATION

PRODUCT: 150Mbps Wireless N PCI-E Adapter

MODEL NO.: RNX-N150PCe

BRAND: Newegg

APPLICANT: Rosewill Inc.

TESTED: Jul. 03 ~ Jul. 07, 2012

(For all tests except 6dB bandwidth and power spectral density)

May 31, 2013 (For 6dB bandwidth and power spectral density)

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: **FCC Part 15, Subpart C (Section 15.247)**

ANSI C63.10-2009

The above equipment (model: RNX-N150PCe) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Maggie Wu , **DATE** : Jun. 03, 2013
Maggie Wu / Specialist

APPROVED BY : Ken Liu , **DATE** : Jun. 03, 2013
Ken Liu / Senior Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -5.95dB at 0.18516MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.8dB at 2390.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is SMA Plug Reverse not a standard connector.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44dB
Radiated emissions	30MHz ~ 200MHz	3.19dB
	200MHz ~1000MHz	3.21dB
	1GHz ~ 18GHz	2.26dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	150Mbps Wireless N PCI-E Adapter
MODEL NO.	RNX-N150PCe
POWER SUPPLY	3.3Vdc (host equipment)
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b:11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 150.0Mbps
OPERATING FREQUENCY	2412 ~ 2462MHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz)
OUTPUT POWER	107.4mW
ANTENNA TYPE	Dipole antenna with 2.0dBi gain
ANTENNA CONNECTOR	SMA Plug Reverse
DATA CABLE	N/A
I/O PORTS	N/A
ACCESSORY DEVICES	N/A

NOTE:

1. The EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX FUNCTION
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	1TX
802.11n (40MHz)	1TX

2. The above EUT information is declared by manufacturer and for more detailed feature description, please refer to the manufacturer's specifications or user's manual.



3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		



3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11g	1 to 11	6	OFDM	BPSK	6.0

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11g	1 to 11	6	OFDM	BPSK	6.0



BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5
-	802.11n (40MHz)	3 to 9	3, 9	OFDM	BPSK	13.5

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Haru Yang
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Haru Yang
PLC	25deg. C, 65%RH	120Vac, 60Hz	Haru Yang
APCM	25deg. C, 65%RH	120Vac, 60Hz	Haru Yang
	25deg. C, 60%RH	120Vac, 60Hz	Nick Chen

3.3 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PC	HP	dx7300MT	SGH72102P3	FCC DoC Approved
2	LCD MONITOR	BENQ	N/A	N/A	FCC DoC Approved
3	KEYBOARD	HP	SK-1688	C0305049702	GYUR84SK
4	MOUSE	BENQ	M501	3B707024SA0000	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	1.8m shielded D-SUB cable with 2 cores.
3	1.3m foil shielded wire, PS/2 Connector, w/o core.
4	1.8m foil shielded wire, USB Connector, w/o core.

NOTE: All power cords of the above support units are non shielded (1.8m).

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST





3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v03r01

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

Tested date: Jul. 03 ~ Jul. 06, 2012

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100212	Aug. 02, 2011	Aug. 01, 2012
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Jul. 21, 2011	Jul. 20, 2012
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Apr. 06, 2012	Apr. 05, 2013
HORN Antenna SCHWARZBECK	9120D	209	Aug. 25, 2011	Aug. 24, 2012
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 20, 2011	Jul. 19, 2012
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent	8447D	2944A10633	Oct. 29, 2011	Oct. 28, 2012
Preamplifier Agilent	8449B	3008A01964	Oct. 29, 2011	Oct. 28, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250723/4	Aug. 30, 2011	Aug. 29, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 106	12738/6+309224/ 4	Aug. 30, 2011	Aug. 29, 2012
Software ADT.	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA	NA
Turn Table ADT.	TT100	TT93021703	NA	NA
Turn Table Controller ADT.	SC100	SC93021703	NA	NA
Mini-Circuits Power Splitter	ZN2PD-9G	NA	Jul. 15, 2011	Jul. 14, 2012
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
High Speed Peak Power Meter	ML2495A	0842014	Apr. 28, 2012	Apr. 27, 2013
Power Sensor	MA2411B	0738404	Apr. 28, 2012	Apr. 27, 2013

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. The test was performed in HwaYa Chamber 3.
 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 5. The FCC Site Registration No. is 988962.
 6. The IC Site Registration No. is IC 7450F-3.



A D T

Tested date: May 31, 2013

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100212	Aug. 06, 2012	Aug. 05, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Jan. 31, 2013	Jan. 30, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Mar. 20, 2013	Mar. 19, 2014
HORN Antenna SCHWARZBECK	9120D	209	Sep. 03, 2012	Sep. 02, 2013
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 11, 2012	Jul. 10, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent	8447D	2944A10633	Oct. 25, 2012	Oct. 24, 2013
Preamplifier Agilent	8449B	3008A01964	Oct. 25, 2012	Oct. 24, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250723/4	Aug. 28, 2012	Aug. 27, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 106	12738/6+309224/ 4	Aug. 28, 2012	Aug. 27, 2013
Software BV ADT	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA	NA
Turn Table BV ADT	TT100	TT93021703	NA	NA
Turn Table Controller BV ADT	SC100	SC93021703	NA	NA
High Speed Peak Power Meter	ML2495A	0842014	Apr. 25, 2013	Apr. 24, 2014
Power Sensor	MA2411B	0738404	Apr. 24, 2013	Apr. 23, 2014

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. The test was performed in HwaYa Chamber 3.
 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 5. The FCC Site Registration No. is 988962.
 6. The IC Site Registration No. is IC 7450F-3.

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. The EUT was installed in the PC.
- b. The PC ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the system in full functions.



A D T

4.1.7 TEST RESULTS

ABOVE 1GHz DATA :

802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2320.00	55.0 PK	74.0	-19.0	1.82 H	62	23.90	31.10
2	2320.00	42.7 AV	54.0	-11.3	1.82 H	62	11.60	31.10
3	2390.00	55.1 PK	74.0	-18.9	1.82 H	62	23.80	31.30
4	2390.00	44.2 AV	54.0	-9.8	1.82 H	62	12.90	31.30
5	*2412.00	105.2 PK			1.82 H	62	73.80	31.40
6	*2412.00	101.7 AV			1.82 H	62	70.30	31.40
7	#3216.00	48.0 PK	85.2	-37.2	1.22 H	6	14.70	33.30
8	#3216.00	43.6 AV	81.7	-38.1	1.22 H	6	10.30	33.30
9	4824.00	47.7 PK	74.0	-26.3	1.01 H	269	10.50	37.20
10	4824.00	37.1 AV	54.0	-16.9	1.01 H	269	-0.10	37.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2320.00	56.8 PK	74.0	-17.2	1.15 V	107	25.70	31.10
2	2320.00	47.9 AV	54.0	-6.1	1.15 V	107	16.80	31.10
3	2390.00	56.1 PK	74.0	-17.9	1.12 V	107	24.80	31.30
4	2390.00	44.0 AV	54.0	-10.0	1.12 V	107	12.70	31.30
5	*2412.00	110.5 PK			1.12 V	107	79.10	31.40
6	*2412.00	106.8 AV			1.12 V	107	75.40	31.40
7	#3216.00	55.7 PK	90.5	-34.8	1.40 V	121	22.40	33.30
8	#3216.00	54.2 AV	86.8	-32.6	1.40 V	121	20.90	33.30
9	4824.00	47.5 PK	74.0	-26.5	1.42 V	127	10.30	37.20
10	4824.00	38.1 AV	54.0	-15.9	1.42 V	127	0.90	37.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.
6. “ # ”: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2350.00	56.6 PK	74.0	-17.4	1.89 H	63	25.40	31.20
2	2350.00	45.7 AV	54.0	-8.3	1.89 H	63	14.50	31.20
3	*2437.00	103.3 PK			1.89 H	63	71.80	31.50
4	*2437.00	99.7 AV			1.89 H	63	68.20	31.50
5	#3249.30	48.4 PK	83.3	-34.9	1.23 H	4	15.00	33.40
6	#3249.30	44.4 AV	79.7	-35.3	1.23 H	4	11.00	33.40
7	4874.00	47.4 PK	74.0	-26.6	1.03 H	215	10.10	37.30
8	4874.00	37.3 AV	54.0	-16.7	1.03 H	215	0.00	37.30
9	7311.00	51.8 PK	74.0	-22.2	1.00 H	101	8.30	43.50
10	7311.00	39.6 AV	54.0	-14.4	1.00 H	101	-3.90	43.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2350.00	58.5 PK	74.0	-15.5	1.13 V	111	27.30	31.20
2	2350.00	49.7 AV	54.0	-4.3	1.13 V	111	18.50	31.20
3	*2437.00	110.8 PK			1.35 V	121	79.30	31.50
4	*2437.00	106.9 AV			1.35 V	121	75.40	31.50
5	#3249.30	56.8 PK	90.8	-34.0	1.39 V	123	23.40	33.40
6	#3249.30	55.2 AV	86.9	-31.7	1.39 V	123	21.80	33.40
7	4874.00	47.3 PK	74.0	-26.7	1.06 V	55	10.00	37.30
8	4874.00	37.7 AV	54.0	-16.3	1.06 V	55	0.40	37.30
9	7311.00	52.4 PK	74.0	-21.6	1.21 V	179	8.90	43.50
10	7311.00	40.5 AV	54.0	-13.5	1.21 V	179	-3.00	43.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “ # “: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	55.1 PK	74.0	-18.9	1.77 H	64	23.80	31.30
2	2377.00	44.7 AV	54.0	-9.3	1.77 H	64	13.40	31.30
3	*2462.00	103.1 PK			1.77 H	64	71.50	31.60
4	*2462.00	99.5 AV			1.77 H	64	67.90	31.60
5	2483.50	55.9 PK	74.0	-18.1	1.77 H	64	24.30	31.60
6	2483.50	43.0 AV	54.0	-11.0	1.77 H	64	11.40	31.60
7	#3282.60	48.8 PK	83.1	-34.3	1.37 H	330	15.30	33.50
8	#3282.60	45.2 AV	79.5	-34.3	1.37 H	330	11.70	33.50
9	4924.00	47.6 PK	74.0	-26.4	1.17 H	230	10.20	37.40
10	4924.00	41.0 AV	54.0	-13.0	1.17 H	230	3.60	37.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	59.0 PK	74.0	-15.0	1.67 V	121	27.70	31.30
2	2377.00	50.6 AV	54.0	-3.4	1.67 V	121	19.30	31.30
3	*2462.00	111.2 PK			1.09 V	122	79.60	31.60
4	*2462.00	107.4 AV			1.09 V	122	75.80	31.60
5	2483.50	58.4 PK	74.0	-15.6	1.09 V	122	26.80	31.60
6	2483.50	45.3 AV	54.0	-8.7	1.09 V	122	13.70	31.60
7	#3282.60	56.8 PK	91.2	-34.4	1.36 V	122	23.30	33.50
8	#3282.60	55.5 AV	87.4	-31.9	1.36 V	122	22.00	33.50
9	4924.00	47.1 PK	74.0	-26.9	1.17 V	116	9.70	37.40
10	4924.00	38.4 AV	54.0	-15.6	1.17 V	116	1.00	37.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “ # “: The radiated frequency is out the restricted band.



A D T

802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.4 PK	74.0	-14.6	1.81 H	63	28.10	31.30
2	2390.00	46.5 AV	54.0	-7.5	1.81 H	63	15.20	31.30
3	*2412.00	104.1 PK			1.81 H	63	72.70	31.40
4	*2412.00	93.8 AV			1.81 H	63	62.40	31.40
5	#3216.00	48.1 PK	84.1	-36.0	1.21 H	7	14.80	33.30
6	#3216.00	43.6 AV	73.8	-30.2	1.21 H	7	10.30	33.30
7	4824.00	45.8 PK	74.0	-28.2	1.01 H	281	8.60	37.20
8	4824.00	32.7 AV	54.0	-21.3	1.01 H	281	-4.50	37.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.1 PK	74.0	-8.9	1.10 V	124	33.80	31.30
2	2390.00	51.4 AV	54.0	-2.6	1.10 V	124	20.10	31.30
3	*2412.00	110.1 PK			1.11 V	125	78.70	31.40
4	*2412.00	100.0 AV			1.11 V	125	68.60	31.40
5	#3216.00	55.6 PK	90.1	-34.5	1.40 V	121	22.30	33.30
6	#3216.00	54.0 AV	80.0	-26.0	1.40 V	121	20.70	33.30
7	4824.00	46.1 PK	74.0	-27.9	1.51 V	131	8.90	37.20
8	4824.00	33.0 AV	54.0	-21.0	1.51 V	131	-4.20	37.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.9 PK	74.0	-17.1	1.80 H	65	25.60	31.30
2	2390.00	45.6 AV	54.0	-8.4	1.80 H	65	14.30	31.30
3	*2437.00	103.4 PK			1.80 H	65	71.90	31.50
4	*2437.00	93.6 AV			1.80 H	65	62.10	31.50
5	#3249.30	48.5 PK	83.4	-34.9	1.20 H	0	15.10	33.40
6	#3249.30	44.2 AV	73.6	-29.4	1.20 H	0	10.80	33.40
7	4874.00	46.0 PK	74.0	-28.0	1.04 H	220	8.70	37.30
8	4874.00	33.4 AV	54.0	-20.6	1.04 H	220	-3.90	37.30
9	7311.00	52.1 PK	74.0	-21.9	1.00 H	102	8.60	43.50
10	7311.00	39.7 AV	54.0	-14.3	1.00 H	102	-3.80	43.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.7 PK	74.0	-11.3	1.10 V	123	31.40	31.30
2	2390.00	51.1 AV	54.0	-2.9	1.10 V	123	19.80	31.30
3	*2437.00	110.5 PK			1.34 V	123	79.00	31.50
4	*2437.00	100.2 AV			1.34 V	123	68.70	31.50
5	#3249.30	56.1 PK	90.5	-34.4	1.38 V	125	22.70	33.40
6	#3249.30	54.6 AV	80.2	-25.6	1.38 V	125	21.20	33.40
7	4874.00	51.4 PK	74.0	-22.6	1.03 V	47	14.10	37.30
8	4874.00	34.4 AV	54.0	-19.6	1.03 V	47	-2.90	37.30
9	7311.00	52.5 PK	74.0	-21.5	1.28 V	189	9.00	43.50
10	7311.00	40.6 AV	54.0	-13.4	1.28 V	189	-2.90	43.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “ # “: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	55.6 PK	74.0	-18.4	1.80 H	65	24.30	31.30
2	2377.00	44.1 AV	54.0	-9.9	1.80 H	65	12.80	31.30
3	*2462.00	103.4 PK			1.80 H	65	71.80	31.60
4	*2462.00	93.4 AV			1.80 H	65	61.80	31.60
5	2483.50	61.0 PK	74.0	-13.0	1.80 H	65	29.40	31.60
6	2483.50	45.0 AV	54.0	-9.0	1.80 H	65	13.40	31.60
7	#3282.60	49.9 PK	83.4	-33.5	1.36 H	21	16.40	33.50
8	#3282.60	47.2 AV	73.4	-26.2	1.36 H	21	13.70	33.50
9	4924.00	45.9 PK	74.0	-28.1	1.14 H	302	8.50	37.40
10	4924.00	33.1 AV	54.0	-20.9	1.14 H	302	-4.30	37.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	59.0 PK	74.0	-15.0	1.11 V	108	27.70	31.30
2	2377.00	48.6 AV	54.0	-5.4	1.11 V	108	17.30	31.30
3	*2462.00	109.4 PK			1.09 V	125	77.80	31.60
4	*2462.00	99.8 AV			1.09 V	125	68.20	31.60
5	2483.50	66.0 PK	74.0	-8.0	1.07 V	120	34.40	31.60
6	2483.50	50.2 AV	54.0	-3.8	1.07 V	120	18.60	31.60
7	#3282.60	56.5 PK	89.4	-32.9	1.35 V	124	23.00	33.50
8	#3282.60	55.2 AV	79.8	-24.6	1.35 V	124	21.70	33.50
9	4924.00	46.1 PK	74.0	-27.9	1.17 V	139	8.70	37.40
10	4924.00	33.4 AV	54.0	-20.6	1.17 V	139	-4.00	37.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “ # “: The radiated frequency is out the restricted band.



A D T

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.0 PK	74.0	-10.0	1.81 H	64	32.70	31.30
2	2390.00	46.9 AV	54.0	-7.1	1.81 H	64	15.60	31.30
3	*2412.00	103.2 PK			1.81 H	64	71.80	31.40
4	*2412.00	92.9 AV			1.81 H	64	61.50	31.40
5	#3216.00	47.6 PK	83.2	-35.6	1.21 H	104	14.30	33.30
6	#3216.00	43.4 AV	72.9	-29.5	1.21 H	104	10.10	33.30
7	4824.00	46.6 PK	74.0	-27.4	1.06 H	265	9.40	37.20
8	4824.00	33.1 AV	54.0	-20.9	1.06 H	265	-4.10	37.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.5 PK	74.0	-2.5	1.10 V	126	40.20	31.30
2	2390.00	52.2 AV	54.0	-1.8	1.10 V	126	20.90	31.30
3	*2412.00	109.7 PK			1.13 V	120	78.30	31.40
4	*2412.00	99.4 AV			1.13 V	120	68.00	31.40
5	#3216.00	55.8 PK	89.7	-33.9	1.39 V	122	22.50	33.30
6	#3216.00	54.2 AV	79.4	-25.2	1.39 V	122	20.90	33.30
7	4824.00	46.1 PK	74.0	-27.9	1.55 V	144	8.90	37.20
8	4824.00	32.8 AV	54.0	-21.2	1.55 V	144	-4.40	37.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.1 PK	74.0	-17.9	1.82 H	62	24.80	31.30
2	2390.00	45.0 AV	54.0	-9.0	1.82 H	62	13.70	31.30
3	*2437.00	102.7 PK			1.82 H	62	71.20	31.50
4	*2437.00	92.3 AV			1.82 H	62	60.80	31.50
5	#3249.30	48.6 PK	82.7	-34.1	1.19 H	0	15.20	33.40
6	#3249.30	44.4 AV	72.3	-27.9	1.19 H	0	11.00	33.40
7	4874.00	46.2 PK	74.0	-27.8	1.04 H	258	8.90	37.30
8	4874.00	33.3 AV	54.0	-20.7	1.04 H	258	-4.00	37.30
9	7311.00	52.2 PK	74.0	-21.8	1.00 H	129	8.70	43.50
10	7311.00	38.5 AV	54.0	-15.5	1.00 H	129	-5.00	43.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.9 PK	74.0	-13.1	1.12 V	126	29.60	31.30
2	2390.00	50.2 AV	54.0	-3.8	1.12 V	126	18.90	31.30
3	*2437.00	109.0 PK			1.35 V	123	77.50	31.50
4	*2437.00	98.6 AV			1.35 V	123	67.10	31.50
5	#3249.30	56.2 PK	89.0	-32.8	1.38 V	122	22.80	33.40
6	#3249.30	54.6 AV	78.6	-24.0	1.38 V	122	21.20	33.40
7	4874.00	45.7 PK	74.0	-28.3	1.05 V	112	8.40	37.30
8	4874.00	32.5 AV	54.0	-21.5	1.05 V	112	-4.80	37.30
9	7311.00	51.8 PK	74.0	-22.2	1.30 V	187	8.30	43.50
10	7311.00	38.1 AV	54.0	-15.9	1.30 V	187	-5.40	43.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “ # “: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	55.8 PK	74.0	-18.2	1.80 H	64	24.50	31.30
2	2377.00	43.9 AV	54.0	-10.1	1.80 H	64	12.60	31.30
3	*2462.00	101.4 PK			1.80 H	64	69.80	31.60
4	*2462.00	91.7 AV			1.80 H	64	60.10	31.60
5	2483.50	57.9 PK	74.0	-16.1	1.80 H	64	26.30	31.60
6	2483.50	45.4 AV	54.0	-8.6	1.80 H	64	13.80	31.60
7	#3282.60	49.3 PK	81.4	-32.1	1.35 H	21	15.80	33.50
8	#3282.60	46.8 AV	71.7	-24.9	1.35 H	21	13.30	33.50
9	4924.00	46.3 PK	74.0	-27.7	1.18 H	276	8.90	37.40
10	4924.00	32.9 AV	54.0	-21.1	1.18 H	276	-4.50	37.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	59.4 PK	74.0	-14.6	1.39 V	108	28.10	31.30
2	2377.00	48.0 AV	54.0	-6.0	1.39 V	108	16.70	31.30
3	*2462.00	108.5 PK			1.10 V	123	76.90	31.60
4	*2462.00	98.5 AV			1.10 V	123	66.90	31.60
5	2483.50	66.4 PK	74.0	-7.6	1.07 V	122	34.80	31.60
6	2483.50	49.8 AV	54.0	-4.2	1.07 V	122	18.20	31.60
7	#3282.60	56.5 PK	88.5	-32.0	1.35 V	123	23.00	33.50
8	#3282.60	55.3 AV	78.5	-23.2	1.35 V	123	21.80	33.50
9	4924.00	45.7 PK	74.0	-28.3	1.09 V	146	8.30	37.40
10	4924.00	32.4 AV	54.0	-21.6	1.09 V	146	-5.00	37.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “ # “: The radiated frequency is out the restricted band.



A D T

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.8 PK	74.0	-13.2	1.85 H	61	29.50	31.30
2	2390.00	47.2 AV	54.0	-6.8	1.85 H	61	15.90	31.30
3	*2422.00	98.9 PK			1.85 H	61	67.50	31.40
4	*2422.00	88.6 AV			1.85 H	61	57.20	31.40
5	#3229.30	48.2 PK	78.9	-30.7	1.19 H	103	14.80	33.40
6	#3229.30	42.9 AV	68.6	-25.7	1.19 H	103	9.50	33.40
7	4844.00	46.5 PK	74.0	-27.5	1.02 H	252	9.20	37.30
8	4844.00	32.8 AV	54.0	-21.2	1.02 H	252	-4.50	37.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	63.5 PK	74.0	-10.5	1.34 V	114	32.20	31.30
2	2390.00	51.4 AV	54.0	-2.6	1.34 V	114	20.10	31.30
3	*2422.00	104.1 PK			1.11 V	106	72.70	31.40
4	*2422.00	94.2 AV			1.11 V	106	62.80	31.40
5	#3229.30	53.9 PK	84.1	-30.2	1.16 V	121	20.50	33.40
6	#3229.30	51.8 AV	74.2	-22.4	1.16 V	121	18.40	33.40
7	4844.00	46.2 PK	74.0	-27.8	1.39 V	172	8.90	37.30
8	4844.00	32.4 AV	54.0	-21.6	1.39 V	172	-4.90	37.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.3 PK	74.0	-18.7	1.81 H	63	24.00	31.30
2	2390.00	42.9 AV	54.0	-11.1	1.81 H	63	11.60	31.30
3	*2437.00	97.7 PK			1.81 H	63	66.20	31.50
4	*2437.00	88.0 AV			1.81 H	63	56.50	31.50
5	#3249.30	47.4 PK	77.7	-30.3	1.18 H	357	14.00	33.40
6	#3249.30	42.5 AV	68.0	-25.5	1.18 H	357	9.10	33.40
7	4874.00	46.8 PK	74.0	-27.2	1.08 H	229	9.50	37.30
8	4874.00	32.9 AV	54.0	-21.1	1.08 H	229	-4.40	37.30
9	7311.00	52.1 PK	74.0	-21.9	1.00 H	122	8.60	43.50
10	7311.00	38.2 AV	54.0	-15.8	1.00 H	122	-5.30	43.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.6 PK	74.0	-17.4	1.36 V	122	25.30	31.30
2	2390.00	45.4 AV	54.0	-8.6	1.36 V	122	14.10	31.30
3	*2437.00	104.3 PK			1.36 V	122	72.80	31.50
4	*2437.00	93.9 AV			1.36 V	122	62.40	31.50
5	#3249.30	54.4 PK	84.3	-29.9	1.38 V	124	21.00	33.40
6	#3249.30	52.6 AV	73.9	-21.3	1.38 V	124	19.20	33.40
7	4874.00	45.7 PK	74.0	-28.3	1.04 V	125	8.40	37.30
8	4874.00	32.1 AV	54.0	-21.9	1.04 V	125	-5.20	37.30
9	7311.00	51.5 PK	74.0	-22.5	1.29 V	176	8.00	43.50
10	7311.00	37.7 AV	54.0	-16.3	1.29 V	176	-5.80	43.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “ # “: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 9	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	55.2 PK	74.0	-18.8	1.80 H	63	23.90	31.30
2	2377.00	42.8 AV	54.0	-11.2	1.80 H	63	11.50	31.30
3	*2452.00	98.0 PK			1.80 H	63	66.50	31.50
4	*2452.00	87.9 AV			1.80 H	63	56.40	31.50
5	2483.50	58.3 PK	74.0	-15.7	1.80 H	63	26.70	31.60
6	2483.50	45.0 AV	54.0	-9.0	1.80 H	63	13.40	31.60
7	#3269.30	47.5 PK	78.0	-30.5	1.30 H	122	14.10	33.40
8	#3269.30	43.1 AV	67.9	-24.8	1.30 H	122	9.70	33.40
9	4904.00	46.1 PK	74.0	-27.9	1.12 H	294	8.70	37.40
10	4904.00	33.3 AV	54.0	-20.7	1.12 H	294	-4.10	37.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2377.00	56.8 PK	74.0	-17.2	1.37 V	120	25.50	31.30
2	2377.00	45.4 AV	54.0	-8.6	1.37 V	120	14.10	31.30
3	*2452.00	104.0 PK			1.37 V	120	72.50	31.50
4	*2452.00	94.1 AV			1.37 V	120	62.60	31.50
5	2483.50	62.6 PK	74.0	-11.4	1.37 V	120	31.00	31.60
6	2483.50	48.6 AV	54.0	-5.4	1.37 V	120	17.00	31.60
7	#3269.30	54.6 PK	84.0	-29.4	1.37 V	122	21.20	33.40
8	#3269.30	52.8 AV	74.1	-21.3	1.37 V	122	19.40	33.40
9	4904.00	45.7 PK	74.0	-28.3	1.06 V	144	8.30	37.40
10	4904.00	32.6 AV	54.0	-21.4	1.06 V	144	-4.80	37.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “ # “: The radiated frequency is out the restricted band.



A D T

BELOW 1GHz WORST-CASE DATA : 802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Haru Yang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	162.11	31.5 QP	43.5	-12.0	1.50 H	4	17.50	14.00
2	214.61	35.7 QP	43.5	-7.8	1.25 H	55	24.10	11.60
3	539.30	33.2 QP	46.0	-12.8	1.50 H	277	12.40	20.80
4	640.41	33.7 QP	46.0	-12.3	1.00 H	313	11.20	22.50
5	749.29	33.0 QP	46.0	-13.0	1.50 H	138	8.70	24.30
6	920.38	34.4 QP	46.0	-11.6	1.25 H	7	7.40	27.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.13	37.6 QP	40.0	-2.4	1.24 V	288	25.70	11.90
2	107.67	30.3 QP	43.5	-13.2	1.00 V	271	19.90	10.40
3	321.54	30.4 QP	46.0	-15.6	1.49 V	247	14.90	15.50
4	545.14	35.8 QP	46.0	-10.2	1.00 V	134	14.90	20.90
5	749.29	32.0 QP	46.0	-14.0	1.00 V	238	7.70	24.30
6	932.05	38.9 QP	46.0	-7.1	1.00 V	136	11.80	27.10

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

Tested date: Jul. 07, 2012

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 19, 2011	Nov. 18, 2012
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 29, 2011	Dec. 28, 2012
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 30, 2011	Dec. 29, 2012
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 06, 2012	Jul. 05, 2013
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 2.
3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS


CONDUCTED WORST-CASE DATA : 802.11g

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18516	0.15	51.87	48.12	52.02	48.27	64.25	54.25	-12.23	-5.98
2	0.24766	0.15	39.64	37.57	39.79	37.72	61.84	51.84	-22.04	-14.11
3	0.49375	0.17	35.39	34.42	35.56	34.59	56.10	46.10	-20.54	-11.51
4	1.19141	0.20	39.67	38.94	39.87	39.14	56.00	46.00	-16.13	-6.86
5	11.54688	0.46	37.88	33.97	38.34	34.43	60.00	50.00	-21.66	-15.57
6	20.07422	0.63	41.25	31.88	41.88	32.51	60.00	50.00	-18.12	-17.49

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18516	0.14	51.02	48.16	51.16	48.30	64.25	54.25	-13.09	-5.95
2	0.24766	0.14	43.56	38.13	43.70	38.27	61.84	51.84	-18.13	-13.56
3	0.49375	0.16	36.29	34.48	36.45	34.64	56.10	46.10	-19.65	-11.46
4	1.19141	0.20	38.21	37.52	38.41	37.72	56.00	46.00	-17.59	-8.28
5	11.73828	0.52	39.46	36.03	39.98	36.55	60.00	50.00	-20.02	-13.45
6	18.65234	0.69	38.17	27.90	38.86	28.59	60.00	50.00	-21.14	-21.41

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = 100 KHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

4.3.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	10.09	0.5	PASS
6	2437	10.10	0.5	PASS
11	2462	10.11	0.5	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.43	0.5	PASS
6	2437	16.44	0.5	PASS
11	2462	16.44	0.5	PASS

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.62	0.5	PASS
6	2437	17.66	0.5	PASS
11	2462	17.65	0.5	PASS

802.11n (40MHz)


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	34.19	0.5	PASS
6	2437	35.19	0.5	PASS
9	2452	35.19	0.5	PASS

4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

- Follow KDB 558074 D01 DTS Meas Guidance v03r01 section 9.1.3.
- A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



A D T

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	55.3	17.43	30	PASS
6	2437	53.8	17.31	30	PASS
11	2462	52.6	17.21	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	106.4	20.27	30	PASS
6	2437	107.4	20.31	30	PASS
11	2462	104.5	20.19	30	PASS

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	94.8	19.77	30	PASS
6	2437	98.9	19.95	30	PASS
11	2462	101.9	20.08	30	PASS

802.11n (40MHz)


CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
3	2422	56.5	17.52	30	PASS
6	2437	55.3	17.43	30	PASS
9	2452	54.2	17.34	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a. Follow KDB 558074 D01 DTS Meas Guidance v03r01 section 10.2.
- b. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
- c. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- d. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-7.92	8	PASS
6	2437	-9.49	8	PASS
11	2462	-9.90	8	PASS

802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-13.47	8	PASS
6	2437	-12.09	8	PASS
11	2462	-13.25	8	PASS

802.11n (20MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-13.78	8	PASS
6	2437	-13.57	8	PASS
11	2462	-14.49	8	PASS

802.11n (40MHz)


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	-19.20	8	PASS
6	2437	-19.01	8	PASS
9	2452	-20.00	8	PASS

4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T

802.11b


CH 1



CH 6




CH 11




802.11g


CH 1



CH 6



CH 11







A D T

802.11n (20MHz)


CH 1



CH 6





CH 11





802.11n (40MHz)



CH 3



CH 6



CH 9



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---