



**FCC TEST REPORT**  
**FCC ID: W6RRW-TH68N**

On Behalf of

**Rosewill Inc.**

**Bluetooth Headphone**

**Model No.: RW-TH68N**

Prepared for : Rosewill Inc.  
Address : 17780, Rowland Street, City of Industry CA 91748 United States

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.  
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,  
Shenzhen, Guangdong, China

Report Number : A2007192-C01-R01  
Date of Receipt : July 23, 2020  
Date of Test : July 23-27, 2020  
Date of Report : July 27, 2020  
Version Number : V0

## TABLE OF CONTENTS

Description	Page
<b>1. Summary of Standards And Results .....</b>	<b>6</b>
1.1. Description of Standards and Results .....	6
<b>2. General Information.....</b>	<b>7</b>
2.1. Description of Device (EUT).....	7
2.2. Accessories of Device (EUT) .....	8
2.3. Tested Supporting System Details .....	8
2.4. Block Diagram of connection between EUT and simulators .....	8
2.5. Test Mode Description.....	8
2.6. Test Conditions .....	9
2.7. Test Facility .....	9
2.8. Measurement Uncertainty.....	9
2.9. Test Equipment List.....	10
<b>3. Maximum Peak Output power .....</b>	<b>11</b>
3.1. Limit .....	11
3.2. Test Procedure .....	11
3.3. Test Setup.....	11
3.4. Test Result .....	11
<b>4. Bandwidth.....</b>	<b>12</b>
4.1. Limit .....	12
4.2. Test Procedure .....	12
4.3. Test Result .....	12
<b>5. Carrier Frequency Separation.....</b>	<b>22</b>
5.1. Limit .....	22
5.2. Test Procedure .....	22
5.3. Test Result .....	22
<b>6. Number Of Hopping Channel.....</b>	<b>24</b>
6.1. Limit .....	24
6.2. Test Procedure .....	24
6.3. Test Result .....	24
<b>7. Dwell Time.....</b>	<b>26</b>
7.1. Test limit .....	26
7.2. Test Procedure .....	26
7.3. Test Result .....	26
<b>8. Radiated emissions.....</b>	<b>30</b>
8.1. Limit .....	30
8.2. Block Diagram of Test setup .....	31
8.3. Test Procedure .....	32
8.4. Test Result .....	32
<b>9. Band Edge Compliance .....</b>	<b>38</b>

---

9.1. Block Diagram of Test Setup.....	38
9.2. Limit .....	38
9.3. Test Procedure .....	38
9.4. Test Result .....	38
<b>10. Power Line Conducted Emissions .....</b>	<b>48</b>
10.1. Block Diagram of Test Setup.....	48
10.2. Limit .....	48
10.3. Test Procedure .....	48
10.4. Test Result .....	48
<b>11. Antenna Requirements .....</b>	<b>51</b>
11.1. Limit .....	51
11.2. Result .....	51
<b>12. Test setup photo .....</b>	<b>52</b>
12.1. Photos of Radiated emission.....	52
12.2. Photos of Conducted Emission test .....	53
<b>13. Photos of EUT .....</b>	<b>54</b>

### TEST REPORT DECLARATION

Applicant : Rosewill Inc.  
 Address : 17780, Rowland Street, City of Industry CA 91748 United States  
 Manufacturer : Shenzhen Vtsonic Co., Ltd  
 Address : No.35, 2<sup>nd</sup> Industrial Road, Tangxiayong Village, Songgang Street, Bao'an District, Shenzhen, Guangdong, China  
 EUT Description : Bluetooth Headphone  
 (A) Model No. : RW-TH68N  
 (B) Trademark : N/A

Measurement Standard Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247**  
**ANSI C63.10:2013**

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.


After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Lucas Pang  
 Project Engineer



Approved by (name + signature).....: Simple Guan  
 Project Manager



Date of issue.....: July 27, 2020

**Revision History**

Revision	Issue Date	Revisions	Revised By
V0	July 27, 2020	Initial released Issue	Lucas Pang

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

<b>Test Item</b>	<b>Standards Paragraph</b>	<b>Result</b>
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013	P
Antenna requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Description	: Bluetooth Headphone
Model Number	: RW-TH68N
Diff	: N/A
Trademark	: N/A
Power supply	: DC 5V from USB, DC 3.7V from battery.
Radio Technology	: Bluetooth V5.0
Operation frequency	: 2402-2480MHz
Channel No.	: 79 Channels
Channel spacing	: 1MHz
Modulation type	: GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type	: Internal Antenna, 2dBi(Max).
Software version	: V1.0
Hardware version	: V1.0
Intend use environment	: Residential, commercial and light industrial environment


## 2.2. Accessories of Device (EUT)

Accessories1 : /  
 Manufacturer : /  
 Model : /  
 Ratings : /

## 2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1.	Notebook PC	ACER	ZQT	--	--

## 2.4. Block Diagram of connection between EUT and simulators



## 2.5. Test Mode Description

Tested mode, channel information		
Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
$\pi$ /4 DQPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
8DPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480



## 2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	980kPa

## 2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,  
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission  
Registration Number: 293961

September 15, 2019 Certificated by IC  
Registration Number: CN0085

## 2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.13dB(Polarize: H)
	4.16dB(Polarize: V)
Uncertainty for radio frequency	$5.4 \times 10^{-8}$
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

## 2.9. Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	N/A	2019.09.06	1 Year
Spectrum analyzer	ROHDE&SCHWARZ	FSU	1166.1660.26	2019.09.06	1 Year
Spectrum analyzer	Agilent	N9020A	MY499100060	2019.09.05	1 Year
Receiver	ROHDE&SCHWARZ	ESR	1316.3003K03-102082-Wa	2019.09.06	1 Year
Receiver	R&S	ESCI	101165	2019.09.05	1 Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2019.09.06	2 Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	2020.04.12	2 Year
Loop Antenna	SCHWARZBECK	FMZB 1519B	00059	2019.09.07	2 Year
Cable	Resenberger	N/A	No.1	2019.09.05	1 Year
Cable	Resenberger	N/A	No.2	2019.09.05	1 Year
Cable	Resenberger	N/A	No.3	2019.09.05	1 Year
Pre-amplifier	HP	HP8347A	2834A00455	2019.09.05	1 Year
Pre-amplifier	Agilent	8449B	3008A02664	2019.09.05	1 Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126-466	2019.09.05	1 Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2019.09.05	1 Year
20db Attenuator	ICPROBING	IATS1	82347	2019.09.20	1 Year
Horn Antenna	A-INFOMW	LB-180100-KF	J211020657	2019.09.20	2 Year
Preamplifier	SKET	LNPA_1840-50	SK2018101801	2019.09.05	1 Year
Power Meter	Agilent	E9300A	MY41496625	2019.09.06	1 Year
Temp. & Humid. Chamber	Weihuang	WHTH-1000-40-880	100631	2019.09.10	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	20140927-6	2019.09.10	1 Year

### 3. MAXIMUM PEAK OUTPUT POWER

#### 3.1.Limit


Please refer section 15.247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

#### 3.2.Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

#### 3.3.Test Setup



#### 3.4.Test Result

Mode	Freq (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)	Result
GFSK	2402	-2.272	0.593	21	Pass
	2441	0.04	1.009	21	Pass
	2480	1.455	<b>1.398</b>	21	Pass
$\pi/4$ DQPSK	2402	-5.69	0.270	21	Pass
	2441	-3.138	0.486	21	Pass
	2480	-1.611	0.690	21	Pass
8DPSK	2402	-5.316	0.294	21	Pass
	2441	-2.942	0.508	21	Pass
	2480	-1.725	0.672	21	Pass
Conclusion: PASS					

## 4. BANDWIDTH

### 4.1.Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


### 4.2.Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### 4.3.Test Result


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant 1	0.8405	0.7606	/	Pass
NVNT	1-DH1	2441	Ant 1	0.7987	0.846	/	Pass
NVNT	1-DH1	2480	Ant 1	0.8217	0.9122	/	Pass
NVNT	2-DH1	2402	Ant 1	1.1515	1.2078	/	Pass
NVNT	2-DH1	2441	Ant 1	1.1581	1.2084	/	Pass
NVNT	2-DH1	2480	Ant 1	1.1403	1.1844	/	Pass
NVNT	3-DH1	2402	Ant 1	1.1135	1.2144	/	Pass
NVNT	3-DH1	2441	Ant 1	1.1223	1.1982	/	Pass
NVNT	3-DH1	2480	Ant 1	1.1377	1.2124	/	Pass

OBW NVNT 1-DH1 2402MHz Ant1




Date: 24.JUL.2020, 06:03:44

-20 dB BW NVNT 1-DH1 2402MHz Ant1




Date: 24.JUL.2020, 06:03:48

OBW NVNT 1-DH1 2441MHz Ant1




Date: 24.JUL.2020, 06:04:23

-20 dB BW NVNT 1-DH1 2441MHz Ant1




Date: 24.JUL.2020, 06:04:26

OBW NVNT 1-DH1 2480MHz Ant1




Date: 24.JUL.2020, 06:05:00

-20 dB BW NVNT 1-DH1 2480MHz Ant1




Date: 24.JUL.2020, 06:05:03

OBW NVNT 2-DH1 2402MHz Ant1



Date: 24.JUL.2020, 05:38:37

-20 dB BW NVNT 2-DH1 2402MHz Ant1



Date: 24.JUL.2020, 05:38:40




OBW NVNT 2-DH1 2441MHz Ant1




Date: 24.JUL.2020, 05:41:36

-20 dB BW NVNT 2-DH1 2441MHz Ant1




Date: 24.JUL.2020, 05:41:39

OBW NVNT 2-DH1 2480MHz Ant1




Date: 24.JUL.2020, 05:42:55

-20 dB BW NVNT 2-DH1 2480MHz Ant1




Date: 24.JUL.2020, 05:42:58

OBW NVNT 3-DH1 2402MHz Ant1




Date: 24.JUL.2020, 05:54:05

-20 dB BW NVNT 3-DH1 2402MHz Ant1




Date: 24.JUL.2020, 05:54:06

OBW NVNT 3-DH1 2441MHz Ant1



Date: 24.JUL.2020, 05:51:23


-20 dB BW NVNT 3-DH1 2441MHz Ant1



Date: 24.JUL.2020, 05:51:26




OBW NVNT 3-DH1 2480MHz Ant1



Date: 24.JUL.2020, 05:57:29

-20 dB BW NVNT 3-DH1 2480MHz Ant1



Date: 24.JUL.2020, 05:57:33

## 5. CARRIER FREQUENCY SEPARATION

### 5.1.Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


### 5.2.Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 20kHz RBW and 62kHz VBW.

### 5.3.Test Result


Condition	Mode	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	2440.808	2441.974	1.166	0.608	Pass
NVNT	2-DH1	2440.962	2441.976	1.014	0.806	Pass
NVNT	3-DH1	2440.974	2441.974	1	0.810	Pass

CFS NVNT 1-DH1 2441MHz




Date: 24.JUL.2020, 06:13:05

CFS NVNT 2-DH1 2441MHz



Date: 24.JUL.2020, 06:22:00

### CFS NVNT 3-DH1 2441MHz



Date: 24.JUL.2020, 06:29:41

## 6. NUMBER OF HOPPING CHANNEL

### 6.1.Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


### 6.2.Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

### 6.3.Test Result

Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	79	15	Pass
NVNT	2-DH1	79	15	Pass
NVNT	3-DH1	79	15	Pass


Hopping No. NVNT 1-DH1 2441MHz



Date: 24.JUL.2020 06:14:35


Hopping No. NVNT 2-DH1 2441MHz





Date: 24.JUL.2020, 06:23:53

### Hopping No. NVNT 3-DH1 2441MHz



Date: 24.JUL.2020, 06:32:27

## 7. DWELL TIME

### 7.1. Test limit

Please refer section 15.247

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channels employed.

### 7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

### 7.3. Test Result

PASS.

Detailed information please see the following page.

Mode	Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Conclusion
GFSK	DH1	2441	0.394	0.126	<0.4	PASS
	DH3	2441	2.406	0.385		PASS
	DH5	2441	2.887	0.308		PASS
$\pi$ /4 DQPSK	DH1	2441	0.408	0.131	<0.4	PASS
	DH3	2441	1.66	0.266		PASS
	DH5	2441	2.908	0.310		PASS
8DPSK	DH1	2441	0.407	0.130	<0.4	PASS
	DH3	2441	1.657	0.265		PASS
	DH5	2441	2.908	0.310		PASS

Note: 1 A period time = 0.4 (s) \* 79 = 31.6(s)

2 DH1 time slot = Pulse Duration \* (1600/(2\*79)) \* A period time/1000


DH3 time slot = Pulse Duration \* (1600/(4\*79)) \* A period time/1000

DH5 time slot = Pulse Duration \* (1600/(6\*79)) \* A period time/1000


Dwell time

GFSK


$\pi/4$ -DQPSK




Channel 39 / 2441 MHz - DH1




Channel 39 / 2441 MHz - 2DH1




Channel 39 / 2441 MHz - DH3



Channel 39 / 2441 MHz - 2DH3




Channel 39 / 2441 MHz - DH5




Channel 39 / 2441 MHz - 2DH5

Dwell time


8DPSK



Channel 39 / 2441 MHz - DH1



Channel 39 / 2441 MHz - DH3



Channel 39 / 2441 MHz - DH5

## 8. RADIATED EMISSIONS

### 8.1.Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

#### 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )


#### 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	




## 8.2. Block Diagram of Test setup


### 8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



### 8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



### 8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

### 8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator as shown in section 1.4 and 6.1
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
  - (a) Change work frequency or channel of device if practicable.
  - (b) Change modulation type of device if practicable.
  - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

### 8.4. Test Result

We have scanned the 10th harmonic from 9KHz to the EUT's highest frequency. Detailed information please see the following page.


From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.




From 30MHz to 1000MHz: Conclusion: PASS

Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		55.4147	12.40	13.57	25.97	40.00	-14.03			peak
2		133.7594	16.76	13.86	30.62	43.50	-12.88			peak
3	*	152.9857	15.95	15.05	31.00	43.50	-12.50			peak
4		232.0431	15.62	12.36	27.98	46.00	-18.02			peak
5		380.3140	11.22	15.92	27.14	46.00	-18.86			peak
6		552.1084	13.38	19.23	32.61	46.00	-13.39			peak

**Horizontal:**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree	Detector	Comment
1	46.2104	10.09	14.10	24.19	40.00	-15.81			peak	
2	135.7916	14.78	14.01	28.79	43.50	-14.71			peak	
3	159.2251	14.56	15.04	29.60	43.50	-13.90			peak	
4	238.3102	17.97	12.51	30.48	46.00	-15.52			peak	
5	311.9606	16.38	14.40	30.78	46.00	-15.22			peak	
6 *	661.3822	11.73	21.23	32.96	46.00	-13.04			peak	

Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz was listed in this report.

From 1G-25GHz

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	41.98	V	33.98	10.22	34.25	51.93	74	22.07	PK
4804	32.50	V	33.98	10.22	34.25	42.45	54	11.55	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	42.72	H	33.98	10.22	34.25	52.67	74	21.33	PK
4804	31.48	H	33.98	10.22	34.25	41.43	54	12.57	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	42.53	V	33.98	10.22	34.25	52.48	74	21.52	PK
4882	32.40	V	33.98	10.22	34.25	42.35	54	11.65	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	42.25	H	33.98	10.22	34.25	52.20	74	21.80	PK
4882	31.82	H	33.98	10.22	34.25	41.77	54	12.23	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	42.48	V	33.98	10.22	34.25	52.43	74	21.57	PK
4960	32.19	V	33.98	10.22	34.25	42.14	54	11.86	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	42.12	H	33.98	10.22	34.25	52.07	74	21.93	PK
4960	32.05	H	33.98	10.22	34.25	42.00	54	12.00	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

From 1G-25GHz

Test Mode: $\pi/4$ DQPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	42.06	V	33.98	10.22	34.25	52.01	74	21.99	PK
4804	32.85	V	33.98	10.22	34.25	42.80	54	11.20	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	42.31	H	33.98	10.22	34.25	52.26	74	21.74	PK
4804	31.38	H	33.98	10.22	34.25	41.33	54	12.67	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: $\pi/4$ DQPSK TX Mid									
4882	42.19	V	33.98	10.22	34.25	52.14	74	21.86	PK
4882	32.97	V	33.98	10.22	34.25	42.92	54	11.08	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	42.07	H	33.98	10.22	34.25	52.02	74	21.98	PK
4882	32.10	H	33.98	10.22	34.25	42.05	54	11.95	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: $\pi/4$ DQPSK TX High									
4960	42.61	V	33.98	10.22	34.25	52.56	74	21.44	PK
4960	32.94	V	33.98	10.22	34.25	42.89	54	11.11	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	42.84	H	33.98	10.22	34.25	52.79	74	21.21	PK
4960	31.41	H	33.98	10.22	34.25	41.36	54	12.64	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/


Note:

- 1, Result = Read level + Antenna factor + cable loss-Amp factor
- 2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Test Mode: 8DPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	42.67	V	33.98	10.22	34.25	52.62	74	21.38	PK
4804	32.50	V	33.98	10.22	34.25	42.45	54	11.55	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	42.79	H	33.98	10.22	34.25	52.74	74	21.26	PK
4804	31.76	H	33.98	10.22	34.25	41.71	54	12.29	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: 8DPSK TX Mid									
4882	42.21	V	33.98	10.22	34.25	52.16	74	21.84	PK
4882	32.39	V	33.98	10.22	34.25	42.34	54	11.66	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	42.52	H	33.98	10.22	34.25	52.47	74	21.53	PK
4882	32.01	H	33.98	10.22	34.25	41.96	54	12.04	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: 8DPSK TX High									
4960	41.97	V	33.98	10.22	34.25	51.92	74	22.08	PK
4960	32.31	V	33.98	10.22	34.25	42.26	54	11.74	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	42.28	H	33.98	10.22	34.25	52.23	74	21.77	PK
4960	32.11	H	33.98	10.22	34.25	42.06	54	11.94	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

## 9. BAND EDGE COMPLIANCE

### 9.1. Block Diagram of Test Setup



### 9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 9.3. Test Procedure


All restriction band and non- restriction band have been tested , only worse case is reported.

### 9.4. Test Result

PASS. (See below detailed test data)


Test Mode: GFSK-Low Hopping-off

Polarization: Vertical



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	2390.000	47.01	-3.40	43.61	74.00	-30.39	peak		
2 *	2402.180	89.51	-3.41	86.10	74.00	12.10	peak		


Polarization: Horizontal



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	2390.000	48.68	-3.40	45.28	74.00	-28.72	peak		
2 *	2402.180	92.92	-3.41	89.51	74.00	15.51	peak		


Test Mode: GFSK-High Hopping-off

Polarization: Vertical



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1 *	2480.200	87.40	-3.38	84.02	74.00	10.02	peak		
2	2483.500	47.36	-3.38	43.98	74.00	-30.02	peak		

Polarization: Horizontal




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1 *	2480.200	94.25	-3.38	90.87	74.00	16.87	peak		
2	2483.500	51.32	-3.38	47.94	74.00	-26.06	peak		

Note: 1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


Test Mode: GFSK-Low Hopping-on

Polarization: Vertical



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	2390.000	45.57	-3.40	42.17	74.00	-31.83			peak
2 *	2410.760	89.85	-3.40	86.45	74.00	12.45			peak


Polarization: Horizontal



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	2390.000	47.79	-3.40	44.39	74.00	-29.61			peak
2 *	2404.820	91.24	-3.41	87.83	74.00	13.83			peak


Test Mode: GFSK-High Hopping-on

Polarization: Vertical



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1 *	2467.400	89.09	-3.39	85.70	74.00	11.70			peak
2	2483.500	43.76	-3.38	40.38	74.00	-33.62			peak

Polarization: Horizontal



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1 *	2462.800	88.49	-3.40	85.09	74.00	11.09			peak
2	2483.500	46.17	-3.38	42.79	74.00	-31.21			peak


Note: 1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.




Test Mode:  $\pi/4$  DQPSK-Low Hopping-off

Polarization: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2390.000	50.01	-3.40	46.61	74.00	-27.39			peak
2	*	2402.180	86.51	-3.41	83.10	74.00	9.10			peak


Polarization: Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2390.000	47.95	-3.40	44.55	74.00	-29.45			peak
2	*	2402.180	94.43	-3.41	91.02	74.00	17.02			peak


Test Mode:  $\pi/4$  DQPSK-High Hopping-off

Polarization: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2480.200	86.40	-3.38	83.02	74.00	9.02			peak
2		2483.500	48.36	-3.38	44.98	74.00	-29.02			peak

Polarization: Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2480.300	93.10	-3.38	89.72	74.00	15.72			peak
2		2483.500	52.32	-3.38	48.94	74.00	-25.06			peak

Note: 1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


Test Mode:  $\pi/4$  DQPSK-Low Hopping-on

Polarization: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2390.000	46.47	-3.40	43.07	74.00	-30.93	peak		
2	*	2403.170	86.68	-3.41	83.27	74.00	9.27	peak		


Polarization: Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2390.000	47.46	-3.40	44.06	74.00	-29.94	peak		
2	*	2414.390	90.84	-3.41	87.43	74.00	13.43	peak		


Test Mode:  $\pi/4$  DQPSK-High Hopping-on

Polarization: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2467.300	86.75	-3.39	83.36	74.00	9.36	peak		
2		2483.500	43.76	-3.38	40.38	74.00	-33.62	peak		

Polarization: Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2454.100	87.78	-3.39	84.39	74.00	10.39	peak		
2		2483.500	46.17	-3.38	42.79	74.00	-31.21	peak		

Note: 1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


Test Mode: 8DPSK-Low Hopping-off

Polarization: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2390.000	46.11	-3.40	42.71	74.00	-31.29	peak		
2	*	2402.290	86.48	-3.41	83.07	74.00	9.07	peak		


Polarization: Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2390.000	48.18	-3.40	44.78	74.00	-29.22	peak		
2	*	2402.180	94.42	-3.41	91.01	74.00	17.01	peak		


Test Mode: 8DPSK-High Hopping-off

Polarization: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	2479.600	86.42	-3.38	83.04	74.00	9.04	peak		
2		2483.500	44.21	-3.38	40.83	74.00	-33.17	peak		

Polarization: Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	2480.000	93.32	-3.38	89.94	74.00	15.94	peak		
2		2483.500	46.86	-3.38	43.48	74.00	-30.52	peak		

Note: 1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


Test Mode: 8DPSK-Low Hopping-on

Polarization: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2390.000	45.07	-3.40	41.67	74.00	-32.33			peak
2	*	2409.550	86.56	-3.40	83.16	74.00	9.16			peak


Polarization: Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2390.000	48.79	-3.40	45.39	74.00	-28.61			peak
2	*	2407.460	91.25	-3.40	87.85	74.00	13.85			peak


Test Mode: 8DPSK-High Hopping-on

Polarization: Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2456.400	86.72	-3.39	83.33	74.00	9.33			peak
2		2483.500	45.42	-3.38	42.04	74.00	-31.96			peak

Polarization: Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2480.300	91.14	-3.38	87.76	74.00	13.76			peak
2		2483.500	52.24	-3.38	48.86	74.00	-25.14			peak


Note: 1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


Conducted Method

GFSK Mode:

Test channel: Lowest channel




No-hopping mode




Hopping mode

Test channel: Highest channel




No-hopping mode




Hopping mode

$\pi$  /4DQPSK Mode:

Test channel: Lowest channel




No-hopping mode




Hopping mode

Test channel: Highest channel



No-hopping mode




Hopping mode

8DPSK Mode:


Test channel:

Lowest channel



Date: 24.01.2020 09:53:29

No-hopping mode




Date: 24.01.2020 09:12:52

Hopping mode


Test channel:

Highest channel



Date: 24.01.2020 09:59:53

No-hopping mode




Date: 24.01.2020 09:16:07

Hopping mode



## 10. POWER LINE CONDUCTED EMISSIONS

### 10.1. Block Diagram of Test Setup



### 10.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB( $\mu$ V)	Average Level dB( $\mu$ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

### 10.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.


### 10.4. Test Result

PASS. (See below detailed test data)


Note: If peak Result comply with AV limit, QP and AV Result is deemed to comply with AV limit



## Line:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1740	47.33	9.93	57.26	64.77	-7.51	QP	
2		0.1740	31.47	9.93	41.40	54.77	-13.37	AVG	
3		0.2220	40.57	9.94	50.51	62.74	-12.23	QP	
4		0.2220	24.85	9.94	34.79	52.74	-17.95	AVG	
5		0.4560	30.28	9.95	40.23	56.77	-16.54	peak	
6		2.2080	19.03	9.89	28.92	56.00	-27.08	peak	
7		4.8360	29.25	10.02	39.27	56.00	-16.73	peak	
8		23.2800	26.82	10.45	37.27	60.00	-22.73	peak	

**Neutral:**

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1560	50.04	9.94	59.98	65.67	-5.69	QP	
2		0.1560	35.49	9.94	45.43	55.67	-10.24	AVG	
3		0.1860	45.11	9.92	55.03	64.21	-9.18	QP	
4		0.1860	28.03	9.92	37.95	54.21	-16.26	AVG	
5		0.2460	37.67	9.97	47.64	61.89	-14.25	peak	
6		0.4920	26.56	9.96	36.52	56.13	-19.61	peak	
7		4.8000	28.29	10.02	38.31	56.00	-17.69	peak	
8		22.8720	27.60	10.45	38.05	60.00	-21.95	peak	

Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz was listed in this report.

## **11. ANTENNA REQUIREMENTS**

### **11.1. Limit**



For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **11.2. Result**

The EUT antenna is Internal Antenna. It complies with the standard requirement.

## 12. TEST SETUP PHOTO

### 12.1. Photos of Radiated emission



## 12.2.Photos of Conducted Emission test







### 13. PHOTOS OF EUT
































-----THE END OF REPORT-----