



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Solid Technologies

Model: Alliance 5W ROU

Description: Multiple-Enclosure Booster System

Chassis: MROU_C_M_AC – ALLIANCE 5W Optical Unit Chassis, AC Power

FCC ID: W6UHM700L (Module MRDU-700LTEF - 5 Watt 700 MHz Full Band LTE Amplifier)
FCC ID: W6UHM80I85C (Module MRDU-800IDEN/850CEL - 5 Watt 800 & 850 MHz Amplifier)
FCC ID: W6UHM1900P (Module MRDU-1900PCS - 5 Watt 1900 MHz Amplifier)
FCC ID: W6UHMAWS1 (Module MRDU-AWS-1 - 5 Watt 2100 MHz Amplifier)

To

FCC Part 1.1310

Date of Issue: April 23, 2014

On the behalf of the applicant:

Solid Technologies
4332 E Siesta Lane
Phoenix, AZ 85050

Attention of:

Gregory Glenn
Ph: (408) 649-4803
E-Mail: greg.glenn@solid.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p13a0006

Mike Graffeo
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

| Revision | Date | Revised By | Reason for Revision |
|----------|----------------|--------------|---------------------|
| 1.0 | April 23, 2014 | Mike Graffeo | Original Document |
| | | | |
| | | | |
| | | | |



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A



Description:

5W 700MHz Full Band LTE Amplifier

This is a permanently mounted (fixed) cell phone booster device used in Controlled Exposure environment.

Limits - Controlled Exposure
47 CFR 1.1310
Table 1, (A)

| | |
|----------------------|---|
| 0.3-3.0 MHz: | Limit [mW/cm ²] = 100 |
| 3.0-30 MHz: | Limit [mW/cm ²] = (900/f ²) |
| 30-300 MHz: | Limit [mW/cm ²] = 1.0 |
| 300-1500 MHz: | Limit [mW/cm²] = f/300 |
| 1500-100,000 MHz | Limit [mW/cm ²] = 5 |

Test Frequencies: **742 MHz**

Power, Conducted: 5000 mW (P)
Antenna Gain Isotropic: 11.0 dBi
Antenna Gain Numeric (G): 12.59
Antenna Type: Stadium
PI = 3.1414
Limit (S): 2.473 mW/cm²

Minimum Safe Distance
Calculations

Formula = $R = ((PG)/(4*PI*S))^{0.5}$
Minimum Safe Distance (R) = 45.02 cm



Description:

5 Watt 800/850MHz Amplifier

This is a permanently mounted (fixed) cell phone booster device used in Controlled Exposure environment.

**Limits - Controlled Exposure
47 CFR 1.1310
Table 1, (A)**

| | |
|----------------------|---|
| 0.3-3.0 MHz: | Limit [mW/cm ²] = 100 |
| 3.0-30 MHz: | Limit [mW/cm ²] = (900/f ²) |
| 30-300 MHz: | Limit [mW/cm ²] = 1.0 |
| 300-1500 MHz: | Limit [mW/cm²] = f/300 |
| 1500-100,000 MHz | Limit [mW/cm ²] = 5 |

Test Frequencies: **865.5 MHz**
Power, Conducted: 5000 mW (P)
Antenna Gain Isotropic: 11.6 dBi
Antenna Gain Numeric (G): 14.45
Antenna Type: Stadium
PI = 3.1414
Limit (S): 2.885 mW/cm²

Minimum Safe Distance Calculations Formula = $R = ((PG)/(4*PI*S))^{0.5}$
Minimum Safe Distance (R) = 44.65 cm

Test Frequencies: **881.5 MHz**
Power, Conducted: 5000 mW (P)
Antenna Gain Isotropic: 11.6 dBi
Antenna Gain Numeric (G): 14.45
Antenna Type: Stadium
PI = 3.1414
Limit (S): 2.938 mW/cm²

Minimum Safe Distance Calculations Formula = $R = ((PG)/(4*PI*S))^{0.5}$
Minimum Safe Distance (R) = 44.25 cm



Description:

5 Watt 1900MHz Amplifier

This is a permanently mounted (fixed) cell phone booster device used in Controlled Exposure environment.

**Limits - Controlled Exposure
47 CFR 1.1310
Table 1, (A)**

| | |
|-------------------------|---|
| 0.3-3.0 MHz: | Limit [mW/cm ²] = 100 |
| 3.0-30 MHz: | Limit [mW/cm ²] = (900/f ²) |
| 30-300 MHz: | Limit [mW/cm ²] = 1.0 |
| 300-1500 MHz: | Limit [mW/cm ²] = f/300 |
| 1500-100,000 MHz | Limit [mW/cm²] = 5 |

Test Frequencies: **1962.5 MHz**
Power, Conducted: 5000 mW (P)
Antenna Gain Isotropic: 11.6 dBi
Antenna Gain Numeric (G): 14.45
Antenna Type: Stadium
PI = 3.1414
Limit (S): 5 mW/cm²

Minimum Safe Distance
Calculations

Formula = $R = ((PG)/(4*PI*S))^{0.5}$
Minimum Safe Distance (R) = 33.92 cm



Description:

5 Watt 2100MHz Amplifier

This is a permanently mounted (fixed) cell phone booster device used in Controlled Exposure environment.

Limits - Controlled Exposure
47 CFR 1.1310
Table 1, (A)

| | |
|-------------------------|---|
| 0.3-3.0 MHz: | Limit [mW/cm ²] = 100 |
| 3.0-30 MHz: | Limit [mW/cm ²] = (900/f ²) |
| 30-300 MHz: | Limit [mW/cm ²] = 1.0 |
| 300-1500 MHz: | Limit [mW/cm ²] = f/300 |
| 1500-100,000 MHz | Limit [mW/cm²] = 5 |

Test Frequencies: **2132.5 MHz**

Power, Conducted: 5000 mW (P)

Antenna Gain Isotropic: 11.6 dBi

Antenna Gain Numeric (G): 14.45

Antenna Type: Stadium

PI = 3.1414

Limit (S): 5 mW/cm²

Minimum Safe Distance
Calculations

$$\text{Formula} = R = ((PG)/(4*PI*S))^{0.5}$$

Minimum Safe Distance (R) = 33.92 cm



Description:

Worse case composite 20Watt: if all 4 amplifiers are simultaneously transmitting within the single enclosure (20000mW). Minimum Safe Distance is based off the highest antenna gain of 14.45 and the strictest limit of 2.473 mW/cm².

Minimum Safe Distance
Calculations

$$\text{Formula} = R = \left(\frac{PG}{4 \cdot \pi \cdot S} \right)^{0.5}$$
$$= \left(\frac{20000 \cdot 14.45}{4 \cdot \pi \cdot 2.473} \right)^{0.5}$$

$$\text{Minimum Safe Distance (R)} = 96.44 \text{ cm}$$

END OF TEST REPORT