

TEST REPORT

FCC MPE Test for TR_N2RDU_AWS13_M

APPLICANT SOLiD, Inc.

REPORT NO. HCT-RF-2005-FC026-R3

DATE OF ISSUE 1 July 2020

Tested byKyung Soo Kang

Technical Manager Jong Seok Lee

HCT CO., LTD.

Soo Chan Lee

SocChan Lee
/ CEO

HCT CO., LTD.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA Tel. +82 31 634 6300 Fax. +82 31 645 6401

TEST REPORT

FCC MPE Test for TR_N2RDU_AWS13_M

REPORT NO.

HCT-RF-2005-FC026-R3

DATE OF ISSUE July 01, 2020

Additional Model

_

Applicant SOLiD, Inc.

10, 9th Floor, SOLiD Space, Pangyoyeok-ro 220, Bundang-gu, Seongnam-si,

Gyeonggi-do, 463-400, South Korea

Eut Type DAS

Model Name TR_N2RDU_AWS13_M

FCC ID W6ULAWS13M

The result shown in this test report refer only to the sample(s) tested unless

otherwise stated.

This test results were applied only to the test methods required by the

standard.

F-TP22-03 (Rev. 03) Page 2 of 6



REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	June 04, 2020	Initial Release
1	June 16, 2020	 Revised Eut Type from 'Alliance TR N2ROU CALA' to 'DAS' Revised the data table. Added MIMO data(optional) and the simultaneous band emission conditions.
2	June 29, 2020	- Revised model name and ID.
3	July 01, 2020	- Revised model name.

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

F-TP22-03 (Rev. 03) Page 3 of 6

^{*} The report shall not be reproduced except in full(only partly) without approval of the laboratory.



RF Exposure Statement

1. LIMITS

According to § 1.1310 and § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range	Electric field Strength (V/m)	Magneticfield	Powerdensity	Averagingtime
(MHz)		Strength (A/m)	(mW/cm²)	(minutes)
0.3 - 1.34······ 1.34 - 30······ 30 - 300······ 300 - 1500······ 1500 - 100.000······	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/ f²) 0.2 f/1500 1.0	30 30 30 30 30

F = frequency in MHz

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$S = PG/4\pi R^2$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

F-TP22-03 (Rev. 03) Page 4 of 6

^{* =} Plane-wave equivalent power density



- AWS – LTE 10 MHz (Downlink)

Max Peak output Power at antenna input terminal	34.00	dBm
Max Peak output Power at antenna input terminal	2511.89	mW
Prediction distance	320.00	cm
Prediction frequency	2120.85	MHz
Antenna Gain(typical)	17.00	dBi
Antenna Gain(numeric)	50.12	-
Power density at prediction frequency(S)	0.0978	mW/cm²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

[Optional: Ant 1 + Ant 2 (MIMO)]

- AWS (Downlink)

Max Peak output Power at antenna input terminal	37.00	dBm
Max Peak output Power at antenna input terminal	5011.87	mW
Prediction distance	320.00	cm
Prediction frequency	2120.85	MHz
Antenna Gain(typical)	17.00	dBi
Antenna Gain(numeric)	50.12	-
Power density at prediction frequency(S)	0.1952	mW/cm²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm²

F-TP22-03 (Rev. 03) Page 5 of 6



Simultaneous band emission conditions

${\sf TR_N2RDU_AWS13_M\&TR_N2RDU_L2600F_M}$

Band	MPE Ratio (Power density / Limit)	Sum of MPE Ratio	
AWS	0.0978	0.1057	≤ 1
BRS/EBS	0.0978	0.1957	

*Note

- 1. The result of each band was applied to the worst value.
- 2. MPE ratios are calculated as $[(Power density1 / MPE Limit) + [(Power density2 / MPE Limit) + \cdots] \leq 1$

F-TP22-03 (Rev. 03) Page 6 of 6