



F-TP22-03 (Rev. 02) Page 93 of 125









F-TP22-03 (Rev. 02) Page 94 of 125









F-TP22-03 (Rev. 02) Page 95 of 125









F-TP22-03 (Rev. 02) Page 96 of 125






F-TP22-03 (Rev. 02) Page 97 of 125









F-TP22-03 (Rev. 02) Page 98 of 125









F-TP22-03 (Rev. 02) Page 99 of 125









F-TP22-03 (Rev. 02) Page 100 of 125






F-TP22-03 (Rev. 02) Page 101 of 125









F-TP22-03 (Rev. 02) Page 102 of 125









F-TP22-03 (Rev. 02) Page 103 of 125









F-TP22-03 (Rev. 02) Page 104 of 125






F-TP22-03 (Rev. 02) Page 105 of 125









F-TP22-03 (Rev. 02) Page 106 of 125









F-TP22-03 (Rev. 02) Page 107 of 125









F-TP22-03 (Rev. 02) Page 108 of 125






F-TP22-03 (Rev. 02) Page 109 of 125









F-TP22-03 (Rev. 02) Page 110 of 125









F-TP22-03 (Rev. 02) Page 111 of 125









F-TP22-03 (Rev. 02) Page 112 of 125






F-TP22-03 (Rev. 02) Page 113 of 125









F-TP22-03 (Rev. 02) Page 114 of 125









F-TP22-03 (Rev. 02) Page 115 of 125









F-TP22-03 (Rev. 02) Page 116 of 125






F-TP22-03 (Rev. 02) Page 117 of 125









F-TP22-03 (Rev. 02) Page 118 of 125









F-TP22-03 (Rev. 02) Page 119 of 125








F-TP22-03 (Rev. 02) Page 120 of 125





F-TP22-03 (Rev. 02) Page 121 of 125



#### 5.6. RADIATED SPURIOUS EMISSIONS

## **Test Requirements:**

### § 2.1053 Measurements required: Field strength of spurious radiation.

- (a) Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of § 2.1049, as appropriate. For equipment operating on frequencies below 890 MHz, an open field test is normally required, with the measuring instrument antenna located in the far-field at all test frequencies. In the event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurements will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from halfwave dipole antennas.
- (b) The measurements specified in paragraph (a) of this section shall be made for the following equipment:
  - (1) Those in which the spurious emissions are required to be 60 dB or more below the mean power of the transmitter.
  - (2) All equipment operating on frequencies higher than 25 MHz.
  - (3) All equipment where the antenna is an integral part of, and attached directly to the transmitter.
  - (4) Other types of equipment as required, when deemed necessary by the Commission.

F-TP22-03 (Rev. 02) Page 122 of 125



#### **Test Procedures:**

Because KDB 935210 D05 procedure does not provide this requirement, measurements were in accordance with the test methods section 5.5 of ANSI C63.26-2015

- a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency.
- b) Each emission under consideration shall be evaluated:
  - 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
  - 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
  - 3) Return the turntable to the azimuth where the highest emission amplitude level was observed.
  - 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
  - 5) Record the measured emission amplitude level and frequency using the appropriate RBW.
- c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.

F-TP22-03 (Rev. 02) Page 123 of 125



#### **Test Result:**


Signal	Frequency (MHz)	Measured Level (dBuV)	Measured Power (dBm)	Ant. Factor (dB/m)	C.L (dB)	A.G. + H.P.F. (dB)	D.F.	Pol.	Result (dBm/m)	dBuV/m@3m
GSM	5,666.25	46.58	-48.62	31.700	7.26	36.28	1.96	٧	-43.980	51.220
CDMA	5,666.25	45.43	-49.77	31.700	7.26	36.28	1.96	٧	-45.130	50.070
WCDMA	5,666.25	44.88	-50.32	31.700	7.26	36.28	1.96	٧	-45.680	49.520
LTE 5 MHz	5,666.25	45.75	-49.45	31.700	7.26	36.28	1.96	V	-44.810	50.390
LTE 10 MHz	5,666.25	45.78	-49.42	31.700	7.26	36.28	1.96	V	-44.780	50.420

<sup>\*</sup> C.L.: Cable Loss / A.G.: Ant. Gain / H.P.F.: High Pass Filter / D.F.: Distance Factor (3.75 m)

#### **Notes:**

- 1. We have done horizontal and vertical polarization in detecting antenna.
- 2. The amplitude of the spurious domain emission attenuated by more than 20 dB over the permissible value was not recorded according to ANSI C63.26, clause 5.1.1., c).

# Plot data of radiated spurious emissions



Note: Only the worst case plots for Radiated Spurious Emissions.

F-TP22-03 (Rev. 02) Page 124 of 125



# **6. Annex A\_EUT AND TEST SETUP PHOTO**

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2005-FC011-P

F-TP22-03 (Rev. 02) Page 125 of 125