

# Assessment report

**REP0031625-1R1ARFWL**

Date of issue: November 1, 2023

Applicant:

**SOLiD CO., LTD**

Product Name:

**SOLiD O-RAN ORU CBRS**

Model

**O-LTR\_CBRSM2**

FCC ID:

**W6UOLRCBRSM2**

Type of assessment:

**MPE Calculation Report**

Specifications:

- ◆ FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ KDB 447498 D01 General RF Exposure Guidance v06

Lab and test locations

---

Company name	Nemko USA, Inc.
Address	1110 Faraday Ave, Suite 150
City	Carlsbad
State	California
Postal code	92008
Country	USA
Telephone	+1 760 444 3500
Website	www.nemko.com

Prepared by	James Cunningham, EMC/WL Manager
Signature	

Limits of responsibility

---

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko USA's ISO/IEC 17025 accreditation.

Copyright notification

---

Nemko USA Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko USA Inc. accepts no responsibility for damages, if any, suffered by any third party because of decisions made or actions based on this report. © Nemko USA Inc.

# Table of Contents

---

<b>Table of Contents</b> .....	<b>3</b>
<b>Section 1 Evaluation summary</b> .....	<b>4</b>
1.1 MPE exemption for stand-alone transmission .....	4

## Section 1 Evaluation summary

### 1.1 MPE exemption for stand-alone transmission

#### 1.1.1 References, definition, and limits

FCC §2.1091(d)

- (2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from the whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

**Table 1.1-1: Table 1 to §1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842 / f	4.89 / f	*(900 / f <sup>2</sup> )	<6
30–300	61.4	0.163	1.0	<6
300–1500			f / 300	<6
1500–100000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824 / f	2.19 / f	*(180 / f <sup>2</sup> )	<30
30–300	27.5	0.073	0.2	<30
300–1500			f / 1500	<30
1500–100000			1.0	<30

Notes: f = frequency in MHz. \* = Plane-wave equivalent power density.

Equation from Page 18 of OET Bulletin 64, Edition 97-01:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm<sup>2</sup> or W/m<sup>2</sup>)  
P = power input to the antenna (mW or W)  
G = power gain of the antenna in the direction of interest relative to an isotropic radiator  
R = distance to the center of radiation of the antenna (cm or m)

## 1.1.2 EUT technical information

---

Operational frequency	3550 – 3700 MHz (Band TDD48)
Antenna type	External (The EUT is professionally installed)
Antenna gain	5.5 dBi (declared by manufacturer as maximum antenna gain)
Number of antennas	2 (2 transmit antenna, correlated output), $10\log_{10}(2) = 3.01$ MIMO correction
Maximum transmitter conducted power	17.82 dBm/MHz (60.53 mW/MHz) (40 MHz system bandwidth) (Taken from maximum EIRP density measurement data in report REP0031625-2TRFWL) Convert to total channel power: Add $10\log_{10}(40/10) = 6.02$ dB = 23.84 dBm (242.10 mW)

### 1.1.3 MPE exemption calculations

---

#### Band TDD48:

Fundamental transmit (prediction) frequency:	<u>3550</u> MHz
Maximum measured conducted peak output power:	<u>23.84</u> dBm
Cable and/or jumper loss:	<u>0</u> dB
Maximum peak power at antenna input terminal:	<u>23.84</u> dBm
Tx On time:	<u>1.000</u> ms
Tx period time:	<u>1.000</u> ms
Average factor:	<u>100</u> %
Maximum calculated average power at antenna input terminal:	<u>242</u> mW
Single Antenna gain (typical):	<u>5.5</u> dBi
Number of antennas:	<u>2</u>
Total system gain:	<u>8.51</u> dBi
<b>FCC limit:</b>	
MPE limit for uncontrolled exposure at prediction frequency:	<u>1.000000</u> mW/cm <sup>2</sup>
	<u>10.000000</u> W/m <sup>2</sup>
Minimum calculated prediction distance for compliance:	<u>80</u> cm
Typical (declared) distance:	<u>80</u> cm
Average power density at prediction frequency:	<u>0.021362</u> mW/cm <sup>2</sup>
	<u>0.213619</u> W/m <sup>2</sup>
<b>Margin of Compliance:</b>	<u>16.70</u> dB
Maximum allowable antenna gain:	<u>25.21</u> dBi

### 1.1.4 Verdict

---

The calculation is below the limit; therefore, the product is compliant with the RF exposure requirements for the declared distance.

**End of test report**