



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 17159  
 Tel: +82-31-323-6008 Fax: +82-31-323-6010  
<http://www.ltalab.com>

Dates of Tests: May 25, 2022 ~ June 16, 2022  
 Test Report S/N: LR500112206O  
 Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID.	<b>W6YHP200</b>
APPLICANT	<b>PASSTECH CO., LTD.</b>

<b>Equipment Class</b>	:	<b>Digital Transmission System (DTS)</b>
<b>Manufacturing Description</b>	:	<b>HOTEL DOOR LOCK</b>
<b>Manufacturer</b>	:	<b>PASSTECH CO., LTD.</b>
<b>Model name</b>	:	<b>HP200</b>
<b>Variant Model name</b>	:	<b>HP200N, HP200N-01, HP200N-02, HP200N-03 HP200-01, HP200-02, HP200-03</b>
<b>Test Device Serial No.:</b>	:	<b>Identical prototype</b>
<b>Rule Part(s)</b>	:	<b>FCC Part 15.247 Subpart C ; ANSI C63.10 - 2013</b>
<b>Frequency Range</b>	:	<b>2405 ~ 2480 MHz Zigbee</b>
<b>Max. Output Power</b>	:	<b>Max -10.33 dBm - Conducted</b>
<b>Data of issue</b>	:	<b>June 16, 2022</b>

This test report is issued under the authority of:

The test was supervised by:

*JaBeom.Koo*

*延正*

Ja-Beom Koo, Manager

Jae-Humm Yeon, Test Engineer

**This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.**



NVLAP LAB Code.: 200723-0

**TABLE OF CONTENTS**

1. GENERAL INFORMATION ----- 3

2. INFORMATION ABOUT TEST ITEM ----- 4

3. TEST REPORT ----- 5

    3.1 SUMMARY OF TESTS ----- 5

    3.2 TECHNICAL CHARACTERISTICS TEST ----- 6

        3.2.1 6 dB BANDWIDTH ----- 6

        3.2.2 PEAK OUTPUT POWER ----- 8

        3.2.3 POWER SPECTRAL DENSITY ----- 10

        3.2.4 BAND EDGE ----- 12

        3.2.5 CONDUCTED SPURIOUS EMISSIONS ----- 14

        3.2.6 RADIATED SPURIOUS EMISSIONS ----- 16

**APPENDIX**

    APPENDIX TEST EQUIPMENT USED FOR TESTS ----- 23

## 1. General information

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 17159  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2022-09-28	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2023-01-25	FCC CAB
VCCI	JAPAN	C-4948,	2023-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2023-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2023-08-15	VCCI registration
VCCI	JAPAN	G-847	2022-12-13	VCCI registration
IC	CANADA	5799A-1	2022-10-18	IC filing

## 2. Information about test item

### 2-1 Client & Manufacturer

Client Company name : PASSTECH CO., LTD.  
 Address : B-402, 215 Galmachi-ro, Jungwon-gu, Seongnam-si, Gyeonggi-do,  
 South Korea 13217  
 Tel / Fax : +82-31-743-7277 / +82-31-743-7276  
 Manufacturer PASSTECH CO., LTD.  
 Address B-402, 215 Galmachi-ro, Jungwon-gu, Seongnam-si, Gyeonggi-do,  
 South Korea 13217  
 Tel / Fax +82-31-743-7277 / +82-31-743-7276

### 2-2 Equipment Under Test (EUT)

Model name : PASSTECH CO., LTD  
 Model name : HP200  
 Variant Model name : HP200N, HP200N-01,HP200N-02,HP200N-03  
 HP200-01,HP200-02,HP200-03  
 Serial number : Identical prototype  
 Date of receipt : May 25 ,2022  
 EUT condition : Pre-production, not damaged  
 Antenna type : Chip Antenna (Max Gain : 3.5 dBi)  
 Frequency Range : 2405 ~ 2480 MHz Zigbee  
 RF output power : Max -10.33 dBm – Conducted  
 Type of Modulation : DSSS, O-QPSK  
 Power Source : DC 6 V

### 2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz) Zigbee	2405	2440	2480

### 2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	-	MS-1736	MSI

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	Conducted	C
15.247(b)	Transmitter Peak Output Power		C
15.247(e)	Transmitter Power Spectral Density		C
15.247(d)	Band Edge & Conducted Spurious emission		C
15.209	Transmitter emission	Radiated	C
15.207	AC Conducted Emissions	Conducted	N/A
15.203	Antenna requirement	-	C

N/A : This product is only operated with DC voltage.

The above equipment was tested by LTA Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247 The test results of this report relate only to the tested sample identified in this report.

The tests were performed according to the method of measurements prescribed in KDB No.558074.

→ Antenna Requirement

PASSTECH CO., LTD FCC ID: W6YHP200 unit complies with the requirement of §15.203.

The antenna type is Chip Antenna

**3.2 Technical Characteristics Test**

**3.2.1 6 dB Bandwidth**

**Procedure:**

The bandwidth at 6 dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

- Center frequency = the highest, middle and the lowest channels
- RBW = 100 kHz
- Span = 3 X RBW
- VBW = 3 X RBW
- Sweep = auto
- Trace = max hold
- Detector function = peak

**Measurement Data : Complies**

**Zigbee Mode**

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2405	1.577	Complies
2440	1.592	Complies
2480	1.592	Complies

- See next pages for actual measured spectrum plots.

**Minimum Standard:**

6 dB Bandwidth ≥ 500 kHz

**Measurement Setup**







Figure 1: Measurement setup for the carrier frequency separation

# Zigbee



### 3.2.2 Peak Output Power Measurement

#### Procedure:

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth :

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW  $\geq$  DTS Bandwidth

Span  $\geq$  3 X RBW

VBW = 3 X RBW

Sweep = auto

Detector function = peak

**Measurement Data : Complies**

#### Mode Zigbee

Frequency (MHz)	Test Results	
	Measured data (dBm)	Result
2405	-10.33	Complies
2440	-12.98	Complies
2480	-12.77	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:




Peak output power	$\leq$ 1 W(30 dBm)
-------------------	--------------------

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)



# Zigbee



**3.2.3 Power Spectral Density**

**Procedure:**

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

The spectrum analyzer is set to:

- RBW = 3 kHz (3 kHz ≤ RBW ≤ 100 kHz)      Span ≥ 1.5 times the DTS bandwidth
- VBW = 3 X RBW      Sweep = auto
- Detector function = peak      Trace = max hold

**Measurement Data : Complies**

**Zigbee Mode**

Frequency (MHz)	Test Results	
	dBm / 3 kHz BW	Result
2405	-25.03	Complies
2440	-29.40	Complies
2480	-27.78	Complies

- See next pages for actual measured spectrum plots.




**Minimum Standard:**

Power Spectral Density	≤ 8 dBm @ 3 kHz BW
------------------------	--------------------

**Measurement Setup**

Same as the Chapter 3.2.1 (Figure 1)

# Zigbee



### 3.2.4 Band Edge

**Procedure:**

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2013.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB..

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1 MHz

VBW  $\geq 3 \times$  RBW

Detector function = peak

Trace = max hold

Sweep = auto

**Measurement Data: Complies**



Frequency (MHz)	Test Results	
	dBc	Result
<b>Low edge</b>	<b>47.65</b>	Complies
<b>High edge</b>	<b>42.14</b>	Complies

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.

- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	$\leq 20$ dBc
--------------------------	---------------

# Zigbee



**3.2.5 Conducted Spurious Emissions**

**Procedure:**

The test follows KDB558074. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz

Sweep = auto

VBW = 100 kHz

Detector function = peak

Trace = max hold

**Measurement Data: Complies**

Frequency (MHz)	Test Results	
	dBc	Result
2405	35.06	Complies
2440	29.09	Complies
2480	33.05	Complies




- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	≥ 20 dBc
--------------------------	----------

**Measurement Setup**

Same as the Chapter 3.2.1 (Figure 1)

### Unwanted Emission – Zigbee (Low,Middle,High)



### 3.2.6 Radiated Spurious Emissions

#### Procedure:

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.10-2013. The EUT is a placed on as turn table. For emissions testing at or below 1 GHz, the table height shall be 0.8 m above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10<sup>th</sup> harmonic.

RBW = 120 kHz ( 30 MHz ~ 1 GHz)

VBW  $\geq$  RBW

= 1 MHz ( 1 GHz ~ 10<sup>th</sup> harmonic )

Trace = max hold


Detector function = peak

Sweep = auto

**Duty cycle : 98.89 %**


**The EUT configureal to transmit continuously(D  $\geq$  98%)/ Duty Factor = 0**

**below 30 MHz**






below 1 GHz (30 MHz to 1 GHz)



above 1 GHz



Measurement Data: **Complies**


- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30MHz.
- The test results for the worst of the various operating modes are presented in accordance with 6.3.4 of ANSI C63.10.
- Checked with a red circle is the fundamental frequency.

**Minimum Standard: FCC Part 15.209(a)**

<b>Frequency (MHz)</b>	<b>Limit (uV/m) @ 3 m</b>
0.009 ~ 0.490	2400/F(kHz) (@ 30 m)
0.490 ~ 1.705	24000/F(kHz) (@ 30 m)
1.705 ~ 30	30(@ 30 m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500


\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Radiated Emissions – Zigbee**




No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	60.07	46.17	-14.81	31.36	40.00	8.64	100	172	horizontal
2.	60.31	45.88	-14.83	31.05	40.00	8.95	100	188	horizontal
3.	71.83	46.28	-16.47	29.81	40.00	10.19	100	360	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	47.58	46.67	-14.63	32.04	40.00	7.96	100	104	vertical
2.	47.95	47.47	-14.62	32.85	40.00	7.15	100	104	vertical
3.	60.19	48.55	-14.82	33.73	40.00	6.27	100	276	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	14570.25	32.58	21.25	53.83	74.00	20.17	100	136	vertical
2.	17683.38	31.99	24.53	56.52	74.00	17.48	100	360	vertical
3.	17921.38	31.50	25.88	57.38	74.00	16.62	100	254	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	14495.88	31.46	21.24	52.70	74.00	21.30	100	140	horizontal
2.	17793.88	31.88	25.42	57.30	74.00	16.70	100	14	horizontal
3.	17970.25	31.22	25.98	57.20	74.00	16.80	100	360	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq MHz	RD PK dB $\mu$ V	RD AV dB $\mu$ V	C.F dB	Result PK dB $\mu$ V	Result AV dB $\mu$ V	Limit PK dB $\mu$ V	Limit AV dB $\mu$ V	Margin PK dB	Margin AV dB	Height cm	Angle deg	Polarity
2.	18298.56	39.22	34.22	17.06	56.28	51.28	74.00	54.00	17.72	2.72	154	162	horizontal
4.	19899.75	40.37	35.37	15.67	56.04	51.04	74.00	54.00	17.96	2.96	282	288	horizontal
6.	20059.13	39.91	34.91	15.39	55.30	50.30	74.00	54.00	18.70	3.70	296	302	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq MHz	RD PK dB $\mu$ V	RD AV dB $\mu$ V	C.F dB	Result PK dB $\mu$ V	Result AV dB $\mu$ V	Limit PK dB $\mu$ V	Limit AV dB $\mu$ V	Margin PK dB	Margin AV dB	Height cm	Angle deg	Polarity
2.	18136.00	37.98	34.98	16.98	54.96	51.96	74.00	54.00	19.04	2.04	229	221	vertical
4.	18756.50	38.14	34.14	16.78	54.92	50.92	74.00	54.00	19.08	3.08	360	360	vertical
6.	19415.25	39.21	33.21	16.23	55.44	49.44	74.00	54.00	18.56	4.56	353	348	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

### 3.2.7 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

**Minimum Standard: FCC Part 15.207(a) / EN 55022**

**Measurement Data: N/A**

#### Class B

Frequency Range	quasi-peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

**APPENDIX**  
**TEST EQUIPMENT USED FOR TESTS**

○	Use	Description	Model No.	Serial No.	Manufacturer	Interval	Next Cal. Date
1	■	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2022-09-06
2	■	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2023-03-16
3		SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2023-03-16
4		Attenuator (3 dB)	8491A	37822	HP	1 year	2022-09-06
5		Attenuator (10 dB)	8491A	63196	HP	1 year	2022-09-06
6	■	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2022-09-06
7		RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2022-09-06
8		RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2023-03-16
9	■	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2022-09-06
10		DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2024-03-18
11		DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2024-03-18
12	■	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2023-03-20
13		Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2023-03-16
14		Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
15	■	DC Power Supply	6674A	3637A01657	Agilent	-	-
17	■	Power Meter	EPM-441A	GB32481702	HP	1 year	2023-03-16
18	■	Power Sensor	8481A	3318A94972	HP	1 year	2022-09-06
19		Audio Analyzer	8903B	3729A18901	HP	1 year	2022-09-06
20		Modulation Analyzer	8901B	3749A05878	HP	1 year	2022-09-06
21		TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2022-09-06
22		Stop Watch	HS-3	812Q08R	CASIO	2 year	2024-03-18
23		LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2022-09-06
24		Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2023-03-16
25		UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2023-03-16
26		Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2023-03-16
27		Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2023-03-16
28		OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2023-03-16
29		Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2023-03-16
30		Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2023-03-16
31	■	Active Loop Antenna	FMZB 1519	1519-031	SCHWARZBECK	2 year	2023-02-26