




TEST REPORT

<p>KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr</p>	<p>Report No.: KR22-SRF0005-B Page (1) of (7)</p>	<p> KCTL</p>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------

1. Client

- Name : ATTOWAVE Co., Ltd.
- Address : 1005, 10F Leader's Tower, 60-15 Gasan-dong, Gumchun-gu, Seoul, 153-801 Korea
- Date of Receipt : 2021-10-12

2. Use of Report : Class II Permissive change

3. Name of Product / Model : Bluetooth Module / BTM0

4. Manufacturer / Country of Origin: ATTOWAVE Co., Ltd. / Korea

5. FCC ID : W75-BTM0

6. Date of Test : 2021-10-21 to 2021-11-25

7. Location of Test : Permanent Testing Lab On Site Testing
 (Address:65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)

8. Test method used : 47 CRF Part 1.1310

9. Test Result : Refer to the test result in the test report

Affirmation	Tested by Name : Yoonseok Choi (Signature)	Technical Manager Name : Heesu Ahn (Signature)
-------------	---------------------------------------------------	-------------------------------------------------------

2022-02-03

KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

REPORT REVISION HISTORY

Date	Revision	Page No
2022-01-19	Originally issued	-
2022-02-03	Updated	4, 5
2022-02-08	Updated	7

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

Note. The report No. KR22-SRF0005-A is superseded by the report No. KR22-SRF0005-B.

General remarks for test reports

Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

Statement not required by the standard or client used for type testing

CONTENTS

- 1. General information4
- 2. Device information4
 - 2.1. Host device information4
 - 2.2. Accessory information4
 - 2.3. Frequency/channel operations.....5
- 3. Antenna requirement5
- 4. RF Exposure.....6
 - 4.1. Test results.....7



1. General information

Client : ATTOWAVE Co., Ltd.
 Address : 1005, 10F Leader's Tower, 60-15 Gasan-dong, Gumchun-gu, Seoul, 153-801 Korea
 Manufacturer : ATTOWAVE Co., Ltd.
 Address : 1005, 10F Leader's Tower, 60-15 Gasan-dong, Gumchun-gu, Seoul, 153-801 Korea
 Laboratory : KCTL Inc.
 Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
 Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
 VCCI Registration No. : R-20080, G-20078, C-20059, T-20056
 CAB Identifier: KR0040, ISED Number: 8035A
 KOLAS No.: KT231

2. Device information

Equipment under test : Bluetooth Module
 Model : BTM0
 Modulation technique : Bluetooth(BLE)_GFSK
 Number of channels : 40 ch
 Frequency range : 2 402 MHz ~ 2 480 MHz (Bluetooth Low Energy)
 Power source : DC 3.3 V
 Antenna specification : Micro-strip Antenna
 Antenna gain : -0.106 dBi
 Software version : V1.00
 Hardware version : B
 Operation temperature : -35 °C ~ 85 °C

2.1. Host device information

Product Name	Model Name	FCC ID
RADAR DETECTOR	R8	AMWUA2102

Note: The EUT is authorized for use in specific End-product.

2.2. Accessory information

Equipment	Manufacturer	Model	Serial NO.	Power source
Laptop	Tech-Front (Chongqing) Computer Co., Ltd	15U50N	008QC�L560879	DC 19 V
AC/DC Adapter	Chicony Power Technology(Suzhou) Co., Ltd.	A13-040N3A	CNYCAG19021C056007P10781 AG19021C056	100 - 240 V~, 50-60 Hz

2.3. Frequency/channel operations

This device contains the following capabilities:
 Bluetooth Low Energy

Ch.	Frequency (MHz)
00	2 402
⋮	⋮
19	2 440
⋮	⋮
39	2 480

Table 2.2.1. Bluetooth Low Energy

3. Antenna requirement

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty (\pm)
Conducted RF power	0.9 dB

4. RF Exposure

Regulation

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
(A) Limits for Occupational / Controlled Exposure				
0.3 ~ 3.0	614	1.63	*100	6
3.0 ~ 30	1842/f	4.89/f	*900/f ²	6
30 ~ 300	61.4	0.163	1.0	6
300 ~ 1 500	/	/	f/300	6
1 500 ~ 15 000	/	/	5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19/f	*180/f ²	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, *=*plane-wave equivalent power density*

Per the guidance of KDB 680106, the E-field and H-field limits shown in the table above are extended down to 100 kHz

4.1. Test results

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm^2]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

Calculation Result of RF exposure (FCC)

Maximum tune-up tolerance

Mode	Frequency [MHz]	Max Tune-up Power [dBm]	Max Tune-up Power [mW]	Ant Gain [dBi]	Power density at 20 cm [mW/cm^2]	Limit [mW/cm^2]
BLE/1 Mbps	2 480	-6.00	0.25	-0.106	0.000 05	1.000 00

Note.

- The power density P_d (5th column) at a distance of 20 cm calculated from the friis transmission Formula is far below the limit of 1 mW/cm^2 .

End of test report