No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663Telephone:

Telephone: +86 (0) 20 82155555 Fax: +86 (0) 20 82075059

Email: sgs internet operations@sgs.com

FEDERAL COMMUNICATIONS COMMISSION

Registration number: 282399

Report No.: SZEMO09020038201

Page: 1 of 11

FCC ID: W89-RC-TOYS

TEST REPORT

Application No.: SZEMO090200382 (SGS HK NO.: 2021399EL)

Applicant: Apple Toys Development Co., Ltd.

Applicant Address: RM1701-02, 17/F, PODIUM PLAZA., 5 HANOI ROAD TST KOWLOON

HONG KONG

FCC ID: W89-RC-TOYS

Fundamental Frequency: 27.145MHz

Equipment Under Test (EUT):

Name: RADIO CONTROL TOYS

Model No.: 8038, 8039, 8322, 9008, 9078, 9023,9025,9027,9083,9085.

Please refer to section 2 of this report which indicates which item was

actually tested and which were electrically identical.

Country of Origin: China Labeled Age Grading: 3+

Standards: FCC PART 15, SUBPART C : 2008

Section 15.227

Date of Receipt: 4 February 2009

Date of Test: 4 to 11 February 2009

Date of Issue: 12 February 2009

Test Result : PASS *

Authorized Signature:

Robinson Lo Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

^{*} In the configuration tested, the EUT complied with the standards specified above.

Report No.: SZEMO09020038201

Page: 2 of 11

2 Test Summary

Test	Test Requirement	Standard Paragraph	Result	
Radiated Emission (30MHz to 1000MHz)	FCC PART 15 :2008	Section 15.227	PASS	
Occupied Bandwidth	FCC PART 15 :2008	Section 15.215	PASS	

.Remark:

Tx: In this whole report Tx (or tx) means Transmitter.
Rx: In this whole report Rx (or rx) means Receiver.

Remark:

Item No: 8038, 8039, 8322, 9008, 9078, 9023, 9025, 9027, 9083, 9085

Only the Item 9023 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above items.

Report No.: SZEMO09020038201

Page: 3 of 11

3 Contents

		Page
1	I COVER PAGE	1
2	2 TEST SUMMARY	2
3	3 CONTENTS	3
4	4 GENERAL INFORMATION	4
	4.1 Details of E.U.T	4
	4.2 DESCRIPTION OF SUPPORT LINITS	Δ
	4.3 TEST LOCATION	4
	4.4 OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
	4.5 TEST FACILITY	5
5		
	5.1 E.U.T. OPERATION	7
	5.2 TEST PROCEDURE & MEASUREMENT DATA	7
	5.2.1 Radiated Emissions	
	5.2.2 Occupied Bandwidth	

FCC ID: W89-RC-TOYS

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Report No.: SZEMO09020038201

Page: 4 of 11

4 General Information

4.1 Details of E.U.T.

Name: RADIO CONTROL TOYS

Model No.: 8038, 8039, 8322, 9008, 9078, 9023,9025,9027,9083,9085

Power Supply: DC 3.0V(2*1.5V"AA" Size Batteries)

Power Cord: N/A-

4.2 Description of Support Units

The EUT was tested as an independent unit: a 27MHz radio transmitter.

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.4 Other Information Requested by the Customer

None.

FCC ID: W89-RC-TOYS

Report No.: SZEMO09020038201

Page: 5 of 11

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

NVLAP – Lab Code: 200611-0

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

ACA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

CNAS L0167

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

• FCC - Registration No.: 282399

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002. With the above and NVLAP's accreditation, SGS-CSTC is an authorized test laboratory for the DoC process.

Industry Canada (IC)

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620B-1.

Date of Registration: Jan 15, 2007. Valid until Jan 15, 2009

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460 and C-2584 respectively.

This certificate is valid until September 14.2009

FCC ID: W89-RC-TOYS

Report No.: SZEMO09020038201

Page: 6 of 11

5 Test Results

Test Instruments

	RE in Chamber							
ltem	tem Test Equipment Manufacturer		Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)		
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2007	15-06-2009		
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2008	11-12-2009		
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A		
4	Coaxial cable	SGS	N/A	SEL0028	18-06-2008	17-06-2009		
5	5 BiConiLog Antenna (26-3000MHz) ETS-LINDGREN 6 Pre-amplifier Agilent Technologies 7 Double-ridged horn (1-18GHz) ETS-LINDGREN		3142C	SEL0014	12-08-2008	11-08-2009		
6			8447D	SEL0053	18-06-2008	17-06-2009		
7			3117	SEL0005	12-08-2008	11-08-2009		
8	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	12-08-2008	11-08-2009		
9	Pre-amplifier		AFS42-00101 800-25-S-42	SEL0081	18-06-2008	17-06-2009		
10	Pre-amplifier Rohde & Schwarz (18-26GHz)		AFS33-18002 650-30-8P-44	SEL0080	18-06-2008	17-06-2009		
11			82346	SEL0094	18-06-2008	17-06-2009		
12			ZN30900A	SEL0097	15-06-2008	14-06-2009		

Report No.: SZEMO09020038201

Page: 7 of 11

5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C
Humidity: 52 % RH
Atmospheric Pressure: 1010 mbar

EUT Operation: Test the EUT in transmitting mode.

5.2 Test Procedure & Measurement Data

5.2.1 Radiated Emissions

Test Requirement: FCC Part15 C Section 15.227

Test Method: ANSI C63.4:2003

Measurement 3m (Semi-Anechoic Chamber)

Distance:

Requirements: Carrier Power will not exceed 80dBuV/m at 3m (Average).

Out of band emissions shall not exceed: $40.0 \text{ dB}_{\mu}\text{V/m}$ between 30MHz & 88MHz $43.5 \text{ dB}_{\mu}\text{V/m}$ between 88MHz & 216MHz $46.0 \text{ dB}_{\mu}\text{V/m}$ between 216MHz & 960MHz

54.0 dBµV/m above 960MHz

Detector: 9KHz to 30MHz RBW=9KHz VBW=30KHz

30MHz to 1000MHz RBW=100KHz VBW=300KHz

Above 1000MHz RBW=1MHz VBW=3MHz

Test Procedure: 1. The EUT is placed on a turntable, which is 0.8m above ground plane.

2. The turntable shall be rotated for 360 degrees to determine the

position of maximum emission level.

3. EUT is set 3m away from the receiving antenna, which is moved from

1m to 4m to find out the maximum emissions.

4. Maximum procedure was performed on the six highest emissions to

ensure EUT compliance.

5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

6. Repeat above procedures until the measurements for all frequencies

are complete.

7. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

27.145MHz Mode

Test Procedure: For testing performed with the loop antenna, testing was performed in accordance to ANSI C63.4:2003 section 8.2.1. The center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

FCC ID: W89-RC-TOYS

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Report No.: SZEMO09020038201

Page: 8 of 11

Intentional emission

Test Frequency	Peak (dBμV/m)		Limits	Marg	in (dB)
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal
27.145	71.03	58.70	100.00	28.97	41.30

Test Frequency	Average (dBμV/m)		Limits	Marg	in (dB)
(MHz)	Vertical	Horizontal	(dBµV/m)	Vertical	Horizontal
27.145	66.63	54.30	80.00	13.37	25.70

Other emissions

Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
54.250	0.80	7.64	28.08	40.21	20.57	40.00	-19.43
89.350	1.10	8.64	27.95	33.83	15.62	43.50	-27.88
324.325	1.98	14.80	26.91	43.24	33.11	46.00	-12.89
378.925	2.14	16.05	27.28	41.19	32.10	46.00	-13.90
514.450	2.62	18.23	27.70	35.21	28.36	46.00	-17.64

Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
133.225	1.29	7.84	27.58	33.74	15.29	43.50	-28.21
269.725	1.77	12.70	26.83	36.58	24.22	46.00	-21.78
297.025	1.88	13.76	26.73	40.47	29.38	46.00	-16.62
324.325	1.98	14.80	26.91	39.60	29.47	46.00	-16.53
378.925	2.14	16.05	27.28	36.08	26.99	46.00	-19.01

Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

Test Results: The unit does meet the FCC Part 15 C Section 15.227 requirements.

FCC ID: W89-RC-TOYS

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Report No.: SZEMO09020038201

Page: 9 of 11

5.2.2 Occupied Bandwidth

Test Requirement: FCC Part 15 C Section 15.215 (C)

Test Method: ANSI C63.4 :2003

Operation within the band 26.960 – 27.280 MHz

Requirements: Intentional radiators operating under the alternative provisions to the

general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band

operation.

Method of measurement:


The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector. The vertical Scale is set to 10dB

per division. The horizontal scale is set to 32KHz per division.

Report No.: SZEMO09020038201

Page: 10 of 11

The graph as below: represents the emissions take for this device.



Date: 10.FEB.2009 15:17:19

The results: The unit does meet the FCC Part 15 C Section 15.215 requirements.

FCC ID: W89-RC-TOYS

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Report No.: SZEMO09020038201

Page: 11 of 11

FCC ID: W89-RC-TOYS

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."