

TTE Technology, Inc.

Application
For
Certification
FCC ID: W8U28S303

LCD TV

Model: 28S305

Additional Models: 28S301, 28S303, 28S307, 28S305-MX, 28S301-MX, 28S303-MX, 28S307-MX, 28S307-MX, 28S30*, 28S30*-MX ("*"=any number, alphabet or character presents different appearance including color, silk-screen or decorative part.)

Brand Name: TCL

Computer Peripheral

Report No.: 170526184GZU-001

Prepared and Checked by:

Approved by:

Sign on file

Jenner Liu
Project Engineer

Kidd Yang
Senior Project Engineer
Date: June 12, 2017

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_PC_b

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labeling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Test Equipment List

INTERTEK TESTING SERVICES

MEASUREMENT / TECHNICAL REPORT

TTE Technology, Inc.

MODEL: 28S305

Additional Models: 28S301, 28S303, 28S307, 28S305-MX, 28S301-MX, 28S303-MX, 28S307-MX, 28S307-MX, 28S30*, 28S30*-MX ("*"=any number, alphabet or character presents different appearance including color, silk-screen or decorative part.)

FCC ID: W8U28S303

This report concerns (check one:) Original Grant Class II Change

Equipment Type: JBP-Class B Computing Device Peripheral

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart B for unintentional radiator – the new 47 CFR [10-01-15 Edition] provision.

Report prepared by:

Jenner Liu
Intertek Testing Services Shenzhen Ltd.
Guangzhou Branch
Block E, No.7-2 Guang Dong Software Science
Park, Caipin Road, Guangzhou Science City,
GETDD Guangzhou, China
Phone: 86-20-8213 9688
Fax: 86-20-3205 7538

TRF No.: FCC 15C_PC_b
FCC ID: W8U28S303
Report No.: 170526184GZU-001

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>General Description</u>	2
1.1	Product Description.....	2
1.2	Related Submittal(s) Grants.....	2
1.3	Test Methodology.....	3
1.4	Test Facility.....	3
2.0	<u>System Test Configuration</u>	5
2.1	Justification.....	5
2.2	EUT Exercising Software.....	5
2.3	Special Accessories.....	5
2.4	Equipment Modification.....	5
2.5	Measurement Uncertainty.....	6
2.6	Support Equipment List and Description.....	6
3.0	<u>Emission Results</u>	8
3.1	Field Strength Calculation.....	9
3.2	Radiated Emission Configuration Photograph.....	11
3.3	Radiated Emission Data.....	12
3.4	Conducted Emission at Mains Terminal.....	14
3.5	Conducted Emission Configuration Photograph.....	14
3.6	Conducted Emission.....	15
4.0	<u>Equipment Photographs</u>	19
5.0	<u>Product Labelling</u>	21
6.0	<u>Technical Specifications</u>	23
7.0	<u>Instruction Manual</u>	25
8.0	<u>Miscellaneous Information</u>	27
9.0	<u>Test Equipment List</u>	31

INTERTEK TESTING SERVICES

List of attached file

Exhibit Type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated photos	radiated photos.pdf
Test Setup Photo	Conducted photos	conducted photos.pdf
External Photo	External Photos	external photos.pdf
Internal Photo	Internal Photos	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
ID Label / Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidential Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is a LCD TV. The device can be used to connect PC by HDMI port. The EUT is powered by AC 120V, 60Hz.

The EUT contains a module which can be operated in the frequency band of 2412MHz to 2462MHz in 802.11b, 802.11g and 802.11n-HT20 modes, 2422MHz to 2452MHz in 802.11n-HT40 mode, and 5180MHz to 5240MHz, 5745MHz to 5825MHz in 802.11a and 802.11n (20MHz, 40MHz, 80MHz) modes.

The Model: 28S301, 28S303, 28S307, 28S305-MX, 28S301-MX, 28S303-MX, 28S307-MX, 28S307-MX, 28S30*, 28S30*-MX ("*"=any number, alphabet or character presents different appearance including color, silk-screen or decorative part.) are the same as the Model: 28S305 in hardware and electrical aspect. The models are difference in packaging and marketing purpose only.

1.2 Related Submittal(s) Grants

This is an application for certification of a computer peripheral. Other digital functions were reported in the verification report: 170526184GZU-002.

The host contains a WIFI module, which has been granted under the FCC ID: 2AC23-WC0HR2601.

INTERTEK TESTING SERVICES

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2014). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **EMTEK (Shenzhen) Co., Ltd** and located at Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052, China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 406365).

INTERTEK TESTING SERVICES

EXHIBIT 2
SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2014).

The device was powered by AC 120V/60Hz during the test. The host device contains a WiFi module which was installed and operating during the test. Only the worst case data was reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. The step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

The frequency range from 30MHz to 29.125GHz was searched for spurious emissions from the device. Only those emissions reported were detected. All other emissions were at least 20 dB below the applicable limits.

2.2 EUT Exercising Software

N/A

2.3 Special Accessories

N/A

2.4 Equipment Modification

Any modifications installed previous to testing by TTE Technology, Inc. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

INTERTEK TESTING SERVICES

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
Laptop	LENOVO	T420
Hard Disk	Smart.drive	HD-003
RJ45 Cable	N/A	Unshielded, Length 450cm
USB Cable	Smart.drive	Unshielded, Length 155cm
USB Memory	TOSHIBA	UHYBS-004G-BL
Dummy Load	N/A	N/A
HDMI Cable*3	N/A	UnShielded, Length 180cm
AV Cable	N/A	Unshielded, Length 120cm
Headphone	N/A	Unshielded, Length 120cm
Tuner Resister	N/A	75ohm
Remote controller	TCL	N/A

INTERTEK TESTING SERVICES

EXHIBIT 3
EMISSION RESULTS

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

INTERTEK TESTING SERVICES

3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG$$

where FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB/m

AG = Amplifier Gain in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG$$

INTERTEK TESTING SERVICES

3.1 Field Strength Calculation (cont'd)

Example

Assume a receiver reading of 62.0dB μ V is obtained. The antenna factor of 7.4dB/m and cable factor of 1.6dB is added. The amplifier gain of 29dB is subtracted. The net field strength for comparison to the appropriate emission limit is 42dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0\text{dB}\mu\text{V}$$

$$AF = 7.4\text{dB/m}$$

$$CF = 1.6\text{dB}$$

$$AG = 29.0\text{dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 = 42\text{dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(42\text{dB}\mu\text{V/m})/20] = 125.9\mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission
At
741.766MHz (HDMI In Mode)

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.pdf.

INTERTEK TESTING SERVICES

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 3.2dB margin (HDMI In Mode)

TEST PERSONNEL:

Sign on file

Jenner Liu, Project Engineer
Typed/Printed Name

June 09, 2017
Date

INTERTEK TESTING SERVICES

Company: TTE Technology, Inc.

Date of Test: June 09, 2017

Model: 28S305

Operating Mode: HDMI In

Table 1

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	148.346	48.2	20.0	10.4	38.6	43.5	-4.9
Horizontal	296.707	41.7	20.0	15.3	37.0	46.0	-9.0
Horizontal	741.776	37.9	20.0	24.8	42.7	46.0	-3.3
Horizontal	1800.100	25.9	20.0	28.2	34.1	54.0	-19.9
Horizontal	3998.000	23.8	20.0	32.5	36.3	54.0	-17.7
Horizontal	4999.000	20.6	20.0	35.5	36.1	54.0	-17.9
Horizontal	10001.000	19.0	20.0	38.9	37.9	54.0	-16.1
Horizontal	11999.000	18.5	20.0	42.1	40.6	54.0	-13.4
Vertical	148.375	45.8	20.0	10.4	36.2	43.5	-7.3
Vertical	372.895	40.3	20.0	17.3	37.6	46.0	-8.4
Vertical	741.766	38.0	20.0	24.8	42.8	46.0	-3.2
Vertical	1800.000	25.4	20.0	27.7	33.1	54.0	-20.9
Vertical	3997.000	25.4	20.0	31.9	37.3	54.0	-16.7
Vertical	5000.000	20.8	20.0	35.0	35.8	54.0	-18.2
Vertical	9500.000	22.3	20.0	35.9	38.2	54.0	-15.8
Vertical	11998.000	18.7	20.0	41.6	40.3	54.0	-13.7

NOTES:

1. Quasi-Peak detector is used for frequency up to 1GHz and Peak detector is used for frequency from 1GHz to 29.125GHz.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.
4. All emissions up to 1GHz are below the QP limit and all emissions between 1GHz to 29.125GHz are below the AV limit.

Test Engineer: Jenner Liu

TRF No.: FCC 15C_PC_b

FCC ID: W8U28S303

Report No.: 170526184GZU-001

INTERTEK TESTING SERVICES

3.4 Conducted Emission at Mains Terminal

3.5 Conducted Emission Configuration Photograph

Worst Case Conducted Configuration
at
0.426 MHz(HDMI In Mode)

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

INTERTEK TESTING SERVICES

3.6 Conducted Emission Data

Judgement: Passed by 10.3 dB margin(HDMI In Mode)

TEST PERSONNEL:

Sign on file

Jenner Liu, Project Engineer
Typed/Printed Name

June 09, 2017
Date

INTERTEK TESTING SERVICES

Company: TTE Technology, Inc.


Date of Test: June 09, 2017

Model: 28S305

Operating Mode: HDMI In

Phase: Live

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.162	48.2	L1	9.6	17.2	65.4
0.214	40.6	L1	9.7	22.4	63.0
0.326	33.0	L1	9.7	26.6	59.6
0.426	43.3	L1	9.7	14.0	57.3
0.586	35.7	L1	9.7	20.3	56.0
0.654	35.8	L1	9.7	20.2	56.0

Result Table AV

Frequency (MHz)	CAverage (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.162	42.0	L1	9.6	13.4	55.4
0.214	34.6	L1	9.7	18.4	53.0
0.326	27.9	L1	9.7	21.7	49.6
0.426	37.0	L1	9.7	10.3	47.3
0.586	27.9	L1	9.7	18.1	46.0
0.654	28.4	L1	9.7	17.6	46.0

Test Engineer: Jenner Liu

TRF No.: FCC 15C_PC_b

FCC ID: W8U28S303

Report No.: 170526184GZU-001

INTERTEK TESTING SERVICES

Company: TTE Technology, Inc.


Date of Test: June 09, 2017

Model: 28S305

Operating Mode: HDMI In

Phase: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.162	48.7	N	9.6	16.7	65.4
0.214	39.6	N	9.7	23.4	63.0
0.318	36.4	N	9.7	23.4	59.8
0.438	43.8	N	9.7	13.3	57.1
0.490	38.2	N	9.7	18.0	56.2
0.598	35.8	N	9.7	20.2	56.0

Result Table AV

Frequency (MHz)	CAverage (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.162	43.0	N	9.6	12.4	55.4
0.214	32.0	N	9.7	21.0	53.0
0.318	29.8	N	9.7	20.0	49.8
0.438	36.3	N	9.7	10.8	47.1
0.490	32.0	N	9.7	14.2	46.2
0.598	28.7	N	9.7	17.3	46.0

Test Engineer: Jenner Liu

TRF No.: FCC 15C_PC_b

FCC ID: W8U28S303

Report No.: 170526184GZU-001

INTERTEK TESTING SERVICES

EXHIBIT 4
EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, photographs of the tested EUT are saved with filename: external photos.pdf and internal photos.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 5
PRODUCT LABELLING

INTERTEK TESTING SERVICES

5.0 Product Labelling

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 6
TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

6.0 Technical Specifications

For electronic filing, the block diagram of the tested EUT is saved with filename: block.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 7
INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold / leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 8

MISCELLANEOUS INFORMATION

INTERTEK TESTING SERVICES

8.0 Miscellaneous Information

This miscellaneous information includes emission measuring procedure.

INTERTEK TESTING SERVICES

8.1 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of computer peripheral operating under Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 – 2014.

The computer peripheral equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The antenna height and polarization are varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions are in QP mode from the frequency band 30MHz to 1GHz with RBW setting 120kHz and in PK & AV mode from frequency band 1GHz to 29.125GHz with RBW setting 1MHz. Detector function for conducted emissions are in QP & AV mode and IFBW setting is 9kHz from the frequency band 150kHz to 30MHz.

For radiated emission, the frequency range scanned is 30MHz to 29.125GHz. For line-conducted emissions, the range scanned is 150kHz to 30MHz with RBW setting 9KHz.

INTERTEK TESTING SERVICES

8.1 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

Conducted measurements are made as described in ANSI C63.4 – 2014.

INTERTEK TESTING SERVICES

EXHIBIT 9
TEST EQUIPMENT LIST

INTERTEK TESTING SERVICES

9.0 Test Equipment List

For Radiated Emission test

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
EE089	EMI Test Receiver	Rohde & Schwarz	ESU	1302.600 5.26	21-May-2017	21-May-2018
EE040	Pre-Amplifier	HP	8447F	2944A07 999	20-May-2017	20-May-2018
EE043	Bilog Antenna	Schwarzbeck	VULB916 3	142	20-May-2017	20-May-2018
EE147	Cable	Schwarzbeck	AK9513	ACRX1	21-May-2017	21-May-2018
EE169	Cable	Rosenberger	N/A	FP2RX2	21-May-2017	21-May-2018
EE168	Cable	Schwarzbeck	AK9513	CRPX1	21-May-2017	21-May-2018
EE170	Cable	Schwarzbeck	AK9513	CRRX2	21-May-2017	21-May-2018
EE096	Pre-Amplifier	A.H.	PAM- 0126	1415261	20-May-2017	20-May-2018
EE094	Horn Antenna	Schwarzbeck	BBHA 9120	707	20-May-2017	20-May-2018
EE097	Cable	H+B	0.5M SF104- 26.5	289147/4	21-May-2017	21-May-2018
EE100	Cable	H+B	3M SF104- 26.5	295838/4	21-May-2017	21-May-2018
EE101	Cable	H+B	6M SF104- 26.5	295840/4	21-May-2017	21-May-2018
EE095	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA917 0399	21-May-2017	21-May-2018
EE343	EMI Test Receiver	Rohde & Schwarz	FSV40	132.1- 3008K39- 100967- AP	20-May-2017	20-May-2018
EE240	Pre-Amplifier	Lunar EM	LNA26G4 0-40	J1013131 028001	20-May-2017	20-May-2018
EE234	Horn Antenna	AHS/USA	SAS-573	184	21-May-2017	21-May-2018
EE312	Cable	A.H	SAC- 40G-1	414	21-May-2017	21-May-2018
EE313	Cable	A.H	SAC- 40G-1	413	21-May-2017	21-May-2018

TRF No.: FCC 15C_PC_b
 FCC ID: W8U28S303
 Report No.: 170526184GZU-001

INTERTEK TESTING SERVICES

9.0 Test Equipment List (cont'd)

For Conducted Emission test

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
EE144	Test Receiver	Rohde & Schwarz	ESCI	26115-010-0027	20-May-2017	20-May-2018
EE145	L.I.S.N.	Rohde & Schwarz	ENV216	101161	20-May-2017	20-May-2018
EE032	L.I.S.N.	ROHDE & SCHWARZ	ESH3-Z5	100191	20-May-2017	20-May-2018
EE041	50Ω Coaxial Switch	Anritsu	MP59B	6100175589	21-May-2017	21-May-2018
EE212	Voltage Probe	Rohde & Schwarz	ESH2-Z3	100122	21-May-2017	21-May-2018