

**TTE Technology, Inc.**

Application  
For  
Certification  
**FCC ID: W8U43S405**

**LED TV**

**Model: 43S405**

**Additional Models: 43S401, 43S403, 43S407, 43S40\*, 43S405-MX, 43S401-MX, 43S403-MX, 43S407-MX, 43S40\*-MX ("\*"=any number, alphabet or character presents different appearance including color, silk-screen or decorative part.)**

**Brand Name: TCL**

Computer Peripheral

Report No.: 170221080GZU-001

Prepared and Checked by:

Approved by:

Sign on file

Jenner Liu  
Project Engineer

---

Kidd Yang  
Senior Project Engineer  
Date: March 06, 2017

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C\_PC\_b

---

# INTERTEK TESTING SERVICES

---

## LIST OF EXHIBITS

### *INTRODUCTION*

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labeling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Test Equipment List

# INTERTEK TESTING SERVICES

## MEASUREMENT / TECHNICAL REPORT

**TTE Technology, Inc.**

**MODEL: 43S405**

**Additional Models: 43S401, 43S403, 43S407, 43S40\*, 43S405-MX, 43S401-MX, 43S403-MX, 43S407-MX, 43S40\*-MX ("\*"=any number, alphabet or character presents different appearance including color, silk-screen or decorative part.)**

**FCC ID: W8U43S405**

This report concerns (check one:)      Original Grant  Class II Change

Equipment Type: JBP-Class B Computing Device Peripheral

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?      Yes       No

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37?      Yes       No

If no, assumed Part 15, Subpart B for unintentional radiator – the new 47 CFR [10-01-15 Edition] provision.

Report prepared by:

Jenner Liu  
Intertek Testing Services Shenzhen Ltd.  
Guangzhou Branch  
Block E, No.7-2 Guang Dong Software Science  
Park, Caipin Road, Guangzhou Science City,  
GETDD Guangzhou, China  
Phone: 86-20-8213 9688  
Fax: 86-20-3205 7538

TRF No.: FCC 15C\_PC\_b  
FCC ID: W8U43S405  
Report No.: 170221080GZU-001

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

<b>1.0</b>	<b><u>General Description</u></b> .....	2
1.1	Product Description.....	2
1.2	Related Submittal(s) Grants.....	2
1.3	Test Methodology.....	3
1.4	Test Facility.....	3
<b>2.0</b>	<b><u>System Test Configuration</u></b> .....	5
2.1	Justification.....	5
2.2	EUT Exercising Software.....	5
2.3	Special Accessories.....	5
2.4	Equipment Modification.....	5
2.5	Measurement Uncertainty.....	6
2.6	Support Equipment List and Description.....	6
<b>3.0</b>	<b><u>Emission Results</u></b> .....	8
3.1	Field Strength Calculation.....	9
3.2	Radiated Emission Configuration Photograph.....	11
3.3	Radiated Emission Data.....	12
3.4	Conducted Emission at Mains Terminal.....	14
3.5	Conducted Emission Configuration Photograph.....	14
3.6	Conducted Emission.....	15
<b>4.0</b>	<b><u>Equipment Photographs</u></b> .....	19
<b>5.0</b>	<b><u>Product Labelling</u></b> .....	21
<b>6.0</b>	<b><u>Technical Specifications</u></b> .....	23
<b>7.0</b>	<b><u>Instruction Manual</u></b> .....	25
<b>8.0</b>	<b><u>Miscellaneous Information</u></b> .....	27
<b>9.0</b>	<b><u>Test Equipment List</u></b> .....	31

## INTERTEK TESTING SERVICES

---

### List of attached file

Exhibit Type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated photos	radiated photos.pdf
Test Setup Photo	Conducted photos	conducted photos.pdf
External Photo	External Photos	external photos.pdf
Internal Photo	Internal Photos	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
ID Label / Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidential Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

# INTERTEK TESTING SERVICES

---

## EXHIBIT 1

### GENERAL DESCRIPTION

---

## INTERTEK TESTING SERVICES

---

### 1.0 General Description

#### 1.1 Product Description

The Equipment Under Test (EUT) is a LED TV. The device can be used to connect PC by HDMI port. The EUT is powered by AC 120V, 60Hz.

The EUT contains a module which can be operated in the frequency band of 2412MHz to 2462MHz in 802.11b, 802.11g and 802.11n-HT20 modes, 2422MHz to 2452MHz in 802.11n-HT40 mode, and 5180MHz to 5240MHz, 5745MHz to 5825MHz in 802.11a and 802.11n (20MHz, 40MHz, 80MHz) modes.

The Model: 43S401, 43S403, 43S407, 43S40\*, 43S405-MX, 43S401-MX, 43S403-MX, 43S407-MX, 43S40\*-MX ("\*"=any number, alphabet or character presents different appearance including color, silk-screen or decorative part.) are the same as the Model: 43S405 in hardware and electrical aspect. The models are difference in colour, silk-screen and decorative parts of appearance (only plastic component) and model number serves as marketing strategy only.

#### 1.2 Related Submittal(s) Grants

This is an application for certification of a computer peripheral. Other digital functions were reported in the verification report: 170221080GZU-002.

The host contains a WIFI module, which has been granted under the FCC ID: 2AC23-WC0HR2601.

---

## INTERTEK TESTING SERVICES

---

### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2014). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### 1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **EMTEK (Shenzhen) Co., Ltd.** and located at Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052, China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 406365).



**INTERTEK TESTING SERVICES**

---

**EXHIBIT 2**  
**SYSTEM TEST CONFIGURATION**

---

## INTERTEK TESTING SERVICES

---

### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2014).

The device was powered by AC 120V/60Hz during the test. The host device contains a WiFi module which was installed and operating during the test. Only the worst case data was reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. The step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit was flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

The frequency range from 30MHz to 29.125GHz was searched for spurious emissions from the device. Only those emissions reported were detected. All other emissions were at least 20 dB below the applicable limits.

#### 2.2 EUT Exercising Software

N/A

#### 2.3 Special Accessories

N/A

#### 2.4 Equipment Modification

Any modifications installed previous to testing by TTE Technology, Inc. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

---

## INTERTEK TESTING SERVICES

---

### 2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

### 2.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
Laptop	LENOVO	T420
Hard Disk	Smart.drive	HD-003
RJ45 Cable	N/A	Unshielded, Length 450cm
RJ45 Cable	N/A	Unshielded, Length 300cm
USB Cable	Smart.drive	Unshielded, Length 155cm
USB Memory	Kingston	DT SE9H 16GB
Dummy Load	N/A	N/A
HDMI Cable*3	N/A	UnShielded, Length 180cm
AV Cable	N/A	Unshielded, Length 120cm
Headphone	N/A	Unshielded, Length 120cm
Tuner Resister	N/A	75ohm
Remote controller	TCL	N/A

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 3**  
**EMISSION RESULTS**

## INTERTEK TESTING SERVICES

---

### 3.0 Emission Results

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

---

## INTERTEK TESTING SERVICES

---

### 3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG$$

where FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB/m

AG = Amplifier Gain in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG$$

## INTERTEK TESTING SERVICES

---

### 3.1 Field Strength Calculation (cont'd)

#### Example

Assume a receiver reading of 62.0dB $\mu$ V is obtained. The antenna factor of 7.4dB/m and cable factor of 1.6dB is added. The amplifier gain of 29dB is subtracted. The net field strength for comparison to the appropriate emission limit is 42dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 62.0\text{dB}\mu\text{V}$$

$$AF = 7.4\text{dB/m}$$

$$CF = 1.6\text{dB}$$

$$AG = 29.0\text{dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 = 42\text{dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(42\text{dB}\mu\text{V/m})/20] = 125.9\mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

### 3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission  
At  
946.140MHz (HDMI In (4K) Mode)

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.pdf.



## INTERTEK TESTING SERVICES

---

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 6.4dB margin (HDMI In (4K) Mode)

#### **TEST PERSONNEL:**

*Sign on file*

Jenner Liu, Project Engineer  
*Typed/Printed Name*

March 03, 2017  
*Date*

## INTERTEK TESTING SERVICES

---

Company: TTE Technology, Inc.  
Date of Test: March 03, 2017  
Model: 43S405  
Operating Mode: HDMI In (4K)

**Table 1**

**Radiated Emissions**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	332.640	36.5	20.0	16.5	33.0	46.0	-13.0
Horizontal	649.860	34.2	20.0	23.3	37.5	46.0	-8.5
Horizontal	946.140	31.9	20.0	27.7	39.6	46.0	-6.4
Horizontal	1750.000	28.1	20.0	27.8	35.9	54.0	-18.1
Horizontal	3002.000	20.0	20.0	31.1	31.1	54.0	-22.9
Horizontal	5999.000	18.6	20.0	36.2	34.8	54.0	-19.2
Horizontal	9500.000	20.5	20.0	37.0	37.5	54.0	-16.5
Horizontal	11998.000	18.6	20.0	42.1	40.7	54.0	-13.3
Vertical	37.760	39.7	20.0	13.8	33.5	40.0	-6.5
Vertical	630.430	34.2	20.0	23.9	38.1	46.0	-7.9
Vertical	891.360	33.5	20.0	26.1	39.6	46.0	-6.4
Vertical	1280.000	26.6	20.0	24.7	31.3	54.0	-22.7
Vertical	3700.000	19.9	20.0	32.1	32.0	54.0	-22.0
Vertical	7500.000	19.7	20.0	37.2	36.9	54.0	-17.1
Vertical	9501.000	20.8	20.0	37.0	37.8	54.0	-16.2
Vertical	11996.000	18.3	20.0	41.6	39.9	54.0	-14.1

**NOTES:**

1. Quasi-Peak detector is used for frequency up to 1GHz and Peak detector is used for frequency from 1GHz to 29.125GHz.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.
4. All emissions up to 1GHz are below the QP limit and all emissions between 1GHz to 29.125GHz are below the AV limit.

Test Engineer: Jenner Liu

---

TRF No.: FCC 15C\_PC\_b  
FCC ID: W8U43S405  
Report No.: 170221080GZU-001

## INTERTEK TESTING SERVICES

---

- 3.4 Conducted Emission at Mains Terminal
- 3.5 Conducted Emission Configuration Photograph

Worst Case Conducted Configuration  
at  
0.198 MHz(HDMI In Mode)

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

## INTERTEK TESTING SERVICES

---

### 3.6 Conducted Emission Data

Judgement: Passed by 8.3 dB margin(HDMI In Mode)

#### **TEST PERSONNEL:**

*Sign on file*

Jenner Liu, Project Engineer  
*Typed/Printed Name*

March 03, 2017  
*Date*

## INTERTEK TESTING SERVICES

---

Company: TTE Technology, Inc.


Date of Test: March 03, 2017

Model: 43S405

Operating Mode: HDMI In

Phase: Live

### Conducted Emission Test - FCC



#### Result Table QP

Frequency (MHz)	QuasiPeak (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.154	55.7	L1	9.6	10.1	65.8
0.198	54.1	L1	9.7	9.6	63.7
0.370	48.6	L1	9.7	9.9	58.5
0.614	43.4	L1	9.7	12.6	56.0
5.718	41.9	L1	9.8	18.1	60.0
21.566	39.9	L1	10.5	20.1	60.0

#### Result Table AV

Frequency (MHz)	Average (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.154	39.8	L1	9.6	16.0	55.8
0.198	44.7	L1	9.7	9.0	53.7
0.370	40.1	L1	9.7	8.4	48.5
0.614	32.1	L1	9.7	13.9	46.0
5.718	34.7	L1	9.8	15.3	50.0
21.566	36.2	L1	10.5	13.8	50.0

Test Engineer: Jenner Liu

---

TRF No.: FCC 15C\_PC\_b

FCC ID: W8U43S405

Report No.: 170221080GZU-001

## INTERTEK TESTING SERVICES

---

Company: TTE Technology, Inc.


Date of Test: March 03, 2017

Model: 43S405

Operating Mode: HDMI In

Phase: Neutral

### Conducted Emission Test - FCC



### Result Table QP

Frequency (MHz)	QuasiPeak (dB μV)	Line	Corr. (dB)	Margin (dB)	Limit (dB μV)
0.150	56.4	N	9.6	9.6	66.0
0.198	54.7	N	9.7	9.0	63.7
0.394	46.9	N	9.7	11.1	58.0
0.662	42.0	N	9.7	14.0	56.0
5.990	42.2	N	9.8	17.8	60.0
22.866	35.6	N	10.5	24.4	60.0

### Result Table AV

Frequency (MHz)	Average (dB μV)	Line	Corr. (dB)	Margin (dB)	Limit (dB μV)
0.150	40.4	N	9.6	15.6	56.0
0.198	45.4	N	9.7	8.3	53.7
0.394	36.3	N	9.7	11.7	48.0
0.662	31.6	N	9.7	14.4	46.0
5.990	35.4	N	9.8	14.6	50.0
22.866	30.6	N	10.5	19.4	50.0

Test Engineer: Jenner Liu

---

TRF No.: FCC 15C\_PC\_b

FCC ID: W8U43S405

Report No.: 170221080GZU-001

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 4**  
**EQUIPMENT PHOTOGRAPHS**

## INTERTEK TESTING SERVICES

---

### 4.0 Equipment Photographs

For electronic filing, photographs of the tested EUT are saved with filename: external photos.pdf and internal photos.pdf.



**INTERTEK TESTING SERVICES**

---

**EXHIBIT 5**  
**PRODUCT LABELLING**

## INTERTEK TESTING SERVICES

---

### 5.0 Product Labelling

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

---

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 6**

**TECHNICAL SPECIFICATIONS**

## INTERTEK TESTING SERVICES

---

### 6.0 Technical Specifications

For electronic filing, the block diagram of the tested EUT is saved with filename: block.pdf.

---

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 7**  
**INSTRUCTION MANUAL**

## INTERTEK TESTING SERVICES

---

### 7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold / leased in the United States.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 8**

**MISCELLANEOUS INFORMATION**

## INTERTEK TESTING SERVICES

---

### 8.0 Miscellaneous Information

This miscellaneous information includes emission measuring procedure.



---

## INTERTEK TESTING SERVICES

---

### 8.1 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of computer peripheral operating under Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 – 2014.

The computer peripheral equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The antenna height and polarization are varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions are in QP mode from the frequency band 30MHz to 1GHz with RBW setting 120kHz and in PK & AV mode from frequency band 1GHz to 29.125GHz with RBW setting 1MHz. Detector function for conducted emissions are in QP & AV mode and IFBW setting is 9kHz from the frequency band 150kHz to 30MHz.

For radiated emission, the frequency range scanned is 30MHz to 29.125GHz. For line-conducted emissions, the range scanned is 150kHz to 30MHz with RBW setting 9KHz.

## INTERTEK TESTING SERVICES

---

### 8.1 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

Conducted measurements are made as described in ANSI C63.4 – 2014.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 9**  
**TEST EQUIPMENT LIST**

## INTERTEK TESTING SERVICES

---

### 9.0 Test Equipment List

For Radiated Emission test

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
EE089	EMI Test Receiver	Rohde & Schwarz	ESU	1302.600 5.26	17-May-2016	17-May-2017
EE040	Pre-Amplifier	HP	8447F	2944A07 999	17-May-2016	17-May-2017
EE043	Bilog Antenna	Schwarzbeck	VULB916 3	142	17-May-2016	17-May-2017
EE147	Cable	Schwarzbeck	AK9513	ACRX1	17-May-2016	17-May-2017
EE169	Cable	Rosenberger	N/A	FP2RX2	17-May-2016	17-May-2017
EE168	Cable	Schwarzbeck	AK9513	CRPX1	29-May-2016	29-May-2017
EE170	Cable	Schwarzbeck	AK9513	CRRX2	29-May-2016	29-May-2017
EE096	Pre-Amplifier	A.H.	PAM- 0126	1415261	17-May-2016	17-May-2017
EE094	Horn Antenna	Schwarzbeck	BBHA 9120	707	29-May-2016	29-May-2017
EE097	Cable	H+B	0.5M SF104- 26.5	289147/4	29-May-2016	29-May-2017
EE100	Cable	H+B	3M SF104- 26.5	295838/4	29-May-2016	29-May-2017
EE101	Cable	H+B	6M SF104- 26.5	295840/4	29-May-2016	29-May-2017
EE095	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA917 0399	17-May-2016	17-May-2017
EE343	EMI Test Receiver	Rohde & Schwarz	FSV40	132.1- 3008K39- 100967- AP	29-May-2016	29-May-2017
EE240	Pre-Amplifier	Lunar EM	LNA26G4 0-40	J1013131 028001	17-May-2016	17-May-2017
EE234	Horn Antenna	AHS/USA	SAS-573	184	17-May-2016	17-May-2017
EE312	Cable	A.H	SAC- 40G-1	414	17-May-2016	17-May-2017
EE313	Cable	A.H	SAC- 40G-1	413	17-May-2016	17-May-2017

---

TRF No.: FCC 15C\_PC\_b  
 FCC ID: W8U43S405  
 Report No.: 170221080GZU-001

## INTERTEK TESTING SERVICES

---

### 9.0 Test Equipment List (cont'd)

For Conducted Emission test

<b>Equipment No.</b>	<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Date</b>	<b>Due Date</b>
EE144	Test Receiver	Rohde & Schwarz	ESCI	26115-010-0027	17-May-2016	17-May-2017
EE145	L.I.S.N.	Rohde & Schwarz	ENV216	101161	17-May-2016	17-May-2017
EE032	L.I.S.N.	ROHDE & SCHWARZ	ESH3-Z5	100191	17-May-2016	17-May-2017
EE041	50Ω Coaxial Switch	Anritsu	MP59B	6100175589	17-May-2016	17-May-2017
EE212	Voltage Probe	Rohde & Schwarz	ESH2-Z3	100122	17-May-2016	17-May-2017