



APPLICATION OF CERTIFICATION

For

TTE Technology Inc.

LCD TV

Brand Name	Model Number
TCL	LE50UHDE5691

FCC ID: W8U50E5691

Prepared for : TTE Technology Inc.  
555 S. Promenade Ave., Suite 103, Corona, CA 92879,  
U.S.A.

Prepared By: Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Fax: (0755) 26632877

Report Number : ACS- F13235-1

Date of Test : Jan.23, 2014

Date of Report : Feb.24, 2014

**TABLE OF CONTENTS**

<b>Description</b>	<b>Page</b>
<b>Test Report Certification</b>	
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>1-1</b>
1.1. Description of Standards and Results .....	1-1
<b>2. GENERAL INFORMATION.....</b>	<b>2-1</b>
2.1. Description of Device (EUT).....	2-1
2.2. Tested Supporting System Details .....	2-2
2.3. Block diagram of connection between the EUT and simulators.....	2-3
2.4. Test Facility .....	2-4
2.5. Measurement Uncertainty (95% confidence levels, k=2).....	2-4
<b>3. POWER LINE CONDUCTED EMISSION MEASUREMENT .....</b>	<b>3-1</b>
3.1. Test Equipment.....	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Power Line Conducted Emission Test Limits .....	3-1
3.4. Configuration of EUT on Test.....	3-1
3.5. Operating Condition of EUT .....	3-2
3.6. Test Procedure .....	3-2
3.7. Conducted Emission at Mains Terminals Test Results.....	3-2
<b>4. RADIATED EMISSION MEASUREMENT .....</b>	<b>4-1</b>
4.1. Test Equipment.....	4-1
4.2. Block Diagram of Test Setup.....	4-2
4.3. Radiated Emission Limit .....	4-3
4.4. EUT Configuration on Test .....	4-3
4.5. Operating Condition of EUT .....	4-3
4.6. Test Procedure .....	4-3
4.7. Radiated Emission Test Results.....	4-4
<b>5. DEVIATION TO TEST SPECIFICATIONS .....</b>	<b>5-1</b>
<b>6. PHOTOGRAPH .....</b>	<b>6-1</b>
6.1. Photos of Power Line Conducted Emission Test.....	6-1
6.2. Photos of Radiated Emission Test (In Anechoic Chamber) .....	6-2
<b>7. PHOTOS OF THE EUT .....</b>	<b>7-1</b>

### TEST REPORT CERTIFICATION

Applicant : TTE Technology Inc.  
 Manufacturer : TCL King Electrical Appliances (Huizhou) Co., Ltd.  
 EUT Description : LCD TV  
 FCC ID : W8U50E5691

(A) Model No. & :	Brand Name	Model Number
	TCL	LE50UHDE5691

(B) Power Supply : AC 120V/60Hz  
 (C) Test Voltage : AC 120V/60Hz

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart B Class B 2012

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B Class B limits both conducted and radiated emissions. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed of full responsibility for the accuracy and completeness of these tests. This report contains data that are not covered by the NVLAP accreditation.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Jan.23, 2014 Report of date: Feb.24, 2014

Prepared by : Julia Zhu Reviewed by : Sun Zeng  
 Julia Zhu / Assistant Sun Zeng / Assistant Manager

信華科技 (深圳) 有限公司  
 Audix Technology (Shenzhen) Co., Ltd.  
 EMC 部門報告專用章  

Stamp only for EMC Dept. Report

Signature: David Jin z-zf

Approved & Authorized Signer: David Jin  
 David Jin / Manager

### Modified History

Rev.	Summary	Date of Rev.	Report No.
A1.0	Original Report.	Aug.21, 2013	ACS-F13235
A1.1	Change the screen	Feb.24, 2014	ACS-F13235-1

1. This report is an additional version with original report number ACS-F13235. the different with original report are See the above table of REV.1.
2. Through evaluation of the above difference, the conducted and radiated emission tests needed to be re-performed. The EUT was retested and all the test data were recorded in this report.
3. This report is based on report of ACS- F13235.

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Results	Remarks
Power Line Conducted Emission Test	FCC Part 15: 2012 ANSI C63.4: 2009	PASS	Meets Class B Limit Minimum passing margin is 20.65dB at 1.197MHz
Radiated Emission Test (30-1000MHz)	FCC Part 15: 2012 ANSI C63.4: 2009	PASS	Meets Class B Limit Minimum passing margin is 4.15dB at 742.950MHz
Radiated Emission Test (1-8GHz)	FCC Part 15: 2012 ANSI C63.4: 2009	PASS	Meets Class B Limit Minimum passing margin is 13.63dB at 1854.225MHz

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Description : LCD TV

Model Number& : Brand Name	Brand Name TCL	Model Number LE50UHDE5691
-------------------------------	-------------------	------------------------------

FCC ID : W8U50E5691

Applicant : TTE Technology Inc.  
555 S. Promenade Ave., Suite 103, Corona, CA 92879,  
U.S.A.

Manufacturer : TCL King Electrical Appliances (Huizhou) Co., Ltd.  
Section 19, Zhongkai Development Zone for New & High-Level  
Tech Industries, Huizhou, Guangdong Province, China, 516006.

FREQUENCIES USED AND GENERATED WITHIN DEVICE		
LVDS (HD)	78MHZ	
LVDS (FHD)	75MHZ	
IF	6MHz	
DC-DC	U302->385KHz	
DDR2	390	
DDR3	1600	

Power Cord : Unshielded, Detachable, 1.8m

Date of Test : Jan.23, 2014


Date of Receipt : Jan.22, 2014

Sample Type : Prototype production

2.2. Tested Supporting System Details

	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
1.	Personal Computer	Test PC S	DELL	Vostro 470	2SP05W1	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID:R33002
		Power Cord: Unshielded, Detachable, 1.8m Display Card: HD3450 (DVI+VGA+HDMI)				
2.	USB Keyboard	ACS-EMC- K04R	DELL	SK-8115	CN-ODJ313-7161 6-6BB-049J	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: T3A002
		Data Cable: shielded, Undetachable, 2.0m				
3.	Headphone	ACS-EMC-EP03	OVANN	OV880V	N/A	<input type="checkbox"/> FCC ID <input type="checkbox"/> BSMI ID
		Cable: Shielded, Undetachabled, 4.0m				
4.	Printer	ACS-EMC-PT04	HP	C9079A	N/A	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R33001
		USB Cable: Shielded, Detachabled, 1.8m Power Cord: Unshielded, Detachabled, 1.8m Power Adapter: HP, M/N: 0957-2119, BSMI ID: R33030, DC Cable: Unshielded, Detachabled, 1.5m				
5.	USB Mouse	ACS-EMC-M04R	DELL	M056UO	512024282	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R41108
		Data Cable: shielded, Undetachable, 1.8m				
6.	iPod nano	ACS-EMC-IP01	APPLE	A1199	YM706MLDVQ5	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R33057
		Data Cable: Shielded, Detachabled, 1.0m				
7.	HDD	ACS-EMC-HDD03	Terasys	F12-UF	A0100215-53900 30	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: 4912A022
		USB Cable: Shielded, Detachable, 1.8m				
8.	Dummy Load (10KΩ & 75Ω)	Component In Cable: Unshielded, Detachabled, 1.8m SPDIF Cable: Unshielded, Detachable, 1.5m (R+L)Audio Cable: Unshielded, Detachable, 1.5m				
9.	D-Sub Cable: Shielded, Detachable, 1.5m HDMI Cable: Shielded, Detachable, 1.5m					

2.3. Block diagram of connection between the EUT and simulators



(EUT: LCD TV)



## 2.4. Test Facility

### Site Description

- Name of Firm : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen, Guangdong, China
- 3m Anechoic Chamber : Certificated by FCC, USA  
Registration Number: 90454  
Valid Date: Feb.22, 2015
- 3m & 10m Anechoic Chamber : Certificated by FCC, USA  
Registration Number: 794232  
Valid Date: Oct.31, 2015
- EMC Lab. : Certificated by DAkkS, Germany  
Registration No: D-PL-12151-01-00  
Valid Date: Dec.15, 2016
- Accredited by NVLAP, USA  
NVLAP Code: 200372-0  
Valid Date: Mar.31, 2014

## 2.5. Measurement Uncertainty (95% confidence levels, k=2)


Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.1dB(150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	3.22dB(30~200MHz, Polarize: H)
	3.23dB(30~200MHz, Polarize: V)
	3.49dB(200M~1GHz, Polarize: H)
	3.39dB(200M~1GHz, Polarize: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	4.97dB(1~6GHz, Distance: 3m)
	4.99dB(6~18GHz, Distance: 3m)
Uncertainty for test site temperature and humidity	3%
	0.6°C

### 3. POWER LINE CONDUCTED EMISSION MEASUREMENT

#### 3.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Apr.18,13	1 Year
2.	Test Receiver	Rohde & Schwarz	ESHS10	838693/001	Oct.31, 13	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	834066/011	Oct.31, 13	1 Year
4.	L.I.S.N.#3	Kyoritsu	KNW-242C	8-1920-1	May.08, 13	1 Year
5.	Terminator	Hubersuhner	50Ω	No. 1	May.08, 13	1 Year
6.	Terminator	Hubersuhner	50Ω	No. 2	May.08, 13	1 Year
7.	RF Cable	Fujikura	3D-2W	No.1	May.08, 13	1Year
8.	Coaxial Switch	Anritsu	MP59B	M50564	May.08, 13	1 Year
9.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100341	May.08, 13	1 Year
10.	MPEG2 Measurement Generator	ROHDE&SCHWARZ	DVG	100319	Dec.11, 13	1 Year
11.	TV Transmitter	ROHDE&SCHWARZ	SFQ	100521	May.08, 13	1 Year
12.	Signal Generator	HP	8648A	3625U00573	May.08, 13	1 Year
13.	Pattern Generator	Philips	PM5418	LO625020	May.08, 13	1 Year

#### 3.2. Block Diagram of Test Setup



#### 3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

- Notes: 1. \* Decreasing linearly with logarithm of frequency.  
 2. The lower limit shall apply at the transition frequencies.

#### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1.LCD TV (EUT)

Model Number : LE50UHDE5691  
 Serial Number : N/A

3.4.2.Support Equipment : As Tested Supporting System Detail, in Section 2.2.

3.5.Operating Condition of EUT

3.5.1.Setup the EUT and simulator as shown as Section 3.2.

3.5.2.Turn on the power of all equipment.

3.5.3.PC system ran the Self-test program “EMC Test. exe” by windows XP and sent “H” Character to LCD TV (EUT) , the Screen of EUT displayed and filled with “H” pattern, use white letters on a black ground, set the contrast control to maximum, set the brightness control to maximum and measure it.

3.5.4.The other peripheral devices were driven and operated in turn during all testing.

3.6.Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1# ). This provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.# 3). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4: 2009 on conducted Emission test.

The bandwidth of test receiver (R&S TEST RECEIVER ESHS10) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked. The test result are reported on Section 3.7.

3.7.Conducted Emission at Mains Terminals Test Results

**PASS.** (All emissions not reported below are too low against the prescribed limits.)

The EUT with the following test modes were tested and selected to read Q.P values and average values, all the test results are listed in next pages.


EUT: LCD TV Model No. : LE50UHDE5691

Test Date: Jan.23, 2014 Temperature: 26.9°C Humidity: 40%

The details of test modes are as follows :

No.	Test Mode	Input Port	Resolution & Frequency	Reference Test Data No.	
				Line	Neutral
1. ※	PC Mode	VGA	1920*1080@60Hz	# 14	# 13
2.		HDMI 1	1920*1080@60Hz	# 16	# 15
3.		<b>HDMI 4</b>	<b>1920*1080@60Hz</b>	<b># 18</b>	<b># 17</b>

(※ Worst test mode)




Trace: (Discrete)

Site no :1#conduction Data No :14  
 Dis./Ant. \*\*: 2013 ESH2-25 LINE  
 Limit :FCC PART 15 B  
 Env./Ins. :26.9°C/40% Engineer :Alan\_Chen  
 EUT :LCD TV M/N:LE50UHDE5691  
 Power Rating :AC 120V/60Hz  
 Test Mode :Running "H" Pattern And 1KHz Playing  
 VGA:1920\*1080@60Hz

No	Freq (MHz)	ISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.18152	0.15	0.01	34.24	34.40	64.42	30.02	QP
2	1.005	0.18	0.03	30.82	31.03	56.00	24.97	QP
3	1.160	0.19	0.03	29.98	30.20	56.00	25.80	QP
4	1.367	0.19	0.03	30.07	30.29	56.00	25.71	QP
5	1.577	0.20	0.04	30.68	30.92	56.00	25.08	QP
6	1.744	0.21	0.04	30.70	30.95	56.00	25.05	QP

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :13  
 Dis./Ant. \*\*: 2013 ESH2-25 NEUTRAL  
 Limit :FCC PART 15 B  
 Env./Ins. :26.9\*C/40% Engineer :Alan\_Chen  
 EUT :LCD TV M/N:LE50UHDE5691  
 Power Rating :AC 120V/60Hz  
 Test Mode :Running "H" Pattern And 1KHz Playing  
 VGA:1920\*1080@60Hz

No	Freq (MHz)	ISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.18152	0.18	0.01	35.22	35.41	64.42	29.01	QP
2	0.82608	0.27	0.03	33.84	34.14	56.00	21.86	QP
3	1.005	0.26	0.03	34.14	34.43	56.00	21.57	QP
4	1.197	0.26	0.03	35.06	35.35	56.00	20.65	QP
5	1.374	0.26	0.03	34.36	34.65	56.00	21.35	QP
6	1.535	0.26	0.04	34.66	34.96	56.00	21.04	QP

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :16  
 Dis./Ant. \*\*: 2013 ESH2-25 LINE  
 Limit :FCC PART 15 B  
 Env./Ins. :26.9\*C/40% Engineer :Alan\_Chen  
 EUT :LCD TV M/N:LE50UHDE5691  
 Power Rating :AC 120V/60Hz  
 Test Mode :Running "H" Pattern And 1KHz Playing  
 HDMI 1:1920\*1080@60Hz

No	Freq (MHz)	ISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.18152	0.15	0.01	38.16	38.32	64.42	26.10	QP
2	0.64058	0.17	0.02	28.56	28.75	56.00	27.25	QP
3	0.81737	0.17	0.03	30.14	30.34	56.00	25.66	QP
4	1.197	0.19	0.03	29.76	29.98	56.00	26.02	QP
5	1.577	0.20	0.04	30.66	30.90	56.00	25.10	QP
6	2.309	0.23	0.04	29.56	29.83	56.00	26.17	QP

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Trace: (Discrete)

Site no :1#conduction Data No :15

Dis./Ant. \*\*: 2013 ESH2-25 NEUTRAL

Limit :FCC PART 15 B

Env./Ins. :26.9\*C/40% Engineer :Alan\_Chen

EUT :LCD TV M/N:LE50UHDE5691


Power Rating :AC 120V/60Hz

Test Mode :Running "H" Pattern And 1KHz Playing

HDMI 1:1920\*1080@60Hz

No	Freq (MHz)	ISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.18152	0.18	0.01	38.54	38.73	64.42	25.69	QP
2	0.64398	0.26	0.02	32.28	32.56	56.00	23.44	QP
3	0.82608	0.27	0.03	33.18	33.48	56.00	22.52	QP
4	1.197	0.26	0.03	33.26	33.55	56.00	22.45	QP
5	1.577	0.26	0.04	33.84	34.14	56.00	21.86	QP
6	2.285	0.27	0.04	32.68	32.99	56.00	23.01	QP

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :18  
 Dis./Ant. \*\*: 2013 ESH2-25 LINE  
 Limit :FCC PART 15 B  
 Env./Ins. :26.9\*C/40% Engineer :Alan\_Chen  
 EUT :LCD TV M/N:LE50UHDE5691  
 Power Rating :AC 120V/60Hz  
 Test Mode :Running "H" Pattern And 1KHz Playing  
 HDMI 4:1920\*1080@60Hz

No	Freq (MHz)	ISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.18152	0.15	0.01	37.14	37.30	64.42	27.12	QP
2	0.81737	0.17	0.03	30.44	30.64	56.00	25.36	QP
3	1.005	0.18	0.03	31.24	31.45	56.00	24.55	QP
4	1.160	0.19	0.03	30.06	30.28	56.00	25.72	QP
5	1.374	0.19	0.03	31.05	31.27	56.00	24.73	QP
6	1.527	0.20	0.04	30.40	30.64	56.00	25.36	QP

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.





Trace: (Discrete)

Site no :1#conduction Data No :17  
 Dis./Ant. \*\*: 2013 ESH2-25 NEUTRAL  
 Limit :FCC PART 15 B  
 Env./Ins. :26.9\*C/40% Engineer :Alan\_Chen  
 EUT :LCD TV M/N:LE50UHDE5691  
 Power Rating :AC 120V/60Hz  
 Test Mode :Running "H" Pattern And 1KHz Playing  
 HDMI 4:1920\*1080@60Hz

No	Freq (MHz)	ISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.18152	0.18	0.01	36.08	36.27	64.42	28.15	QP
2	0.64398	0.26	0.02	32.18	32.46	56.00	23.54	QP
3	0.83047	0.27	0.03	33.16	33.46	56.00	22.54	QP
4	1.016	0.26	0.03	33.10	33.39	56.00	22.61	QP
5	1.197	0.26	0.03	33.78	34.07	56.00	21.93	QP
6	1.388	0.26	0.03	32.38	32.67	56.00	23.33	QP

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

## 4. RADIATED EMISSION MEASUREMENT

### 4.1. Test Equipment

#### 4.1.1. For frequency range 30MHz~1000MHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.24, 13	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 13	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 13	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 13	1 Year
5	Bilog Antenna	TESEQ	CBL6112D	35375	May.30, 13	1 Year
6	RF Cable	MIYAZAKI	CFD400-NL	3# Chamber No.1	May.08, 13	1 Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 13	1 Year
8	MPEG2 Measurement Generator	ROHDE&SCHWARZ	DVG	100319	Dec.11, 13	1 Year
9	TV Transmitter	ROHDE&SCHWARZ	SFQ	100521	May.08, 13	1 Year
10	Signal Generator	HP	8648A	3625U00573	May.08, 13	1 Year
11	Pattern Generator	Philips	PM5418	LO625020	May.08, 13	1 Year

#### 4.1.2. For frequency range 1GHz~8GHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	EMC Analyzer	Agilent	E7405A	MY45116588	Oct.31, 13	1 Year
2.	Horn Antenna	EMCO	3115	9607-4877	Aug.27, 13	1 Year
3.	Amplifier	Agilent	8449B	3008A00863	May.08, 13	1 Year
4.	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	May.08, 13	1 Year
5.	RF Cable	Hubersuhner	SUCOFLEX106	28616/2	May.08, 13	1 Year
6.	EMC Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year

### 4.2. Block Diagram of Test Setup

#### 4.2.1. For frequency range 30MHz-1000MHz



#### 4.2.2. For frequency range 1GHz-8GHz



### 4.3. Radiated Emission Limit

Frequency MHz	Distance (Meters)	Field Strengths Limits dB(μV)/m
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
960 ~ 1000	3	54.0
Above 1000	3	74(Peak)54(Average)

- Remark: (1) Emission level = Antenna Factor + Cable Loss + Reading  
Emission level = Antenna Factor - Amp Factor + Cable Loss + Reading  
(above 1000MHz)
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

### 4.4. EUT Configuration on Test

The configurations of EUT are listed in Section 3.4

### 4.5. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.5. except the test set up replaced by Section 4.2.

### 4.6. Test Procedure

The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4: 2009 on Radiated Emission test.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz.

4.7. Radiated Emission Test Results

**PASS.** (All emissions not reported below are too low against the prescribed limits.)

EUT: LCD TV Model No. : LE50UHDE5691

**For frequency range 30MHz~1000MHz**

The EUT with the following test modes were tested and selected to read Q.P values, all the test results are listed in next pages.

Test Date: Jan.23, 2014 Temperature: 25.7°C Humidity: 52%

The details of test modes are as follows :

No.	Test Mode	Input Port	Resolution & Frequency	Reference Test Data No.	
				Horizontal	Vertical
1.	PC Mode	VGA	1920*1080@60Hz	# 17	# 18
2. ※		HDMI 1	<b>1920*1080@60Hz</b>	<b># 16</b>	<b># 15</b>
3.		HDMI 4	1920*1080@60Hz	# 13	# 14

(※ Worst test mode)

**For frequency range 1GHz~8GHz**

The EUT with below test mode were measured within Anechoic Chamber and the test results listed in next pages


Note: For all the emissions above 1GHz, the peak measured level comply with peak limit, so the average level were deemed to comply with average limit.

Test Date: Jan.23, 2014 Temperature: 26.7°C Humidity: 49%

NO.	Test Mode	Resolution & Frequency	Reference Test Data No.	
			Horizontal	Vertical
1. ※	VGA	<b>1920*1080 @60Hz</b>	<b># 23</b>	<b># 24</b>
2.	HDMI 1	1920*1080 @60Hz	# 20	# 19
3.	HDMI 4	1920*1080 @60Hz	# 21	# 22

(※ Worst test mode)


30MHz~1000MHz



Site no. : 3m Chamber Data no. : 17  
 Dis. / Ant. : 3m 2013 CBL6111C 35375 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B (3M)  
 Env. / Ins. : 25.7°C/52% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power rating : AC 120V/60Hz  
 Test Mode : Running "H" Pattern And 1KHz Playing  
 VGA:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	160.950	11.20	1.64	21.27	34.11	43.50	9.39	QP
2	180.350	9.38	1.72	24.81	35.91	43.50	7.59	QP
3	193.930	9.50	1.77	21.28	32.55	43.50	10.95	QP
4	426.730	17.17	2.54	13.77	33.48	46.00	12.52	QP
5	701.240	20.90	3.33	7.98	32.21	46.00	13.79	QP
6	747.800	22.00	3.46	7.23	32.69	46.00	13.31	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 18  
 Dis. / Ant. : 3m 2013 CBL6111C 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B (3M)  
 Env. / Ins. : 25.7°C/52% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power rating : AC 120V/60Hz  
 Test Mode : Running "H" Pattern And 1KHz Playing  
 VGA:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	31.940	18.93	0.86	10.76	30.55	40.00	9.45	QP
2	40.670	13.77	1.02	15.01	29.80	40.00	10.20	QP
3	95.960	9.69	1.39	19.77	30.85	43.50	12.65	QP
4	180.350	9.38	1.72	22.72	33.82	43.50	9.68	QP
5	214.300	10.01	1.84	19.94	31.79	43.50	11.71	QP
6	485.900	17.92	2.71	14.15	34.78	46.00	11.22	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 16  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B (3M)  
 Env. / Ins. : 26.7°C/49% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power rating : AC 120V/60Hz  
 Test Mode : Running "H" Pattern And 1kHz Playing  
 HDMI1:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	224.000	10.80	1.88	20.84	33.52	46.00	12.48	QP
2	371.440	15.73	2.38	18.79	36.90	46.00	9.10	QP
3	558.650	18.80	2.92	16.28	38.00	46.00	8.00	QP
4	743.920	20.30	3.45	12.58	36.33	46.00	9.67	QP
5	864.200	21.48	3.81	9.99	35.28	46.00	10.72	QP
6	930.160	21.80	4.02	10.63	36.45	46.00	9.55	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 15  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B (3M)  
 Env. / Ins. : 26.7°C/49% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power rating : AC 120V/60Hz  
 Test Mode : Running "H" Pattern And 1kHz Playing  
 HDMI1:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	289.960	13.80	2.13	18.05	33.98	46.00	12.02	QP
2	408.300	17.03	2.48	15.55	35.06	46.00	10.94	QP
3	558.650	18.80	2.92	16.74	38.46	46.00	7.54	QP
4	597.450	19.15	3.03	14.56	36.74	46.00	9.26	QP
5	742.950	20.30	3.45	18.10	41.85	46.00	4.15	QP
6	930.160	21.80	4.02	13.19	39.01	46.00	6.99	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 13  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B (3M)  
 Env. / Ins. : 26.7°C/49% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power rating : AC 120V/60Hz  
 Test Mode : Running "H" Pattern And 1kHz Playing  
 HDMI4:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	65.260	6.60	1.26	23.20	31.06	40.00	8.94	QP
2	303.540	14.07	2.18	18.23	34.48	46.00	11.52	QP
3	371.290	15.73	2.38	18.99	37.10	46.00	8.90	QP
4	427.700	17.19	2.54	15.17	34.90	46.00	11.10	QP
5	556.800	18.80	2.91	18.30	40.01	46.00	5.99	QP
6	742.950	20.30	3.45	16.84	40.59	46.00	5.41	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 14  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B (3M)  
 Env. / Ins. : 26.7°C/49% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power rating : AC 120V/60Hz  
 Test Mode : Running "H" Pattern And 1kHz Playing  
 HDMI4:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	192.960	9.75	1.76	20.00	31.51	43.50	11.99	QP
2	289.960	13.80	2.13	19.77	35.70	46.00	10.30	QP
3	303.540	14.07	2.18	18.97	35.22	46.00	10.78	QP
4	558.650	18.80	2.92	15.25	36.97	46.00	9.03	QP
5	594.540	19.09	3.02	14.56	36.67	46.00	9.33	QP
6	742.950	20.30	3.45	17.40	41.15	46.00	4.85	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.


1~8GHz



Site no. : 10m chamber (RF) Data no. : 23  
 Dis. / Ant. : 3m 2012 3115 (4877) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B PEAK  
 Env. / Ins. : 22.5°C/38% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power Rating : AC 120V/60Hz  
 Test Mode : Running "H"Pattern And 1KHz Playing  
 VGA:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1196.000	23.49	1.61	33.99	59.61	50.72	74.00	23.28	Peak
2	1196.325	23.49	1.61	33.99	48.70	39.81	54.00	14.19	Average
3	1490.000	24.08	1.85	33.57	57.90	50.26	74.00	23.74	Peak
4	1490.185	24.08	1.85	33.57	45.94	38.30	54.00	15.70	Average
5	2393.000	23.81	2.77	33.40	57.01	50.19	74.00	23.81	Peak
6	2393.185	23.81	2.77	33.40	45.07	38.25	54.00	15.75	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m chamber (RF) Data no. : 24  
 Dis. / Ant. : 3m 2012 3115 (4877) Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B PEAK  
 Env. / Ins. : 22.5°C/38% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power Rating : AC 120V/60Hz  
 Test Mode : Running "H"Pattern And 1KHz Playing  
 VGA:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1182.000	23.46	1.60	34.01	60.05	51.10	74.00	22.90	Peak
2	1182.225	23.46	1.60	34.00	47.08	38.14	54.00	15.86	Average
3	1490.000	24.08	1.85	33.57	57.59	49.95	74.00	24.05	Peak
4	1490.114	24.08	1.85	33.57	46.57	38.93	54.00	15.07	Average
5	1854.000	24.17	2.26	33.40	57.38	50.41	74.00	23.59	Peak
6	1854.225	24.17	2.26	33.40	47.34	40.37	54.00	13.63	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m chamber (RF) Data no. : 20  
 Dis. / Ant. : 3m 2012 3115 (4877) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B PEAK  
 Env. / Ins. : 22.5°C/38% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power Rating : AC 120V/60Hz  
 Test Mode : Running "H"Pattern And 1KHz Playing  
 HDMI 1:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1119.000	23.34	1.55	34.09	58.38	49.18	74.00	24.82	Peak
2	1119.325	23.34	1.55	34.09	48.38	39.18	54.00	14.82	Average
3	1504.000	24.10	1.86	33.56	57.33	49.73	74.00	24.27	Peak
4	1504.158	24.10	1.86	33.56	44.40	36.80	54.00	17.20	Average
5	1784.000	24.16	2.18	33.43	57.23	50.14	74.00	23.86	Peak
6	1784.187	24.16	2.18	33.43	46.29	39.20	54.00	14.80	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m chamber (RF) Data no. : 19  
 Dis. / Ant. : 3m 2012 3115 (4877) Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B PEAK  
 Env. / Ins. : 22.5°C/38% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power Rating : AC 120V/60Hz  
 Test Mode : Running "H"Pattern And 1KHz Playing  
 HDMI 1:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1196.000	23.49	1.61	33.99	58.80	49.91	74.00	24.09	Peak
2	1196.339	23.49	1.61	33.99	48.73	39.84	54.00	14.16	Average
3	1700.000	24.14	2.09	33.47	58.03	50.79	74.00	23.21	Peak
4	1700.315	24.14	2.09	33.47	46.08	38.84	54.00	15.16	Average
5	1994.000	24.20	2.42	33.33	57.77	51.06	74.00	22.94	Peak
6	1994.158	24.20	2.42	33.33	46.79	40.08	54.00	13.92	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 10m chamber (RF) Data no. : 21  
 Dis. / Ant. : 3m 2012 3115 (4877) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B PEAK  
 Env. / Ins. : 22.5°C/38% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power Rating : AC 120V/60Hz  
 Test Mode : Running "H"Pattern And 1KHz Playing  
 HDMI 4:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1133.000	23.37	1.56	34.07	58.85	49.71	74.00	24.29	Peak
2	1133.268	23.37	1.56	34.07	47.86	38.72	54.00	15.28	Average
3	1336.000	23.77	1.73	33.79	58.70	50.41	74.00	23.59	Peak
4	1336.315	23.77	1.73	33.79	46.68	38.39	54.00	15.61	Average
5	2015.000	24.19	2.44	33.33	57.28	50.58	74.00	23.42	Peak
6	2015.258	24.18	2.44	33.33	45.25	38.54	54.00	15.46	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 10m chamber (RF) Data no. : 22  
 Dis. / Ant. : 3m 2012 3115 (4877) Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B PEAK  
 Env. / Ins. : 22.5°C/38% Engineer : Even\_Deng  
 EUT : LCD TV M/N:LE50UHDE5691  
 Power Rating : AC 120V/60Hz  
 Test Mode : Running "H"Pattern And 1KHz Playing  
 HDMI 4:1920\*1080@60Hz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1175.000	23.45	1.59	34.01	58.37	49.40	74.00	24.60	Peak
2	1175.175	23.45	1.59	34.01	47.35	38.38	54.00	15.62	Average
3	1490.000	24.08	1.85	33.57	57.88	50.24	74.00	23.76	Peak
4	1490.147	24.08	1.85	33.57	45.86	38.22	54.00	15.78	Average
5	2764.000	25.02	2.95	33.38	55.64	50.23	74.00	23.77	Peak
6	2764.288	25.02	2.95	33.38	41.63	36.22	54.00	17.78	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

## 5. DEVIATION TO TEST SPECIFICATIONS

[NONE]