



APPLICATION OF CERTIFICATION

For

TTE Technology Inc.

LCD TV

Brand Name	Model Number
TCL	LE32HDE3000; LE32HDE3011 LE32HDE5311; LE32HDF3310TA LE32HDF3311; LE32HDF3312

FCC ID: W8ULE32HDE3000

Prepared for : TTE Technology Inc.
1255 Graphite Drive, Corona, CA 92881, U.S.A.

Prepared By: Audix Technology (Shenzhen) Co., Ltd.
No. 6, Ke Feng Rd., 52 Block,
Shenzhen Science & Industrial Park,
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496
Fax: (0755) 26632877

Report Number : ACS- F13012
Date of Test : Jan.07, 2013
Date of Report : Feb.05, 2013

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. SUMMARY OF STANDARDS AND RESULTS	1-1
1.1. Description of Standards and Results	1-1
2. GENERAL INFORMATION.....	2-1
2.1. Description of Device (EUT).....	2-1
2.2. Tested Supporting System Details	2-2
2.3. Block diagram of connection between the EUT and simulators.....	2-3
2.4. Test Facility	2-4
2.5. Measurement Uncertainty (95% confidence levels, k=2).....	2-4
3. POWER LINE CONDUCTED EMISSION TEST	3-1
3.1. Test Equipment.....	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Power Line Conducted Emission Test Limits	3-1
3.4. Configuration of EUT on Test.....	3-1
3.5. Operating Condition of EUT	3-2
3.6. Test Procedure	3-2
3.7. Conducted Disturbance at Mains Terminals Test Results	3-2
4. RADIATED EMISSION TEST.....	4-1
4.1. Test Equipment.....	4-1
4.2. Block Diagram of Test Setup.....	4-1
4.3. Radiated Emission Limit	4-2
4.4. EUT Configuration on Test	4-2
4.5. Operating Condition of EUT	4-2
4.6. Test Procedure	4-3
4.7. Radiated Disturbance Test Results	4-3
5. DEVIATION TO TEST SPECIFICATIONS	5-1
6. PHOTOGRAPH	6-1
6.1. Photos of Power Line Conducted Emission Test.....	6-1
6.2. Photos of Radiated Emission Test (In Anechoic Chamber)	6-2
7. PHOTOS OF THE EUT	7-1

TEST REPORT CERTIFICATION

Applicant : TTE Technology Inc.
 Manufacturer : TCL King Electrical Appliances (Huizhou) Co., Ltd.
 EUT Description : LCD TV
 FCC ID : W8ULE32HDE3000

(A) Model No. & Brand Name :	Brand Name	Model Number
	TCL	LE32HDE3000; LE32HDE3011 LE32HDE5311; LE32HDF3310TA LE32HDF3311; LE32HDF3312

(B) Power Supply : AC 120V/60Hz
 (C) Test Voltage : AC 120V/60Hz

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart B Class B 2011, ANSI C63.4: 2009 ICES-003 Issue 4 February 2004.

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B Class B limits both conducted and radiated emissions. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed of full responsibility for the accuracy and completeness of these tests. This report contains data that are not covered by the NVLAP accreditation.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Jan.07, 2013 Report of date: Feb.05, 2013

Prepared by : June shao Reviewed by : Sun Zeng
June Shao/ Assistant Sun Zeng / Supervisor

信華科技 (深圳) 有限公司
 Audix Technology (Shenzhen) Co., Ltd.
 EMC 部門報告專用章
 Stamp only for EMC Dept. Report
 Signature: Ken Lu

Approved & Authorized Signer : Ken Lu
Ken Lu / Manager

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Results	Remarks
Power Line Conducted Emission Test	FCC Part 15: 2011 ANSI C63.4: 2009	PASS	Meets Class B Limit Minimum passing margin is 14.37dB at 1.178MHz
Radiated Emission Test (30-1000MHz)	FCC Part 15: 2011 ANSI C63.4: 2009	PASS	Meets Class B Limit Minimum passing margin is 1.04dB at 328.000MHz
Radiated Emission Test (1-2GHz)	FCC Part 15: 2011 ANSI C63.4: 2009	PASS	Meets Class B Limit Minimum passing margin is 6.52dB at 1995.845MHz

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description : LCD TV

Model Number& Brand Name	Brand Name	Model Number
	TCL	LE32HDE3000; LE32HDE3011 LE32HDE5311; LE32HDF3310TA LE32HDF3311; LE32HDF3312

Only the Model name ,appearance color and shell is different

FCC ID : W8ULE32HDE3000

Applicant : TTE Technology Inc.
1255 Graphite Drive, Corona, CA 92881, U.S.A.

Manufacturer : TCL King Electrical Appliances (Huizhou) Co., Ltd.
Section 19, Zhongkai Development Zone for New and
High-Level Tech Industries, Huizhou, Guangdong Province,
China, 516006.

FREQUENCIES USED AND GENERATED WITHIN DEVICE		
X54M1	45-OSC54M-0Y1CR	54MHz
LVDS CLOCK	81.43MHZ	
IF	6MHz	
DC-DC	U302->385KHz	U303->1MHz
DDR	390MHz	
AMP	384KHz	

Power Cord : Unshielded, Undetachable, 2.0m

Date of Test : Jan.07, 2013


Date of Receipt : Jan.04, 2013

Sample Type : Prototype production

2.2. Tested Supporting System Details

	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
1.	Personal Computer	Test PC M	DELL	Studio 540	224XK2X	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID:R33002
Power Cord: Unshielded, Detachable, 1.8m Display Card: HD3450 (DVI+VGA+HDMI)						
2.	USB Keyboard	ACS-EMC- K04R	DELL	SK-8115	CN-ODJ313-7161 6-6BB-049J	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: T3A002
Power Cord: shielded, Undetachable, 2.0m						
3.	Headphone	ACS-EMC-EP03	OVANN	OV880V	N/A	<input type="checkbox"/> FCC ID <input type="checkbox"/> BSMI ID
Cable: Shielded, Undetachable, 4.0m						
4.	Printer	ACS-EMC-PT04	HP	C9079A	N/A	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R33001
USB Cable: Shielded, Detachable, 1.8m Power Cord: Unshielded, Detachable, 1.8m Power Adapter: HP, M/N: 0957-2119, BSMI ID: R33030, DC Cable: Unshielded, Detachable, 1.5m						
5.	USB Mouse	ACS-EMC-M04R	DELL	M056UO	512024282	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R41108
Power Cord: shielded, Undetachable, 1.8m						
6.	iPod nano	ACS-EMC-IP03	APPLE	A1199	YM711H3LVQ5	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R33057
Data Cable: Shielded, Detachable, 1.0m						
7.	HDD	ACS-EMC-HDD03	Terasys	F12-UF	A0100215-53900 30	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: 4912A022
USB Cable: Shielded, Detachable, 1.8m						
8.	ATV SG	-	Philips	PM5418M	N/A	N/A
9.	DTV SG	-	R&S	SFQ&DVG	N/A	N/A
10.	TCL TV	ACS-EMC-TV01T	TCL	14149A	N/A	N/A
11.	TCL TV	ACS-EMC-TV02T	TCL	22HR5434	N/A	N/A
12.	Dummy Load (10KΩ & 75Ω)	Component In Cable: Unshielded, Detachable, 1.5m AV Cable: Unshielded, Detachable, 1.5m Coaxial Cable: Unshielded, Detachable, 1.5m				
13.	D-Sub Cable: Shielded, Detachable, 1.5m HDMI Cable: Shielded, Detachable, 1.8m Audio Cable: Unshielded, Detachable, 1.5m					

2.3. Block diagram of connection between the EUT and simulators



(EUT: LCD TV)

2.4. Test Facility

Site Description

- Name of Firm : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen, Guangdong, China
- 3m Anechoic Chamber : Certificated by FCC, USA
Registration Number: 90454
Valid Date: Feb.22, 2015
- 3m & 10m Anechoic Chamber : Certificated by FCC, USA
Registration Number: 794232
Valid Date: Oct.31, 2015
- EMC Lab. : Certificated by DAkkS, Germany
Registration No: D-PL-12151-01-01
Valid Date: Feb.01, 2014
- Accredited by NVLAP, USA
NVLAP Code: 200372-0
Valid Date: Mar.31, 2013

2.5. Measurement Uncertainty (95% confidence levels, k=2)


Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.48dB dB(9KHz to 150KHz)
	3.06dB(150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	3.6 dB(30~200MHz, Polarize: H)
	3.8 dB(30~200MHz, Polarize: V)
	4.2 dB(200M~1GHz, Polarize: H)
	3.8 dB(200M~1GHz, Polarize: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	3.1dB(Distance: 3m Polarize: V)
	3.7 dB(Distance: 3m Polarize: H)
Uncertainty for test site temperature and humidity	3%
	0.6°C

3. POWER LINE CONDUCTED EMISSION TEST

3.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESHS10	838693/001	Oct.31, 12	1 Year
2.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	834066/011	Oct.31, 12	1 Year
3.	L.I.S.N.#3	Kyoritsu	KNW-242C	8-1920-1	May.08, 12	1 Year
4.	Terminator	Hubersuhner	50Ω	No. 1	May.08, 12	1 Year
5.	Terminator	Hubersuhner	50Ω	No. 2	May.08, 12	1 Year
6.	RF Cable	Fujikura	3D-2W	No.1	May.08, 12	1 Year
7.	Coaxial Switch	Anritsu	MP59B	M50564	May.08, 12	1 Year
8.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100341	May.08, 12	1 Year

3.2. Block Diagram of Test Setup



3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

- Notes: 1. * Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.


3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1. LCD TV (EUT)

Model Number : LE32HDE3000
 Serial Number : N/A

3.4.2. Support Equipment : As Tested Supporting System Detail, in Section 2.2.




Trace: (Discrete)

Site no :1#conduction Data No :33
 Dis./Ant. **: 2012 ESH2-25 LINE
 Limit :FCC PART 15 B
 Env./Ins. :24.5*C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :VGA:640*480@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15000	0.19	9.94	35.95	46.08	66.00	19.92	QP
2	0.49150	0.19	9.95	29.95	40.09	56.14	16.05	QP
3	0.95313	0.21	9.94	30.67	40.82	56.00	15.18	QP
4	1.289	0.22	9.94	29.14	39.30	56.00	16.70	QP
5	1.585	0.23	9.94	30.27	40.44	56.00	15.56	QP
6	2.765	0.26	9.94	29.32	39.52	56.00	16.48	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

Data: 34 File: D:\DATA\2012 Report data\TCL\ACS12Q2748.em6 (42) Date: 2013-01-07




Trace: (Discrete)

Site no :1#conduction Data No :34
 Dis./Ant. **: 2012 ESH2-Z5 NEUTRAL
 Limit :FCC PART 15 B
 Env./Ins. :24.5*C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :VGA:640*480@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15160	0.21	9.94	35.06	45.21	65.91	20.70	QP
2	0.29088	0.22	9.95	29.23	39.40	60.50	21.10	QP
3	0.49937	0.23	9.95	28.36	38.54	56.01	17.47	QP
4	0.97354	0.24	9.94	29.83	40.01	56.00	15.99	QP
5	1.310	0.26	9.94	28.02	38.22	56.00	17.78	QP
6	4.622	0.33	9.95	28.16	38.44	56.00	17.56	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :36
 Dis./Ant. **: 2012 ESH2-25 LINE
 Limit :FCC PART 15 B
 Env./Ins. :24.5°C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :VG&:1024*768@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15000	0.19	9.94	36.81	46.94	66.00	19.06	QP
2	0.49150	0.19	9.95	30.67	40.81	56.14	15.33	QP
3	0.94308	0.21	9.94	28.91	39.06	56.00	16.94	QP
4	1.585	0.23	9.94	29.36	39.53	56.00	16.47	QP
5	2.794	0.26	9.94	29.60	39.80	56.00	16.20	QP
6	9.204	0.43	9.97	31.89	42.29	60.00	17.71	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :35
 Dis./Ant. **: 2012 ESH2-25 NEUTRAL
 Limit :FCC PART 15 B
 Env./Ins. :24.5°C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :VGA:1024*768@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15000	0.21	9.94	35.02	45.17	66.00	20.83	QP
2	0.45155	0.23	9.95	29.11	39.29	56.85	17.56	QP
3	0.48375	0.23	9.95	28.75	38.93	56.27	17.34	QP
4	0.94308	0.24	9.94	28.77	38.95	56.00	17.05	QP
5	2.978	0.31	9.94	27.83	38.08	56.00	17.92	QP
6	4.549	0.33	9.95	28.03	38.31	56.00	17.69	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

Data: 37 File: D:\DATA\2012 Report data\TCL\ACS12Q2748.em6 (42) Date: 2013-01-07




Trace: (Discrete)

Site no :1#conduction Data No :37
 Dis./Ant. **: 2012 ESH2-25 LINE
 Limit :FCC PART 15 B
 Env./Ins. :24.5*C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :VGA:1366*768@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15000	0.19	9.94	34.89	45.02	66.00	20.98	QP
2	0.49673	0.19	9.95	29.39	39.53	56.05	16.52	QP
3	0.94308	0.21	9.94	29.76	39.91	56.00	16.09	QP
4	1.289	0.22	9.94	28.01	38.17	56.00	17.83	QP
5	2.736	0.26	9.94	28.07	38.27	56.00	17.73	QP
6	4.338	0.30	9.95	28.61	38.86	56.00	17.14	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :38
 Dis./Ant. **: 2012 ESH2-25 NEUTRAL
 Limit :FCC PART 15 B
 Env./Ins. :24.5°C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :VGA:1366*768@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15000	0.21	9.94	35.38	45.53	66.00	20.47	QP
2	0.20181	0.21	9.94	32.26	42.41	63.54	21.13	QP
3	0.50469	0.23	9.95	29.62	39.80	56.00	16.20	QP
4	0.95313	0.24	9.94	31.35	41.53	56.00	14.47	QP
5	1.310	0.26	9.94	29.75	39.95	56.00	16.05	QP
6	2.809	0.30	9.94	28.46	38.70	56.00	17.30	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :40
 Dis./Ant. **: 2012 ESH2-25 LINE
 Limit :FCC PART 15 B
 Env./Ins. :24.5°C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :HDMI 1:1920*1080@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15160	0.19	9.94	34.30	44.43	65.91	21.48	QP
2	0.45395	0.19	9.95	31.00	41.14	56.80	15.66	QP
3	0.50203	0.19	9.95	28.89	39.03	56.00	16.97	QP
4	0.96840	0.21	9.94	30.35	40.50	56.00	15.50	QP
5	3.025	0.26	9.94	27.94	38.14	56.00	17.86	QP
6	4.549	0.30	9.95	29.77	40.02	56.00	15.98	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :39
 Dis./Ant. :** 2012 ESH2-25 NEUTRAL
 Limit :FCC PART 15 B
 Env./Ins. :24.5°C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :HDMI 1:1920*1080@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15485	0.21	9.94	36.33	46.48	65.74	19.26	QP
2	0.19969	0.21	9.94	31.35	41.50	63.62	22.12	QP
3	0.50737	0.23	9.95	30.12	40.30	56.00	15.70	QP
4	0.95313	0.24	9.94	31.11	41.29	56.00	14.71	QP
5	1.178	0.25	9.94	31.44	41.63	56.00	14.37	QP
6	1.441	0.26	9.94	30.14	40.34	56.00	15.66	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)

Site no :1#conduction Data No :41
 Dis./Ant. :** 2012 ESH2-25 LINE
 Limit :FCC PART 15 B
 Env./Ins. :24.5°C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :HDMI 2:1920*1080@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15000	0.19	9.94	35.17	45.30	66.00	20.70	QP
2	0.49937	0.19	9.95	29.55	39.69	56.01	16.32	QP
3	0.96840	0.21	9.94	28.37	38.52	56.00	17.48	QP
4	1.577	0.23	9.94	27.25	37.42	56.00	18.58	QP
5	2.794	0.26	9.94	29.60	39.80	56.00	16.20	QP
6	9.913	0.45	9.97	30.40	40.82	60.00	19.18	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Trace: (Discrete)

Site no :1#conduction Data No :42
 Dis./Ant. **: 2012 ESH2-25 NEUTRAL
 Limit :FCC PART 15 B
 Env./Ins. :24.5°C/56% Engineer :Alan_Chen
 EUT :LCD TV M/N:LE32HDE3000
 Power Rating :AC 120V/60Hz
 Test Mode :Running "H" Pattern And 1KHz Playing
 :HDMI 2:1920*1080@60Hz

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15403	0.21	9.94	36.92	47.07	65.78	18.71	QP
2	0.49673	0.23	9.95	29.22	39.40	56.05	16.65	QP
3	0.95313	0.24	9.94	29.93	40.11	56.00	15.89	QP
4	1.289	0.25	9.94	29.78	39.97	56.00	16.03	QP
5	2.854	0.30	9.94	25.93	36.17	56.00	19.83	QP
6	9.603	0.44	9.97	29.90	40.31	60.00	19.69	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
 2.If the average limit is met when using a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

4. RADIATED EMISSION TEST

4.1. Test Equipment

4.1.1. For frequency range 30MHz~1000MHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.24,12	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 12	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 12	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 12	1 Year
5	Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-429	Nov.27, 12	1.0 Year
6	RF Cable	MIYAZAKI	CFD400-N L	3# Chamber No.1	May.08, 12	1 Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 12	1 Year

4.1.2. For frequency range 1GHz~2GHz


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	May.08, 12	1 Year
2	Horn Antenna	EMCO	3115	9510-4580	June.05, 12	1 Year
3	Amplifier	Agilent	8449B	3008A00863	May.08, 12	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX106	77980/6	May.08, 12	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	May.08, 12	1 Year

4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-2GHz



4.3. Radiated Emission Limit

Frequency MHz	Distance (Meters)	Field Strengths Limits dB(μ V)/m
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
960 ~ 1000	3	54.0
Above 1000	3	74(Peak)54(Average)

- Remark: (1) Emission level = Antenna Factor + Cable Loss + Reading
Emission level = Antenna Factor - Amp Factor + Cable Loss + Reading (above 1000MHz)
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.4. EUT Configuration on Test

The configurations of EUT are listed in Section 3.4

4.5. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.5. except the test set up replaced by Section 4.2.

4.6. Test Procedure

The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4: 2009 on Radiated Emission test.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz.

4.7. Radiated Disturbance Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)

EUT: LCD TV Model No. : LE32HDE3000

For frequency range 30MHz~1000MHz

The EUT with the following test modes were tested and selected to read Q.P values, all the test results are listed in next pages.

Test Date: Jan.07, 2013 Temperature: 24°C Humidity: 56%

The details of test modes are as follows :

No.	Test Mode	Input Port	Resolution & Frequency	Reference Test Data No.	
				Horizontal	Vertical
1.	PC Mode	VGA	640*480@60Hz	#38	#37
2.			1024*768@60Hz	#35	#36
3. ※			1366*768@60Hz	#34	#33
4.		HDMI 1	1920*1080@60Hz	#39	#40
5.		HDMI 2	1920*1080@60Hz	#42	#41

(※ Worst test mode)

For frequency range 1GHz~2GHz

The EUT with below test mode were measured within Anechoic Chamber and the test results listed in next pages

Note: For all the emissions above 1GHz, the peak measured level comply with peak limit, so the average level were deemed to comply with average limit.


Test Date:Jan.07, 2013

Temperature: 24°C

Humidity: 56%

NO.	Test Mode	Resolution & Frequency	Reference Test Data No.	
			Horizontal	Vertical
1.	VGA	1366*768@60Hz	#48	#47
2.	HDMI 1	1920*1080@60Hz	#45	#46
3.	HDMI 2	1920*1080@60Hz	#43	#44


30MHz~1000MHz



Site no. : 3m Chamber Data no. : 38
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : VGA:640*480@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	165.800	10.09	0.99	22.54	33.62	43.50	9.88	QP
2	241.460	11.79	1.15	18.54	31.48	46.00	14.52	QP
3	328.760	14.55	1.37	24.59	40.51	46.00	5.49	QP
4	584.840	20.09	2.07	14.25	36.41	46.00	9.59	QP
5	742.950	22.11	2.54	10.45	35.10	46.00	10.90	QP
6	807.940	22.66	2.71	11.64	37.01	46.00	8.99	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 37
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : VGA:640*480@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	136.700	11.32	0.93	18.26	30.51	43.50	12.99	QP
2	322.940	14.32	1.35	23.23	38.90	46.00	7.10	QP
3	390.840	16.36	1.52	20.00	37.88	46.00	8.12	QP
4	553.800	19.35	1.99	12.44	33.78	46.00	12.22	QP
5	648.860	20.68	2.25	11.14	34.07	46.00	11.93	QP
6	751.680	22.34	2.56	8.33	33.23	46.00	12.77	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 35
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : VGA:1024*768@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	165.800	10.09	0.99	23.87	34.95	43.50	8.55	QP
2	194.900	9.00	1.04	24.40	34.44	43.50	9.06	QP
3	328.200	14.52	1.37	24.90	40.79	46.00	5.21	QP
4	485.900	18.42	1.79	16.15	36.36	46.00	9.64	QP
5	584.840	20.09	2.07	16.04	38.20	46.00	7.80	QP
6	745.860	22.18	2.54	10.71	35.43	46.00	10.57	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 36
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : VGA:1024*768@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	70.740	6.00	0.72	25.33	32.05	40.00	7.95	QP
2	136.700	11.32	0.93	21.38	33.63	43.50	9.87	QP
3	322.940	14.32	1.35	20.67	36.34	46.00	9.66	QP
4	390.840	16.36	1.52	19.58	37.46	46.00	8.54	QP
5	575.140	20.10	2.05	16.57	38.72	46.00	7.28	QP
6	665.350	20.96	2.32	14.06	37.34	46.00	8.66	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 34
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : VGA:1366*768@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	63.950	5.30	0.69	22.09	28.08	40.00	11.92	QP
2	165.800	10.09	0.99	24.35	35.43	43.50	8.07	QP
3	194.900	9.00	1.04	23.62	33.66	43.50	9.84	QP
4	328.000	14.51	1.35	29.10	44.96	46.00	1.04	QP
5	585.000	20.09	2.07	17.30	39.46	46.00	6.54	QP
6	807.940	22.66	2.71	13.04	38.41	46.00	7.59	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 33
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : VGA:1366*768@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	136.700	11.32	0.93	23.18	35.43	43.50	8.07	QP
2	328.760	14.55	1.37	22.81	38.73	46.00	7.27	QP
3	390.000	16.32	1.52	25.60	43.44	46.00	2.56	QP
4	485.900	18.42	1.79	17.10	37.31	46.00	8.69	QP
5	575.140	20.10	2.05	13.36	35.51	46.00	10.49	QP
6	665.350	20.96	2.32	11.14	34.42	46.00	11.58	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 39
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : HDMI 1:1920*1080@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	161.920	10.36	0.99	22.33	33.68	43.50	9.82	QP
2	194.900	9.00	1.04	24.59	34.63	43.50	8.87	QP
3	245.340	12.17	1.16	23.26	36.59	46.00	9.41	QP
4	330.700	14.63	1.37	25.39	41.39	46.00	4.61	QP
5	594.540	20.32	2.11	15.75	38.18	46.00	7.82	QP
6	807.940	22.66	2.71	12.76	38.13	46.00	7.87	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 40
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : HDMI 1:1920*1080@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	97.900	9.28	0.85	19.75	29.88	43.50	13.62	QP
2	160.950	10.42	0.99	19.04	30.45	43.50	13.05	QP
3	245.340	12.17	1.16	19.67	33.00	46.00	13.00	QP
4	322.940	14.32	1.35	23.40	39.07	46.00	6.93	QP
5	390.000	16.32	1.52	24.10	41.94	46.00	4.06	QP
6	891.000	23.44	2.80	14.40	40.64	46.00	5.36	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 42
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : HDMI 2:1920*1080@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	194.900	9.00	1.04	22.10	32.14	43.50	11.36	QP
2	330.700	14.63	1.37	27.89	43.89	46.00	2.11	QP
3	409.270	16.88	1.58	18.23	36.69	46.00	9.31	QP
4	585.000	20.09	2.07	19.30	41.46	46.00	4.54	QP
5	806.970	22.66	2.71	9.88	35.25	46.00	10.75	QP
6	891.000	23.44	2.80	15.10	41.34	46.00	4.66	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 41
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power rating : AC 120V/60Hz
 Test Mode : HDMI 2:1920*1080@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	30.000	18.74	0.45	12.34	31.53	40.00	8.47	QP
2	328.760	14.55	1.37	23.77	39.69	46.00	6.31	QP
3	390.840	16.36	1.52	20.93	38.81	46.00	7.19	QP
4	410.240	16.92	1.58	20.00	38.50	46.00	7.50	QP
5	485.900	18.42	1.79	16.60	36.81	46.00	9.19	QP
6	891.000	23.44	2.80	18.60	44.84	46.00	1.16	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


1GHz~2GHz



Site no. : 3m Chamber Data no. : 48
 Dis. / Ant. : 3m 2011 3115 9607-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B PEAK
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power Rating : AC 120V/60Hz
 Test Mode : VGA:1366*768@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1560.584	25.85	1.03	35.90	59.85	50.83	74.00	23.17	Peak
2	1561.215	25.85	1.03	35.90	46.26	37.24	54.00	16.76	Average
3	1601.215	25.98	1.04	35.84	47.22	38.40	54.00	15.60	Average
4	1602.280	25.98	1.04	35.84	59.37	50.55	74.00	23.45	Peak
5	1999.356	27.50	1.13	35.40	46.25	39.48	54.00	14.52	Average
6	2000.000	27.50	1.13	35.40	60.05	53.28	74.00	20.72	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 47
 Dis. / Ant. : 3m 2011 3115 9607-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B PEAK
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power Rating : AC 120V/60Hz
 Test Mode : VGA:1366*768@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1111.345	23.78	0.97	36.39	50.21	38.57	54.00	15.43	Average
2	1112.945	23.78	0.97	36.36	63.26	51.65	74.00	22.35	Peak
3	1796.245	26.74	1.09	35.62	45.24	37.45	54.00	16.55	Average
4	1798.254	26.74	1.09	35.62	60.70	52.91	74.00	21.09	Peak
5	1994.845	27.50	1.13	35.40	52.23	45.46	54.00	8.54	Average
6	1995.214	27.50	1.13	35.40	65.14	58.37	74.00	15.63	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 45
 Dis. / Ant. : 3m 2011 3115 9607-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B PEAK
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power Rating : AC 120V/60Hz
 Test Mode : HDMI 1:1920*1080@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1560.878	25.85	1.03	35.90	60.83	51.81	74.00	22.19	Peak
2	1561.215	25.85	1.03	35.90	47.26	38.24	54.00	15.76	Average
3	1670.151	26.23	1.06	35.76	59.31	50.84	74.00	23.16	Peak
4	1671.215	26.23	1.06	35.76	46.58	38.11	54.00	15.89	Average
5	1995.845	27.50	1.13	35.40	54.25	47.48	54.00	6.52	Average
6	1996.245	27.50	1.13	35.40	63.83	57.06	74.00	16.94	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 46
 Dis. / Ant. : 3m 2011 3115 9607-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B PEAK
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power Rating : AC 120V/60Hz
 Test Mode : HDMI 1:1920*1080@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	1110.422	23.70	0.96	36.39	63.09	51.36	74.00	22.64	Peak
2	1112.241	23.78	0.97	36.39	51.21	39.57	54.00	14.43	Average
3	1197.525	24.19	0.98	36.28	50.55	39.44	54.00	14.56	Average
4	1198.849	24.19	0.98	36.28	61.93	50.82	74.00	23.18	Peak
5	1992.545	27.44	1.13	35.40	53.34	46.51	54.00	7.49	Average
6	1995.241	27.50	1.13	35.40	65.12	58.35	74.00	15.65	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 43
 Dis. / Ant. : 3m 2011 3115 9607-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B PEAK
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power Rating : AC 120V/60Hz
 Test Mode : HDMI 2:1920*1080@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	1197.845	24.19	0.98	36.28	47.22	36.11	54.00	17.89	Average
2	1198.845	24.19	0.98	36.28	59.18	48.07	74.00	25.93	Peak
3	1552.480	25.79	1.03	35.90	56.72	47.64	74.00	26.36	Peak
4	1553.845	25.85	1.03	35.90	47.93	38.91	54.00	15.09	Average
5	1597.456	25.98	1.04	35.84	48.28	39.46	54.00	14.54	Average
6	1598.245	25.98	1.04	35.84	59.22	50.40	74.00	23.60	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 44
 Dis. / Ant. : 3m 2011 3115 9607-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B PEAK
 Env. / Ins. : 24°C/56% Engineer : Even_Deng
 EUT : LCD TV M/N:LE32HDE3000
 Power Rating : AC 120V/60Hz
 Test Mode : HDMI 2:1920*1080@60Hz
 Running "H" Pattern And 1KHz Playing

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1560.745	25.85	1.03	35.90	58.43	49.41	74.00	24.59	Peak
2	1561.248	25.85	1.03	35.90	48.66	39.64	54.00	14.36	Average
3	1602.348	25.98	1.04	35.84	58.15	49.33	74.00	24.67	Peak
4	1602.845	25.98	1.04	35.84	49.85	41.03	54.00	12.97	Average
5	1998.548	27.50	1.13	35.40	50.21	43.44	54.00	10.56	Average
6	1999.515	27.50	1.13	35.40	61.24	54.47	74.00	19.53	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.

5. DEVIATION TO TEST SPECIFICATIONS

[NONE]