



W66 N220 Commerce Court • Cedarburg, WI 53012  
Phone: 262.375.4400 • Fax: 262.375.4248  
[www.lsr.com](http://www.lsr.com)

RF Evaluation Exclusion Exhibit For:

**8000-WiFi Module**

Prepared by:

Peter Feilen, EMC Engineer

11-5-2015



W66 N220 Commerce Court • Cedarburg, WI 53012  
Phone: 262.375.4400 • Fax: 262.375.4248  
[www.lsr.com](http://www.lsr.com)

## Contents

Product Description: .....	3
Associated Antenna(s): .....	3
Statement of compliance: .....	3
Limits: .....	3
Calculations: .....	5
Summary: .....	6
Summary: .....	<b>Error! Bookmark not defined.</b>



W66 N220 Commerce Court • Cedarburg, WI 53012  
Phone: 262.375.4400 • Fax: 262.375.4248  
[www.lsr.com](http://www.lsr.com)

## Product Description:

The 8000-WIFI is a module with support for WLAN (802.11 a/b/g/n)

## Associated Antenna(s):

Corresponding antenna data associated with the EUT:

1. Peak gain of 2.5dBi – 2.4 GHz
2. Peak gain of 4.6 dBi – 5 GHz

## Statement of compliance:

The 8000-WiFi Module was evaluated against the requirements and limits of OET Bulletin 65, KDB 447498 as well as RSS-102 Issue 5 and was found to be compliant.

## Limits:

### A. Mobile (MPE)

OET Bulletin 65 limits for General population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

\*Plane-wave equivalent power density



W66 N220 Commerce Court • Cedarburg, WI 53012  
 Phone: 262.375.4400 • Fax: 262.375.4248  
[www.lsr.com](http://www.lsr.com)

RSS 102 limits for General population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>21</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ $f$	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 <sup>-4</sup> $f^{0.5}$	6.67 x 10 <sup>-5</sup> $f$	616000/ $f^{1.2}$
<b>Note:</b> $f$ is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

Per RSS 102 issue 5 section 2.5.2, RF exposure evaluation is required if separation distance between the user and/or bystander and the device's radiating element is greater than 20cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 22.48/  $f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1.31 x 10<sup>-2</sup>  $f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).



W66 N220 Commerce Court • Cedarburg, WI 53012  
Phone: 262.375.4400 • Fax: 262.375.4248  
[www.lsr.com](http://www.lsr.com)

## Calculations:

### A. MPE Calculation

The following MPE calculations are based on a measured conducted RF power of +16.0 dBm as presented to the antenna. The peak gain of this antenna, based on the data sheet is 2.5 dBi.

#### Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 16.00 (dBm)

Maximum peak output power at antenna input terminal: 39.811 (mW)

Antenna gain(typical): 2.5 (dBi)

Maximum antenna gain: 1.778 (numeric)

Prediction distance: 20 (cm)

Prediction frequency: 2437 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm<sup>2</sup>)

Power density at prediction frequency: 0.014084 (mW/cm<sup>2</sup>)

Maximum allowable antenna gain: 21.0 (dBi)

Margin of Compliance at 20 cm = 18.5 dB

Power Density = 0.0141mW/cm<sup>2</sup> = 0.141 W/m<sup>2</sup>



W66 N220 Commerce Court • Cedarburg, WI 53012  
Phone: 262.375.4400 • Fax: 262.375.4248  
[www.lsr.com](http://www.lsr.com)

### RF Exposure Evaluation:

Evaluated against exposure limits: General Public Use  Controlled Use

Duty cycle used in evaluation: 100 %

Standard(s)/Procedure(s) used for evaluation (e.g. IEEE C95.3): OET Buletin 65 and RSS 102

Measurement distance: 20 cm

RF field strength value: **0.141** V/m  A/m  W/m<sup>2</sup>

Measured  Computed  Calculated

### Summary:

The calculated power density of the EUT was found to be below the OET Bulletin 65 MPE limit.

Per RSS 102 issue 5 section 2.5.2, since the EUT operates at less than

$$1.31 \times 10^{-2} * (2437)^{0.6834} W = 2.70W$$

The EUT is excluded from Routine evaluation.

Based on the calculation above, the EUT complies with RF exposure requirement when used at a minimum separation distance of at least **20 cm**.