

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	IP Phone
Model Name	A41W
FCC ID	W9D-A40XA41X

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

According to the follow transmitter output power ( $P_t$ ) formula:

According to the report AGC01180160702FE05,

$P_t = 9.74 \text{ dBm} = 9.42 \text{ mW}$

The result for RF exposure evaluation

$\text{SAR} = (9.42 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.462(\text{GHz})}] = 2.96 < 3.0$  for 1-g SAR

Note: For RF exposure evaluation, the Maximum power at WIFI mode is the worst case.

### 4. CONCLUSION

The SAR evaluation is not required.