

Application for FCC Certificate
On Behalf of
Hisense Electric Co., Ltd.

LCD TV

Model No.	Serial No.	Brand
LHDN26W57US	--	Hisense
LHDN26W60US	--	
LHDN26W58US	--	
LHDN26W61US	--	
LHD26V68US	--	
ELCHS262	E2009080301	Element
ELCHW261	--	

FCC ID : W9HLCDB0001

Prepared For : Hisense Electric Co., Ltd.
No.218 Qianwangang Road, Economy & Technology
Development Zone, Qingdao, China

Prepared By : Audix Technology (Shanghai) Co., Ltd.
3F 34Bldg 680 Guiping Rd,
Caohejing Hi-Tech Park,
Shanghai 200233, China

Tel: +86-21-64955500
Fax: +86-21-64955491

Report No. : ACI-F09072A1
Date of Test : Aug 04, 2009
Date of Report : Aug 07, 2009

TABLE OF CONTENTS

	Page
1 SUMMARY OF STANDARDS AND RESULTS	4
1.1 Description of Standards and Results.....	4
2 GENERAL INFORMATION	5
2.1 Description of Equipment Under Test.....	5
2.2 Peripherals.....	7
2.3 Description of Test Facility.....	8
2.4 Measurement Uncertainty.....	8
3 CONDUCTED EMISSION TEST	9
3.2 Block Diagram of Test Setup.....	9
3.3 Conducted Emission Limit [FCC Part 15 Subpart B 15.107(a)].....	10
3.4 Test Configuration.....	10
3.5 Operating Condition of EUT.....	11
3.6 Test Procedures.....	11
3.7 Test Results.....	12
4 RADIATED EMISSION TEST	19
4.1 Test Equipment.....	19
4.2 Block Diagram of Test Setup.....	19
4.3 Radiated Emission Limit [FCC Part 15 Subpart B 15.109(a)].....	20
4.4 Test Configuration.....	20
4.5 Operating Condition of EUT.....	20
4.6 Test Procedures.....	21
4.7 Test Results.....	21
5 DEVIATION TO TEST SPECIFICATIONS	28
6 DEBUG DESCRIPTION	29

TEST REPORT FOR FCC CERTIFICATE

Applicant : Hisense Electric Co., Ltd.
 Manufacturer : Hisense Electric Co., Ltd.
 EUT Description : LCD TV

Model No.	Serial No.	Brand	Power Supply
LHDN26W57US	--	Hisense	120V/60Hz
LHDN26W60US	--		
LHDN26W58US	--		
LHDN26W61US	--		
LHD26V68US	--		
ELCHS262	E2009080301	Element	
ELCHW261	--		

Test Procedure Used:

*FCC RULES AND REGULATIONS PART 15 SUBPART B CLASS B OCTOBER 2008
AND ANSI C63.4-2003*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B (Class B) limits both radiated and conducted emissions.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report shows that the EUT (M/N: Refer to Sec.2.1; S/N: Refer to Sec.2.1) which was tested in 3m anechoic chamber Aug 04, 2009 is technically compliance with the FCC official limits also.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

This report contains data that are not covered by the NVLAP accreditation.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

The test results for EUT's TV function are contained in No.F09071A1, a Verification report.

Date of Test : Aug 04, 2009 Date of Report : Aug 07, 2009

Producer : Zeno Gu
ZENO GU / Assistant

Review : Byron Wu
BYRON WU / Supervisor

AUDIX[®] For and on behalf of
Audix Technology (Shanghai) Co., Ltd.

Signatory : Di Yang
Authorized Signature **ENDUO YANG** / Deputy Assistant Manager

1 SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Description of Test Item	Standard	Limits	Results
EMISSION			
Conducted Disturbance at the Mains Terminal	FCC RULES AND REGULATIONS PART 15 SUBPART B OCTOBER 2008 AND ANSI C63.4-2003	15.107(a) Class B	Pass
Radiated Disturbance	FCC RULES AND REGULATIONS PART 15 SUBPART B OCTOBER 2008 AND ANSI C63.4-2003	15.109(a) Class B	Pass

2 GENERAL INFORMATION

2.1 Description of Equipment Under Test

Description : LCD TV

Type of EUT : Production Pre-product Pro-type

Model No.	Serial No.	Brand
LHDN26W57US	--	Hisense
LHDN26W60US	--	
LHDN26W58US	--	
LHDN26W61US	--	
LHD26V68US	--	
ELCHS262	E2009080301	Element
ELCHW261	--	

Note 1 : The difference list for all models are as follows:

Report No.	Model No.	Rev. Summary	Edition No.	Data of Rev.
ACI-F09072	LHDN26W57US, LHDN26W60US, LHDN26W58US, LHDN26W61US,	Original Report.	0	Aug 03, 2009
ACI-F09072A1	LHD26V68US, ELCHS262, ELCHW261	(1) To Change LCD panel. (2) To add one core	Rev. A1	Aug 07, 2009

Note 2 : The ELCHS262 was tested and recorded in this report.

Applicant : Hisense Electric Co., Ltd.
No.218 Qianwangang Road, Economy &
Technology Development Zone, Qingdao, China

Manufacturer : Hisense Electric Co., Ltd.
No.218 Qianwangang Road, Economy &
Technology Development Zone, Qingdao, China

LCD Panel : Manufacturer : IVO
M/N : M260TWR1

Tuner : Manufacturer : XuGuang Tech Co., Ltd.
M/N : DVT-8ADC1/W41F2ROH

Max Resolution : 1360*768@60Hz

D-Sub Cable : Shielded, Detachable, 1.85m,
with two cores on cable

HDMI Cable : Shielded, Detachable, 1.85m,
without core on cable

Power Cord : Unshielded, Detachable, 1.80m

Remark:

The EUT is a LCD TV which input/output ports as follows:

Rear View:

- | | | |
|-----|------------------------------------|--------------------------|
| (1) | One component of YPbPr1 Port | Connected with DVD #1 |
| (2) | One component of YPbPr1 Audio Port | Connected with DVD #1 |
| (3) | One component of YpbPr2 Port | Connected with DVD #2 |
| (4) | One component of YPbPr2 Audio Port | Connected with DVD #2 |
| (5) | One HDMI1 Port | Connected with PC/DVD #1 |
| (6) | One HDMI2 Port | Connected with PC/DVD #2 |
| (7) | One VGA Port | Connected with PC |
| (8) | One VGA Audio Port | Connected with PC |
| (9) | One Audio Out Port | Connected with Speaker |

Side Port:

- | | | |
|------|-----------------------------|-------------------------------------|
| (10) | One S-Video Port | Connected with TV SG |
| (11) | One ANT Port | Connected with TV SG/ATSC SG |
| (12) | One component of AV In Port | Connected with DVD #1 |
| (13) | One COAXIAL Port | Connected with DVD #1 |
| (14) | One Earphone Port | Connected with Earphone |
| (15) | One USB (Service) Port | Connected with U-Disk as Terminator |

2.2 Peripherals

2.2.1 PC

Manufacturer : HP
Model Number : dx7200MT
Serial Number : CNG622017W
Power Cord : Unshielded, Detachable, 1.8m
Certificate : FCC DoC; CE/EMC; VCCI; C-Tick; UL
BSMI (R33001) 3C (A000111)
MIC (E-A011-04-2659(B))

2.2.2 Printer

Manufacturer : HP
Model Number : C3990A
Serial Number : JPZX020487
Data Cable : Shielded, detachable, 1.5m
Certificate : GS, CE/EMC, C-Tick, FCC DoC

2.2.3 Keyboard

Manufacturer : Microsoft
Model Number : RT2300
Serial Number : 7668200662248
Data Cable : Shielded, undetachable ,1.8m
Certificate : CE/EMC, FCC DoC, VCCI, MIC, C-Tick,
BSMI

2.2.4 Mouse

Manufacturer : Microsoft
Model Number : RT2300
Serial Number : 6965712071551
Data Cable : Shielded, undetachable, 1.8m.
Certificate : CE/EMC, FCC DoC, VCCI, MIC, C-Tick,
BSMI

2.2.5 Modem

Manufacturer : TP-LINK
Model Number : TM-EC5658V
Serial Number : 07123301053
Data Cable : Shielded, Detachable, 1.8m
Certificate : FCC DoC, CE/EMC, CCC

2.2.6 Earphone

Manufacturer : SONY
Model Number : MDR-E808
Serial Number : 1808030805305506

2.2.7 TV Signal Generator

Manufacturer : FLUKE
Model Number : 54200m01
Serial Number : 814008
Data Cable : Shielded, detachable, 2.0m
Power Cord : Unshielded, detachable, 2.0m
Certificate : CE/EMC, FCC DoC, CCC

2.2.8 ATSC Signal Generator

Manufacturer : SENCORE
Model Number : ATSC997
Serial Number : 6790071

2.2.9 DVD#1

Manufacturer : PHILIPS
Model Number : DVP3986K/93
Serial Number : KX1A0902120108
Certificate : FCC DoC, CE/EMC, CCC

2.2.10 DVD#2

Manufacturer : PHILIPS
Model Number : DVP3986K/93
Serial Number : KX1A0902120082
Certificate : FCC DoC, CE/EMC, CCC

2.2.11 Speaker

Manufacturer : DIBA
Model Number : T520
Serial Number : 10628

2.2.12 U-Disk

Manufacturer : LG
Model Number : 1GB
Serial Number : N/A

2.3 Description of Test Facility

Site Description (Semi-Anechoic Chamber) : Sept. 17, 1998 file on
Apr 29, 2009 Renewed
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046, USA

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3F 34Bldg 680 Guiping Rd,
Caohejing Hi-Tech Park,
Shanghai 200233, China

NVLAP Lab Code : 200371-0

2.4 Measurement Uncertainty

Conducted Emission Expanded Uncertainty: U = 1.26 dB
Radiated Emission Expanded Uncertainty : U = 3.02 dB

3 CONDUCTED EMISSION TEST


3.1.1 Test Equipment

The following test equipments are used during the conducted emission test in a shielded room:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Test Receiver	R&S	ESCI	100841	Nov 21, 2008	Nov 21, 2009
2.	Artificial Mains Network (AMN)	R&S	ESH2-Z5	843890/011	Apr 02, 2009	Apr 02, 2010
3.	Line Impedance Stabilization Network (LISN)	Kyoritsu	KNW-407	8-1280-4	Apr 02, 2009	Apr 02, 2010
4.	50 Ω Coaxial Switch	Anritsu	MP59B	6200426389	Mar 19, 2009	Sep 19, 2009
5.	50 Ω Terminator	Anritsu	BNC	001	Apr 02, 2009	Apr 02, 2010
6.	Software	Audix	E3	SET00200 9804M592	--	--


3.2 Block Diagram of Test Setup

3.2.1 EUT & Peripherals



■ : Ferrite core

3.2.2 Conducted Disturbance Test Setup



3.3 Conducted Emission Limit [FCC Part 15 Subpart B 15.107(a)]

Frequency Range (MHz)	Limits dB (μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66~56	56~46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE 1 – The lower limit shall apply at the transition frequencies.
 NOTE 2 – The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz~0.50 MHz

3.4 Test Configuration

The EUT (listed in Sec.2.1) and the peripherals (listed in Sec 2.2) were installed as shown on Sec.3.2 to meet FCC requirement and operating in a manner that tends to maximize its emission level in a normal application.

3.5 Operating Condition of EUT

3.5.1 Setup the EUT and peripherals as shown in Sec. 3.2.

3.5.2 Turn on the power of all equipments and the EUT.

3.5.3 Set the contrast & brightness of EUT to maximum.

3.5.4 PC system ran the self-test program “EMC Test” by windows XP and sent “H” characters to EUT through graphic card, the EUT’s screen displayed and filled with “H” pattern by its resolution (Via D-Sub & HDMI Input).

3.5.5 Repeat above procedure from 3.5.3 to 3.5.4 for difference test mode.

3.5.6 The other peripherals devices were driven and operated during the test.

3.5.7 The test modes are as follows:

Test Mode
D-Sub 640*480@60Hz
D-Sub 1024*768@60Hz
D-Sub 1360*768@60Hz
HDMI 640*480@60Hz
HDMI 1024*768@60Hz
HDMI 1360*768@60Hz

3.6 Test Procedures

The EUT and peripherals were connected to the power mains through an Artificial Mains Network (AMN). This provided a 50 ohm coupling impedance for the measuring equipment.

Both sides of AC line (Line & Neutral) were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed or manipulated according to ANSI C63.4:2003 during conducted emission test.

The bandwidth of R&S Test Receiver ESCI was set at 9 kHz.

The frequency range from 150 kHz to 30 MHz was checked.

The test modes were done on conducted disturbance test and all the test results are listed in Sec. 3.7.

3.7 Test Results

< **PASS** >

The frequency and amplitude of the highest conducted emission relative to the limit is reported. All emissions not reported below are too low against the prescribed limits.

Test Mode	Data Page
D-Sub 640*480@60Hz	P13
D-Sub 1024*768@60Hz	P14
D-Sub 1360*768@60Hz	P15
HDMI 640*480@60Hz	P16
HDMI 1024*768@60Hz	P17
HDMI 1360*768@60Hz	P18

NOTE 1 – Factor = Cable Loss + AMN Factor.

NOTE 2 – Emission Level = Meter Reading + Factor.

NOTE 3 – “QP” means “Quasi-Peak” values, “AV” means “Average” values.

NOTE 4 – The worst case is for D-Sub 1360*768@60Hz test mode. The worst emission is detected at 0.521 MHz (Average) with corrected signal level of 34.94 dB (μ V) (limit is 46.00 dB (μ V)), when the Neutral of the EUT is connected to AMN.

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 48%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : D-Sub 640*480@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μ V)	Factor (dB)	Emission Level dB(μ V)	Limits dB(μ V)	Margin (dB)	Remark
Line	0.169	28.52	0.22	28.74	64.99	36.25	QP
	0.393	32.08	0.28	32.36	57.99	25.63	
	0.521	33.37	0.29	33.66	56.00	22.34	
	4.721	34.53	0.44	34.97	56.00	21.03	
	5.419	34.26	0.44	34.70	60.00	25.30	
	17.383	39.52	0.81	40.33	60.00	19.67	
	0.169	25.99	0.22	26.21	54.99	28.78	AV
	0.393	30.38	0.28	30.66	47.99	17.33	
	0.521	33.47	0.29	33.76	46.00	12.24	
	4.721	27.59	0.44	28.03	46.00	17.97	
	5.419	26.13	0.44	26.57	50.00	23.43	
	17.383	31.95	0.81	32.76	50.00	17.24	
Neutral	0.168	31.81	0.20	32.01	65.08	33.07	QP
	0.389	33.24	0.25	33.49	58.08	24.59	
	0.521	34.09	0.26	34.35	56.00	21.65	
	4.574	32.85	0.45	33.30	56.00	22.70	
	5.419	33.21	0.45	33.66	60.00	26.34	
	16.486	39.33	0.73	40.06	60.00	19.94	
	0.168	28.59	0.20	28.79	55.08	26.29	AV
	0.389	32.44	0.25	32.69	48.08	15.39	
	0.521	33.31	0.26	33.57	46.00	12.43	
	4.574	26.17	0.45	26.62	46.00	19.38	
	5.419	26.43	0.45	26.88	50.00	23.12	
	16.486	32.85	0.73	33.58	50.00	16.42	

TEST ENGINEER: HUGH HUANG

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 48%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : D-Sub 1024*768@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μ V)	Factor (dB)	Emission Level dB(μ V)	Limits dB(μ V)	Margin (dB)	Remark
Line	0.170	28.57	0.22	28.79	64.94	36.15	QP
	0.393	32.34	0.28	32.62	57.99	25.37	
	0.521	33.56	0.29	33.85	56.00	22.15	
	4.721	34.87	0.44	35.31	56.00	20.69	
	5.419	35.26	0.44	35.70	60.00	24.30	
	16.839	37.91	0.78	38.69	60.00	21.31	
	0.170	25.22	0.22	25.44	54.94	29.50	AV
	0.393	30.48	0.28	30.76	47.99	17.23	
	0.521	33.65	0.29	33.94	46.00	12.06	
	4.721	28.51	0.44	28.95	46.00	17.05	
	5.419	25.21	0.44	25.65	50.00	24.35	
	16.839	31.82	0.78	32.60	50.00	17.40	
Neutral	0.169	32.13	0.20	32.33	64.99	32.66	QP
	0.389	34.00	0.25	34.25	58.08	23.83	
	0.521	34.67	0.26	34.93	56.00	21.07	
	4.721	32.82	0.45	33.27	56.00	22.73	
	5.419	34.25	0.45	34.70	60.00	25.30	
	16.839	40.47	0.74	41.21	60.00	18.79	
	0.169	28.95	0.20	29.15	54.99	25.84	AV
	0.389	32.79	0.25	33.04	48.08	15.04	
	0.521	34.58	0.26	34.84	46.00	11.16	
	4.721	26.69	0.45	27.14	46.00	18.86	
	5.419	25.37	0.45	25.82	50.00	24.18	
	16.839	32.62	0.74	33.36	50.00	16.64	

TEST ENGINEER: HUGH HUANG

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 48%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : D-Sub 1360*768@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
Line	0.169	28.84	0.22	29.06	64.99	35.93	QP
	0.393	32.89	0.28	33.17	57.99	24.82	
	0.521	34.10	0.29	34.39	56.00	21.61	
	4.721	33.85	0.44	34.29	56.00	21.71	
	5.419	35.54	0.44	35.98	60.00	24.02	
	17.383	40.06	0.81	40.87	60.00	19.13	
	0.169	26.10	0.22	26.32	54.99	28.67	AV
	0.393	30.92	0.28	31.20	47.99	16.79	
	0.521	34.23	0.29	34.52	46.00	11.48	
	4.721	27.10	0.44	27.54	46.00	18.46	
	5.419	26.71	0.44	27.15	50.00	22.85	
	17.383	34.39	0.81	35.20	50.00	14.80	
Neutral	0.169	32.17	0.20	32.37	64.99	32.62	QP
	0.389	34.15	0.25	34.40	58.08	23.68	
	0.521	34.86	0.26	35.12	56.00	20.88	
	1.744	35.80	0.35	36.15	56.00	19.85	
	5.419	35.76	0.45	36.21	60.00	23.79	
	16.486	38.22	0.73	38.95	60.00	21.05	
	0.169	28.81	0.20	29.01	54.99	25.98	AV
	0.389	32.94	0.25	33.19	48.08	14.89	
	0.521	34.68	0.26	34.94	46.00	11.06	
	1.744	30.42	0.35	30.77	46.00	15.23	
	5.419	27.73	0.45	28.18	50.00	21.82	
	16.486	31.77	0.73	32.50	50.00	17.50	

TEST ENGINEER: HUGH HUANG

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 48%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : HDMI 640*480@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μ V)	Factor (dB)	Emission Level dB(μ V)	Limits dB(μ V)	Margin (dB)	Remark
Line	0.280	29.31	0.25	29.56	60.81	31.25	QP
	0.389	34.24	0.28	34.52	58.08	23.56	
	1.236	42.05	0.32	42.37	56.00	13.63	
	4.721	32.19	0.44	32.63	56.00	23.37	
	5.805	35.46	0.45	35.91	60.00	24.09	
	16.839	36.52	0.78	37.30	60.00	22.70	
	0.280	29.60	0.25	29.85	50.81	20.96	AV
	0.389	32.49	0.28	32.77	48.08	15.31	
	1.236	33.62	0.32	33.94	46.00	12.06	
	4.721	26.84	0.44	27.28	46.00	18.72	
	5.805	28.31	0.45	28.76	50.00	21.24	
	16.839	29.48	0.78	30.26	50.00	19.74	
Neutral	0.170	31.91	0.20	32.11	64.94	32.83	QP
	0.389	35.43	0.25	35.68	58.08	22.40	
	1.236	42.78	0.32	43.10	56.00	12.90	
	4.721	36.36	0.45	36.81	56.00	19.19	
	5.774	37.25	0.46	37.71	60.00	22.29	
	15.552	34.55	0.69	35.24	60.00	24.76	
	0.170	29.16	0.20	29.36	54.94	25.58	AV
	0.389	33.60	0.25	33.85	48.08	14.23	
	1.236	33.99	0.32	34.31	46.00	11.69	
	4.721	28.47	0.45	28.92	46.00	17.08	
	5.774	32.11	0.46	32.57	50.00	17.43	
	15.552	26.26	0.69	26.95	50.00	23.05	

TEST ENGINEER: HUGH HUANG

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 48%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : HDMI 1024*768@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μ V)	Factor (dB)	Emission Level dB(μ V)	Limits dB(μ V)	Margin (dB)	Remark
Line	0.169	28.73	0.22	28.95	64.99	36.04	QP
	0.389	34.24	0.28	34.52	58.08	23.56	
	1.236	40.59	0.32	40.91	56.00	15.09	
	4.721	34.91	0.44	35.35	56.00	20.65	
	5.805	38.02	0.45	38.47	60.00	21.53	
	17.199	38.48	0.79	39.27	60.00	20.73	
	0.169	26.76	0.22	26.98	54.99	28.01	AV
	0.389	32.36	0.28	32.64	48.08	15.44	
	1.236	34.13	0.32	34.45	46.00	11.55	
	4.721	27.83	0.44	28.27	46.00	17.73	
	5.805	29.55	0.45	30.00	50.00	20.00	
	17.199	29.78	0.79	30.57	50.00	19.43	
Neutral	0.169	31.99	0.20	32.19	64.99	32.80	QP
	0.389	35.25	0.25	35.50	58.08	22.58	
	1.236	42.02	0.32	42.34	56.00	13.66	
	2.707	37.35	0.39	37.74	56.00	18.26	
	5.805	36.42	0.46	36.88	60.00	23.12	
	15.552	31.96	0.69	32.65	60.00	27.35	
	0.169	29.53	0.20	29.73	54.99	25.26	AV
	0.389	33.54	0.25	33.79	48.08	14.29	
	1.236	33.03	0.32	33.35	46.00	12.65	
	2.707	31.62	0.39	32.01	46.00	13.99	
	5.805	25.48	0.46	25.94	50.00	24.06	
	15.552	25.37	0.69	26.06	50.00	23.94	

TEST ENGINEER: HUGH HUANG

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 48%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : HDMI 1360*768@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μ V)	Factor (dB)	Emission Level dB(μ V)	Limits dB(μ V)	Margin (dB)	Remark
Line	0.170	28.54	0.22	28.76	64.94	36.18	QP
	0.389	33.88	0.28	34.16	58.08	23.92	
	1.236	40.21	0.32	40.53	56.00	15.47	
	4.926	32.10	0.44	32.54	56.00	23.46	
	5.805	39.34	0.45	39.79	60.00	20.21	
	16.839	36.61	0.78	37.39	60.00	22.61	
	0.170	26.11	0.22	26.33	54.94	28.61	AV
	0.389	32.06	0.28	32.34	48.08	15.74	
	1.236	32.81	0.32	33.13	46.00	12.87	
	4.926	25.61	0.44	26.05	46.00	19.95	
	5.805	32.02	0.45	32.47	50.00	17.53	
	16.839	29.76	0.78	30.54	50.00	19.46	
Neutral	0.169	32.28	0.20	32.48	64.99	32.51	QP
	0.389	34.96	0.25	35.21	58.08	22.87	
	1.236	39.05	0.32	39.37	56.00	16.63	
	4.721	34.41	0.45	34.86	56.00	21.14	
	5.867	37.34	0.46	37.80	60.00	22.20	
	15.552	31.59	0.69	32.28	60.00	27.72	
	0.169	29.56	0.20	29.76	54.99	25.23	AV
	0.389	33.26	0.25	33.51	48.08	14.57	
	1.236	31.32	0.32	31.64	46.00	14.36	
	4.721	29.83	0.45	30.28	46.00	15.72	
	5.867	32.00	0.46	32.46	50.00	17.54	
	15.552	24.60	0.69	25.29	50.00	24.71	

TEST ENGINEER: HUGH HUANG

4 RADIATED EMISSION TEST


4.1 Test Equipment

The following test equipments are used during the radiated emission test in a semi-anechoic chamber:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Test Receiver	R&S	ESVS10	844594/001	Mar 07, 2009	Mar 07, 2010
2.	Preamplifier	Agilent	8447D	2944A10548	Mar 19, 2009	Sep 19, 2009
3.	Bi-log Antenna	TESEQ	CBL6112D	23193	May 14, 2008	May 14, 2010
4.	Spectrum	Agilent	E7405A	MY45106600	May 19, 2009	May 19, 2010
5.	Software	Audix	E3	SET00200 9912M295-2	--	--


4.2 Block Diagram of Test Setup

4.2.1 EUT and Peripherals



■ : Ferrite core

4.2.2 Radiated emission test setup



■ : 50 ohm Coaxial Switch

4.3 Radiated Emission Limit [FCC Part 15 Subpart B 15.109(a)]

Frequency (MHz)	Distance (m)	Field strength limits	
		($\mu\text{V/m}$)	dB ($\mu\text{V/m}$)
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
Above 960	3	500	54.0

NOTE 1 - Emission Level dB ($\mu\text{V/m}$) = 20 log Emission Level ($\mu\text{V/m}$)

NOTE 2 - The tighter limit applies at the band edges.

NOTE 3 - Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

NOTE 4 - The limits shown are based on Quasi-peak value detector.

4.4 Test Configuration

The configuration of the EUT and peripherals are same as those used in conducted emission test.

Please refer to Sec.3.4.

4.5 Operating Condition of EUT

Same as conducted emission test which is listed in Sec.3.5, except for the test setup replaced by Sec.4.2.

4.6 Test Procedures

The EUT and peripherals were placed on a FRP turntable that is 0.8 meter above ground. The FRP turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. Broadband antenna (Calibrated Bilog Antenna) was used as receiving antenna. The antenna moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarizations of the antenna were set on measurement. In order to find the maximum emission, all of the interference cables were manipulated according to ANSI C63.4:2003 requirements during radiated emission test.

The bandwidth of Test Receiver R&S ESVS10 was set at 120 kHz.

The frequency range from 30 MHz to 1000MHz was checked for all test modes.

The test modes were done on radiated disturbance test and all the test results are listed in Sec.4.7.

4.7 Test Results

<PASS>

The frequency and amplitude of the highest radiated emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Test Mode	Data Page
D-Sub 640*480@60Hz	P22
D-Sub 1024*768@60Hz	P23
D-Sub 1360*768@60Hz	P24
HDMI 640*480@60Hz	P25
HDMI 1024*768@60Hz	P26
HDMI 1360*768@60Hz	P27

NOTE 1 – Emission Level = Antenna Factor + Cable Loss + Meter Reading.

NOTE 2 – The emission levels that are 20dB below the official limit are not reported.

NOTE 3 – 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.

NOTE 4 – The worst case is for HDMI 1360*768@60Hz test mode. The worst emission at horizontal polarization was detected at 244.370 MHz with corrected signal level of 42.01 dB ($\mu\text{V}/\text{m}$) (limit is 46.00dB ($\mu\text{V}/\text{m}$)), when the antenna was 1.00 m height and the turntable was at 120°. The worst emission at vertical polarization was detected at 530.520 MHz with corrected signal level of 40.81 dB ($\mu\text{V}/\text{m}$) (limit is 46.00 dB ($\mu\text{V}/\text{m}$)), when the antenna was 1.00 m height and the turntable was at 315°.

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 60%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : D-Sub 640*480@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	97.900	18.39	11.11	1.07	30.57	43.50	12.93
	151.250	20.56	11.19	1.23	32.98	43.50	10.52
	234.670	26.14	12.32	1.66	40.12	46.00	5.88
	299.660	13.38	13.90	1.88	29.16	46.00	16.84
	526.640	16.12	18.24	2.51	36.87	46.00	9.13
	809.880	13.53	20.80	3.21	37.54	46.00	8.46
Vertical	33.880	14.18	17.44	0.64	32.26	40.00	7.74
	120.210	16.24	12.98	1.15	30.37	43.50	13.13
	242.430	21.26	12.64	1.67	35.57	46.00	10.43
	301.600	9.99	13.97	1.89	25.85	46.00	20.15
	526.640	15.02	18.24	2.51	35.77	46.00	10.23
	608.120	16.14	19.25	2.76	38.15	46.00	7.85

TEST ENGINEER: RAVEN JIN

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 60%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : D-Sub1024*768@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μ V/m)	Limits dB (μ V/m)	Margin (dB)
Horizontal	97.900	18.99	11.11	1.07	31.17	43.50	12.33
	151.250	20.99	11.19	1.23	33.41	43.50	10.09
	259.890	23.63	13.10	1.74	38.47	46.00	7.53
	300.630	14.58	13.93	1.88	30.39	46.00	15.61
	530.520	20.16	18.30	2.53	40.99	46.00	5.01
	809.880	14.50	20.80	3.21	38.51	46.00	7.49
Vertical	34.850	14.77	16.97	0.65	32.39	40.00	7.61
	152.220	19.60	11.09	1.25	31.94	43.50	11.56
	238.550	21.59	12.48	1.67	35.74	46.00	10.26
	302.570	10.43	13.97	1.89	26.29	46.00	19.71
	530.520	17.21	18.30	2.53	38.04	46.00	7.96
	608.120	15.97	19.25	2.76	37.98	46.00	8.02

TEST ENGINEER: RAVEN JIN

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 60%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : D-Sub1360*768@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μ V/m)	Limits dB (μ V/m)	Margin (dB)
Horizontal	97.900	22.51	11.11	1.07	34.69	43.50	8.81
	142.520	19.66	11.91	1.20	32.77	43.50	10.73
	244.370	26.65	12.68	1.68	41.01	46.00	4.99
	302.570	13.66	13.97	1.89	29.52	46.00	16.48
	530.520	19.80	18.30	2.53	40.63	46.00	5.37
	809.880	14.18	20.80	3.21	38.19	46.00	7.81
Vertical	33.880	14.49	17.44	0.64	32.57	40.00	7.43
	114.390	17.50	12.64	1.13	31.27	43.50	12.23
	250.190	22.16	12.90	1.70	36.76	46.00	9.24
	299.660	10.76	13.90	1.88	26.54	46.00	19.46
	530.520	17.98	18.30	2.53	38.81	46.00	7.19
	608.120	18.63	19.25	2.76	40.64	46.00	5.36

TEST ENGINEER: RAVEN JIN

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 60%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : HDMI 1024*768@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	97.900	19.99	11.11	1.07	32.17	43.50	11.33
	151.250	21.99	11.19	1.23	34.41	43.50	9.09
	259.890	24.63	13.10	1.74	39.47	46.00	6.53
	300.630	14.58	13.93	1.88	30.39	46.00	15.61
	530.520	19.16	18.30	2.53	39.99	46.00	6.01
	809.880	12.50	20.80	3.21	36.51	46.00	9.49
Vertical	87.230	21.68	8.96	1.00	31.64	40.00	8.36
	152.220	21.60	11.09	1.25	33.94	43.50	9.56
	238.550	23.59	12.48	1.67	37.74	46.00	8.26
	302.570	12.43	13.97	1.89	28.29	46.00	17.71
	530.520	19.21	18.30	2.53	40.04	46.00	5.96
	608.120	16.97	19.25	2.76	38.98	46.00	7.02

TEST ENGINEER: RAVEN JIN

EUT : LCD TV Temperature : 22°C

Model No. : ELCHS262 Humidity : 60%RH

Serial No. : E2009080301 Date of Test : Aug 04, 2009

Test Mode : HDMI 1360*768@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	32.910	4.02	17.95	0.64	22.61	40.00	17.39
	97.900	23.51	11.11	1.07	35.69	43.50	7.81
	244.370	27.65	12.68	1.68	42.01	46.00	3.99
	302.570	13.66	13.97	1.89	29.52	46.00	16.48
	530.520	18.80	18.30	2.53	39.63	46.00	6.37
	809.880	13.18	20.80	3.21	37.19	46.00	8.81
Vertical	33.880	16.49	17.44	0.64	34.57	40.00	5.43
	137.670	17.06	12.19	1.19	30.44	43.50	13.06
	250.190	24.16	12.90	1.70	38.76	46.00	7.24
	299.660	10.76	13.90	1.88	26.54	46.00	19.46
	530.520	19.98	18.30	2.53	40.81	46.00	5.19
	608.120	16.63	19.25	2.76	38.64	46.00	7.36

TEST ENGINEER: RAVEN JIN

5 DEVIATION TO TEST SPECIFICATIONS

None.


6 DEBUG DESCRIPTION

The following components are used during the countermeasure procedures:

Name	M/N	Specifications (mm)	Manufacturer	Location
Ferrite Core	ZCAT3035-1330 \ROH	30*35*13	ROH	See Internal Photo Figure 14
Ferrite Core	ZCAT2132-1130 \ROH	21*32*11	ROH	See Internal Photo Figure 15
Ferrite Core	ZCAT3035-1330 \ROH	30*35*13	ROH	See Internal Photo Figure 16

Note: We had required the applicant and manufacturer that all electrical and mechanical devices employed for spurious radiation suppression, including any modifications made during certification testing, must be incorporated in each unit marked

TEST ENGINEER:



(RAVEN JIN)