

RF Exposure Calculations

SAF Tehnika	Model: 58F2DMX Sprint MXM		Test Number: 170615 (For Point to Point operation only)				
MPE Calculator	MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi.						
	dBi = dB gain compared to an isotropic radiator.						
	S = power density in mW/cm ²						
		Output Power	dBd + 2.17 = dBi		Antenna Gain (dBi)	41.2	
		Maximum (Watts)	1.000000		dBi to dBd	2.2	
Tx Frequency (MHz)	5785				Antenna Gain (dBd)	39.03	
Cable Loss (dB)	0.0	(dBm)	30.0		Antenna minus cable (dBi)	41.20	
	Calculated ERP (mw)	7998342.550	EIRP = Po(dBm) + Gain (dB)				
	Calculated EIRP (mw)	13182567.386			Radiated (EIRP) dBm	71.200	
		Power density (S)	ERP = EIRP - 2.17 dB				
		EIRP			Radiated (ERP) dBm	69.030	
		----- = mW/cm ²					
		4 π r ²					
		EIRP (mW), r (cm)					
	Occupational Limit	FCC radio frequency radiation exposure limits per 1.1310					
5	mW/cm ²	Frequency (MHz)	Occupational Limit (mW/cm ²)	Public Limit (mW/cm ²)			
50	W/m ²	300-1,500	ƒ300	ƒ1500			
	General Public Limit	1,500-10,000	5	1			
1	mW/cm ²						
10	W/m ²						
	Occupational Limit	IC radio frequency radiation exposure limits per RSS-102					
0.6455 ^{f^{0.5}}	W/m ²	Frequency (MHz)	Occupational Limit (W/m ²)	Public Limit (W/m ²)			
49.09621	W/m ²	100-6,000	0.6455 ^{f^{0.5}}				
	General Public Limit	6,000-15,000	50				
0.02619 ^{f^{0.6834}}	W/m ²	48-300		1.291			
9.75649	W/m ²	300-6,000		0.02619 ^{f^{0.6834}}			
		6,000-15,000	50	10			
EIRP	S	S	Distance	Distance	Distance	Distance	
milliwatts	mW/cm ²	W/m ²	cm	meter	inches	Feet	
13182567.386	0.26226	2.62259	2000.00	20.00	787.40	65.62	
13182567.386	0.46624	4.66238	1500.00	15.00	590.55	49.21	
13182567.386	0.53522	5.35222	1400.00	14.00	551.18	45.93	
13182567.386	0.62073	6.20731	1300.00	13.00	511.81	42.65	
13182567.386	0.72850	7.28497	1200.00	12.00	472.44	39.37	
13182567.386	0.86697	8.66971	1100.00	11.00	433.07	36.09	
13182567.386	0.95151	9.51506	1050.00	10.50	413.39	34.45	
13182567.386	1.04904	10.49035	1000.00	10.00	393.70	32.81	
13182567.386	1.29511	12.95105	900.00	9.00	354.33	29.53	
13182567.386	1.63912	16.39118	800.00	8.00	314.96	26.25	
13182567.386	2.14089	21.40889	700.00	7.00	275.59	22.97	
13182567.386	2.91399	29.13987	600.00	6.00	236.22	19.69	
13182567.386	4.19614	41.96142	500.00	5.00	196.85	16.40	
13182567.386	4.85159	48.51592	465.00	4.650	183.07	15.26	
13182567.386	4.95763	49.57634	460.00	4.600	181.10	15.09	
13182567.386	5.18042	51.80422	450.00	4.500	177.17	14.76	
13182567.386	6.55647	65.56471	400.00	4.000	157.48	13.12	
		Frequency (MHz)	Occupational Limit minimum Distance (meters)	Public Limit minimum distance (meters)			
		47CFR 1.1310	4.65	10.50			
		RSS-102	4.65	10.50			

Rogers Labs, Inc.
 4405 W. 259th Terrace
 Louisburg, KS 66053
 Phone/Fax: (913) 837-3214
 Revision 1

SAF Tehnika AS
 Models: S06SPR18L and S06SPR18H
 Test #: 170615
 Test to: 47CFR, 15.407, RSS-247
 File: 58F2DMX RFExp

S/N's: 348670100505/348670100505
 FCC ID: W9Z-58F2DMX
 IC: 8855A-58F2DMX
 Date: August 31, 2017
 Page 1 of 1