

RF Exposure Calculations

SAF Tehnika AS	Model: ARANETTPR	Test Number:	171106C			
MPE Calculator	MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi.					
	dBi = dB gain compared to an isotropic radiator.					
	S = power density in mW/cm ²					
		Output Power	dBd + 2.17 = dBd	Antenna Gain (dBi)	1	
Tx Frequency (MHz)	915	Maximum (Watts)	0.029	dBi to dBd	2.2	
				Antenna Gain (dBd)	-1.17	
Cable Loss (dB)	0.0	(dBm)	14.6	Antenna minus cable (dBi)	1.00	
	Calculated ERP (mw)	22.131	EIRP = Po(dBm) + Gain (dB)			
	Calculated EIRP (mw)	36.475		Radiated (EIRP) dBm	15.620	
	Power density (S)		ERP = EIRP - 2.17 dB	Radiated (ERP) dBm	13.450	
	EIRP ----- = mW/cm ² 4 π r ²					
	Occupational Limit	FCC radio frequency radiation exposure limits per 1.1310				
3.05	mW/cm ²	Frequency (MHz)	Occupational Limit (mW/cm ²)	Public Limit (mW/cm ²)		
30.50	W/m ²	300-1,500	ƒ/300	ƒ/1500		
	General Public Limit	1,500-10,000	5	1		
0.61	mW/cm ²					
6.10	W/m ²					
	Occupational Limit	IC radio frequency radiation exposure limits per RSS-102				
0.6455ƒ ^{0.5}	W/m ²	Frequency (MHz)	Occupational Limit (W/m ²)	Public Limit (W/m ²)		
19.52571	W/m ²	100-6,000	0.6455ƒ ^{0.5}			
	General Public Limit	6,000-15,000	50			
0.02619ƒ ^{0.6834}	W/m ²	48-300		1.291		
2.76675	W/m ²	300-6,000		0.02619ƒ ^{0.6834}		
		6,000-15,000	50	10		
EIRP	S	S	Distance	Distance	Distance	Distance
milliwatts	mW/cm ²	W/m ²	cm	meter	inches	Feet
36.475	0.00020	0.00202	120.00	1.20	47.24	3.94
36.475	0.00036	0.00358	90.00	0.90	35.43	2.95
36.475	0.00045	0.00454	80.00	0.80	31.50	2.62
36.475	0.00059	0.00592	70.00	0.70	27.56	2.30
36.475	0.00081	0.00806	60.00	0.60	23.62	1.97
36.475	0.00116	0.01161	50.00	0.50	19.69	1.64
36.475	0.00181	0.01814	40.00	0.40	15.75	1.31
36.475	0.00323	0.03225	30.00	0.30	11.81	0.98
36.475	0.00726	0.07257	20.00	0.20	7.87	0.66
36.475	0.01290	0.12901	15.00	0.15	5.91	0.49
36.475	0.02903	0.29026	10.00	0.100	3.94	0.33
36.475	0.03583	0.35835	9.00	0.090	3.54	0.30
36.475	0.04535	0.45353	8.00	0.080	3.15	0.26
36.475	0.05924	0.59237	7.00	0.070	2.76	0.23
36.475	0.08063	0.80628	6.00	0.060	2.36	0.20
36.475	0.11610	1.16105	5.00	0.050	1.97	0.16
36.475	0.18141	1.81414	4.00	0.040	1.57	0.13
		Frequency (MHz)	Occupational Limit minimum Distance (meters)	Public Limit minimum distance (meters)		
		47CFR 1.1310	0.04	0.20		
		RSS-102	0.04	0.20		

Rogers Labs, Inc.
 4405 W. 259th Terrace
 Louisburg, KS 66053
 Phone/Fax: (913) 837-3214
 Revision 1

SAF Tehnika AS
 Model: TDSPCOU1, Aranet CO₂ Sensor
 Test #: 171106B
 Test to: CFR47 15C, RSS-Gen RSS-247
 File: ARANETCO2 RFExp

S/N's: 00001, 2, 3, 4 and 5
 FCC ID: W9Z-ARANETCO2
 IC: 8855A- ARANETCO2
 Date: February 1, 2018
 Page 1 of 1