

Submittal Application Report

For
Model: Integra-WS-24

Product Marketing Name: Integra-WS-24

Low Power Point-To-Point Transmitter

FCC: W9Z-INTEGRA24W


IC: 8855A-INTEGRA24W


FOR

SAF Tehnika AS

24a, Ganibu dambis
Riga Latvia LV-1005

Test Report Number: 170403
FCC Site Registration: 90910, 315994
IC Test Site Registration: 3041A-1

Authorized Signatory: 
Scot D. Rogers



ROGERS LABS, INC.

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

Engineering Test Report For Grant of Certification Application

For

CFR 47, Paragraph 15.249(b) and
Industry Canada RSS-210 (Annex I)
License Exempt Intentional Radiator Module

SAF Tehnika AS

24a, Ganibu dambis
Riga Latvia LV-1005

Model: Integra-WS-24

PMN: Integra-WS-24

Low Power Point-To-Point Transmitter

Frequency Range: 24,070 - 24,200 MHz

FCC ID: W9Z-INTEGRA24W

IC: 8855A-INTEGRA24W

Test Report Number: 170403

Test Date: April 3, 2017

Authorized Signatory: *Scot D. Rogers*

Scot D. Rogers
Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Telephone/Facsimile: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory.
This report must not be used by the client to claim product certification, approval, or
endorsement by NVLAP, NIST, or any agency of the Federal Government.

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 3

SAF Tehnika AS
Model: Integra-WS-24
Test #: 170403
Test to: 47CFR 15.249(b), RSS-210
File: SAF Tehnika Integra-WS-24 TstRpt 170403 r3Page 2 of 32

PMN: Integra-WS-24
FCC: W9Z-INTEGRA24W
IC: 8855A-INTEGRA24W
Date: June 7, 2017

Table Of Contents

TABLE OF CONTENTS.....	3
REVISIONS.....	4
FORWARD	5
OPINION / INTERPRETATION OF RESULTS	5
EQUIPMENT TESTED.....	6
Equipment Function and Configuration	6
Configuration options for the EUT	6
APPLICATION FOR CERTIFICATION.....	7
APPLICABLE STANDARDS & TEST PROCEDURES	8
EQUIPMENT TESTING PROCEDURES	8
AC Line Conducted Emission Test Procedure.....	8
Radiated Emission Test Procedure	8
Diagram 1 Test arrangement for Conducted emissions.....	9
Diagram 2 Test arrangement for radiated emissions of tabletop equipment	10
Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)	11
TEST SITE LOCATIONS	11
LIST OF TEST EQUIPMENT	12
UNITS OF MEASUREMENTS	13
ENVIRONMENTAL CONDITIONS.....	13
INTENTIONAL RADIATORS.....	13
Antenna Requirements.....	13
Restricted Bands of Operation	13
Table 1 Radiated Emissions in Restricted Bands Data.....	14
Summary of Results for Radiated Emissions in Restricted Bands	14

AC Line Conducted Emissions Procedure.....15

Figure One AC Line Conducted emissions of EUT line 1 16

Figure Two AC Line Conducted emissions of EUT line 2 16

Table 2 AC Line Conducted Emissions Data L1 17

Table 3 AC Line Conducted Emissions Data L2 17

Summary of Results for AC Line Conducted General Emissions..... 17

General Radiated Emissions Procedure18

Table 4 General Radiated Emissions from EUT Data..... 19

Summary of Results for General Radiated Emissions..... 19

Operation in the Band 24.05-24.25 GHz.....20

Figure Three Radiated Emissions in Band (40 MHz Channels Across the Frequency Band).....21

Figure Four Radiated Emissions in Band (80 MHz Channels Across the Frequency Band)21

Figure Five 99% Occupied Bandwidth (40 MHz Operation).....22

Figure Six 99% Occupied Bandwidth (40 MHz Operation)22

Figure Seven 99% Occupied Bandwidth (40 MHz Operation)23

Figure Eight 99% Occupied Bandwidth (80 MHz Operation)23

Figure Nine 99% Occupied Bandwidth (80 MHz Operation)24

Table 5 Transmitter Radiated Emissions.....25

Table 6 Transmitter Frequency Stability Data (Temperature)25

Table 7 Transmitter Frequency Stability Data (Voltage)26

Summary of Results for Transmitter Radiated Emissions.....26

STATEMENT OF MODIFICATIONS AND DEVIATIONS 26

ANNEX..... 27

Annex A Measurement Uncertainty Calculations28

Annex B Rogers Labs Test Equipment List29

Annex C Rogers Qualifications.....30

Annex D FCC Site Registration Letter31

Annex E Industry Canada Site Registration Letter.....32

Revisions

Revision 3 Issued June 7, 2017 – corrected type errors page 5 (frequency Range)

Forward

This report documents supporting information for requesting Grant of Certification for low power equipment operating per 47CFR Paragraph 15.249 and Industry Canada RSS-210 Issue 9 (annex I). The results have been reviewed and equipment found to demonstrate compliance with all the requirements investigated for this report.

Name of Applicant: SAF Tehnika AS
 24a, Ganibu dambis
 Riga Latvia LV-1005

Model: Integra-WS-24
 PMN: Integra-WS-24

FCC ID: W9Z-INTEGRA24W FRN: 0018662312

IC: 8855A-INTEGRA24W

Frequency Range: 24,070 - 24,230 MHz

Operating Power: Peak Radiated field strength 126.9 dB μ V/m @ 3 meters Average 118.6
 Occupied Bandwidth: 37200 (40 MHz Channel), 75400 (80 MHz Channel)

Channel (MHz)	Frequency Band (MHz)	Occupied Band Width (kHz)
40	24070-24230	37,200
80	24090-24210	75,400

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Emissions as per CFR 47 paragraphs 2 and 15.205, RSS-210	-2.0	Complies
Emissions as per CFR 47 paragraphs 2 and 15.207, RSS-210	-9.6	Complies
Emissions as per CFR 47 paragraphs 2 and 15.209, RSS-210	-5.4	Complies
Harmonic Emissions per CFR 47 15.249, RSS-210	-10.4	Complies

Equipment Tested


<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
EUT (#1)	Integra-WS-24	3884401 00237
EUT (#2)	Integra-WS-24	3884301 00238
Antenna	C24A12T3D306	N/A
AC Adapter	CFIP-AC-PS	3615701 25614
Power Over Ethernet (POE)	CFIP-TPI	3913501 09321
CPU	PP35L	921LBN1

Test results in this report relate only to the items tested.

Equipment Function and Configuration

The EUT is a low power Point-To-Point 24 GHz transmitter with operation capability over the 24,070 - 24,200 MHz frequency band. The design utilizes unique antenna connection point for use with authorized antenna systems. Two test samples were provided for testing, (1) covering frequency band 24,070-24,148 MHz and (2) covering the frequency band 24,148-24,200 MHz. The transmitter provides channel width operation of 40 or 80 MHz. The EUT was assembled with antenna (M/N: C24A12T3D306) and set to transmit on channels during testing. The authorized antennas must comply with requirements of 47CFR and RSS-210 (gain higher than 33 dBi and beam width less than 3.5 degrees). The EUT provides a USB interface, 2 network ports and an SFP (Small Form-factor Pluggable) port. The transmitter offers no other interface connections than those in the configuration presented. The EUT receives power from externally provided POE option as shown in configuration diagram. As requested by the manufacturer and required by regulations, the unit was tested for emissions compliance using the available configurations with the worst-case data presented. Test results in this report relate only to the products described in this report.

Configuration options for the EUT



Application for Certification

- (1) Manufacturer: SAF Tehnika AS
24a, Ganibu dambis
Riga Latvia LV-1005
- (2) Identification: Model: Integra-WS-24, PMN: Integra-WS-24
FCC ID: W9Z-INTEGRA24W IC: 8855A-INTEGRA24W
- (3) Copy of the installation and operating manual: Refer to exhibit for Draft Instruction Manual.
- (4) Description of Circuit Functions, Device Operation: The Integra-WS-24 is a point-to-point communications system incorporating a low power Transmitter. This device features low power Point-To-Point transmitter operation in communications frequency band of 24.05-24.25 GHz.
- (5) Block Diagram with Frequencies: Refer to exhibit for the Block Diagram
- (6) Report of measurements demonstrating compliance with the pertinent technical requirements is provided in this report.
- (7) Photographs of equipment are provided in application exhibits.
- (8) Peripheral equipment or accessories for the equipment. The EUT provides a USB interface, 2 network ports and an SFP (Small Form-factor Pluggable) port. Optional equipment available for the EUT includes AC/DC (Power Over Ethernet) POE power adapter. The available configuration options were investigated for this and other reports in compliance with required standards.
- (9) Transition Provisions of 15.37 are not being requested.
- (10) The equipment is not a scanning receiver.
- (11) The equipment is not a transmitter operating in the 59-64 GHz frequency range.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This section is not applicable to this equipment.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

Applicable Standards & Test Procedures

In accordance with the Federal Communications Code of Federal Regulations, dated October 1, 2016, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.249, and RSS-210 Issue 9 and RSS-Gen Issue 4 the following information is submitted. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2013.


Equipment Testing Procedures

AC Line Conducted Emission Test Procedure

Testing for the AC line-conducted emissions was performed as defined in ANSI C63.10-2013. The test setup, including the EUT, was arranged in the test configurations as presented during testing. The test configuration was placed on a 1 x 1.5-meter wooden bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- μ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to diagram 1 showing typical test arrangement and photographs in exhibits for EUT placement used during testing.


Radiated Emission Test Procedure

The EUT was placed on a rotating 0.9 x 1.2 platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. Radiated emissions testing was performed as required in CFR47 15, RSS-210 and specified ANSI C63.10-2013. EMI energy was maximized by equipment placement, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. The frequency spectrum from 9 kHz to 105,000 MHz was searched for during preliminary investigation. Refer to diagrams 2 and 3 showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.




1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long see (see 6.2.3.2).
2. The I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.2.2).
3. EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. LISN may be placed on top of, or immediately beneath, reference ground plane (see 6.2.2 and 6.2.3).
 - 3.1 All other equipment powered from additional LISN(s).
 - 3.2 Multiple-outlet strip can be used for multiple power cords of non-EUT equipment.
 - 3.3 LISN at least 80 cm from nearest part of EUT chassis
4. Non-EUT components of EUT system being tested
5. Rear of EUT, including peripherals, shall all be aligned and flush with edge of tabletop (see 6.2.3.2).
6. Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane (see 6.2.2 for options).
7. Antenna may be integral or detachable. If detachable, the antenna shall be attached for this test.

Diagram 1 Test arrangement for Conducted emissions



1. A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).
 - 1.1 LISN spaced at least 80 cm from nearest part of EUT chassis.
2. Antenna can be integral or detachable, depending on the EUT (see 6.3.1).
3. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).
4. For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 2 Test arrangement for radiated emissions of tabletop equipment



Frequency: 9 kHz-30 MHz	Frequency: 30 MHz- 1 GHZ	Frequency: Above 1 GHz
Loop Antenna	Broadband Biconilog	Horn
RBW = 9 kHz	RBW = 120 kHz	RBW = 1 MHz
VBW = 30 kHz	VBW = 120 kHz	VBW = 1 MHz
Sweep time = Auto	Sweep time = Auto	Sweep time = Auto
Detector = PK, QP	Detector = PK, QP	Detector = PK, AV
Antenna Height 1m	Antenna Height 1-4m	Antenna Height 1-4m

Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)

Test Site Locations

Conducted EMI The AC power line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259th Terrace, Louisburg, KS

Radiated EMI The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 West 259th Terrace, Louisburg, KS

Site Registration Refer to Annex for Site Registration Letters

NVLAP Accreditation Lab code 200087-0

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 3

SAF Tehnika AS
Model: Integra-WS-24
Test #: 170403
Test to: 47CFR 15.249(b), RSS-210
File: SAF Tehnika Integra-WS-24 TstRpt 170403 r3

PMN: Integra-WS-24
FCC: W9Z-INTEGRA24W
IC: 8855A- INTEGRA24W
Date: June 7, 2017

List of Test Equipment

A Rohde and Schwarz ESU40 and/or Hewlett Packard 8591EM was used as the measuring device for the emissions testing of frequencies below 1 GHz. A Rohde and Schwarz ESU40 and/or Hewlett Packard 8562A Spectrum Analyzer was used as the measuring device for testing the emissions at frequencies above 1 GHz. The analyzer settings used are described in the following table. Refer to the appendix for a complete list of test equipment.

AC Line Conducted Emissions (0.150 -30 MHz)		
RBW	AVG. BW	Detector Function
9 kHz	30 kHz	Peak / Quasi Peak
Emissions (30-1000 MHz)		
RBW	AVG. BW	Detector Function
120 kHz	300 kHz	Peak / Quasi Peak
Emissions (Above 1000 MHz)		
RBW	Video BW	Detector Function
100 kHz	100 kHz	Peak
1 MHz	1 MHz	Peak / Average

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date</u>	<u>Due</u>
<input checked="" type="checkbox"/> LISN	FCC	FCC-LISN-50-2-10(1PA) (160611)	.15-30MHz	5/16	5/17
<input checked="" type="checkbox"/> Cable	Time Microwave	750HF290-750 (L10M)	9kHz-40 GHz	10/16	10/17
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/16	10/17
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/16	10/17
<input type="checkbox"/> Antenna	ARA	BCD-235-B (169)	20-350MHz	10/16	10/17
<input type="checkbox"/> Antenna	EMCO	3147 (40582)	200-1000MHz	10/16	10/17
<input checked="" type="checkbox"/> Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	5/16	5/18
<input type="checkbox"/> Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/15	10/17
<input checked="" type="checkbox"/> Antenna	Com Power	AH-840 (101046)	18-40 GHz	5/16	5/18
<input checked="" type="checkbox"/> Antenna	Com Power	AL-130 (121055)	.001-30 MHz	10/16	10/17
<input checked="" type="checkbox"/> Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/16	10/17
<input type="checkbox"/> Antenna	EMCO	3143 (9607-1277)	20-1200 MHz	5/16	5/17
<input type="checkbox"/> Analyzer	HP	8591EM (3628A00871)	9kHz-1.8GHz	5/16	5/17
<input checked="" type="checkbox"/> Analyzer	HP	8562A (3051A05950)	9kHz-110GHz	5/16	5/17
<input checked="" type="checkbox"/> Analyzer	HP External Mixers	11571, 11970	25GHz-110GHz	5/16	5/17
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	5/16	5/17
<input checked="" type="checkbox"/> Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/16	10/17
<input checked="" type="checkbox"/> Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/16	10/17
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/16	10/17
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/13	10/14

Units of Measurements

Conducted EMI Data is in dB μ V; dB referenced to one microvolt

Radiated EMI Data is in dB μ V/m; dB/m referenced to one microvolt per meter

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Gain = amplification gains and/or cable losses

RFS (dB μ V/m @ 3m) = FSM (dB μ V) + A.F. (dB) - Gain (dB)

Environmental Conditions

Ambient Temperature	21.6° C
Relative Humidity	48%
Atmospheric Pressure	996.8 mb

Intentional Radiators

As per 47CFR, 15.249(b), RSS-GEN, and RSS-210 (Annex I) Issue 9, August 2016, the following information is submitted for consideration in obtaining a grant of certification for unlicensed low power Point-To-Point Transmitter.

Antenna Requirements

The design utilizes a unique antenna mount offering connection for approved antenna systems. The end product is marketed and sold for professional installation only. The antenna connection point complies with the unique antenna connection requirements.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values take into account the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

Table 1 Radiated Emissions in Restricted Bands Data

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
24000.0	47.3	N/A	40.2	47.8	N/A	40.6	54.0
96280.0	64.4	N/A	51.6	64.4	N/A	51.9	54.0
96440.0	64.6	N/A	51.9	64.6	N/A	51.9	54.0
96920.0	64.6	N/A	52.0	64.8	N/A	51.9	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of restricted bands of operation. The EUT worst-case configuration demonstrated minimum margin of -2.0 dB below the limits. Other emissions were present with amplitudes at least 20 dB below the required limits.

AC Line Conducted Emissions Procedure

The EUT was arranged in typical equipment configurations (POE and AC power adapter). Testing was performed with the EUT placed on a 1 x 1.5-meter wooden bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. Testing for the line-conducted emissions were the procedures of ANSI C63.10-2013. The AC adapter for the EUT was connected to the LISN for line-conducted emissions testing. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the EUT. All power cords except the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor, internal to the LISN. Power line conducted emissions testing was carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequencies of each of the emissions, which had the highest amplitudes. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz then data was recorded with maximum conducted emissions levels. Refer to Figures one and two showing plots of the worst-case AC Line conducted emissions frequency spectrum taken in the screen room.




Figure One AC Line Conducted emissions of EUT line 1




Figure Two AC Line Conducted emissions of EUT line 2

Table 2 AC Line Conducted Emissions Data L1

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	150.000000000 kHz	41.05	Quasi Peak	-24.95
1	174.000000000 kHz	55.13	Quasi Peak	-9.64
2	178.000000000 kHz	44.91	Average	-9.66
1	234.000000000 kHz	45.82	Quasi Peak	-16.48
2	238.000000000 kHz	34.13	Average	-18.03
2	8.720000000 MHz	29.01	Average	-20.99
1	9.628000000 MHz	39.22	Quasi Peak	-20.78
1	10.112000000 MHz	39.66	Quasi Peak	-20.34
2	10.136000000 MHz	31.83	Average	-18.17
2	10.344000000 MHz	32.05	Average	-17.95
1	10.804000000 MHz	39.58	Quasi Peak	-20.42
2	26.496000000 MHz	27.28	Average	-22.72

Other emissions present had amplitudes at least 20 dB below the limit.

Table 3 AC Line Conducted Emissions Data L2

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	174.000000000 kHz	55.05	Quasi Peak	-9.72
2	178.000000000 kHz	43.33	Average	-11.25
1	234.000000000 kHz	45.61	Quasi Peak	-16.70
2	238.000000000 kHz	32.36	Average	-19.81
2	7.932000000 MHz	28.32	Average	-21.68
1	7.964000000 MHz	36.81	Quasi Peak	-23.19
2	8.268000000 MHz	30.16	Average	-19.84
2	8.916000000 MHz	32.61	Average	-17.39
1	8.924000000 MHz	40.92	Quasi Peak	-19.08
1	10.228000000 MHz	43.06	Quasi Peak	-16.94
1	10.424000000 MHz	43.20	Quasi Peak	-16.80
2	10.572000000 MHz	34.94	Average	-15.06

Other emissions present had amplitudes at least 20 dB below the limit.

Summary of Results for AC Line Conducted General Emissions

The EUT demonstrated compliance with the conducted emissions requirements of 47CFR 15C and RSS-GEN and other applicable standards for Intentional Radiators. The EUT worst-case configuration demonstrated minimum margin of -9.6 dB below the limit. Other emissions were present with recorded data representing the worst-case amplitudes.

General Radiated Emissions Procedure

The EUT was arranged in a typical equipment configuration and operated through all available modes with worst-case data recorded. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated emissions measurements were performed. Final data was taken with the EUT located at the OATS at a distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 100 GHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers from 1 GHz to 100 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

Table 4 General Radiated Emissions from EUT Data

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
44.1	25.7	21.2	N/A	33.3	30.1	N/A	40.0
44.1	24.4	19.0	N/A	33.9	31.8	N/A	40.0
49.3	26.7	20.2	N/A	31.1	25.3	N/A	40.0
52.0	29.3	21.7	N/A	23.8	18.5	N/A	40.0
58.7	23.9	18.4	N/A	24.8	20.7	N/A	40.0
59.7	22.1	15.3	N/A	22.6	16.2	N/A	40.0
63.1	20.2	15.2	N/A	22.4	15.8	N/A	40.0
63.2	22.9	18.4	N/A	23.3	17.9	N/A	40.0
63.7	21.4	16.2	N/A	22.3	16.6	N/A	40.0
68.4	22.4	17.3	N/A	20.5	14.1	N/A	40.0
69.7	22.9	18.3	N/A	19.4	13.6	N/A	40.0
87.8	31.4	27.8	N/A	31.1	27.8	N/A	40.0
125.0	39.6	35.0	N/A	43.1	38.1	N/A	43.5

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of CFR47 Part 15C paragraph 15.209 and RSS-210 Intentional Radiators. The EUT demonstrated a minimum margin of -5.4 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the Band 24.05-24.25 GHz

The transmitter output power; harmonics and general emissions were measured on an open area test site @ 3 meters. The EUT was placed on a turntable elevated as required above the ground plane and at a distance of 3 meters from the FSM antenna. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. The amplitude of each emission was then recorded from the analyzer display. Emissions radiated outside of the specified bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits, whichever is the lesser attenuation. Plots were taken of transmitter performance for reference in this and other documentation. Refer to figures three through nine showing plots taken of the transmitter performance displaying compliance with the specifications. The amplitude of each radiated emission was measured on the OATS at a distance of 3 meters from the FSM. The amplitude of each radiated emission was maximized by varying the FSM antenna height, polarization, and by rotating the turntable. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas and/or mixers from 1 GHz to 100 GHz. Emissions were measured in dB μ V/m @ 3 meters.




Figure Three Radiated Emissions in Band (40 MHz Channels Across the Frequency Band)




Figure Four Radiated Emissions in Band (80 MHz Channels Across the Frequency Band)




Figure Five 99% Occupied Bandwidth (40 MHz Operation)




Figure Six 99% Occupied Bandwidth (40 MHz Operation)




Figure Seven 99% Occupied Bandwidth (40 MHz Operation)




Figure Eight 99% Occupied Bandwidth (80 MHz Operation)




Figure Nine 99% Occupied Bandwidth (80 MHz Operation)

Table 5 Transmitter Radiated Emissions

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
24070.0	126.4	N/A	117.9	119.3	N/A	110.9	128.0
48140.0	66.0	N/A	56.1	69.1	N/A	56.8	68.0
72210.0	69.0	N/A	56.1	68.8	N/A	57.3	68.0
96280.0	64.4	N/A	51.6	64.4	N/A	51.9	68.0
24110.0	126.9	N/A	118.6	119.7	N/A	111.3	128.0
48220.0	69.1	N/A	55.6	69.7	N/A	54.8	68.0
72330.0	68.6	N/A	55.6	69.5	N/A	57.5	68.0
96440.0	64.6	N/A	51.9	64.6	N/A	51.9	68.0
24230.0	126.7	N/A	118.5	119.4	N/A	111.0	128.0
48460.0	70.0	N/A	57.6	69.8	N/A	56.8	68.0
72690.0	69.3	N/A	56.1	68.6	N/A	56.0	68.0
96920.0	64.6	N/A	52.0	64.8	N/A	51.9	68.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 6 Transmitter Frequency Stability Data (Temperature)

Frequency 24.1102097 (GHz)	Frequency Stability Vs Temperature									
	Temperature °C	-30	-20	-10	0	+10	+20	+30	+40	+50
Change (Hz)		-2700	-2000	1300	1600	600	-189400	5700	11000	
%		0.000	0.000	0.000	0.000	0.000	-0.001	0.000	0.000	
Limit ±0.001	--	±0.001	±0.001	±0.001	±0.001	±0.001	±0.001	±0.001	±0.001	±0.001

Table 7 Transmitter Frequency Stability Data (Voltage)

Frequency 24.1102097 (GHz)	Frequency Stability Vs Voltage Variation 120.0 volts nominal		
Voltage V _{ac}	102.0	120.0	138.0
Change (Hz)	0.0	0.0	0.0
%	0.0	0.0	0.0
Limit ±0.001	±0.001	±0.001	±0.001

Summary of Results for Transmitter Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR 15.249 and Industry Canada RSS-GEN and RSS-210 standards for Intentional Radiators. The EUT worst-case configuration demonstrated maximum average amplitude emission of 118.6 dB μ V/m and Peak amplitude of 126.9 dB μ V/m. The EUT worst-case configuration demonstrated minimum radiated harmonic emission -10.4 dB below the limit. The EUT worst-case configuration demonstrated minimum margin of -5.4 dB below the general radiated emission limits. Other radiated emissions found in the restricted bands presented with amplitudes at least 20 dB below limits. Other emissions were present with amplitudes at least 20 dB below the Limits.

Statement of Modifications and Deviations

No modifications to the EUT were required for the equipment to demonstrate compliance with 47CFR 15.249(b) and Industry Canada Radio Standards Specifications RSS-GEN and RSS-210 (Annex I). There were no deviations to the specifications.

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Rogers Labs Test Equipment List
- Annex C Rogers Qualifications
- Annex D FCC Site Registration Letter
- Annex E Industry Canada Site Registration Letter

Annex A Measurement Uncertainty Calculations

Measurement uncertainty calculations were made for the laboratory. Result of measurement uncertainty calculations are recorded below for AC line conducted and radiated emission measurements.

Measurement Uncertainty	$U_{(E)}$	$U_{(lab)}$
3 Meter Horizontal 30-200 MHz Measurements	2.08	4.16
3 Meter Vertical 30-200 MHz Measurements	2.16	4.33
3 Meter Vertical Measurements 200-1000 MHz	2.99	5.97
10 Meter Horizontal Measurements 30-200 MHz	2.07	4.15
10 Meter Vertical Measurements 30-200 MHz	2.06	4.13
10 Meter Horizontal Measurements 200-1000 MHz	2.32	4.64
10 Meter Vertical Measurements 200-1000 MHz	2.33	4.66
3 Meter Measurements 1-6 GHz	2.57	5.14
3 Meter Measurements 6-18 GHz	2.58	5.16
AC Line Conducted	1.72	3.43

Annex B Rogers Labs Test Equipment List

List of Test Equipment	Calibration	Date	Due
Spectrum Analyzer: Rohde & Schwarz ESU40		5/16	5/17
Spectrum Analyzer: HP 8562A, HP Adapters: 11518, 11519, and 11520 Mixers: 11517A, 11970A, 11970K, 11970U, 11970V, 11970W		5/16	5/17
Spectrum Analyzer: HP 8591EM		5/16	5/17
Antenna: EMCO Biconilog Model: 3143		5/16	5/17
Antenna: Sunol Biconilog Model: JB6		10/16	10/17
Antenna: EMCO Log Periodic Model: 3147		10/16	10/17
Antenna: Com Power Model: AH-118		10/16	10/17
Antenna: Com Power Model: AH-840		5/16	5/18
Antenna: Antenna Research Biconical Model: BCD 235		10/16	10/17
Antenna: Com Power Model: AL-130		10/16	10/17
Antenna: EMCO 6509		10/16	10/17
LISN: Compliance Design Model: FCC-LISN-2.Mod.cd, 50 µHy/50 ohms/0.1 µf		10/16	10/17
R.F. Preamp CPPA-102		10/16	10/17
Attenuator: HP Model: HP11509A		10/16	10/17
Attenuator: Mini Circuits Model: CAT-3		10/16	10/17
Attenuator: Mini Circuits Model: CAT-3		10/16	10/17
Cable: Belden RG-58 (L1)		10/16	10/17
Cable: Belden RG-58 (L2)		10/16	10/17
Cable: Belden 8268 (L3)		10/16	10/17
Cable: Time Microwave: 4M-750HF290-750		10/16	10/17
Cable: Time Microwave: 10M-750HF290-750		10/16	10/17
Frequency Counter: Leader LDC825		2/17	2/18
Oscilloscope Scope: Tektronix 2230		2/17	2/18
Wattmeter: Bird 43 with Load Bird 8085		2/17	2/18
Power Supplies: Sorensen SRL 20-25, SRL 40-25, DCR 150, DCR 140		2/17	2/18
R.F. Generators: HP 606A, HP 8614A, HP 8640B		2/17	2/18
R.F. Power Amp 65W Model: 470-A-1010		2/17	2/18
R.F. Power Amp 50W M185- 10-501		2/17	2/18
R.F. Power Amp A.R. Model: 10W 1010M7		2/17	2/18
R.F. Power Amp EIN Model: A301		2/17	2/18
LISN: Compliance Eng. Model 240/20		2/17	2/18
LISN: Fischer Custom Communications Model: FCC-LISN-50-16-2-08		2/17	2/18
Antenna: EMCO Dipole Set 3121C		2/17	2/18
Antenna: C.D. B-101		2/17	2/18
Antenna: Solar 9229-1 & 9230-1		2/17	2/18
Audio Oscillator: H.P. 201CD		2/17	2/18
ELGAR Model: 1751		2/17	2/18
ELGAR Model: TG 704A-3D		2/17	2/18
ESD Test Set 2010i		2/17	2/18
Fast Transient Burst Generator Model: EFT/B-101		2/17	2/18
Field Intensity Meter: EFM-018		2/17	2/18
Shielded Room 5 M x 3 M x 3.0 M			

Annex C Rogers Qualifications

Scot D. Rogers, Engineer

Rogers Labs, Inc.

Mr. Rogers has approximately 17 years' experience in the field of electronics. Engineering experience includes six years in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

Positions Held

Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

Educational Background

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University.
- 2) Bachelor of Science Degree in Business Administration Kansas State University.
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.

Scot D. Rogers

Scot D. Rogers

Annex D FCC Site Registration Letter

FEDERAL COMMUNICATIONS COMMISSION

**Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046**

April 16, 2015

Registration Number: 90910

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053

Attention: Scot Rogers,


Re: Measurement facility located at Louisburg
3 & 10 meter site
Date of Renewal: April 16, 2015

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,



Phyllis Parrish
Industry Analyst

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 3

SAF Tehnika AS
Model: Integra-WS-24
Test #: 170403
Test to: 47CFR 15.249(b), RSS-210
File: SAF Tehnika Integra-WS-24 TstRpt 170403 r3Page 31 of 32

PMN: Integra-WS-24
FCC: W9Z-INTEGRA24W
IC: 8855A- INTEGRA24W
Date: June 7, 2017

Annex E Industry Canada Site Registration Letter



June 08, 2015

OUR FILE: 46405-3041
Authorization No: 010277847-001

Rogers Labs Inc.
4405 West 259th Terrace
Louisburg, KS
USA
66053

Attention: Mr. Scot D. Rogers

Dear Sir:

The Bureau has received your application for the renewal of 3m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (**Site# 3041A-1**). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- The company address code associated to the site(s) located at the above address is: **3041A**

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2009 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2009 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2009 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed **three years**. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL; http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification.bureau@ic.gc.ca Please reference our file and submission number above for all correspondence.

Yours sincerely,

A handwritten signature in black ink that reads "Bill Payn".

Bill Payn
For: Wireless Laboratory Manager
Certification and Engineering Bureau
3701 Carling Ave., Building 94
P.O. Box 11490, Station AH@
Ottawa, Ontario K2H 8S2
Email: certification.bureau@ic.gc.ca

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 3

SAF Tehnika AS
Model: Integra-WS-24
Test #: 170403
Test to: 47CFR 15.249(b), RSS-210
File: SAF Tehnika Integra-WS-24 TstRpt 170403 r3

PMN: Integra-WS-24
FCC: W9Z-INTEGRA24W
IC: 8855A- INTEGRA24W
Date: June 7, 2017