

HPD8-5.2

2.4 M | 8 FT HIGH PERFORMANCE PARABOLIC REFLECTOR ANTENNA, DUAL-POLARIZED, 5.25-5.85GHZ

The HP High Performance Series by RadioWaves offers a full line of high performance parabolic antennas engineered to provide ETSI class 2/3 radiation pattern performance as well as excellent gain. RadioWaves field-proven pre-assembled antennas and robust pole-mounts ensure “set and forget” installation with minimal post-installation maintenance. The included radome ensures robust and reliable performance under the most challenging conditions. If it’s rugged, it must be RadioWaves!



FEATURES AND BENEFITS

- High Performance ETSI Class 2/3* Parabolic Antennas – Excellent performance for a wide range of applications
- Fully Preassembled at the Factory – Simplifies installation on site and guarantees “factory-tested” quality
- Warranty – Industry leading 7-year warranty

*ETSI Class depends on frequency band

SPECIFICATIONS

General

Antenna Type	High Performance Parabolic Reflector Antenna	Standard RF Connector Type	N-Female
Size, nominal	8 ft 2.4 m	Standard RF Connector Suffix	NS (append suffix to model number)
Polarization	Dual		

Electrical

Operating Frequency Band	5.25 - 5.85 GHz	Gain, Low Frequency	40.2 dBi
Half Power Beamwidth, Horizontal	1.5 degrees	Gain, Mid Frequency	40.7 dBi
Half Power Beamwidth, Vertical	1.5 degrees	Gain, High Frequency	41.2 dBi
Cross-Polarization Discrimination	30 dB	VSWR	1.5:1
Front to Back Ratio (F/B)	55 dB	Return Loss	-14 dB

Mechanical

Fine Azimuth Adjustment	+/- 5 degrees
Fine Elevation Adjustment	+/- 5 degrees
Mounting Pipe Diameter, Min	4.5 inch 11.4 cm
Mounting Pipe Diameter, Max	4.5 inch 11.4 cm
Net Weight	424 lbs 194.5 kg
Wind Velocity Operational	90 mph 145 km/h
Wind Velocity Survival Rating	125 mph 201 km/h

Mechanical Configuration	HP8
Axial Force (FA)	2773 lbs 12334 N
Side Force (FS)	1422 lbs 6325 N
Twisting Moment (MT)	4400 ft-lbs 5965 Nm
Operating Temperature Range	-40 to +60 C
Max Pressure, PSIG, (if waveguide interface)	5

Regulatory Compliance

FCC	undeclared
Industry Canada Compliance	undeclared

ETSI	undeclared
RoHS-compliant	Yes

Shipping Information

Package Type	Wood Crate
Gross Weight	1122 lbs 508.9 kg

Dimensions, L x W x H	105 x 63 x 95in 249 x 203 x 218 cm
Shipping Volume	363.67 cu ft 10.3 cu m

Note that all 5.2 models will operate 4.9-6.0 GHz with slightly degraded specifications

Contact RadioWaves Sales for alternate RF interface options. RadioWaves specializes in direct connect solutions for microwave radios.

TECHNICAL DRAWINGS

