

RF Exposure Statement

1. LIMITS

1-1 Limits for FCC

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

| Frequency range (MHz) | Electric field Strength (V/m) | Magnetic field Strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--------------------------|----------------------------------|----------------------------------|--|-----------------------------|
| 0.3 - 1.34..... | 614 | 1.63 | *(100) | 30 |
| 1.34 - 30..... | 824/f | 2.19/f | *(180/ f ²) | 30 |
| 30 - 300..... | 27.5 | 0.073 | 0.2 | 30 |
| 300 - 1500..... | | | f/1500 | 30 |
| 1500 - 100.000..... | | | 1.0 | 30 |

F = frequency in MHz

* = Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. RESULTS

3-1. GSM 850 BAND

| | |
|---|----------|
| Max Average output Power at antenna input terminal (dBm) | 32.800 |
| Max Average output Power at antenna input terminal (mW) | 1905.461 |
| Prediction distance (cm) | 20.000 |
| Prediction frequency (MHz) | 824.200 |
| Antenna Gain(Peak) (dBi) | -1.500 |
| Antenna Gain(numeric) | 0.7 |
| Power density at prediction frequency (mW/cm ²) | 0.26837 |
| MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²) | 0.549 |

3-2. GSM 1900 BAND

| | |
|---|-----------|
| Max Average output Power at antenna input terminal (dBm) | 30.200 |
| Max Average output Power at antenna input terminal (mW) | 1047.129 |
| Prediction distance (cm) | 20.0000 |
| Prediction frequency (MHz) | 1850.2000 |
| Antenna Gain(Peak) (dBi) | -1.20000 |
| Antenna Gain(numeric) | 0.75858 |
| Power density at prediction frequency (mW/cm ²) | 0.158027 |
| MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²) | 1.00000 |