

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR TRANSMITTER

Test Report No. : OT-199-RWD-007

AGR No. : A197A-418

Applicant : Suntech International Ltd.

Address : A-1705, A-1706, Greatvally, 32, Digital-ro 9-gil, Geumcheon-Gu, Seoul, Korea

Manufacturer : Suntech International Ltd.

Address : A-1705, A-1706, Greatvally, 32, Digital-ro 9-gil, Geumcheon-Gu, Seoul, Korea

Type of Equipment : Tracking Device

FCC ID. : WA2ST4310

Model Name : ST4310

Serial number : N/A

Total page of Report : 10 pages (including this page)

Date of Incoming : August 02, 2019

Date of issue : September 02, 2019

SUMMARY


The equipment complies with the regulation; **FCC PART Part 2, Part 22 Subpart H, Part 24 Subpart E, Part 27 Subpart C** This test report only contains the result of a single test of the sample supplied for the examination. It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:



Tae-Ho, Kim / Senior Manager
ONETECH Corp.

Approved by:



Ki-Hong, Nam / Chief Engineer
ONETECH Corp.

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT	5
3. EUT MODIFICATIONS	6
4. MAXIMUM PERMISSIBLE EXPOSURE	7
4.1 RF EXPOSURE CALCULATION	7
IMPORTANT NOTE:	7
4.2 EUT DESCRIPTION	8
5 EVALUATION RESULTS	9
5.1 ASSESSMENT RESULT OF RF POWER AND ANTENNA GAIN	9
5.1.1 LTE Band 2	9
5.1.2 LTE Band 4	9
5.1.3 LTE Band 5	9
5.1.4 LTE Band 12	9
5.1.5 LTE Band 13	9

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-199-RWD-007	September 02, 2019	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : Suntech International Ltd.
 Address : A-1705, A-1706, Greatvally, 32, Digital-ro 9-gil, Geumcheon-Gu, Seoul, Korea
 Contact Person : Yohan Kim / Manager
 Telephone No. : 82-2-6327-5661
 FCC ID : WA2ST4310
 Model Name : ST4310
 Serial Number : N/A
 Date : September 02, 2019

EQUIPMENT CLASS	PCB-PCS Licensed Transmitter
KIND OF EQUIPMENT	Tracking Device
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.26:2015, KDB Publication 971168 D01
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART Part 2, Part 22 Subpart H, Part 24 Subpart E, Part 27 Subpart C
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The Suntech International Ltd., Model ST4310 (referred to as the EUT in this report) is a Tracking Device. The product specification described herein was obtained from product data sheet or user’s manual.

DEVICE TYPE	Tracking Device			
OPERATING FREQUENCY	LTE Band 2	TX	1 850 MHz ~ 1 910 MHz	
		RX	1 930 MHz ~ 1 990 MHz	
	LTE Band 4	TX	1 710 MHz ~ 1 755 MHz	
		RX	2 110 MHz ~ 2 155 MHz	
	LTE Band 5	TX	824 MHz ~ 849 MHz	
		RX	869 MHz ~ 894 MHz	
	LTE Band 12	TX	699 MHz ~ 716 MHz	
		RX	729 MHz ~ 746 MHz	
	LTE Band 13	TX	777 MHz ~ 787 MHz	
		RX	746 MHz ~ 756 MHz	
	LTE Channel Bandwidth	10 MHz		
	Modulation Type	QPSK, 16QAM		
Maximum EIRP Power	LTE Band 2	21.57 dBm		
	LTE Band 4	20.41 dBm		
Maximum ERP Power	LTE Band 5	22.67 dBm		
	LTE Band 12	22.05 dBm		
	LTE Band 13	21.71 dBm		
ANTENNA TYPE	PIFA Antenna			
ANTENNA GAIN	LTE Band 2	1.16 dBi		
	LTE Band 4	1.13 dBi		
	LTE Band 5	2.14 dBi		
	LTE Band 12	-1.55 dBi		
	LTE Band 13	1.00 dBi		
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	26 MHz			

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500$ mW/cm² for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm² for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm² exposure is calculated as follows:

$$E = \sqrt{(30 * P * G)} / d, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm², Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 * d (m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm²

IMPORTANT NOTE:

To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device. There is no simultaneous operation within the bands used in this EUT

4.2 EUT Description

Kind of EUT	Tracking Device			
Operating Frequency Band	LTE Band 2	TX	1 850 MHz ~ 1 910 MHz	
		RX	1 930 MHz ~ 1 990 MHz	
	LTE Band 4	TX	1 710 MHz ~ 1 755 MHz	
		RX	2 110 MHz ~ 2 155 MHz	
	LTE Band 5	TX	824 MHz ~ 849 MHz	
		RX	869 MHz ~ 894 MHz	
	LTE Band 12	TX	699 MHz ~ 716 MHz	
		RX	729 MHz ~ 746 MHz	
	LTE Band 13	TX	777 MHz ~ 787 MHz	
		RX	746 MHz ~ 756 MHz	
	MAX. RF OUTPUT POWER	LTE Band 2	22.84 dBm	
		LTE Band 4	22.96 dBm	
LTE Band 5		23.64 dBm		
LTE Band 12		23.38 dBm		
LTE Band 13		23.48 dBm		
Antenna Gain	LTE Band 2	1.16 dBi		
	LTE Band 4	1.13 dBi		
	LTE Band 5	2.14 dBi		
	LTE Band 12	-1.55 dBi		
	LTE Band 13	1.00 dBi		
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A			

5 Evaluation Results

5.1 Assessment result of RF Power and Antenna gain

5.1.1 LTE Band 2

Operating Mode	Operating Frequency (MHz)	Avg. Power Level	
		(dBm)	(W)
LTE Band 2	1 905	22.84	0.192

5.1.2 LTE Band 4

Operating Mode	Operating Frequency (MHz)	Avg. Power Level	
		(dBm)	(W)
LTE Band 4	1 750	22.96	0.198

5.1.3 LTE Band 5

Operating Mode	Operating Frequency (MHz)	Avg. Power Level	
		(dBm)	(W)
LTE Band 5	829	23.64	0.231

5.1.4 LTE Band 12

Operating Mode	Operating Frequency (MHz)	Avg. Power Level	
		(dBm)	(W)
LTE Band 12	707.5	23.38	0.218

5.1.5 LTE Band 13

Operating Mode	Operating Frequency (MHz)	Avg. Power Level	
		(dBm)	(W)
LTE Band 13	782	23.48	0.223



Tested by: Ju Yun Park / Assistant Manager

5.1.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

Operating Mode	Operating Frequency (MHz)	Conducted Average Power		Antenna Gain (dBi)		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
		(dBm)	(mW)	Log	Linear			
LTE Band 2	1 905	22.84	192.31	1.16	1.306	4.47	0.050 0	1.00
LTE Band 4	1 750	22.96	197.70	1.13	1.297	4.52	0.051 0	1.00

Operating Mode	Operating Frequency (MHz)	Conducted Average Power		Antenna Gain (dBd)		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
		(dBm)	(mW)	Log	Linear			
LTE Band 5	829	23.64	231.21	2.14	1.637	5.49	0.075 3	0.55
LTE Band 12	707.5	23.38	217.77	-1.55	0.700	3.48	0.030 3	0.47
LTE Band 13	782	23.48	222.84	1.00	1.259	4.72	0.055 8	0.52

$$\text{limit} = 829/1500 = 0.55 \text{ mW/cm}^2$$

$$\text{limit} = 707.5/1500 = 0.47 \text{ mW/cm}^2$$

$$\text{limit} = 782/1500 = 0.52 \text{ mW/cm}^2$$

$$\begin{aligned} \text{LTE Band 2 Power Density} &= \text{Conducted Average Power} * \text{Antenna Gain(dBi)} / (4\pi R^2) \\ &= (192.31 * 1.306) / (4 * \pi * 20^2) = 0.050 0 \text{ mW/cm}^2 \end{aligned}$$

$$\begin{aligned} \text{LTE Band 4 Power Density} &= \text{Conducted Average Power} * \text{Antenna Gain(dBi)} / (4\pi R^2) \\ &= (197.70 * 1.297) / (4 * \pi * 20^2) = 0.051 0 \text{ mW/cm}^2 \end{aligned}$$

$$\begin{aligned} \text{LTE Band 5 Power Density} &= \text{Conducted Average Power} * \text{Antenna Gain(dBd)} / (4\pi R^2) \\ &= (231.21 * 1.637) / (4 * \pi * 20^2) = 0.075 3 \text{ mW/cm}^2 \end{aligned}$$

$$\begin{aligned} \text{LTE Band 12 Power Density} &= \text{Conducted Average Power} * \text{Antenna Gain(dBd)} / (4\pi R^2) \\ &= (217.77 * 0.700) / (4 * \pi * 20^2) = 0.030 3 \text{ mW/cm}^2 \end{aligned}$$

$$\begin{aligned} \text{LTE Band 13 Power Density} &= \text{Conducted Average Power} * \text{Antenna Gain(dBd)} / (4\pi R^2) \\ &= (222.84 * 1.259) / (4 * \pi * 20^2) = 0.055 8 \text{ mW/cm}^2 \end{aligned}$$



Tested by: Ju Yun Park / Assistant Manager