

FCC REPORT

Applicant: Verykool USA Inc
Address of Applicant: 3636 Nobel Drive, Suite 325, San Diego, CA 92122 USA

Equipment Under Test (EUT)

Product Name: SMART PHONE
Model No.: s5012
FCC ID: WA6S5012
Applicable standards: FCC CFR Title 47 Part 15 Subpart B
Date of sample receipt: 25 Jul., 2014
Date of Test: 28 Jul., to 14 Aug., 2014
Date of report issued: 15 Aug., 2014
Test Result: 25 Jul., 2014

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	15 Aug., 2014	Original

Prepared by: Sera Xiang **Date:** 15 Aug., 2014
Report Clerk

Reviewed by: Abanb Yang **Date:** 15 Aug., 2014
Project Engineer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE.....	5
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 LABORATORY FACILITY.....	6
5.6 LABORATORY LOCATION.....	6
5.7 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION.....	11
7 TEST SETUP PHOTO	17
8 EUT CONSTRUCTIONAL DETAILS	19

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	Pass
Radiated Emission	Part15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Verykool USA Inc
Address of Applicant:	3636 Nobel Drive, Suite 325, San Diego, CA 92122 USA
Manufacturer:	Amer Mobile Co.LTD
Address of Manufacturer:	9 th Floor Nongke Commerical center, Hongli West Road Futian District Shenzhen,China

5.2 General Description of E.U.T.

Product Name:	SMART PHONE
Model No.:	s5012
Power supply:	Rechargeable Li-ion Battery DC3.7V-1800mAh
AC adapter :	Model:SC050070-US Input: AC 100-240V 50/60Hz 0.4A Output: DC 5.0V, 700mA

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+recording mode	Keep the EUT in Charging+recording mode
Charging+Play mode	Keep the EUT in Charging+Play mode
FM mode	Keep the EUT in FM receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
 Bao'an District, Shenzhen, Guangdong, China
 Tel: 0755-23118282
 Fax: 0755-23116366

5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	June 09 2014	June 08 2015
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	May 25 2014	May 24 2015
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	May 25 2014	May 24 2015
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Coaxial Cable	CCIS	N/A	CCIS0016	Apr. 01 2014	Mar. 31 2015
6	Coaxial Cable	CCIS	N/A	CCIS0017	Apr. 01 2014	Mar. 31 2015
7	Coaxial cable	CCIS	N/A	CCIS0018	Apr. 01 2014	Mar. 31 2015
8	Coaxial Cable	CCIS	N/A	CCIS0019	Apr. 01 2014	Mar. 31 2015
9	Coaxial Cable	CCIS	N/A	CCIS0087	Apr. 01 2014	Mar. 31 2015
10	Amplifier(10kHz-1.3GHz)	HP	8447D	CCIS0003	Apr. 01 2014	Mar. 31 2015
11	Amplifier(1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	June 09 2014	June 08 2015
12	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Apr. 01 2014	Mar. 31 2015
13	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2014	Mar. 29 2015
14	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
15	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
16	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP	CCIS0023	May. 25 2014	May. 24 2015
17	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	Apr 01 2014	Mar. 31 2015
18	Loop antenna	Laplace instrument	RF300	EMC0701	Aug. 22 2013	Aug. 22 2014
19	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	May. 25 2014	May. 24 2015
20	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	May. 25 2014	May. 24 2015

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	June 09 2014	June 08 2015
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	May 25 2014	May. 24 2015
3	LISN	CHASE	MN2050D	CCIS0074	Apr. 01 2014	Mar. 31 2015
4	Coaxial Cable	CCIS	N/A	CCIS0086	Apr. 01 2014	Mar. 31 2015


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part15 B Section 15.107														
Test Method:	ANSI C63.4:2003														
Test Frequency Range:	150kHz to 30MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9kHz, VBW=30kHz														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>0.5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dB μ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50
Frequency range (MHz)	Limit (dB μ V)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
0.5-30	60	50													
Test setup:	<p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement. 														
Test environment:	Temp.: 23 °C Humid.: 56% Press.: 1 01kPa														
Measurement Record:	Uncertainty: 3.28dB														
Test Instruments:	Refer to section 5.7 for details														
Test mode:	Refer to section 5.3 for details														
Test results:	Pass														

Measurement data:

Line:




Trace: 5

Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 Job No. : 605RF
 EUT : SMART PHONE
 Model : s5012
 Test Mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Carey

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.150	38.27	0.27	10.78	49.32	66.00	-16.68	QP
2	0.150	24.50	0.27	10.78	35.55	56.00	-20.45	Average
3	0.174	35.10	0.27	10.77	46.14	64.77	-18.63	QP
4	0.186	23.40	0.28	10.76	34.44	54.20	-19.76	Average
5	0.226	31.44	0.27	10.75	42.46	62.61	-20.15	QP
6	0.226	19.65	0.27	10.75	30.67	52.61	-21.94	Average
7	0.373	28.95	0.28	10.73	39.96	58.43	-18.47	QP
8	0.373	18.61	0.28	10.73	29.62	48.43	-18.81	Average
9	0.683	12.00	0.22	10.77	22.99	46.00	-23.01	Average
10	0.759	22.80	0.23	10.80	33.83	56.00	-22.17	QP
11	4.407	12.73	0.29	10.87	23.89	46.00	-22.11	Average
12	4.574	24.46	0.29	10.87	35.62	56.00	-20.38	QP

Neutral:



Trace: 7
 Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 Job No. : 605RF
 EUT : SMART PHONE
 Model : s5012
 Test Mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Carey

	Read Freq	LISN Level	Cable Factor	Cable Loss	Limit Level	Over Line	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.150	38.94	0.25	10.78	49.97	66.00	-16.03 QP
2	0.150	23.90	0.25	10.78	34.93	56.00	-21.07 Average
3	0.182	36.14	0.25	10.77	47.16	64.42	-17.26 QP
4	0.186	22.61	0.25	10.76	33.62	54.20	-20.58 Average
5	0.219	17.92	0.25	10.76	28.93	52.88	-23.95 Average
6	0.246	30.34	0.26	10.75	41.35	61.91	-20.56 QP
7	0.373	30.38	0.25	10.73	41.36	58.43	-17.07 QP
8	0.417	17.25	0.26	10.73	28.24	47.51	-19.27 Average
9	0.641	14.38	0.21	10.77	25.36	46.00	-20.64 Average
10	0.647	27.38	0.21	10.77	38.36	56.00	-17.64 QP
11	0.755	15.14	0.19	10.79	26.12	46.00	-19.88 Average
12	0.899	26.65	0.21	10.84	37.70	56.00	-18.30 QP

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

6.2 Radiated Emission


Test Requirement:	FCC Part15 B Section 15.109				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Peak		1MHz	10Hz	Average Value	
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
Above 1GHz	54.0		Average Value		
	74.0		Peak Value		
Test setup:	Below 1GHz				
Test setup:	Above 1GHz				

<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
<p>Test environment:</p>	<p>Temp.: 25 °C Humid.: 55% Press.: 1 01kPa</p>
<p>Measurement Record:</p>	<p style="text-align: right;">Uncertainty: 4.88dB</p>
<p>Test Instruments:</p>	<p>Refer to section 5.7 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Passed</p>

Measurement Data

Below 1GHz

Horizontal:




```

Site       : 3m chamber
Condition  : FCC PART15 CLASS B 3m WULB9163(30M1G) HORIZONTAL
Pro        : 605RF
EUT        : SMART PHONE
Model      : s5012
Test mode  : PC mode
Power Rating : AC 120V/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: Carey
REMARK     :
    
```

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Gain	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	177.509	50.16	9.49	1.36	28.99	32.02	43.50	-11.48	QP
2	314.377	44.71	13.26	1.82	28.48	31.31	46.00	-14.69	QP
3	350.477	43.10	14.27	1.94	28.56	30.75	46.00	-15.25	QP
4	647.386	39.85	18.62	2.78	28.79	32.46	46.00	-13.54	QP
5	721.726	46.69	19.10	2.97	28.58	40.18	46.00	-5.82	QP
6	801.786	40.51	20.06	3.17	28.19	35.55	46.00	-10.45	QP

Vertical:




```

Site       : 3m chamber
Condition  : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL
Pro       : 605RF
EUI       : SMART PHONE
Model     : s5012
Test mode : PC mode
Power Rating : AC 120V/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: Carey
REMARK    :
    
```

	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	54.261	34.09	13.07	0.64	29.80	18.00	40.00	-22.00 QP
2	106.013	34.45	12.59	1.01	29.48	18.57	43.50	-24.93 QP
3	143.830	42.65	8.22	1.28	29.25	22.90	43.50	-20.60 QP
4	177.509	40.78	9.49	1.36	28.99	22.64	43.50	-20.86 QP
5	239.987	57.80	12.09	1.58	28.59	42.88	46.00	-3.12 QP
6	314.377	48.92	13.26	1.82	28.48	35.52	46.00	-10.48 QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 Pro : 605RF
 EUT : SMART PHONE
 Model : s5012
 Test mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Carey
 REMARK :

	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2095.928	44.24	26.97	5.01	40.56	35.66	74.00 -38.34 Peak
2	2095.928	34.75	26.97	5.01	40.56	26.17	54.00 -27.83 Average
3	3480.112	47.06	28.76	6.30	39.46	42.66	74.00 -31.34 Peak
4	3480.112	37.57	28.76	6.30	39.46	33.17	54.00 -20.83 Average
5	5015.753	47.06	31.85	9.12	39.99	48.04	74.00 -25.96 Peak
6	5015.753	37.81	31.85	9.12	39.99	38.79	54.00 -15.21 Average

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 Pro : 605RF
 EUT : SMART PHONE
 Model : s5012
 Test mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Carey
 REMARK :

	ReadAntenna	Cable Preamp	Limit	Over					
Freq	Level	Factor	Loss	Factor	Level				
MHz	dBuV	dB/m	dB	dB	dBuV/m				
1	2036.695	44.97	26.34	4.90	40.73	35.48	74.00	-38.52	Peak
2	2036.695	34.80	26.34	4.90	40.73	25.31	54.00	-28.69	Average
3	3399.987	46.77	28.46	6.44	38.84	42.83	74.00	-31.17	Peak
4	3399.987	36.46	28.46	6.44	38.84	32.52	54.00	-21.48	Average
5	5097.292	47.60	32.11	9.13	40.04	48.80	74.00	-25.20	Peak
6	5097.292	37.81	32.11	9.13	40.04	39.01	54.00	-14.99	Average