



Prüfbericht - Nr.: <i>Test Report No.:</i>		16016173 001		Seite 1 von 18 <i>Page 1 of 18</i>	
Auftraggeber: <i>Client:</i>		Zhongshan K-mate General Elec. Co., Ltd. Fuwan Industrial Zone, Fuwan South Road, Sunwen East Road, East District, Zhongshan, Guangdong, P.R. China			
Gegenstand der Prüfung: FM Transmitter <i>Test item:</i>					
Bezeichnung: <i>Identification:</i>		AT-1500	FCC ID: <i>FCC ID</i>	WAD-AT1500	
Wareneingangs-Nr.: <i>Receipt No.:</i>		173042538	Eingangsdatum: 21.01.2009 <i>Date of receipt:</i>		
Prüfart: <i>Testing location:</i>		TÜV Rheinland (Guangdong) Ltd. EMC Laboratory Guangzhou Auto Market, Yuan Gang Section of Guangshan Road, Guangzhou 510650, P. R. China		Listed test laboratory according to FCC rules section 2.948 for measuring devices under Parts 15	
Prüfgrundlage: <i>Test specification:</i>		ANSI C63.4: 2003 FCC Part 15: 20, Sep. 2007 Subpart C section 15.239			
Prüfergebnis: <i>Test Result:</i>		Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n). <i>The test item passed the test specification(s).</i>			
Prüflaboratorium: <i>Testing Laboratory:</i>		TÜV Rheinland (Guangdong) Ltd.			
geprüft/ tested by:			kontrolliert/ reviewed by:		
07. Apr. 2009 <i>Date</i>		Ricky Liu Project Manager <i>Name/Position</i>	07. Apr. 2009 <i>Date</i>		Liangdong Xie Project Manager <i>Name/Position</i>
		 <i>Unterschrift</i> <i>Signature</i>			 <i>Unterschrift</i> <i>Signature</i>
Sonstiges/ Other Aspects:					
Abkürzungen:		P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet		Abbreviations:	
				P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested	
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>					

Prüfbericht - Nr.:
Test Report No.:

16015495 001

Seite 2 von 18
Page 2 of 18

Test Summary

FCC Rules		Test items	Result
Paragraph	Released Date		
Part 15 Per Section 15.239(c)	20. Sep, 2007	Radiated Spurious Emission	Pass
Part 15 Per Section 15.239(b)	20. Sep, 2007	Inband Radiated Emission	Pass
Part 15 Per Section 15.239(a)	20. Sep, 2007	26dB Bandwidth	Pass

Contents

1	GENERAL REMARKS.....	4
1.1	COMPLEMENTARY MATERIALS	4
2	TEST SITES.....	4
2.1	TEST FACILITIES	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	5
2.3	TRACEABILITY	5
2.4	CALIBRATION.....	5
2.5	MEASUREMENT UNCERTAINTY	6
2.6	LOCATION OF ORIGINAL DATA.....	6
2.7	STATUS OF FACILITY USED FOR TESTING	6
3	GENERAL PRODUCT INFORMATION.....	6
3.1	PRODUCT FUNCTION AND INTENDED USE	6
3.2	RATINGS AND SYSTEM DETAILS	6
3.3	INDEPENDENT OPERATION MODES.....	6
3.4	SUBMITTED DOCUMENTS.....	6
4	TEST SET-UP AND OPERATION MODE	6
4.1	PRINCIPLE OF CONFIGURATION SELECTION.....	6
4.2	TEST OPERATION AND TEST SOFTWARE.....	6
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....	6
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	6
4.5	TEST SET-UP	6
5	TEST RESULTS EMISSION	6
5.1	RADIATED SPURIOUS EMISSION.....	6
5.2	INBAND RADIATED EMISSION	6
5.3	26DB BANDWIDTH.....	6
6	PHOTOGRAPHS OF THE TEST SET-UP	6
7	LIST OF TABLES.....	6
8	LIST OF PHOTOGRAPHS.....	6

Prüfbericht - Nr.:
Test Report No.:

16015495 001

Seite 4 von 18
Page 4 of 18

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix 1: Test result

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Guangdong) Ltd. EMC Laboratory

Guangzhou Auto Market, Yuan Gang Section of Guangshan Road
Guangzhou 510650

P. R. China

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Kind of Equipment	Type	Manufacturer	S/N	Calibrated until	Calibrated Interval
EMI Test Receiver	ESCI	Rohde & Schwarz	100216	26.Nov.2009	1 year
Spectrum Analyzer	FSP30	Rohde & Schwarz	100286	27.Aug.2009	1 year
Trilog-Broadband Antenna	VULB9168	SCHWARZBECK MESS-ELEKTRONIK	210	08.May.2009	2 year
Double-Ridged Waveguide Horn Antenna	HF906	Rohde & Schwarz	100385	18.Jul.2009	2 year
Double-Ridged Waveguide Horn Antenna	HF906	Rohde & Schwarz	100407	08.May.2009	2 year
Standard Gain Horn Antenna	3160-09	EMCO	21642	N/A	N/A
Standard Gain Horn Antenna	3160-09	EMCO	21645	N/A	N/A
Pre-amplifier	AFS33- 18002650- 30-8P-44	MITEQ	1108282	31.Jul.2009	2 year
3m Anechoic Chamber	N/A	Albatross Project GmbH	N/A	16.Apr.2009	3 year
Audio Analyzer	VA-2230A	Kenwood	1008729 0	07.Oct.2008	1 Year

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications.

Prüfbericht - Nr.:
Test Report No.:

16015495 001

Seite 6 von 18
Page 6 of 18

2.5 Measurement Uncertainty

Uncertainty for conducted emissions measurements is ± 2.51 dB.

Uncertainty for radiated emissions measurements is ± 4.94 dB (30M-1GHz) and ± 4.88 dB (> 1GHz)

The reported expanded uncertainty is based on a standard uncertainty multiply by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

2.6 Location of original data

The original copies of test data taken during actual testing were attached at Appendix 1 of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Guangdong) file for certification follow-up purposes.

2.7 Status of facility used for testing

TÜV Rheinland (Guangdong) Ltd. EMC Laboratory; Guangzhou Auto Market, Yuan Gang Section of Guangshan Road, Guangzhou 510650, P. R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements, the register no. 833845

Prüfbericht - Nr.: 16015495 001
Test Report No.:

Seite 7 von 18
Page 7 of 18

3 General Product Information

Brief description of the test sample:

The EUT is a FM transmitter powered by the DC 12V of vehicle battery.

For details, refer to technical documentation and the user manual.

3.1 Product Function and Intended Use

Refer to the Technical Documentation and user manual.

3.2 Ratings and System Details

Frequency range	:	88.1MHz – 107.9MHz
Total Number of channels	:	199 channels
Channel Spacing	:	100 kHz
Modulation Type	:	FM
Type of antenna	:	Integral antenna
Power supply of Bluetooth headset	:	12V DC by vehicle battery
Ports	:	iPod music port & 3.5mm audio port, 12V DC port,
Protection Class	:	III

Refer to the Technical Documentation for further information

Prüfbericht - Nr.:
*Test Report No.:***16015495 001****Seite 8 von 18**
Page 8 of 18

3.3 Independent Operation Modes

RF Tx Off/On with channel adjustable

For further information refer to User Manual

3.4 Submitted Documents

Block Diagram
Schematics
Operation Description
Components List
FCC label and location
User Manual
Internal Photos
External Photos
Application form

4 Test Set-up and Operation Mode

4.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Refer to test set-up in chapter 5.

4.3 Special Accessories and Auxiliary Equipment


None.

4.4 Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the technical document. No additional measures were employed to achieve compliance.

4.5 Test set-up

Diagram 1 of Configuration for Testing Radiated Emission above 1 GHz



Prüfbericht - Nr.:
Test Report No.:

16015495 001

Seite 11 von 18
Page 11 of 18

5 Test Results EMISSION

5.1 Radiated Spurious Emission

RESULT:

Pass

Date of testing	:	30.03.2009
Test specification	:	FCC Part 15 Per Section 15.239(c)
Limits	:	FCC Part 15 Per Section 15.209(a)
Test procedure	:	Procedure specified in ANSI C63.4
Deviations from Standard Test procedures	:	None
Kind of test site	:	3m Semi-anechoic chamber
Operation mode	:	RF transmitting at fix channel with max power (High, Low, Mid)
Power supply	:	DC 12V
Temperature	:	22°C
Humidity	:	50%

Test procedure:

1. The EUT was placed on the top of a rotatable table 0.8 meters above the ground with 3-orthogonal direction and be kept close enough to the receiving antenna. The table was rotated 360 degrees to determine the suspected emission frequency and the position of the worst radiation case with both horizontal and vertical antenna polarization.
2. The EUT was then set 3 meters away from the receiving antenna, which was mounted on a variable-height antenna tower.
3. For each suspected emission frequency recorded in step 1, the EUT was arranged to its worst case that the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to read the maximum emission.

Table 2: Radiated Spurious Emission (Transmitting at channel low)

Frequency	QP	AV	PK	Polarity	Limit		
					QP	AV	PK
[MHz]	[dB μ V/m]			(H/V)	[dB μ V/m]		
52.400	12.7	N/A	N/A	H	40.0	N/A	N/A
55.700	16.5	N/A	N/A	H	40.0	N/A	N/A
97.150	15.8	N/A	N/A	H	43.5	N/A	N/A
108.700	17.2	N/A	N/A	H	43.5	N/A	N/A
35.550	24.4	N/A	N/A	V	40.0	N/A	N/A
44.350	21.3	N/A	N/A	V	40.0	N/A	N/A
47.300	19.3	N/A	N/A	V	40.0	N/A	N/A
50.200	22.4	N/A	N/A	V	40.0	N/A	N/A
55.700	28.9	N/A	N/A	V	40.0	N/A	N/A
71.850	19.4	N/A	N/A	V	40.0	N/A	N/A
*)---							

Table 3: Radiated Spurious Emission (Transmitting at channel mid)

Frequency	QP	AV	PK	Polarity	Limit		
					QP	AV	PK
[MHz]	[dB μ V/m]			(H/V)	[dB μ V/m]		
56.450	19.1	N/A	N/A	H	40.0	N/A	N/A
57.150	18.4	N/A	N/A	H	40.0	N/A	N/A
92.600	14.2	N/A	N/A	H	43.5	N/A	N/A
107.600	15.7	N/A	N/A	H	43.5	N/A	N/A
35.200	23.5	N/A	N/A	V	40.0	N/A	N/A
49.050	23.9	N/A	N/A	V	40.0	N/A	N/A
55.700	28.8	N/A	N/A	V	40.0	N/A	N/A
56.100	28.3	N/A	N/A	V	40.0	N/A	N/A
73.700	21.3	N/A	N/A	V	40.0	N/A	N/A
77.050	20.8	N/A	N/A	V	40.0	N/A	N/A
*)---							

Prüfbericht - Nr.:

16015495 001

Seite 13 von 18

Test Report No.:

Page 13 of 18

Table 4: Radiated Spurious Emission (Transmitting at channel high)

Frequency	QP	AV	PK	Polarity	Limit		
					QP	AV	PK
[MHz]	[dB μ V/m]			(H/V)	[dB μ V/m]		
55.700	18.3	N/A	N/A	H	40.0	N/A	N/A
98.000	16.2	N/A	N/A	H	40.0	N/A	N/A
100.800	17.4	N/A	N/A	H	43.5	N/A	N/A
113.400	18.1	N/A	N/A	H	43.5	N/A	N/A
35.600	22.3	N/A	N/A	V	40.0	N/A	N/A
43.650	21.0	N/A	N/A	V	40.0	N/A	N/A
49.450	20.0	N/A	N/A	V	40.0	N/A	N/A
56.100	27.9	N/A	N/A	V	40.0	N/A	N/A
59.700	21.6	N/A	N/A	V	40.0	N/A	N/A
76.850	20.2	N/A	N/A	V	40.0	N/A	N/A
*)---							

*) Note:

The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz at frequency below 1GHz.

The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz at frequency above 1GHz.

Measurement is made from 30 MHz to 1080 MHz. Disturbances other than those mentioned above are small or not detectable.

Prüfbericht - Nr.:
Test Report No.:

16015495 001

Seite 14 von 18
Page 14 of 18

5.2 Inband Radiated Emission

RESULT:

Pass

Date of testing	:	30.03.2009
Test specification	:	FCC Part 15 Per Section 15.239(b)
Limits	:	FCC Part 15 Per Section 15.239(b)
Test procedure	:	Procedure specified in ANSI C63.4
Deviations from Standard Test procedures	:	None
Kind of test site	:	3m Semi-anechoic chamber
Operation mode	:	RF transmitting at fix channel with max power (High, Low, Mid)
Power supply	:	DC 12V
Temperature	:	22°C
Humidity	:	50%

Test procedure:

1. The EUT was placed on the top of a rotatable table 0.8 meters above the ground with 3-orthogonal direction and be kept close enough to the receiving antenna. The table was rotated 360 degrees to determine the suspected emission frequency and the position of the worst radiation case with both horizontal and vertical antenna polarization.
2. The EUT was then set 3 meters away from the receiving antenna, which was mounted on a variable-height antenna tower.
3. For each suspected emission frequency recorded in step 1, the EUT was arranged to its worst case that the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to read the maximum emission.

Prüfbericht - Nr.: 16015495 001
Test Report No.:

Seite 15 von 18
Page 15 of 18

Table 5: Radiated Inband Emission (Transmitting at channel low)

Frequency	QP	AV	PK	Polarity	Limit		
					QP	AV	PK
[MHz]	[dB μ V/m]			(H/V)	[dB μ V/m]		
88.100	N/A	21.9	22.0	H	N/A	48	68
88.100	N/A	31.0	31.5	V	N/A	48	68
*)---							

Table 6: Radiated Inband Emission (Transmitting at channel mid)

Frequency	QP	AV	PK	Polarity	Limit		
					QP	AV	PK
[MHz]	[dB μ V/m]			(H/V)	[dB μ V/m]		
98.100	N/A	32.1	32.5	H	N/A	48	68
98.100	N/A	30.9	32.0	V	N/A	48	68
*)---							

Table 7: Radiated Inband Emission (Transmitting at channel high)

Frequency	QP	AV	PK	Polarity	Limit		
					QP	AV	PK
[MHz]	[dB μ V/m]			(H/V)	[dB μ V/m]		
107.900	N/A	46.2	46.3	H	N/A	48	68
107.900	N/A	38.8	39.2	V	N/A	48	68
*)---							

*) Note:

The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz at frequency below 1GHz.

Measurement is made from carrier frequency-100 kHz to carrier frequency+100 kHz and maximum reading among the range is listed.

5.3 26dB Bandwidth

RESULT:
Pass

Date of testing	:	30.03.2009
Test specification	:	FCC Part 15 Per Section 15.239(a)
Limits	:	FCC Part 15 Per Section 15.239(a)
Deviations from Standard Test procedures	:	None
Test procedure	:	Procedure specified in ANSI C63.4
Operation mode	:	Continuously transmitting on the measured channel with maximum volume specified by the applicant.
Kind of test site	:	Shielded room
Power supply	:	DC 12V
Temperature	:	22°C
Humidity	:	50%

Test procedure:

1. Set the EUT to proper test channel.
2. Spectrum analyzer setting: Centered Frequency= measured channel, RBW=10kHz, VBW=30kHz.
3. Mark the peak power frequency point and the -26dB upper and lower frequency points.
4. Read the frequency delta value between the -26dB upper and lower frequency points.
5. Repeat step 1 to 4 until all the channels required are finished.

Table 8: 26dB Bandwidth

Channel	Lowest Frequency (MHz)	Highest Frequency (MHz)	Test Result (kHz)
Lowest 88.100MHz	88.016	88.190	174
Middle 98.100MHz	98.017	98.191	174
Highest 107.900MHz	107.817	107.991	174

Please refer to Appendix 1 for measurement data.

Prüfbericht - Nr.:
Test Report No.:

16015495 001

Seite 17 von 18
Page 17 of 18

6 Photographs of the Test Set-Up

Photograph 1: Set-up for Radiation Measurement



7 List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Radiated Spurious Emission (Transmitting at channel low)	6
Table 3: Radiated Spurious Emission (Transmitting at channel mid)	6
Table 4: Radiated Spurious Emission (Transmitting at channel high)	6
Table 5: Radiated Inband Emission (Transmitting at channel low)	6
Table 6: Radiated Inband Emission (Transmitting at channel mid)	6
Table 7: Radiated Inband Emission (Transmitting at channel high)	6
Table 8: 26dB Bandwidth.....	6

8 List of Photographs


Photograph 1: Set-up for Radiation Measurement	6
--	---

Prüfbericht - Nr.: 16016173 001

Seite 1 von 3
Page 1 of 3

Test Report no.:

015 / 015




down 3dB

Date: 2.APR.2009 00:03:00



013 / 015



Date: 2.APR.2009 00:04:33




Prüfbericht - Nr.: 16016173 001

Test Report no.:

Seite 3 von 3

Page 3 of 3

014 / 015



Date: 2.APR.2009 00:06:25