

Report No.: SZEM130800457201

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 75

FCC REPORT

Application No: SZEM1308004572RF

Applicant: Zhongshan K-mate General Electronics Co., Ltd Manufacturer: Zhongshan K-mate General Electronics Co., Ltd Factory: Zhongshan K-mate General Electronics Co., Ltd

Product Name: Bluetooth Stereo Headset

Model No.(EUT): BTH059
Add Model No.: CubeBand

FCC ID: WAD-BTH059

Standards: 47 CFR Part 15, Subpart C (2012)

Date of Receipt: 2013-08-20

Date of Test: 2013-08-22 to 2013-09-03

Date of Issue: 2013-09-05

Test Result: PASS *

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM130800457201

Page: 2 of 75

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2009)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2009)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (b)	ANSI C63.10 (2009)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2009)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS
Band Edge (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	I ANSLC63 10 (2009)	

Remark:

Model No.: BTH059, CubeBand

Only the Model BTH059 was tested. All above models are identical in interior structure, electrical circuits and components with different model names for the marketing requirement. Only different on colour of the shell.



Report No.: SZEM130800457201

Page: 3 of 75

3 Contents

1 COVER PAGE 2 TEST SUMMARY 2 3 CONTENTS 4 GENERAL INFORMATION 4.1 CLIENT INFORMATION 4.2 GENERAL DESCRIPTION OF EUT 4.3 TEST ENVIRONMENT 4.4 DESCRIPTION OF SUPPORT UNITS 4.5 TEST LOCATION 4.6 TEST FACILITY 4.7 DEVIATION FROM STANDARDS 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER 4.10 EQUIPMENT LIST 5 TEST RESULTS AND MEASUREMENT DATA 11 5.1 ANTENNA REQUIREMENT 5.3 CONDUCTED EMISSIONS 5.4 200B OCCUPY BANDWIDTH 5.5 CARRIER FREQUENCIES SEPARATION 5.6 HOPPING CHANNEL NUMBER 5.7 DWELL TIME 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 5.10 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 5.11 Radiated Emission below 1GHz 5.11. Radiated Emission above 1GHz			Page
3 CONTENTS 4 GENERAL INFORMATION 4.1 CLIENT INFORMATION 4.2 GENERAL DESCRIPTION OF EUT 4.3 TEST ENVIRONMENT 4.4 DESCRIPTION OF SUPPORT UNITS 4.5 TEST LOCATION 4.6 TEST FACILITY 4.7 DEVIATION FROM STANDARDS 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER 4.10 EQUIPMENT LIST 5 TEST RESULTS AND MEASUREMENT DATA 11 5.1 ANTENNA REQUIREMENT 5.2 CONDUCTED EMISSIONS 5.3 CONDUCTED PEAK OUTPUT POWER 5.4 200B OCCUPY BANDWIDTH 5.5 CARRIER FREQUENCIES SEPARATION 5.6 HOPPING CHANNEL NUMBER 5.7 DWELL TIME 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 5.10 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 5.11.1 Radiated Emission below 1GHz 5.11.2 Transmitter Emission above 1GHz	1	1 COVER PAGE	1
3 CONTENTS 4 GENERAL INFORMATION 4.1 CLIENT INFORMATION 4.2 GENERAL DESCRIPTION OF EUT 4.3 TEST ENVIRONMENT 4.4 DESCRIPTION OF SUPPORT UNITS 4.5 TEST LOCATION 4.6 TEST FACILITY 4.7 DEVIATION FROM STANDARDS 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER 4.10 EQUIPMENT LIST 5 TEST RESULTS AND MEASUREMENT DATA 11 5.1 ANTENNA REQUIREMENT 5.2 CONDUCTED EMISSIONS 5.3 CONDUCTED PEAK OUTPUT POWER 5.4 200B OCCUPY BANDWIDTH 5.5 CARRIER FREQUENCIES SEPARATION 5.6 HOPPING CHANNEL NUMBER 5.7 DWELL TIME 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 5.10 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 5.11.1 Radiated Emission below 1GHz 5.11.2 Transmitter Emission above 1GHz	2	2 TEST SUMMARY	2
4 GENERAL INFORMATION 4 4.1 CLIENT INFORMATION 4 4.2 GENERAL DESCRIPTION OF EUT 4 4.3 TEST ENVIRONMENT 6 4.4 DESCRIPTION OF SUPPORT UNITS 6 4.5 TEST LOCATION 6 4.6 TEST FACILITY 7 4.7 DEVIATION FROM STANDARDS 1 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 1 4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER 1 4.10 EQUIPMENT LIST 8 5 TEST RESULTS AND MEASUREMENT DATA 1 5.1 ANTENNA REQUIREMENT 1 5.2 CONDUCTED EMISSIONS 12 5.3 CONDUCTED PEAK OUTPUT POWER 16 5.4 20DB OCCUPY BANDWIDTH 22 5.5 CARRIER FREQUENCIES SEPARATION 25 5.6 HOPPING CHANNEL NUMBER 36 5.7 DWELL TIME 33 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 44 5.9 SPURIOUS RF CONDUCTED EMISSIONS 56 5.11 Radiated Emission below 1GHz 56 5.11.1 Radiated Emission below 1GHz 66 5.11.2 Transmitter Emission above 1GHz 66			
4.2 GENERAL DESCRIPTION OF EUT			
5.1 Antenna Requirement 1 5.2 Conducted Emissions 12 5.3 Conducted Peak Output Power 16 5.4 20dB Occupy Bandwidth 25 5.5 Carrier Frequencies Separation 29 5.6 Hopping Channel Number 36 5.7 Dwell Time 35 5.8 Band-edge for RF Conducted Emissions 45 5.9 Spurious RF Conducted Emissions 52 5.10 Pseudorandom Frequency Hopping Sequence 56 5.11 Radiated Spurious Emission 59 5.11.1 Radiated Emission below 1GHz 62 5.11.2 Transmitter Emission above 1GHz 62		 4.2 GENERAL DESCRIPTION OF EUT. 4.3 TEST ENVIRONMENT. 4.4 DESCRIPTION OF SUPPORT UNITS. 4.5 TEST LOCATION. 4.6 TEST FACILITY. 4.7 DEVIATION FROM STANDARDS. 4.8 ABNORMALITIES FROM STANDARD CONDITIONS. 4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER. 4.10 EQUIPMENT LIST. 	
5.2 CONDUCTED EMISSIONS 12 5.3 CONDUCTED PEAK OUTPUT POWER 16 5.4 20DB OCCUPY BANDWIDTH 20 5.5 CARRIER FREQUENCIES SEPARATION 29 5.6 HOPPING CHANNEL NUMBER 36 5.7 DWELL TIME 39 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 45 5.9 SPURIOUS RF CONDUCTED EMISSIONS 52 5.10 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 56 5.11.1 RADIATED SPURIOUS EMISSION 59 5.11.1 Radiated Emission below 1GHz 62 5.11.2 Transmitter Emission above 1GHz 62	5		
		5.2 CONDUCTED EMISSIONS 5.3 CONDUCTED PEAK OUTPUT POWER 5.4 20DB OCCUPY BANDWIDTH 5.5 CARRIER FREQUENCIES SEPARATION 5.6 HOPPING CHANNEL NUMBER 5.7 DWELL TIME 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 5.9 SPURIOUS RF CONDUCTED EMISSIONS 5.10 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 5.11 RADIATED SPURIOUS EMISSION 5.11.1 Radiated Emission below 1GHz	
TO DANGE GRADUATED EMISSIONE			



Report No.: SZEM130800457201

Page: 4 of 75

4 General Information

4.1 Client Information

Applicant:	Zhongshan K-mate General Electronics Co., Ltd
Address of Applicant:	Fuwan Industrial Zone, Fuwan South Road, Sunwen East Road, East District, Zhongshan, China
Manufacturer:	Zhongshan K-mate General Electronics Co., Ltd
Address of Manufacturer:	Fuwan Industrial Zone, Fuwan South Road, Sunwen East Road, East District, Zhongshan, China
Factory:	Zhongshan K-mate General Electronics Co., Ltd
Address of Factory:	Fuwan Industrial Zone, Fuwan South Road, Sunwen East Road, East District, Zhongshan, China

4.2 General Description of EUT

Name:	Bluetooth Stereo Headset		
Model No.:	BTH059, Cube	eBand	
Trade Mark:	K-mate		
Operation Frequency:	2402MHz~248	30MHz	
Bluetooth Version:	V2.1+EDR		
Modulation Technique:	Frequency Ho	pping Spread Spectrum(FHSS)	
Modulation Type:	GFSK, π/4DQ	PSK, 8DPSK	
Number of Channel:	79		
Hopping Channel Type:	Adaptive Freq	uency Hopping systems	
Sample Type:	Portable produ	uction	
Test Power Grade:	255, 50 (manufacturer declare)		
Test Software of EUT:	CSR blue suite (manufacturer declare)		
Antenna Type	Integral		
Antenna Gain	0dBi		
Power Supply:	Adapter:	USB charge	
	Battery: 3.7V 300mAh rechargeable battery		
Test Voltage:	AC 120V 60Hz		
	DC 3.7V battery fully charged		
USB Charging Cable:	120cm(Unshie	eld)	



Report No.: SZEM130800457201

Page: 5 of 75

Operation I	Operation Frequency each of channel						
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz



Report No.: SZEM130800457201

Page: 6 of 75

4.3 Test Environment

Operating Environment:		
Temperature:	24.0 °C	
Humidity:	50 % RH	
Atmospheric Pressure:	1000mbar	

4.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Adapter	Supply by SGS	SKP0500500P

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM130800457201

Page: 7 of 75

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.



Report No.: SZEM130800457201

Page: 8 of 75

4.10 Equipment List

	Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)	
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2014-06-10	
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2013-10-24	
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2014-05-16	
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T8-02	SEL0162	2013-11-10	
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T4-02	SEL0163	2013-11-10	
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T2-02	SEL0164	2013-11-10	
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2014-05-16	
8	Coaxial Cable	SGS	N/A	SEL0025	2014-05-29	
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24	
10	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2013-10-24	
11	Barometer	Chang Chun	DYM3	SEL0088	2014-05-24	



Report No.: SZEM130800457201

Page: 9 of 75

	RE in Chamber				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2014-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2014-05-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2013-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2013-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2013-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2014-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2013-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2014-05-29
10	Coaxial cable	SGS	N/A	SEL0189	2014-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2014-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2014-05-29
13	Band filter	Amindeon	82346	SEL0094	2014-05-16
14	Barometer	Chang Chun	DYM3	SEL0088	2014-05-24
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2013-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2014-05-16
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2013-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2014-06-04



Report No.: SZEM130800457201

Page: 10 of 75

	RF connected test				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2013-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2013-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2014-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2014-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2014-05-24
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2014-05-16
8	Band filter	amideon	82346	SEL0094	2014-05-16
9	POWER METER	R&S	NRVS	SEL0144	2013-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2014-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2013-10-24

Note: The calibration interval is one year, all the instruments are valid.



Report No.: SZEM130800457201

Page: 11 of 75

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.





Report No.: SZEM130800457201

Page: 12 of 75


5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207			
Test Method:	ANSI C63.10: 2009			
Test Frequency Range:	150kHz to 30MHz			
Limit:	Limit (dBuV)			
	Frequency range (MHz)	Quasi-peak	Average	
	0.15-0.5	66 to 56*	56 to 46*	
	0.5-5	56	46	
	5-30	60	50	
	* Decreases with the logarithm	n of the frequency.		•
Test Procedure:	 The mains terminal disturb room. 	bance voltage test was	s conducted in a shie	elded
	 The mains terminal disturbance voltage test was conducted in a shielded room. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to 			he was ear he of 2.



Report No.: SZEM130800457201

Page: 13 of 75





Report No.: SZEM130800457201


Page: 14 of 75

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:



Site : Shielding Room

Condition : 47 CFR PART15C QP CE LINE

EUT : 4572RF Test mode : Charge + TX


	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.49673	0.01	9.80	28.50	38.31	56.05	-17.74	QP
2	0.49673	0.01	9.80	16.58	26.39	46.05	-19.66	Average
3	1.178	0.02	9.80	22.68	32.50	56.00	-23.50	QP
4	1.178	0.02	9.80	10.59	20.41	46.00	-25.59	Average
5	1.848	0.02	9.80	22.33	32.15	56.00	-23.85	QP
6	1.848	0.02	9.80	11.23	21.05	46.00	-24.95	Average
7	2.608	0.02	9.83	9.89	19.74	46.00	-26.26	Average
8	2.608	0.02	9.83	21.86	31.71	56.00	-24.29	QP
9	3.346	0.02	9.86	10.12	19.99	46.00	-26.01	Average
10	3.346	0.02	9.86	21.02	30.89	56.00	-25.11	QP
11	4.070	0.01	9.88	19.58	29.47	56.00	-26.53	QP
12	4.070	0.01	9.88	8.65	18.54	46.00	-27.46	Average



Report No.: SZEM130800457201

Page: 15 of 75

Neutral line:



Site : Shielding Room

Condition : 47 CFR PART15C QP CE NEUTRAL

EUT : 4572RF Test mode : Charge + TX

		Freq	Cable Loss	LISN Factor			Limit Line	Over Limit	Remark
		MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	@	0.49673	0.01	9.80	30.92	40.73	56.05	-15.33	QP
2		0.49673	0.01	9.80	20.01	29.82	46.05	-16.23	Average
3		0.99440	0.02	9.80	25.62	35.44	56.00	-20.56	QP
4		0.99440	0.02	9.80	14.28	24.10	46.00	-21.90	Average
5		1.888	0.02	9.80	25.06	34.88	56.00	-21.12	QP
6		1.888	0.02	9.80	13.97	23.79	46.00	-22.21	Average
7		2.594	0.02	9.83	24.49	34.34	56.00	-21.66	QP
8		2.594	0.02	9.83	12.98	22.83	46.00	-23.17	Average
9		3.364	0.02	9.86	10.98	20.85	46.00	-25.15	Average
10		3.364	0.02	9.86	22.85	32.73	56.00	-23.27	QP
11		4.092	0.01	9.88	21.31	31.20	56.00	-24.80	QP
12		4.092	0.01	9.88	9.58	19.47	46.00	-26.53	Average

Notes:


- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM130800457201

Page: 16 of 75

5.3 Conducted Peak Output Power





Report No.: SZEM130800457201

Page: 17 of 75

Measurement Data

Weasurement Data						
	GFSK mode					
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	0.26	30.00	Pass			
Middle	0.50	30.00	Pass			
Highest	-0.48	30.00	Pass			
	π/4DQPSK m	node				
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	-0.88	30.00	Pass			
Middle	-0.62	30.00	Pass			
Highest	-1.90	30.00	Pass			
8DPSK mode						
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	-0.61	30.00	Pass			
Middle	-0.35	30.00	Pass			
Highest	-1.58	30.00	Pass			




Report No.: SZEM130800457201


Page: 18 of 75

Test plot as follows:

Test mode: GFSK Test channel: Lowest



Test mode: GFSK Test channel: Middle







Report No.: SZEM130800457201

Page: 19 of 75

Test mode: GFSK Test channel: Highest



Test mode: π/4DQPSK Test channel: Lowest









Report No.: SZEM130800457201

Page: 20 of 75

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM130800457201

Page: 21 of 75

Test mode: 8DPSK Test channel: Lowest



Test mode: 8DPSK Test channel: Middle






Report No.: SZEM130800457201

Page: 22 of 75

Test mode: 8DPSK Test channel: Highest






Report No.: SZEM130800457201

Page: 23 of 75

5.4 20dB Occupy Bandwidth



Measurement Data

Test showned	20dB Occupy Bandwidth (kHz)				
Test channel	GFSK	π/4DQPSK	8DPSK		
Lowest	874.99999985	1250.000000	1216.346154		
Middle	879.807692283	1221.153846	1221.153846		
Highest	879.807692295	1221.153846	1221.153846		




Report No.: SZEM130800457201


Page: 24 of 75

Test plot as follows:

Test mode: GFSK Test channel: Lowest












Report No.: SZEM130800457201

Page: 25 of 75

Test mode: GFSK Test channel: Highest








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM130800457201

Page: 26 of 75

Test mode: π/4DQPSK Test channel: Middle








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM130800457201

Page: 27 of 75

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM130800457201

Page: 28 of 75

Test mode: 8DPSK Test channel: Highest





Report No.: SZEM130800457201

Page: 29 of 75

5.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)		
Test Method:	ANSI C63.10:2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table		
	Ground Reference Plane		
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)		
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type		
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type, 2-DH1 of data type is worse case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is worse case of 8DPSK modulation type.		
Instruments Used:	Refer to section 4.10 for details		
Test Results:	Pass		





Report No.: SZEM130800457201

Page: 30 of 75

Measurement Data

GFSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Lowest	1006	≥833	Pass		
Middle	1006	≥833	Pass		
Highest	1002	≥833	Pass		
	π/4DQPSK m	ode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Lowest	1002	≥833	Pass		
Middle	1002	≥833	Pass		
Highest	1002	≥833	Pass		
8DPSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Lowest	1006	≥833	Pass		
Middle	1006	≥833	Pass		
Highest	1006	≥833	Pass		

Note: According to section 5.4,

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	879.807692295	587
π/4DQPSK	1250.000000	833
8DPSK	1221.153846	814




Report No.: SZEM130800457201


Page: 31 of 75

Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM130800457201

Page: 32 of 75

Test mode: GFSK Test channel: Highest



Test mode: π/4DQPSK Test channel: Lowest







Report No.: SZEM130800457201

Page: 33 of 75

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM130800457201

Page: 34 of 75

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM130800457201

Page: 35 of 75

Test mode: 8DPSK Test channel: Highest






Report No.: SZEM130800457201

Page: 36 of 75

5.6 Hopping Channel Number



Measurement Data

Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15




Report No.: SZEM130800457201


Page: 37 of 75

Test plot as follows:

Test mode: GFSK



Test mode: $\pi/4DQPSK$






Report No.: SZEM130800457201

Page: 38 of 75

Test mode: 8DPSK





Report No.: SZEM130800457201

Page: 39 of 75

5.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)					
Test Method:	ANSI C63.10:2009					
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane					
Instruments Used:						
	Refer to section 4.10 for details					
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.					
Limit:	0.4 Second					
Test Results:	Pass					

Measurement Data

Mode	Packet	Dwell time (second)	Limit (second)
	DH1	0.16288	0.4
GFSK	DH3	0.28336	0.4
	DH5	0.32309	0.4
	2-DH1	0.16800	0.4
π/4DQPSK	2-DH3	0.28336	0.4
	2-DH5	0.19488	0.4
	3-DH1	0.16672	0.4
8DPSK	3-DH3	0.28464	0.4
	3-DH5	0.32480	0.4

Test Result:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

The lowest channel (2402MHz), middle channel (2441MHz), highest channel (2480MHz) as 1500 km

DH1 time slot=0.509 (ms)*(1600/ (2*79))*31.6=162.88ms

DH3 time slot=1.771 (ms)*(1600/ (4*79))*31.6=283.36ms

DH5 time slot=3.029 (ms)*(1600/ (6*79))*31.6=323.09ms





Report No.: SZEM130800457201


Page: 40 of 75

Test plot as follows:













Report No.: SZEM130800457201

Page: 41 of 75





Test Packet: 2-DH1





[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM130800457201

Page: 42 of 75





Test Packet: 2-DH5





[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM130800457201

Page: 43 of 75





Test Packet: 3-DH3





[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM130800457201

Page: 44 of 75







Report No.: SZEM130800457201

Page: 45 of 75

5.8 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)				
Test Method:	ANSI C63.10:2009				
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane				
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.				
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.				
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type				
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type, 2-DH1 of data type is worse case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is worse case of 8DPSK modulation type.				
Instruments Used:	Refer to section 4.10 for details				
Test Results:	Pass				





Report No.: SZEM130800457201

Page: 46 of 75

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM130800457201

Page: 47 of 75

Test mode: GFSK Test channel: Highest









Report No.: SZEM130800457201

Page: 48 of 75

Test mode: π/4DQPSK Test channel: Lowest









Report No.: SZEM130800457201

Page: 49 of 75

Test mode: π/4DQPSK Test channel: Highest











Report No.: SZEM130800457201

Page: 50 of 75

Test mode: 8DPSK Test channel: Lowest









Report No.: SZEM130800457201

Page: 51 of 75

Test mode: 8DPSK Test channel: Highest







Report No.: SZEM130800457201

Page: 52 of 75

5.9 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)				
Test Method:	ANSI C63.10:2009				
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane				
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.				
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.				
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type				
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type, 2-DH1 of data type is worse case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is worse case of 8DPSK modulation type.				
Instruments Used:	Refer to section 4.10 for details				
Test Results:	Pass				




Report No.: SZEM130800457201

Page: 53 of 75

Test mode: GFSK Test channel: Lowest








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM130800457201

Page: 54 of 75

Test mode: GFSK Test channel: Highest








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM130800457201

Page: 55 of 75

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM130800457201

Page: 56 of 75

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM130800457201

Page: 57 of 75

Test mode: 8DPSK Test channel: Highest





Report No.: SZEM130800457201

Page: 58 of 75

5.10 Pseudorandom Frequency Hopping Sequence

Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1) requirement:


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- · Number of shift register stages: 9
- Length of pseudo-random sequence: 29 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



Report No.: SZEM130800457201

Page: 59 of 75

5.11 Radiated Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205								
Test Method:	ANSI C63.10: 2009								
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)								
Receiver Setup:	Frequency		Detector	RBW	VBW	Remark			
	0.009MHz-0.090MH	Z	Peak	10kHz	z 30kHz	Peak			
	0.009MHz-0.090MH	Z	Average	10kHz	30kHz	Average			
	0.090MHz-0.110MH	Z	Quasi-peak	10kHz	z 30kHz	Quasi-peak			
	0.110MHz-0.490MH	Z	Peak	10kHz	z 30kHz	Peak			
	0.110MHz-0.490MH	Z	Average	10kHz	z 30kHz	Average			
	0.490MHz -30MHz		Quasi-peak	10kHz	z 30kHz	Quasi-peak			
	30MHz-1GHz		Quasi-peak	100 kH	Iz 300kHz	Quasi-peak			
	Above 1GHz		Peak	1MHz	3MHz	Peak			
	Above IGHZ		Peak	1MHz	10Hz	Average			
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Remark	Measuremer distance (m			
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300			
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30			
	1.705MHz-30MHz		30	-	-	30			
	30MHz-88MHz		100	40.0	Quasi-peak	3			
	88MHz-216MHz		150	43.5	Quasi-peak	3			
	216MHz-960MHz		200	46.0	Quasi-peak	3			
	960MHz-1GHz		500	54.0	Quasi-peak	3			
	Above 1GHz		500	54.0	Average	3			
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequence emissions is 20dB above the maximum permitted average emission line applicable to the equipment under test. This peak limit applies to the top								






Report No.: SZEM130800457201

Page: 60 of 75

Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB



Report No.: SZEM130800457201

Page: 61 of 75

	margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass




Report No.: SZEM130800457201

Page: 62 of 75

5.11.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)						
Test mode:	Charge + Transmitting	Vertical				





Condition: FCC 15.209 3m 3142C VERTICAL

Job No. : 4572RF Test mode: Charge+TX

COL	mode. Char	80,177						
		CableA	ntenna	Preamp	Read		Limit	Over
	F							Limit
	Freq	LUSS	ractor	Factor	rever	rever	Line	LIMIL
	MHz	dB	_dB/m	dB	-dBuV	dBuV/m	dBuV/m	dB
	11112	an an	CD/III	an an	abay	abay/m	abay/m	an an
1	121.55	1.26	7.77	27.06	53.58	35.55	43.50	-7.95
2	157.56	1.33	9.55	26.87	48. 97	32 92	43.50	-10.52
3	317.70	1.96	9.82	26.54	52.84	38.08	46.00	-7.92
4	389.35	2.17	11.77	27.07	53. 78	40.65	46, 00	-5.35
_								
5	446.41	2.40	12.67	27.42	50.35	38.00	46.00	-8.00
6	578.67	2.68	15.10	27. 57	43.80	34.01	46 00	-11.99
~	010.01	2. 00	10.10	21.01	10.00	01.01	10.00	TT. 00




Report No.: SZEM130800457201

Page: 63 of 75

Test mode: Charge + Transmitting Horizontal

Data: 16



Condition: FCC 15.209 3m 3142C HORIZONTAL

Job No. : 4572RF Test mode: Charge+TX

	Freq			Preamp Factor	Read Level		Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 3 4 5 6	157.56 261.06 315.48 389.35 452.72 582.74	1.33 1.73 1.95 2.17 2.42 2.68	9.55 9.00 9.85 11.77 12.92 15.26	26.87 26.50 26.52 27.07 27.46 27.57	44. 04 55. 36 53. 61 53. 53 52. 02 45. 66	28. 05 39. 59 38. 89 40. 40 39. 90 36. 03		-15. 45 -6. 41 -7. 11 -5. 60 -6. 10 -9. 97



Report No.: SZEM130800457201

Page: 64 of 75

5.11.2 Transmitter Emission above 1GHz

Worse case	mode:	GFSK(DH	1) Test	channel:	Lowest	t Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3350.560	3.61	33.26	40.56	48.93	45.24	74	-28.76	Vertical
4920.955	4.74	34.51	41.71	50.90	48.44	74	-25.56	Vertical
6764.538	5.33	36.04	40.27	49.77	50.87	74	-23.13	Vertical
7547.013	6.17	36.00	39.57	50.24	52.84	74	-21.16	Vertical
8882.347	6.16	36.51	38.42	48.65	52.90	74	-21.10	Vertical
10944.090	6.21	38.48	37.84	46.89	53.74	74	-20.26	Vertical
3308.185	3.58	33.28	40.52	48.82	45.16	74	-28.84	Horizontal
4772.910	4.67	34.76	41.61	49.28	47.10	74	-26.90	Horizontal
6347.466	5.22	36.12	40.63	50.03	50.74	74	-23.26	Horizontal
7245.810	5.83	35.90	39.84	49.71	51.60	74	-22.40	Horizontal
8377.241	6.19	36.15	38.87	48.91	52.38	74	-21.62	Horizontal
10348.050	6.06	38.12	37.59	47.31	53.90	74	-20.10	Horizontal

Worse case	mode:	GFSK(DH1) Te	st channel:	Middle		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit (dBu\		Over Limit (dB)	Polarization
3376.244	3.64	33.25	40.58	49.21	45.52	74	ļ.	-28.48	Vertical
4582.422	4.55	35.06	41.47	49.65	47.79	74	ļ.	-26.21	Vertical
5532.263	4.96	34.96	41.32	50.35	48.95	74	ļ.	-25.05	Vertical
6412.427	5.23	36.18	40.56	50.29	51.14	74	ŀ	-22.86	Vertical
7413.726	6.02	35.97	39.69	49.77	52.07	74	ļ.	-21.93	Vertical
11027.980	6.23	38.49	37.88	46.44	53.28	74	ļ.	-20.72	Vertical
3625.669	3.84	33.34	40.76	48.98	45.40	74		-28.60	Horizontal
4971.316	4.76	34.43	41.75	51.86	49.30	74		-24.70	Horizontal
6816.394	5.35	35.99	40.22	50.33	51.45	74	ļ.	-22.55	Horizontal
7624.250	6.23	36.00	39.51	49.94	52.66	74	L	-21.34	Horizontal
8377.241	6.19	36.15	38.87	48.91	52.38	74		-21.62	Horizontal
10560.940	6.11	38.32	37.68	46.84	53.59	74		-20.41	Horizontal



Report No.: SZEM130800457201

Page: 65 of 75

Worse case	mode:	GFSK(DH1)	Tes	t channel:	Highest	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3672.110	3.88	33.41	40.80	50.51	47.00	74	-27.00	Vertical
5631.725	5.00	35.09	41.24	50.82	49.67	74	-24.33	Vertical
6561.030	5.27	36.25	40.43	50.25	51.34	74	-22.66	Vertical
7547.013	6.17	36.00	39.57	50.24	52.84	74	-21.16	Vertical
8527.851	6.18	36.23	38.73	49.09	52.77	74	-21.23	Vertical
10587.850	6.12	38.33	37.69	46.78	53.54	74	-20.46	Vertical
3552.582	3.78	33.26	40.70	48.95	45.29	74	-28.71	Horizontal
4536.000	4.52	35.14	41.43	49.94	48.17	74	-25.83	Horizontal
6347.466	5.22	36.12	40.63	50.03	50.74	74	-23.26	Horizontal
7394.878	6.00	35.96	39.71	49.67	51.92	74	-22.08	Horizontal
8377.241	6.19	36.15	38.87	48.91	52.38	74	-21.62	Horizontal
11112.520	6.25	38.48	37.91	46.33	53.15	74	-20.85	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: SZEM130800457201

Page: 66 of 75

5.12Band edge (Radiated Emission)

Test Requirement:	47 CFR Part 15C Section 15	47 CFR Part 15C Section 15.209 and 15.205								
Test Method:	ANSI C63.10: 2009									
Test Site:	Measurement Distance: 3m	Measurement Distance: 3m (Semi-Anechoic Chamber)								
Limit:	Frequency	Limit (dBuV/m @3m)	Remark							
	30MHz-88MHz	40.0	Quasi-peak Value							
	88MHz-216MHz	43.5	Quasi-peak Value							
	216MHz-960MHz	46.0	Quasi-peak Value							
	960MHz-1GHz	54.0	Quasi-peak Value							
	Above 1GHz	54.0	Average Value							
	Above IGHZ	74.0	Peak Value							
			·							
Test Setup:										






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



Report No.: SZEM130800457201

Page: 67 of 75

Test Procedure:	 a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel , the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worse case of
	GFSK modulation type
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass




Report No.: SZEM130800457201

Page: 68 of 75

Test plot as follows:

Worse case mode: GFSK (DH5) Test channel:	Lowest	Remark:	Peak	Vertical	l
---	--------	---------	------	----------	---



Condition : FCC PART15(>1G) PK 3m VERTICAL

Job No. : 4572RF

Mode : 2402 Bandedge


1040	Freq			Preamp Factor			Limit Line	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 X	2390.000 2402.245			39.85 39.86				



Report No.: SZEM130800457201

Page: 69 of 75

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Peak Horizontal



Condition : FCC PART15(>1G) PK 3m HORIZONTAL

Job No. : 4572RF

Mode : 2402 Bandedge

			Cable	Antenna	Preamp	Read		Limit	Over
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1		2390.000	2.98	32.51	39.85	46.78	42.42	74.00	-31.58
2	X	2402.245	2.98	32.51	39.86	97.35	92.98	74.00	18.98






Report No.: SZEM130800457201

Page: 70 of 75

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Average Vertical



Condition : FCC PART15(>1G) AV 3m VERTICAL

Job No. : 4572RF Mode : 2402 Bandedge


> CableAntenna Preamp Read Limit Over Freq Loss Factor Factor Level Level Line Limit MHz dΒ dB/m dΒ dBuV dBuV/m dBuV/m 2390.000 2.98 32.51 39.85 35.85 31.50 54.00 -22.50 2 X 2.98 32.51 39.86 89.88 85.51 54.00 31.51 2401.770



Report No.: SZEM130800457201

Page: 71 of 75

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Average Horizontal



Condition : FCC PART15(>1G) AV 3m HORIZONTAL

Job No. : 4572RF

Mode : 2402 Bandedge


	Freq			Preamp Factor				
_	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
	2390.000 2401.770			39.85 39.86				



Report No.: SZEM130800457201

Page: 72 of 75

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Peak Vertical



Frequency (MHz)

Condition : FCC PART15(>1G) PK 3m VERTICAL

Job No. : 4572RF

Mode : 2480 Bandedge

		Freq			Preamp Factor			Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	X	2479.775 2483.500			39.92 39.92				


[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms.e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM130800457201

Page: 73 of 75

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Peak Horizontal



......

Condition : FCC PART15(>1G) PK 3m HORIZONTAL

Job No. : 4572RF Mode : 2480 Bandedge

		Freq			Preamp Factor				
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	X	2479.775 2483.500			39.92 39.92				


[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms.e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM130800457201

Page: 74 of 75

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Average Vertical



Condition : FCC PART15(>1G) AV 3m VERTICAL

Job No. : 4572RF Mode : 2480 Bandedge

		Cable	Antenna	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2479.875	3.03	32.67	39.92	91.66	87.44	54.00	33.44
2	2483.500	3.03	32.67	39.92	53.78	49.56	54.00	-4.44


[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms.e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM130800457201

Page: 75 of 75

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Average Horizontal



Condition : FCC PART15(>1G) AV 3m HORIZONTAL

Job No. : 4572RF

Mode : 2480 Bandedge

		Cable.	Antenna	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2479.975	3.03	32.67	39.92	89.74	85.52	54.00	31.52
2	2483.500	3.03	32.67	39.92	54.89	50.67	54.00	-3.33

Note

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."