



RF EXPOSURE EVALUATION REPORT

APPLICANT : Testo SE & Co. KGaA
PRODUCT NAME : testo 550s
MODEL NAME : 0564 5500
BRAND NAME : Testo
FCC ID : WAF-05645500
STANDARD(S) : 47CFR 2.1091
KDB 447498
RECEIPT DATE : 2020-11-09
TEST DATE : 2020-11-18 to 2020-11-30
ISSUE DATE : 2020-12-14

Edited by: Peng Mi
Peng Mi (Rapporteur)

Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information..... 3
- 1.1 Applicant and Manufacturer Information..... 3
- 1.2 Equipment under Test (EUT) Description..... 3
- 1.3 Applied Reference Documents 4
- 2. Device Category and RF Exposure Limit 5
- 3. RF Exposure Assessment..... 7
- Annex A General Information..... 8

Change History		
Version	Date	Reason for Change
1.0	2020-12-14	First edition



1. Technical Information

Note: Provide by applicant.

1.1 Applicant and Manufacturer Information

Applicant:	Testo SE & Co. KGaA
Applicant Address:	Testo-Strasse 1, Lenzkirch, 79853, Germany
Manufacturer:	Testo Instruments (Shenzhen) Co., Ltd
Manufacturer Address:	Block A, B4 Building, China Merchants Guangming Sci&Tech Park, No.3009 Guan Guang Road, Guangming New District, Shenzhen City

1.2 Equipment under Test (EUT) Description

Product Name:	testo 550s
Serial No.:	(N/A, marked #1 by test site)
Hardware Version:	0216 5505_2.1
Software Version:	V1.0.0
Bluetooth Version:	5.0
Frequency Bands:	2402MHz - 2480MHz
Modulation Mode:	GFSK(1Mbps, 2Mbps)
Antenna Type:	Built-in omnidirectional Antenna
Antenna Gain:	2.43dBi

Note 1: This test report is updated from report (Report No.: SZ20110119S01, FCC ID: WAF-05645570), based on the similarity between before, only change product name, model name and FCC ID, the others are the same as before. The changes do not affect the test results.



1.3 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title	Method determination /Remark
1	47 CFR§2.1091	Radio Frequency Radiation Exposure Assessment: mobile devices	No deviation
2	KDB 447498 D01v06	General RF Exposure Guidance	No deviation

Note 1: The test item is not applicable.

Note 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% risk level.



2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz* = Plane-wave equivalent power density

**<Bluetooth Output Power>**

Mode	Channel	Frequency (MHz)	Average power (dBm)	
			GFSK	
			1Mbps	2Mbps
Bluetooth LE	CH 00	2402	16.51	16.95
	CH 19	2440	16.77	17.29
	CH 39	2480	16.62	17.04
Tune-up Limit			17.0	18.0

Note:

1. According to KDB 447498 Section 4.3, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. The average output power is from the report No.SZ20120123W01.

3. RF Exposure Assessment

➤ **Standalone Transmission Assessment:**

Bands	Frequency (MHz)	Tune-up Power(dBm)	Antenna Gain(dBi)	E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit for MPE (mW/cm ²)
Bluetooth	2440	18	2.43	110.41	0.022	1.0

Note:

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

2. MPE calculate method

$$\text{Power Density} = \text{E.I.R.P.}/4\pi R^2$$

Where: E.I.R.P. = P+G

P = Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)

➤ **Simultaneous Transmission Assessment:**

This device only incorporates a Bluetooth transmitter, Therefore simultaneous SAR assessment is not required.

➤ **Conclusion:**

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



Annex A General Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

The FCC designation number is CN1192, the test firm registration number is 226174.

————— END OF REPORT —————