



FCC PART 15.247

MEASUREMENT AND TEST REPORT

For

NEW POS Technology Limited

14F/A Financia Technology Building, Science & Technology Park,
No.11 Keyuan Road, Nanshan District, Shenzhen, China

FCC ID: WALNEW7110

Report Type: Class II Permissive Change	Product Type: EFT-POS
Test Engineer: <u>Gardon Zhang</u> 	
Report Number: <u>RSZ120929002-00A1</u>	
Report Date: <u>2012-10-09</u>	
Reviewed By: <u>Alvin Huang</u>  <u>RF Leader</u>	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk “★”

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	8
FCC §15.247 (i) & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	9
APPLICABLE STANDARD	9
MPE CALCULATION.....	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
TEST DATA	11
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY.....	12
EUT SETUP	12
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	13
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST PROCEDURE	13
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.247(a) (2) – 6 dB BANDWIDTH TESTING.....	19
APPLICABLE STANDARD	19
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST PROCEDURE	19
TEST DATA	19
FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER.....	22
APPLICABLE STANDARD	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST PROCEDURE	22
TEST DATA	22
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	25

APPLICABLE STANDARD	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST PROCEDURE	25
TEST DATA	25
FCC §15.247(e) - POWER SPECTRAL DENSITY	28
APPLICABLE STANDARD	28
TEST EQUIPMENT LIST AND DETAILS.....	28
TEST PROCEDURE	28
TEST DATA	28

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *NEW POS Technology Limited*'s product, model number: *NEW7110* (FCC ID: *WALNEW7110*) or the "EUT" as referred to in this report is a *Wi-Fi device*, named as *EFT-POS* by applicant, which measures approximately: 23.0 cm (L) x 10.2 cm (W) x 7.3 cm (H). Rated input voltage: DC 12V from adapter.

Adapter information: Switching power supply

Model: CPS036A120300

Input: 100-240V~ 50/60Hz 1.0A

Output: 12V DC, 3A

** All measurement and test data in this report was gathered from production sample serial number: 71001947 (Assigned by Applicant). The EUT was received on 2012-09-29.*

Objective

This type approval report is prepared on behalf of *NEW POS Technology Limited* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

This is the CHIPC application for adding the modulation of 802.11g by the software.

Note: For the change made to the device, all the items except conducted emission were performed. And the test data of 802.11b modulation please refer to the report RSZ120726003-00C with FCC ID: *WALNEW7110*, which was granted on 2012-09-18.

Related Submittal(s)/Grant(s)

The original submission with FCC ID: *WALNEW7110* was granted on 2012-09-18.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11g mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

EUT for 802.11g mode were tested with Channel 1, 6 and 11.

EUT Exercise Software


Test software supplied by client

Equipment Modifications

No modification was made to the unit tested.

External I/O Cable

Cable Description	Length (m)	From/Port	To
Unshielded Detachable DC Power Cable	1.56	EUT	Adapter

Block Diagram of Test Setup

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b)(1), §2.1091	Maximum Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a),	Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Note: The the data of 802.11b please refer to the report RSZ120726003-00C with FCC ID: WALNEW7110, which was granted on 2012-09-18.

FCC §15.247 (i) & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

MPE Calculation

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = Antenna gain

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

802.11b mode:

Please refer to the report RSZ120726003-00C with FCC ID: WALNEW7110, which was granted on 2012-09-18.

802.11g mode:

Mode	Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11g	2462	-6.36	0.23	15.05	31.99	20	0.00146	1.0

Result: The EUT is mobile isage and meets FCC MPE limit at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a monopole antenna for Wi-Fi, which in accordance to section 15.203, the maximum gain is -6.36 dBi; please refer to the internal photos.

Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207

Test Data

Please refer to the report RSZ120726003-00C with FCC ID: WALNEW7110, which was granted on 2012-09-18.

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB($k=2$, 95% level of confidence), and the uncertainty will not be taken into consideration for all the test data recorded in the report.

EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
30MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2011-11-24	2012-11-23
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-11-28	2012-11-27
Mini-Circuits	Amplifier	ZVA-213+	N/A	2011-11-24	2012-11-23
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2012-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
Agilent	Spectrum Analyzer	8564E	3943A01781	2012-05-17	2013-05-16
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2011-10-14	2012-10-13
Rohde & Schwarz	Auto Test Software	EMC32	V6.30	-	-

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

For the radiated emissions test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all Installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:

2.07 dB at 396 MHz in the **Horizontal** polarization

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

The testing was performed by Gardon Zhang on 2012-08-20.

Test Mode: Transmitting

802.11b mode:

Please refer to the report RSZ120726003-00C with FCC ID: WALNEW7110, which was granted on 2012-09-18.


802.11g mode:**30 MHz - 25 GHz:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrd. Amp. (dBuV/m)	FCC Part 15.247/15.205/15.209		
	Reading (dB μ V/m)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)	Comment
Low Channel (2412 MHz)										
2412	96.39	PK	22	1.2	H	6.13	102.52	/	/	Fund.
2412	76.67	Ave.	22	1.2	H	6.13	82.8	/	/	Fund.
2412	91.36	PK	16	1.3	V	6.13	97.49	/	/	Fund.
2412	77.28	Ave.	16	1.3	V	6.13	83.41	/	/	Fund.
396	55.22	QP	128	1.1	H	-11.58	43.64	46	2.36*	Spurious
4824.0	36.59	PK	321	1.2	H	12.40	48.99	74	25.01	Harmonic
4824.0	21.14	Ave.	321	1.2	H	12.40	33.54	54	20.46	Harmonic
7236.0	33.26	PK	63	1.3	H	16.62	49.88	74	24.12	Harmonic
7236.0	18.26	Ave.	63	1.3	H	16.62	34.88	54	19.12	Harmonic
9648.0	32.29	PK	55	1.1	V	19.29	51.58	74	22.42	Harmonic
9648.0	17.75	Ave.	55	1.1	V	19.29	37.04	54	16.96	Harmonic
2335.1	35.21	PK	9	1.2	V	5.48	40.69	74	33.31	Spurious
2335.1	21.87	Ave.	9	1.2	V	5.48	27.35	54	26.65	Spurious
2390.0	38.96	PK	75	1.3	H	6.13	45.09	74	28.91	Spurious
2390.1	24.81	Ave.	75	1.3	H	6.13	30.94	54	23.06	Spurious
2483.5	37.13	PK	62	1.2	V	6.81	43.94	74	30.06	Spurious
2483.5	23.89	Ave.	62	1.2	V	6.81	30.70	54	23.30	Spurious
Middle Channel (2437 MHz)										
2437	95.75	PK	36	1.2	H	6.13	101.88	/	/	Fund.
2437	76.63	Ave.	36	1.2	H	6.13	82.76	/	/	Fund.
2437	90.21	PK	95	1.1	V	6.13	96.34	/	/	Fund.
2437	77.93	Ave.	95	1.1	V	6.13	84.06	/	/	Fund.
396	55.51	QP	110	1.1	H	-11.58	43.93	46	2.07*	Spurious
4874.0	36.68	PK	85	1.2	H	12.46	49.14	74	24.86	Harmonic
4874.0	21.09	Ave.	85	1.2	H	12.46	33.55	54	20.45	Harmonic
7311.0	33.66	PK	21	1.3	H	16.49	50.15	74	23.85	Harmonic
7311.0	18.52	Ave.	21	1.3	H	16.49	35.01	54	18.99	Harmonic
9748.0	32.91	PK	22	1.1	V	19.40	52.31	74	21.69	Harmonic
9748.0	17.88	Ave.	22	1.1	V	19.40	37.28	54	16.72	Harmonic
2335.9	35.26	PK	6	1.2	V	5.48	40.74	74	33.26	Spurious
2335.9	21.14	Ave.	6	1.2	V	5.48	26.62	54	27.38	Spurious
2389.2	36.03	PK	86	1.1	H	6.13	42.16	74	31.84	Spurious
2389.2	22.06	Ave.	86	1.1	H	6.13	28.19	54	25.81	Spurious
2483.5	35.84	PK	35	1.2	V	6.81	42.65	74	31.35	Spurious
2483.5	21.33	Ave.	35	1.2	V	6.81	28.14	54	25.86	Spurious


Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrd. Amp. (dBuV/m)	FCC Part 15.247/15.205/15.209		
	Reading (dB μ V/m)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)	Comment
High Channel (2462 MHz)										
2462	95.73	PK	226	1.3	H	7.21	102.94	/	/	Fund.
2462	76.91	Ave.	226	1.3	H	7.21	84.12	/	/	Fund.
2462	90.09	PK	25	1.3	V	6.81	96.9	/	/	Fund.
2462	78.35	Ave.	25	1.3	V	6.81	85.16	/	/	Fund.
396	55.28	QP	143	1.1	H	-11.58	43.7	46	2.3*	Spurious
4924.0	36.89	PK	36	1.2	H	12.50	49.39	74	24.61	Harmonic
4924.0	21.33	Ave.	36	1.2	H	12.50	33.83	54	20.17	Harmonic
7386.0	33.64	PK	95	1.3	H	15.91	49.55	74	24.45	Harmonic
7386.0	18.26	Ave.	95	1.3	H	15.91	34.17	54	19.83	Harmonic
9848.0	32.47	PK	71	1.2	V	19.39	51.86	74	22.14	Harmonic
9848.0	17.41	Ave.	71	1.2	V	19.39	36.80	54	17.20	Harmonic
2332.3	39.65	PK	33	1.2	V	5.48	45.13	74	28.87	Spurious
2332.3	25.58	Ave.	33	1.2	V	5.48	31.06	54	22.94	Harmonic
2393.4	41.14	PK	8	1.3	H	6.13	47.27	74	26.73	Spurious
2393.4	27.34	Ave.	8	1.3	H	6.13	33.47	54	20.53	Harmonic
2499.6	41.61	PK	125	1.1	V	6.81	48.42	74	25.58	Spurious
2499.6	27.38	Ave.	125	1.1	V	6.81	34.19	54	19.81	Spurious

Antenna Port Conducted Spurious Emissions:


802.11g Low Channel



802.11g Middle Channel



802.11g High Channel



FCC §15.247(a) (2) – 6 dB BANDWIDTH TESTING

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

The testing was performed by Gardon Zhang on 2012-09-28.

Test Mode: Transmitting

Test Result: Pass.

802.11b mode:


Please refer to the report RSZ120726003-00C with FCC ID: WALNEW7110, which was granted on 2012-09-18.

802.11g mode:

Please refer to the following tables and plots.


Channel	Frequency (MHz)	Data Rate (Mbps)	6 dB bandwidth (MHz)	Limit (kHz)	Result
802.11g mode					
Low	2412	6	16.74	> 500	Pass
Middle	2437	6	16.74	> 500	Pass
High	2462	6	16.74	> 500	Pass

Low Channel




Date: 28.SEP.2012 17:55:59

Middle Channel



Date: 28.SEP.2012 17:51:00

High Channel



Date: 28.SEP.2012 17:45:30

FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER

Applicable Standard

According to §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

The testing was performed by Gardon Zhang on 2012-09-28.

Test Mode: Transmitting

Test Result: Compliance.


802.11b mode:

Please refer to the report RSZ120726003-00C with FCC ID: WALNEW7110, which was granted on 2012-09-18.


802.11g mode:

Channel	Frequency (MHz)	Data Rate (Mbps)	Conducted Output Power (dBm)	Limit (dBm)	Result
802.11g mode					
Low	2412	6	13.35	30	Pass
Middle	2437	6	14.56	30	Pass
High	2462	6	15.05	30	Pass


RF Output Power, Low Channel



Date: 28.SEP.2012 17:57:41

RF Output Power, Middle Channel

Date: 28.SEP.2012 17:48:58

RF Output Power, High Channel

Date: 28.SEP.2012 17:47:31

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
4. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

The testing was performed by Gardon Zhang on 2012-09-28.

Test Mode: Transmitting

Test Result: *Compliance.*

802.11b mode:


Please refer to the report RSZ120726003-00C with FCC ID: WALNEW7110, which was granted on 2012-09-18.

802.11g mode:

Channel	Frequency Band	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result
802.11g mode				
Low	Left-band	26.01	20	Pass
High	Right-band	49.12	20	Pass


Please refer to following plots.

Band Edge, Left Side



Date: 28.SEP.2012 17:59:07

Band Edge, Right Side



Date: 28.SEP.2012 17:43:49

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 100 kHz.
3. Set the VBW \geq 300 kHz.
4. Set the span to 5-30 % greater than the EBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
10. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3 \text{ kHz}/100 \text{ kHz}) = -15.2 \text{ dB}$.
11. The resulting peak PSD level must be $\leq 8 \text{ dBm}$.



Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

The testing was performed by Gardon Zhang on 2012-09-28.

Test Mode: Transmitting

Test Result: Pass


802.11b mode:

Please refer to the report RSZ120726003-00C with FCC ID: WALNEW7110, which was granted on 2012-09-18.


802.11g mode:

Channel	Frequency (MHz)	Data Rate (Mbps)	Power Spectral Density (dBm/100 kHz)	BWCF (dB)	Power Spectral Density (dBm/3 kHz)	Limit (dBm/3 kHz)
802.11g mode						
Low	2412	6	-6.80	-15.2	-22.00	8
Middle	2437	6	-6.11	-15.2	-21.31	8
High	2462	6	-5.55	-15.2	-20.75	8


Power Spectral Density, Low Channel



Date: 28.SEP.2012 17:53:39

Power Spectral Density, Middle Channel

Date: 28.SEP.2012 17:52:53

Power Spectral Density, High Channel

Date: 28.SEP.2012 17:46:32

******* END OF REPORT *******