

RF TEST REPORT



Report No.: FCC_RF_SL14020601-GEO-002 Rev1.0
Supersede Report No.: FCC_RF_SL14020601-GEO-002

Applicant	:	Geospace Technologies Corporation
Product Name	:	Geospace Seismic Record (GSX-LF)
Model No.	:	GSX-LF
Test Standard	:	47 CRF 15.247: 2013 RSS-210 Issue 8: 2010
Test Method	:	ANSI C63.4: 2009 558074 D01 DTS Meas Guidance v03r02
FCC ID	:	WAOGSXLF
IC ID	:	7733A-GSXLF
Dates of test	:	June 13, 2014 to June 19, 2014
Issue Date	:	7/25/2014
Test Result	:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
Equipment complied with the specification [X] Equipment did not comply with the specification []		

This Test Report is Issued Under the Authority of:	
Teody Manansala	Nima Molaei
Test Engineer	Engineer Reviewer

Issued By:
SIEMIC Laboratories
775 Montague Expressway, Milpitas, 95035 CA



775 Montague Expressway, Milpitas, CA 95035, USA • Phone: (+1) 408 526 1188 • Facsimile (+1) 408 526 1088

Visit us at: www.siemic.com; Follow us at:

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC, RF/Wireless, Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom
Taiwan	BSMI, NCC, NIST	EMC, RF, Telecom, Safety
Hong Kong	OFTA, NIST	RF/Wireless, Telecom
Australia	NATA, NIST	EMC, RF, Telecom, Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF, Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom, Safety

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB, NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom

CONTENTS

1	REPORT REVISION HISTORY	4
2	EXECUTIVE SUMMARY	5
3	CUSTOMER INFORMATION	5
4	TEST SITE INFORMATION	5
5	MODIFICATION	5
6	EUT INFORMATION	6
6.1	EUT Description	6
6.2	Radio Description	6
6.3	EUT test modes/configuration Description.....	6
6.4	EUT Photos - External	7
6.5	EUT Photos - Internal	9
6.6	EUT Test Setup Photos	11
7	SUPPORTING EQUIPMENT/SOFTWARE AND CABLING DESCRIPTION.....	12
7.1	Supporting Equipment	12
7.2	Cabling Description	12
7.3	Test Software Description	12
8	TEST SUMMARY.....	13
9	MEASUREMENT UNCERTAINTY	14
10	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	15
10.1	Conducted Emissions.....	15
10.2	6dB Bandwidth	16
10.3	Peak Output Power	19
10.4	Band Edge	22
10.5	Peak Spectral Density	25
10.6	Radiated Emissions below 1GHz.....	28
10.7	Radiated Spurious Emissions above 1GHz.....	31
ANNEX A. TEST INSTRUMENT.....		34
ANNEX B. USER MANUAL, BLOCK & CIRCUIT DIAGRAM.....		35
ANNEX C. SIEMIC ACCREDITATION		36

1 Report Revision History

Report No.	Report Version	Description	Issue Date
FCC_RF_SL14020601-GEO-002	None	Original	06/30/2014
FCC_RF_SL14020601-GEO-002 Rev1.0	Rev1.0	Add 99% plot at 10.2 Add table for spectrum setting at 10.7 Change 18GHz to 25 GHz at 10.7 Replaced top and bottom EUT photo	7/18/2014

2 Executive Summary

The purpose of this test program was to demonstrate compliance of the Geospace Seismic Record (GSX-LF), model GSX-LF against the current Stipulated Standards. The GSX-LF has demonstrated compliance with the Stipulated Standard listed on 1st page.

3 Customer information

Applicant Name	:	Geospace Technologies Corporation
Applicant Address	:	7007 Pine Drive, Huston, TX 77040 USA
Manufacturer Name	:	Geospace Technologies Corporation
Manufacturer Address	:	7007 Pine Drive, Huston, TX 77040 USA

4 Test site information

Lab performing tests	SIEMIC Laboratories
Lab Address	775 Montague Expressway, Milpitas, CA 95035
FCC Test Site No.	881796
IC Test Site No.	4842D-2
VCCI Test Site No.	A0133

5 Modification

Index	Item	Description	Note
-	-	-	-

6 EUT Information

6.1 EUT Description

Product Name	:	Geospace Seismic Record (GSX-LF)
Model No.	:	GSX-LF
Trade Name	:	Geospace
Serial No.	:	00019838
Input Power	:	16VDC
Power Adapter Manu/Model	:	N/A
Power Adapter SN	:	N/A
Hardware version	:	N/A
Software version	:	N/A
Date of EUT received	:	June 05, 2014
Equipment Class/ Category	:	2.4GHz Zigbee
Clock Frequencies	:	N/A
Port/Connectors	:	DC input

6.2 Radio Description


Spec for Radio -

Radio Type	Zigbee
Operating Frequency	2405MHz-2480MHz
Modulation	O-QPSK
Channel Spacing	5MHz
Antenna Type	Internal F Antenna
Antenna Gain	3.3 dBi
Antenna Connector Type	N/A

6.3 EUT test modes/configuration Description


Test Item	Operating mode	Tested antenna port	Test frequencies
Frequency	Continuous Transmitting	TX port	Low, Mid, High
Occupied Bandwidth (99%)	Continuous Transmitting	TX port	Low, Mid, High
Spread spectrum Bandwidth (90%)	Continuous Transmitting	TX port	Low, Mid, High
Spurious emission Intensity	Continuous Transmitting	TX port	Low, Mid, High
Antenna Power	Continuous Transmitting	TX port	Low, Mid, High
Secondary Radiated Emissions	Continuous Transmitting	RX port	Low, Mid, High
Note: None			

6.4 EUT Photos - External





Battery Pack – Top View



Battery Pack – Bottom View


6.5 EUT Photos - Internal




EUT –PCBA1 Component Side



EUT – PCBA1 Solder Side




EUT –PCBA2 Component Side




EUT – PCBA2 Solder Side



EUT –PCBA3 Component Side




EUT – PCBA3 Solder Side




EUT -without cover

6.6 EUT Test Setup Photos



Radiated Emissions (<1GHz) – Front View



Radiated Emissions (<1GHz) – Rear View




Radiated Emissions (>1GHz) – Front View



Radiated Emissions (>1GHz) – Rear View



Radiated Emissions (>18GHz) – Front View



Radiated Emissions (>18GHz) – Rear View

7 Supporting Equipment/Software and cabling Description

7.1 Supporting Equipment

Item	Supporting Equipment Description	Model	Serial Number	Manufacturer	Note
1	Handheld Computer	ALGIZ7	OBX KIT 1010A	Geospace	-
2	DC Power Supply	EA10521D-120	124300517	EDACPOWER ELEC	-
3	AYCBL, GSR Data Retrieval	453-03150-01 B	N/A	Geospace	

7.2 Cabling Description

Name	Connection Start		Connection Stop		Length / shielding Info		Note
	From	I/O Port	To	I/O Port	Length (m)	Shielding	
AYCBL, GSR Data Retrieval	EUT	Power input	Handheld	Ethernet Port	<1m	Unshielded	-

7.3 Test Software Description

Test Item	Software	Description
RF Testing	GSR Tester 32 99.1.24.5	Set the EUT to transmit continuously

8 Test Summary

Test Item	Test standard		Test Method/Procedure		Pass / Fail
Restricted Band of Operation	FCC	15.205	FCC	ANSI C63.4 – 2009 558074 D01 DTS Meas Guidance v03r02	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
	IC	RSS 210 (2.2)	IC	-	
AC Conducted Emissions Voltage	FCC	15.207(a)	FCC	ANSI C63.4 – 2009	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS Gen (7.2.2)	IC	-	

Test Item	Test standard		Test Method/Procedure		Pass / Fail
Channel Separation	FCC	15.247 (a)(1)	FCC	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS210 (A8.1)	IC	-	
Occupied Bandwidth	FCC	15.247(a)(1)	FCC	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS210(A8.1)	IC	-	
Bandwidth	FCC	15.247(a)(2)	FCC	558074 D01 DTS Meas Guidance v03r02	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
	IC	RSS210 (A8.2)	IC	-	
Number of Hopping Channels	FCC	15.247(a)(1)	FCC	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS210(A8.1)	IC	-	
Band Edge and Radiated Spurious Emissions	FCC	15.247(d)	FCC	ANSI C63.4 – 2009, 558074 D01 DTS Meas Guidance v03r02	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
	IC	RSS210(A8.5)	IC	-	
Time of Occupancy	FCC	15.247(a)(1)	FCC	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS210(A8.1)	IC	-	
Output Power	FCC	15.247(b)	FCC	558074 D01 DTS Meas Guidance v03r02	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
	IC	RSS210 (A8.4)	IC	-	
Receiver Spurious Emissions	FCC	15.247(d)	FCC	-	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
	IC	RSS Gen (4.8)	IC	-	
Antenna Gain > 6 dBi	FCC	15.247(e)	FCC	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS210(A8.4)	IC	-	
Power Spectral Density	FCC	15.247(e)	FCC	558074 D01 DTS Meas Guidance v03r02	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A
	IC	RSS210(A8.3)	IC	-	
Hybrid System Requirement	FCC	15.247(f)	FCC	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS210(A8.3)	IC	-	
Hopping Capability	FCC	15.247(g)	FCC	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS210(A8.1)	IC	-	
Hopping Coordination Requirement	FCC	15.247(h)	FCC	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS210(A8.1)	IC	-	
RF Exposure requirement	FCC	15.247(i)	FCC	-	<input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A
	IC	RSS Gen(5.5)	IC	-	
Remark	<ol style="list-style-type: none"> All measurement uncertainties do not take into consideration for all presented test results. The applicant shall ensure frequency stability by showing that an emission is maintained within the band of operation under all normal operating conditions as specified in the user's manual. 				

9 Measurement Uncertainty


Emissions			
Test Item	Frequency Range	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	30MHz – 1GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
Band Edge and Radiated Spurious Emissions	1GHz – 40GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+4.3dB/-4.1dB

10 Measurements, Examination and Derived Results

10.1 Conducted Emissions

Conducted Emission Limit

Frequency ranges (MHz)	Limit (dBuV)	
	QP	Average
0.15 ~ 0.5	66 – 56	56 – 46
0.5 ~ 5	56	46
5 ~ 30	60	50


Spec	Item	Requirement	Applicable
47CFR§15.207, RSS210(A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequency ranges.	<input type="checkbox"/>
Test Setup	 <p>Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>		
Procedure	<ul style="list-style-type: none"> - The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B. - The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. - All other supporting equipment was powered separately from another main supply. 		
Remark	EUT tested with Handheld computer and Battery Pack.		
Result	<input type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A

Test Plot Yes (See below) N/A

10.2 6dB Bandwidth

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW≥500KHz;	<input checked="" type="checkbox"/>
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>558074 D01 DTS Meas Guidance v03r02, 8.1 DTS bandwidth</p> <p><u>6dB Emission bandwidth measurement procedure</u></p> <ul style="list-style-type: none"> - Set RBW = 100 kHz. - Set the video bandwidth (VBW) ≥ 3 RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. - Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. <p>EUT tested with Handheld computer and battery Pack.</p>		
Test Date	06/14/2014	Environmental condition	Temperature 22°C Relative Humidity 42% Atmospheric Pressure 1021mbar
Remark	EUT tested with Handheld computer and Battery Pack.		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Equipment Setting

TEST	RBW	VBW	SPAN	Detector	SWEEP	Trace	NOTES
6 dB DTS Bandwidth	1-5% of DTS BW (≤ 100 KHz)	3 x RBW	>EBW	PK	Auto	Max hold	-

Test Data Yes N/A
Test Plot Yes N/A


6dB Bandwidth measurement result

Type	Freq (MHz)	CH	Result (MHz)	Limit (MHz)	Result
6dB BW	2405	Low	1.621	≥0.5	Pass
6dB BW	2440	Mid	1.542	≥0.5	Pass
6dB BW	2480	High	1.488	≥0.5	Pass


99% Bandwidth measurement result

Type	Freq (MHz)	CH	Result (MHz)	Limit (MHz)	Result
99% OBW	2405	Low	2.5652	-	-
99% OBW	2440	Mid	2.5449	-	-
99% OBW	2480	High	2.6205	-	-


Test Plots



6dB BW TX-Zigbee 2405



6dB BW TX-Zigbee 2440



6dB BW TX-Zigbee 2480



99% BW TX-Zigbee 2405



99% BW TX-Zigbee 2440




99% BW TX-Zigbee 2480

10.3 Peak Output Power

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(b) (2), RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with ≥ 25 & < 50 channels: ≤ 0.25 Watt	<input type="checkbox"/>
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: ≤ 1 Watt	<input checked="" type="checkbox"/>



Test Procedure	<p>558074 D01 DTS Meas Guidance v03r02, 9.1.1</p> <p><u>Maximum output power measurement procedure</u></p> <ul style="list-style-type: none"> - Set the RBW \geq DTS bandwidth - Set the VBW $\geq 3x$ RBW - Set the span $\geq 1.5 x$ DTS bandwidth. - Detector = peak. - Sweep time = auto couple. - Trace mode = max hold. - Allow trace to fully stabilize. - Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth. 		
----------------	--	--	--

Test Date	06/14/2014	Environmental condition	Temperature 23°C Relative Humidity 44% Atmospheric Pressure 1021mbar
-----------	------------	-------------------------	--

Remark	EUT tested with Handheld computer and Battery Pack.
--------	---

Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
--------	--

Equipment Setting

TEST	RBW	VBW	SPAN	Detector	SWEEP	Trace	NOTES
PK output power	\geq DTS bandwidth	$\geq 3 X$ RBW	$\geq 3 X$ RBW	Peak	Auto	Max hold	-


Test Data Yes N/A

Test Plot Yes (See below) N/A


Output Power measurement result

Type	Freq (MHz)	CH	Conducted Power (dBm)	Limit (dBm)	Result
Output power	2405	Low	2.609	30	Pass
Output power	2440	Mid	2.670	30	Pass
Output power	2480	High	2.561	30	Pass


Test Plots



PWR-Zigbee 2405




PWR TX-Zigbee 2440



PWR-Zigbee 2480

10.4 Band Edge

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(d), RSS210 (A8.5)	a)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209 (a) is not required <input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down	☒
Test Setup			
Test Procedure	558074 D01 DTS Meas Guidance v03r02, 13.3 Method <u>Band Edge measurement procedure</u> <ul style="list-style-type: none"> - Set analyzer center frequency to the frequency of the emission to be measured. - Set the span to 2 MHz. - Set the RBW to: 100 kHz. - Set the VBW $\geq 1/T$. - Detector = peak. - Sweep time = auto couple. - Trace mode = max hold. - Allow trace to fully stabilize. - Use the peak marker function to determine the maximum amplitude level within the RBW. - If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. 		
Test Date	06/19/2014	Environmental condition	Temperature 22°C Relative Humidity 46% Atmospheric Pressure 1020mbar
Remark	EUT tested with Handheld computer and Battery Pack.		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Equipment Setting

TEST	RBW	VBW	SPAN	Detector	SWEEP	Trace	NOTES
Band Edge	100KHz	$\geq 1/T$	2MHz	Peak	Auto	Max hold	-


Test Data Yes N/A

Test Plot Yes (See below) N/A

Band Edge measurement result


Type	Freq (MHz)	CH	Conducted Band Edge (dBm/MHz)	PSD (dBm/MHz)	Difference (dB)	Limit (dB)	Result
Band Edge	2400	Low	-33.81	-1.66	32.15	≥20	Pass
Band Edge	2483.5	High	-27.69	-1.55	26.14	≥20	Pass

Test Plots



10.5 Peak Spectral Density

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(e), RSS210 (A8.3)	a)	DSSS: ≤8dBm/3KHz	<input checked="" type="checkbox"/>
	b)	DSSS in hybrid sys with FH turned off: ≤8dBm/3KHz	<input type="checkbox"/>
Test Setup			
Test Procedure	558074 D01 DTS Meas Guidance v03r01, 10.2 Method PKPSD (peak PSD) <u>Peak spectral density measurement procedure</u> <ul style="list-style-type: none"> - Set analyzer center frequency to DTS channel center frequency. - Set the span to 1.5 times the DTS bandwidth. - Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz. - Set the VBW ≥ 3 x RBW. - Detector = peak. - Sweep time = auto couple. - Trace mode = max hold. - Allow trace to fully stabilize. - Use the peak marker function to determine the maximum amplitude level within the RBW. - If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. 		
Test Date	06/14/2014	Environmental condition	Temperature 22°C Relative Humidity 46% Atmospheric Pressure 1020mbar
Remark	EUT tested with Handheld computer and Battery Pack.		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Equipment Setting


TEST	RBW	VBW	SPAN	Detector	SWEEP	Trace	NOTES
PSD	100KHz	≥3x RBW	1.5x DTS BW	Peak	Auto	Max hold	-

Test Data Yes N/A
Test Plot Yes (See below) N/A


PSD measurement result

Type	Freq (MHz)	CH	Conducted PSD (dBm/MHz)	Limit (dBm/MHz)	Result
Maximum PSD	2405	Low	-1.659	≤8	Pass
Maximum PSD	2440	Mid	-1.821	≤8	Pass
Maximum PSD	2480	High	-1.554	≤8	Pass


Test Plots



PSD-Zigbee 2405



PSD-Zigbee 2440



PSD-Zigbee 2480

10.6 Radiated Emissions below 1GHz

Requirement(s):


Spec	Item	Requirement	Applicable										
47CFR§15.247(d), RSS210(A8.5)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (uV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (uV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	☒
Frequency range (MHz)	Field Strength (uV/m)												
30 – 88	100												
88 – 216	150												
216 960	200												
Above 960	500												
Test Setup													
Procedure		<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission. A Quasi-peak measurement was then made for that frequency point. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. 											
Remark		The EUT was scanned up to 1GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case.											
Result		☒ Pass ☒ Fail											

Test Data ☒ Yes (See below) ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Radiated Emission Test Results (Below 1GHz)


Test specification	below 1GHz			Result	Pass
Environmental Conditions:	Temp (°C):	21.3			
	Humidity (%)	50.6			
	Atmospheric (mPa):	1010			
Mains Power:	110VAC, 60Hz				
Tested by:	Teody Manansala				
Test Date:	16-Jun-14				
Remarks:	Zigbee 2405				



Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
31.40	26.87	1.16	-17.31	10.72	Quasi Max	H	186.00	246	40	-29.28	Pass
38.18	27.81	1.16	-22.79	6.18	Quasi Max	H	377.00	342.00	40.00	-33.82	Pass
605.96	33.85	4.19	-21.71	16.33	Quasi Max	H	183	52.00	46.00	-29.67	Pass
748.18	31.91	4.67	-19.55	17.03	Quasi Max	H	211.00	302.00	46.00	-28.97	Pass
762.00	32.44	4.72	-18.98	18.17	Quasi Max	H	280.00	76.00	46.00	-27.83	Pass
934.15	31.94	5.06	-17.66	19.34	Quasi Max	H	232.00	109.00	46.00	-26.66	Pass

Note: Both horizontal and vertical polarities were investigated. The results above show only the worst case.

Test specification	below 1GHz			Result	Pass
Environmental Conditions:	Temp (°C):	21.3			
	Humidity (%)	50.6			
	Atmospheric (mPa):	1010			
Mains Power:	110VAC, 60Hz				
Tested by:	Teody Manansala				
Test Date:	18-Jun-14				
Remarks:	Zigbee Receiver Mode				



Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
30.38	26.71	1.16	-16.45	11.42	Quasi Max	V	196.00	291.00	40.00	-28.58	Pass
80.43	31.89	1.51	-31.86	1.54	Quasi Max	V	376.00	44.00	40.00	-38.46	Pass
81.56	31.89	1.53	-32.00	1.42	Quasi Max	V	258.00	10.00	40.00	-38.58	Pass
82.21	31.94	1.54	-32.05	1.42	Quasi Max	V	234.00	276.00	40.00	-38.58	Pass
785.20	31.27	4.79	-19.27	16.79	Quasi Max	V	130.00	164.00	46.00	-29.21	Pass
906.07	32.49	5.01	-17.95	19.55	Quasi Max	H	245.00	275.00	46.00	-26.45	Pass

10.7 Radiated Spurious Emissions above 1GHz

Requirement(s):

Spec	Item	Requirement	Applicable
47CFR§15.247(d), RSS210(A8.5)	a)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required <input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down	<input checked="" type="checkbox"/>
	b)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	<input checked="" type="checkbox"/>
Test Setup			
Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission. An average measurement was then made for that frequency point. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. 		
Remark	The EUT was scanned up to 25GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case.		
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Equipment Setting

TEST	RBW	VBW	SPAN	Detector	SWEEP	Trace	NOTES
Radiated Spurious Emission	1MHz	3MHz	1GHz - 25 GHz	Peak	Auto	Max hold	PK Measurement
Radiated Spurious Emission	1MHz	10Hz	1GHz - 25 GHz	Peak	Auto	Max hold	Ave Measurement

Test Data Yes (See below) N/A

Test Plot Yes (See below) N/A

Radiated Emission Test Results (Above 1GHz)

Above 1GHz-25GHz – Zigbee 2405

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
17946.91	41.17	7.01	14.29	62.46	Peak Max	H	213.00	73.00	74.00	-11.54	Pass
3939.62	40.85	2.85	-0.29	43.42	Peak Max	H	199.00	80.00	74.00	-30.58	Pass
4567.16	40.58	3.10	-0.20	43.47	Peak Max	V	173.00	259.00	74.00	-30.53	Pass
1619.91	40.38	1.56	-5.81	36.12	Peak Max	V	233.00	92.00	74.00	-37.88	Pass
17946.91	27.90	7.01	14.29	49.20	Average Max	H	213.00	73.00	54.00	-4.80	Pass
3939.62	27.55	2.85	-0.29	30.12	Average Max	H	199.00	80.00	54.00	-23.88	Pass
4567.16	26.92	3.10	-0.20	29.82	Average Max	V	173.00	259.00	54.00	-24.18	Pass
1619.91	27.38	1.56	-5.81	23.12	Average Max	V	233.00	92.00	54.00	-30.88	Pass

Restricted Band - Low CH

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
2390.00	41.54	2.12	-3.53	40.12	Peak Max	H	297.00	205.00	74.00	-33.88	Pass
2390.00	40.97	2.12	-3.53	39.55	Peak Max	V	294.00	270.00	74.00	-34.45	Pass
2390.00	27.92	2.12	-3.53	26.50	Average Max	H	297.00	205.00	54.00	-27.50	Pass
2390.00	27.82	2.12	-3.53	26.40	Average Max	V	294.00	27.00	54.00	-27.60	Pass

Above 1GHz-25GHz- Zigbee 2440

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
17981.63	40.76	7.01	14.40	62.17	Peak Max	H	198.00	307.00	74.00	-11.83	Pass
14474.84	43.55	6.60	10.92	61.07	Peak Max	H	222.00	256.00	74.00	-12.93	Pass
3928.14	41.27	2.85	-0.31	43.80	Peak Max	V	246.00	278.00	74.00	-30.20	Pass
1509.45	41.61	1.44	-6.24	36.80	Peak Max	H	289.00	248.00	74.00	-37.20	Pass
17981.63	27.82	7.01	14.40	49.23	Average Max	H	198.00	307.00	54.00	-4.77	Pass
14474.84	29.78	6.60	10.92	47.30	Average Max	H	222.00	256.00	54.00	-6.70	Pass
3928.14	27.76	2.85	-0.31	30.29	Average Max	V	246.00	278.00	54.00	-23.71	Pass
1509.45	28.21	1.44	-6.24	23.41	Average Max	H	289.00	248.00	54.00	-30.59	Pass

Above 1GHz-25GHz- Zigbee 2480

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
17906.92	41.04	7.00	14.15	62.20	Peak Max	V	233.00	297.00	74.00	-11.80	Pass
14475.07	43.15	6.60	10.92	60.67	Peak Max	H	209.00	227.00	74.00	-13.33	Pass
3937.67	40.85	2.85	-0.30	43.41	Peak Max	V	276.00	325.00	74.00	-30.59	Pass
17906.92	27.87	7.00	14.15	49.03	Average Max	V	233.00	297.00	54.00	-4.97	Pass
14475.07	29.75	6.60	10.92	47.27	Average Max	H	209.00	227.00	54.00	-6.73	Pass
3937.67	27.58	2.85	-0.30	30.14	Average Max	V	276.00	325.00	54.00	-23.86	Pass
17906.92	41.04	7.00	14.15	62.2	Peak Max	V	233.00	297.00	74.00	-11.80	Pass
14475.07	43.15	6.60	10.92	60.67	Peak Max	H	209.00	227.00	74.00	-13.33	Pass

Restricted Band - High CH

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
2483.50	73.61	2.15	-3.32	72.44	Peak Max	H	123.00	332.00	74.00	-1.56	Pass
2483.50	69.15	2.15	-3.32	67.99	Peak Max	V	299.00	159.00	74.00	-6.01	Pass
2483.50	52.88	2.15	-3.32	51.71	Average Max	H	123.00	332.00	54.00	-2.29	Pass
2483.50	48.80	2.15	-3.32	47.64	Average Max	V	299.00	159.00	54.00	-6.36	Pass

















Annex A. TEST INSTRUMENT








Instrument	Model	Serial #	Cal Date	Cal Cycle	Cal Due	In use
Conducted Emissions						
R & S Receiver	ESIB 40	100179	04/20/2014	1 Year	04/20/2015	<input type="checkbox"/>
R&S LISN	ESH2-Z5	861741/013	05/18/2014	1 Year	05/18/2015	<input type="checkbox"/>
CHASE LISN	MN2050B	1018	07/24/2013	1 Year	07/24/2014	<input type="checkbox"/>
Sekonic Hygro Hermograph	ST-50	HE01-000092	05/25/2014	1 Year	05/25/2015	<input type="checkbox"/>
Radiated Emissions						
R & S Receiver	ESL6	100178	03/01/2014	1 Year	03/01/2015	<input checked="" type="checkbox"/>
R & S Receiver	ESIB 40	100179	04/20/2014	1 Year	04/20/2015	<input checked="" type="checkbox"/>
ETS-Lingren Loop Antenna	6512	00049120	05/13/2014	1 Year	05/13/2015	<input type="checkbox"/>
Bi-Log antenna (30MHz~2GHz)	JB1	A030702	07/03/2014	1 Year	07/03/2015	<input checked="" type="checkbox"/>
Horn Antenna (1-26.5GHz)	3115	10SL0059	04/26/2014	1 Year	04/26/2015	<input checked="" type="checkbox"/>
Horn Antenna (18-40 GHz)	AH-840	101013	04/23/2014	1 Year	04/23/2015	<input checked="" type="checkbox"/>
Pre-Amplifier (1-26.5GHz)	8449B	3008A00715	05/30/2014	1 Year	05/30/2015	<input checked="" type="checkbox"/>
Microwave Preamplifier (18-40 GHz)	PA-840	181251	05/30/2014	1 Year	05/30/2015	<input checked="" type="checkbox"/>
3 Meters SAC	3M	N/A	10/13/2013	1 Year	10/13/2014	<input checked="" type="checkbox"/>
10 Meters SAC	10M	N/A	06/05/2014	1 Year	06/05/2015	<input checked="" type="checkbox"/>
Sekonic Hygro Hermograph	ST-50	HE01-000092	05/25/2014	1 Year	05/25/2015	<input checked="" type="checkbox"/>
RF Conducted Measurement						
Spectrum Analyzer	N9010A	MY50210206	05/30/2014	1 Year	05/30/2015	<input checked="" type="checkbox"/>
Spectrum Analyzer	E4407B	US88441016	05/31/2014	1 Year	05/31/2015	<input checked="" type="checkbox"/>
R & S Receiver	ESIB 40	100179	04/20/2014	1 Year	04/20/2015	<input checked="" type="checkbox"/>

Annex B. USER MANUAL, BLOCK & CIRCUIT DIAGRAM

Please see attachment

Annex C. SIEMIC Accreditation

Accreditations	Document	Scope / Remark
ISO 17025 (A2LA)		Please see the documents for the detailed scope
ISO Guide 65 (A2LA)		Please see the documents for the detailed scope
TCB Designation		A1, A2, A3, A4, B1, B2, B3, B4, C
FCC DoC Accreditation		FCC Declaration of Conformity Accreditation
FCC Site Registration		3 meter site
FCC Site Registration		10 meter site
IC Site Registration		3 meter site
IC Site Registration		10 meter site
EU NB		Radio & Telecommunications Terminal Equipment: EN45001 – EN ISO/IEC 17025
		Electromagnetic Compatibility: EN45001 – EN ISO/IEC 17025
Singapore iDA CB(Certification Body)	 	Phase I, Phase II
Vietnam MIC CAB Accreditation		Please see the document for the detailed scope
Hong Kong OFCA		(Phase II) OFCA Foreign Certification Body for Radio and Telecom
		(Phase I) Conformity Assessment Body for Radio and Telecom
Industry Canada CAB		Radio: Scope A – All Radio Standard Specification in Category I
		Telecom: CS-03 Part I, II, V, VI, VII, VIII

Japan Recognized Certification Body Designation		<p>Radio: A1. Terminal equipment for purpose of calling</p> <p>Telecom: B1. Specified radio equipment specified in Article 38-2, Paragraph 1, Item 1 of the Radio Law</p>
Korea CAB Accreditation		<p>EMI: KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI KN22: Test Method for EMI</p> <p>EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS KN24, KN61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS</p>
		<p>Radio: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10, RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21, RRL Notice 2007-80, RRL Notice 2004-68</p> <p>Telecom: President Notice 20664, RRL Notice 2007-30, RRL Notice 2008-7 with attachments 1, 3, 5, 6; President Notice 20664, RRL Notice 2008-7 with attachment 4</p>
Taiwan NCC CAB Recognition		LP0002, PSTN01, ADSL01, ID0002, IS6100, CNS14336, PLMN07, PLMN01, PLMN08
Taiwan BSMI CAB Recognition		CNS 13438
Japan VCCI		R-3083: Radiation 3 meter site
		C-3421: Main Ports Conducted Interference Measurement T-1597: Telecommunication Ports Conducted Interference Measurement
Australia CAB Recognition		<p>EMC: AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR22, AS/NZS 61000.6.3, AS/NZS 61000.6.4</p>
		<p>Radio communications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771</p>
		<p>Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06 AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/ACIF S60950.1</p>
Australia NATA Recognition		AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016, AS/ACIF S031, AS/ACIF S038, AS/ACIF S040, AS/ACIF S041, AS/ACIF S043.2