

For FCC Standalone SAR test exclusion considerations

FCC ID: WAP-CY5677

Tunable Range	
F(GHz) Low	F(GHz) High
2.402	2.480

According to **KDB 447498 D01 General RF Exposure Guidance v06**

4.3.1 Standalone SAR test exclusion considerations

The 1-g and 10-g SAR test exclusion thresholds for below 100 MHz at test separation distances ≤ 50 mm are determined by:

- The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances > 50 mm and < 200 mm
- The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm
- SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable. Note: when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Based on the Maximum measured transmitter power:

Frequency (MHz)	Pout Conducted (dBm)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
BT3.0	1.99	1.6	2.29

$EIRP = P_{\text{Conducted}} + \text{Antenna Gain}$

Threshold for no SAR evaluation is 10.00 mW

Maximum TX Power is 2.29 mW EIRP

Maximum TX Power is 2.29 mW

Conclusion: No SAR evaluation required since maximum Transmitter Pout is below FCC threshold