

### Cypress Semiconductor

### **Request for Modular/Limited Modular Approval**

Date:	e: August 14, 2019					
Subje	iect: Manufacturer's Declaration for □ - Modular Approval □ - Limited Modular Approva	☐ - Split Modull ☐ - Limited Sp				
Confi	fidentiality Request for: FCC ID: WAP3053					
	8 Basic Requirements – FCC Part 15.21 For Items Marked "NO(*)", the Limited Module Description Must b		Following Pag	es		
	Modular Approval Requirement Requirement Requirement Met					
1.	The modular transmitter must have its own RF shielding. This is intended to end does not have to rely upon the shielding provided by the device into which it is all modular transmitter emissions to comply with FCC limits. It is also intended between the RF circuitry of the module and any wires or circuits in the device in module is installed. Such coupling may result in non-compliant operation. The tuning capacitors may be located external to the shielded radio elements. 15.212	installed in order for to prevent coupling nto which the physical crystal and	⊠ - YES	□ - NO(*)		
	Details: <example a="" all="" and="" antenna="" board="" circuitry.="" components="" connector="" contains="" covers="" is="" located="" metal="" module="" next="" of="" on="" rf="" shield="" the="" to="" top="" which="" –=""></example>					
2.	The modular transmitter must have buffered modulation/data inputs (if such inpensure that the module will comply with FCC requirements under conditions of or over-modulation. 15.212(a)(1)(ii)		⊠ - YES	☐ - NO(*)		
	Details: <example application="" as="" buffered="" circuit="" data="" described="" in="" is="" modulation="" the="" to="" –=""></example>	n the operational desc	ription provid	led with the		
3.	The modular transmitter must have its own power supply regulation on the mod to ensure that the module will comply with FCC requirements regardless of the supplying circuitry in the device into which the module is installed. 15.212(a)(1)	design of the power	⊠ - YES	□ - NO(*)		
	Details: <example application="" contains="" i="" its="" module="" own="" power="" regulation.="" supply="" the="" –=""></example>	Please refer to schemo	atic filed with	this		
4.	The modular transmitter must comply with the antenna and transmission system 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must either attached or employ a "unique" antenna coupler (at all connections between the antenna, including the cable). The "professional installation" provision of § 15 applicable to modules but can apply to limited modular approvals under paragra 15.212(a)(1)(iv)	be permanently module and the .203 is not	⊠ - YES	□ - NO(*)		
	Details: <example a="" an="" and="" antenna="" antennas="" application="" approved="" be="" connector.="" connects="" device="" four="" its="" list="" may="" module="" of="" tested="" the="" this="" to="" ufl="" using="" with="" –=""></example>					
	The modular transmitter must be tested in a stand-alone configuration, i.e., the rinside another device during testing. This is intended to demonstrate that the mocomplying with Part 15 emission limits regardless of the device into which it is Unless the transmitter module will be battery powered, it must comply with the requirements found in Section 15.207. AC or DC power lines and data input/out to the module must not contain ferrites, unless they will be marketed with the module must not contain ferrites, unless they will be marketed with the module must not contain ferrites, unless they will be marketed with the module must not contain ferrites, unless they will be marketed with the module during testing shall be length typical of actual use or, if the unknown, at least 10 centimeters to insure that there is no coupling between the and supporting equipment. Any accessories, peripherals, or support equipment of module during testing shall be unmodified or commercially available (see Section 15.212(a)(1)(v)	odule is capable of eventually installed. AC line conducted tput lines connected todule (see Section at length is case of the module connected to the	⊠ - YES	□ - NO(*)		
	Details: <example as="" in="" module="" setu<="" shown="" stand-alone="" td="" test="" tested="" the="" was="" –=""><td>p photographs filed w</td><td>rith this applic</td><td>cation&gt;</td></example>	p photographs filed w	rith this applic	cation>		





## CYPRESS Cypress Semiconductor

	Modular Approval Requirement		Requirement Met	
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748).  If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.  If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)	⊠ - YES	□ - NO(*)	
	Details: <example a="" application.="" are="" as="" exhibit="" filed="" in="" installation="" instructions="" is="" label="" labeling="" manual="" module="" on="" shown="" the="" there="" this="" with="" –=""></example>	application. 1	Host specific	
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)	
	Details: <example 15c="" application.="" complies="" fcc="" filed="" installation="" instructions="" manual="" module="" online="" part="" requirements.="" the="" this="" to="" with="" –=""></example>	EM installer (	are provided	
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)	
	Details: <example application.="" as="" exclusion="" exposure="" in="" info="" levels="" meets="" module="" portable="" rf="" shown="" the="" –=""></example>	rmation filed	with this	



## CYPRESS Cypress Semiconductor

### **Limited Module Description – When Applicable**

\* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <example - N/A>

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)					
Requirement	Requirement Met				
<ol> <li>For non-Software Defined Radio transmitter modules where software is used to ensure compliance of the device, technical description must be provided about hos such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.</li> </ol>					
Details: <example a="" adjusted="" application.="" as="" be="" by="" can="" cover="" described="" device="" end="" filed="" firmware="" in="" letter="" modified="" not="" of="" or="" separate="" the="" this="" user="" with="" –=""></example>					
<ol> <li>For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.</li> </ol>	$ \begin{array}{c c} \hline  & \square \text{ - Provided in Separate} \\ \hline  & \text{Cover Letter} \end{array} \qquad \boxed{\square} \text{ - N/A} $				
Details: <example -n="" a=""></example>					

Split Modular Requirements						
Requirement	Provided in Manual					
<ol> <li>For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained.</li> </ol>	☐ - Provided in Separate  Cover Letter	⊠ - N/A				
Details: <example a="" n="" –=""></example>						



# CYPRESS Cypress Semiconductor

OEM Integration Manual Guidance – KDB 996369 D03 Section 2						
Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures						
for third-parties to use and/or integrate the module into a host device.						
Requirement						
Kequii ement	-					
		□ - No,	. 11 1			
		If No, and LMA applies, the applicant can optionally choose to				
		not make the following detailed info public. However there still needs to be basic integration instructions for a users manual and				
Is this module intended for	□ - YES	the information below must still be included in the operational				
sale to third parties?		description. If the applicant wishes to keep this info confidential,				
		this will require a separate statement co				
		module is not for sale to third partie				
		instructions are internal confide	ential documents.			
		nual – See KDB 996369 D03, Section 2				
		formation to be in the installation manual				
		for all these items indicating clearly when				
		indicate "Not Applicable". Also if a modu				
		parties, the user instructions may not need iption, but this should include a cover let				
List of applicable FCC rules.			ter as cited above.			
	s related to the transmitter.					
2. Summarize the specific opera		96369 D03 Section 2.3				
		e loss, reduction of power for point to point				
	essional installation info					
3. Limited Module Procedures.		4				
		uses to verify the host meets the necessary				
limiting condi		•	☐ - All Items shown to			
	ce is ensured, such as Class II	for new hosts, etc.	the Modular Integration			
4. Trace antenna designs. KDE			Guide (or UM) for Full			
		onnectors, isolation requirements, tests for	Modular Approval			
	design verification, and production test procedures for ensuring compliance. If					
		lential must be identified and information				
5. RF exposure considerations.	ne operational description.	6	☐ - An LMA applies			
		llow host manufacturers to use the	and is approved ONLY			
		ssary: first to the host manufacturer to	for use by the grantee in			
		from body) and second additional text	their own products, and			
needed to be j	provided to the end user in the	host product manuals.	not intended for sale to			
6. Antennas. KDB 996369 D03			3 <sup>rd</sup> parties as provided in			
		and all applicable professional installer	a separate cover letter.  Therefore the			
		st shall also identify the antenna types	information shown to			
		nni-directional" is not considered a type)	the left is found in the			
7. Label and compliance inform a. Advice to hos		provide a physical or e-label stating	theory of operation.			
	C ID: " with their finished pro					
		ents. KDB 996369 D03, Section 2.9				
		eration by host integrators including				
	necessary for stand-alone and					
	mation on how to configure tes					
9. Additional testing, Part 15 St	ubpart B disclaimer. KDB 996	369 D03, Section 2.10				
XIALI SO ZINON	NA					
Sincerely, Auglian Thur	0					
		V '' 71				
By:	_System Engineer	Xuejiao Zhang				
(Sign	ature/Title <sup>1</sup> )	(Print name)				

<sup>&</sup>lt;sup>1</sup> - Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.