



Test report No:
2440634R-RF-US-P20V01

SAR Exemption Evaluation Report

| | |
|---|--|
| Product Name | AIROC Bluetooth LE Module |
| Trademark |  |
| Model and /or type reference | CYW20829-P4TAI200, CYW20829-P4EPI200, CYW20829-P4EFI200 |
| FCC ID | WAP829I20 |
| Applicant's name / address | Cypress Semiconductor 198 Champion Ct, San Jose, California 95134, United States |
| Test method requested, standard | FCC 47CFR §2.1091 |
| Verdict Summary | IN COMPLIANCE |
| Documented By (name / position & signature) | Tim Cao / Project Manager  |
| Approved by (name / position & signature) | Jack Zhang / Manager  |
| Date of issue | 2024-07-08 |
| Report Version | V1.0 |
| Report template No | Template_FCC MPE-RF-V1.0 |

INDEX

| | page |
|--|------|
| Competences and Guarantees..... | 3 |
| General conditions..... | 3 |
| Environmental conditions..... | 3 |
| Possible test case verdicts..... | 4 |
| Abbreviations | 4 |
| Document History..... | 5 |
| Remarks and Comments | 5 |
| 1. RF Exposure Evaluation..... | 6 |
| 1.1. Limits | 6 |
| 1.2. Test Procedure | 7 |
| 1.3. General Description of the Item(s)..... | 7 |
| 1.4. Antenna Information | 8 |
| 1.5. Test Result of RF Exposure Evaluation | 8 |

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

| | |
|-----------------------|--|
| Test Location | No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China |
| Date (receive sample) | Apr. 23, 2024 |
| Date (start test) | May. 15, 2024 |
| Date (finish test) | May. 25, 2024 |

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

| | |
|-----------------------|--------------|
| Ambient temperature | 15°C - 35 °C |
| Relative Humidity air | 30% - 60% |

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

| | |
|---|-----------------|
| Test case does not apply to test object | N/A |
| Test object does meet requirement | P (Pass) / PASS |
| Test object does not meet requirement | F (Fail) / FAIL |
| Not measured | N/M |

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

| | |
|------|-------------------------------|
| EUT | : Equipment Under Test |
| QP | : Quasi-Peak |
| CAV | : CISPR Average |
| AV | : Average |
| CDN | : Coupling Decoupling Network |
| SAC | : Semi-Anechoic Chamber |
| OATS | : Open Area Test Site |
| BW | : Bandwidth |
| AM | : Amplitude Modulation |
| PM | : Pulse Modulation |
| HCP | : Horizontal Coupling Plane |
| VCP | : Vertical Coupling Plane |
| UN | : Nominal voltage |
| Tx | : Transmitter |
| Rx | : Receiver |
| N/A | : Not Applicable |
| N/M | : Not Measured |

DOCUMENT HISTORY

| Report No. | Version | Description | Issued Date |
|-----------------------|---------|--------------------------|-------------|
| 2440634R-RF-US-P20V01 | V1.0 | Initial issue of report. | 2024-07-08 |
| | | | |
| | | | |
| | | | |
| | | | |

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on the device are for the purpose of demonstrating Compliance with FCC 47CFR §2.1091.
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, it is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1.4 Antenna information.

1. RF Exposure Evaluation

1.1. Limits

According to § 1.1307(b)(3)(i)(B)

The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);


Finally, when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption threshold.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. General Description of the Item(s)

| | |
|----------------------------|--|
| Product Name | AIROC Bluetooth LE Module |
| Model No..... | CYW20829-P4TAI200, CYW20829-P4EPI200, CYW20829-P4EFI200 |
| Trademark..... |  |
| FCC ID..... | WAP829I20 |
| SoftwareVersion | REV1.0 |
| HardwareVersion..... | REV1.0 |
| Operating temperature..... | -30°C to +85°C |
| Manufacturer | Cypress Semiconductor |
| Manufacturer address..... | 198 Champion Ct, San Jose, California 95134, United States |
| Factory..... | FITTEC ELECTRONICS (Suzhou) CO., LTD. |
| Factory address..... | No. 29, Donfu Road, Loufeng East District, Suzhou Industrial Park, Suzhou, Jiangsu Province, P.R.China |
| Model difference | Three modules share the same design, the difference is antenna configuration, CYW20829-P4TAI200 is PCB antenna; CYW20829-P4EPI200 is RF pad which connect external antenna, CYW20829-P4EFI200 is RF connector which connect external antenna. CYW20829-P4EFI200 as the main test equipment, and the other 2 models verify power and RSE. |

| | | | | | | |
|------------------------------|-------------------------------------|---------|-------------------------------------|---------|-------------------------------------|----------------|
| Wireless specification | Bluetooth (LE) | | | | | |
| Operating frequency range(s) | 2402~2480MHz | | | | | |
| Type of Modulation | GFSK | | | | | |
| PHYs..... | <input checked="" type="checkbox"/> | LE 1M | <input checked="" type="checkbox"/> | LE 2M | <input checked="" type="checkbox"/> | LE Coded S=2/8 |
| Data Rate..... | <input checked="" type="checkbox"/> | 1Mbit/s | <input checked="" type="checkbox"/> | 2Mbit/s | <input checked="" type="checkbox"/> | 500/125 Kbit/s |
| Number of channels | 40 | | | | | |

| | | | | | | |
|--------------------------|-------------------------------------|--------------------------------|--|--|--|--|
| Rated power supply | Voltage and Frequency | | | | | |
| | <input type="checkbox"/> | AC: 220 - 240 V, 50/60 Hz | | | | |
| | <input type="checkbox"/> | AC: 100 - 240 Vac, 50/60 Hz | | | | |
| | <input checked="" type="checkbox"/> | DC: 3.3 Vdc | | | | |
| | <input type="checkbox"/> | Poe: | | | | |
| Mounting position | <input type="checkbox"/> | Table top equipment | | | | |
| | <input type="checkbox"/> | Wall/Ceiling mounted equipment | | | | |
| | <input type="checkbox"/> | Floor standing equipment | | | | |

| | | |
|--|-------------------------------------|------------------------------|
| | <input type="checkbox"/> | Hand-held/Portable equipment |
| | <input checked="" type="checkbox"/> | Other: |

1.4. Antenna Information

| | | | |
|--------------------------|-------------------------------------|---|--|
| Antenna Delivery | <input checked="" type="checkbox"/> | 1TX + 1RX | |
| | <input type="checkbox"/> | 2TX + 2RX | |
| | <input type="checkbox"/> | Others: | |
| Antenna technology | <input checked="" type="checkbox"/> | SISO | |
| | <input type="checkbox"/> | MIMO | <input type="checkbox"/> CDD |
| | <input type="checkbox"/> | | <input type="checkbox"/> Beam-forming |
| Antenna Type | <input checked="" type="checkbox"/> | External | <input checked="" type="checkbox"/> Dipole |
| | <input type="checkbox"/> | | <input type="checkbox"/> Sectorized |
| | <input checked="" type="checkbox"/> | | Internal |
| | <input type="checkbox"/> | <input type="checkbox"/> PIFA | |
| | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> PCB | |
| | <input type="checkbox"/> | Others..... | |
| Antenna Gain | External Antenna | | Internal Antenna |
| | 2.0 dBi | | -0.5 dBi |

Note 1: The data shown in report was based on External Antenna which gain is higher.

Note 2: The antenna information for the EUT in clause 1.4 are provided and confirmed by the client.

1.5. Test Result of RF Exposure Evaluation

| Mode | Exposure Condition | Pmax (dBm) | EIRP (mW) | ERP (mW) | Distance (mm) | f(GHz) | Pth (mW) | RF Exposure Test |
|-----------|--------------------|------------|-----------|----------|---------------|--------|----------|------------------|
| Bluetooth | Body | 20.95 | 124.45 | 75.86 | 200 | 2.480 | 3060 | Exemption |

Conclusion: Exemption from RF Exposure Testing.

_____ The End _____