



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Packet Power, LLC

Model: EMB1

Description: Battery Powered Environmental Monitor

FCC ID: ECGP5EMB1

To

FCC Part 1.1310

Date of Issue: February 5, 2015

On the behalf of the applicant:

**Packet Power, LLC
2716 Summer St NE
Minneapolis, MN 55413**

Attention of:

**Paul Bieganski, CTO
Ph: (877)560-8770
E-Mail: paul@packetpower.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p14b0019**

**Alex Macon
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	January 30, 2015	Alex Macon	Original Document



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: EMB1

Description: Battery Powered Environmental Monitor

Software: NMX Packet Power URL

Serial Number: N/A

Additional Information:

The EUT is an inline voltage and current meter which incorporates a 2.4 GHz radio and a 900 MHz radio with an integral antenna.



Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Radiated Peak Output Power (mW)	Duty Cycle	Average Power (mW)
902.4	0.005 mW	100%	mW
2401	0.401 mW	100%	mW

Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)

0.3-1.234 MHz	Limit [mW/cm ²] = 100
1.34-30 MHz	Limit [mW/cm ²] = (180/f ²)
30-300 MHz	Limit [mW/cm ²] = 0.2
300-1500 MHz	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

927.6 MHz Limit is 0.6016 mW/cm²

2401 MHz limit is 1.0 mW/cm²

END OF TEST REPORT