



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Comprod Communications Ltd.

Model: BDA896940

Description: 30 dBm BDA 900 with MCU

Serial Number: 5F35567

FCC ID: WDM-896940

To

FCC Part 1.1310

Date of Issue: February 4, 2016

On the behalf of the applicant:

Comprod Communications Ltd.
88 boul, Industriel
Boucherville, QB J4B 2X2
Canada

Attention of:

Jawad Abulnour, Engineer
Ph: (514)777-2892
Email: jawad@comprodcom.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p15a0020

Greg Corbin
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested

Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	February 2, 2016	Greg Corbin	Original Document

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: BDA896940

Description: 30 dBm BDA 900 with MCU

Firmware: BDA RF GUI v1.02

Serial Number: 5F35567

Additional Information:

The EUT is classified as a Part 90 PS **Class B** industrial signal booster

The EUT is a Bi-directional Amplifier that operates from 896 - 901 MHz (Uplink, Mobile to Base) and 935 - 940 MHz (Downlink, Base to Mobile).

System Power is 120 VAC @ 60 Hz.

MPE Evaluation

This is a Fixed device used in **Uncontrolled** Exposure environment.

Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

The MPE calculation was performed using the manufacturers rated output power of (+31.5 dBm) with an antenna gain of 0 dBi.

Test Frequency, MHz	896
Power, Conducted, mW (P)	1412
Antenna Gain Isotropic	0 dBi
Antenna Gain Numeric (G)	1
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) = 0.281 mw/cm ²
Limit =(from above table) = 0.597 mw/cm ²