

MPE Calculations(WLAN: 802.11b)

- Frequency range : **2412** MHz ~ **2462** MHz
- Maximum RF output power : **19.23** dBm
- Maximum antenna peak gain : **0.77** dBi

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

<ul style="list-style-type: none">▪ EIRP = P + G= 19.23 dBm + 0.77 dBi= 20.00 dBm	<ul style="list-style-type: none">- NoteP = Power input to the antenna(dBm)G = Power gain of the antenna(dBi)
-----------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------

- Power density at the specific separation

<ul style="list-style-type: none">▪ S = $P G / (4 R^2 \pi)$= 83.75 X 1.194 / (4 X 20² X π)= 0.01989 mW/cm²	<ul style="list-style-type: none">- NoteS = Maximum power density(mW/cm²)P = Power input to the antenna(mW)G = Numeric power gain of the antennaR = Distance to the center of the radiation of the antenna(20cm)
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Conclusion : **The exposure condition of this device is compliant with FCC rules.**

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm².
The power density at 20cm does not exceed the 1.0mW/cm².

MPE Calculations(WLAN: 802.11g)

- Frequency range : **2412** MHz ~ **2462** MHz
- Maximum RF output power : **23.32** dBm
- Maximum antenna peak gain : **0.77** dBi

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

<ul style="list-style-type: none">▪ EIRP = P + G= 23.32 dBm + 0.77 dBi= 24.09 dBm	<ul style="list-style-type: none">- NoteP = Power input to the antenna(dBm)G = Power gain of the antenna(dBi)
-----------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------

- Power density at the specific separation

<ul style="list-style-type: none">▪ S = $P G / (4 R^2 \pi)$= 214.78 X 1.194 / (4 X 20² X π)= 0.05102 mW/cm²	<ul style="list-style-type: none">- NoteS = Maximum power dencity(mW/cm²)P = Power input to the antenna(mW)G = Numeric power gain of the antennaR = Distance to the center of the radiation of the antenna(20cm)
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Conclusion : **The exposure condition of this device is compliant with FCC rules.**

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm².
The power desity at 20cm does not exceed the 1.0mW/cm².

MPE Calculations(WLAN: 802.11n HT20)

- Frequency range : **2412** MHz ~ **2462** MHz
- Maximum RF output power : **21.67** dBm
- Maximum antenna peak gain : **0.77** dBi

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

<ul style="list-style-type: none">▪ EIRP = P + G= 21.67 dBm + 0.77 dBi= 22.44 dBm	<ul style="list-style-type: none">- NoteP = Power input to the antenna(dBm)G = Power gain of the antenna(dBi)
-----------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------

- Power density at the specific separation

<ul style="list-style-type: none">▪ S = $P G / (4 R^2 \pi)$= 146.89 X 1.194 / (4 X 20² X π)= 0.03489 mW/cm²	<ul style="list-style-type: none">- NoteS = Maximum power density(mW/cm²)P = Power input to the antenna(mW)G = Numeric power gain of the antennaR = Distance to the center of the radiation of the antenna(20cm)
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Conclusion : **The exposure condition of this device is compliant with FCC rules.**

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm².
The power density at 20cm does not exceed the 1.0mW/cm².

MPE Calculations(WLAN: 802.11n HT40)

- Frequency range : **2422** MHz ~ **2452** MHz
- Maximum RF output power : **21.79** dBm
- Maximum antenna peak gain : **0.77** dBi

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

<ul style="list-style-type: none">▪ EIRP = P + G= 21.79 dBm + 0.77 dBi= 22.56 dBm	<ul style="list-style-type: none">- NoteP = Power input to the antenna(dBm)G = Power gain of the antenna(dBi)
-----------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------

- Power density at the specific separation

<ul style="list-style-type: none">▪ S = P G / (4 R² π)= 151.01 X 1.194 / (4 X 20² X π)= 0.03587 mW/cm²	<ul style="list-style-type: none">- NoteS = Maximum power dencity(mW/cm²)P = Power input to the antenna(mW)G = Numeric power gain of the antennaR = Distance to the center of the radiation of the antenna(20cm)
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Conclusion : **The exposure condition of this device is compliant with FCC rules.**

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm².
The power desity at 20cm does not exceed the 1.0mW/cm².