



**FCC CFR47 PART 15 SUBPART C  
INDUSTRY CANADA RSS-210 ISSUE 7  
CERTIFICATION TEST REPORT**

**FOR**

**1047- 01 SECURITY TRANSMITTER**

**MODEL NUMBER: 2GIG-TAKE-319**

**FCC ID: WDQ-TAK1319**

**IC: 7794A-TAK1319**

**REPORT NUMBER: 09U12445-1**

**ISSUE DATE: MARCH 23, 2009**

*Prepared for*

**2GIG Technologies, Inc.**

**200 Broadhollow Rd. Suite 207**

**Melville, NY 11747**

*Prepared by*

**COMPLIANCE CERTIFICATION SERVICES**

**47173 BENICIA STREET**

**FREMONT, CA 94538 U.S.A.**

**TEL: (510) 771-1000**

**FAX: (510) 661-0888**



**NVLAP LAB CODE 200065-0**

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
---	03/23/09	Initial Issue	T. Chan

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	5
3. FACILITIES AND ACCREDITATION.....	5
4. CALIBRATION AND UNCERTAINTY.....	5
4.1. MEASURING INSTRUMENT CALIBRATION .....	5
4.2. MEASUREMENT UNCERTAINTY.....	5
5. EQUIPMENT UNDER TEST .....	6
5.1. DESCRIPTION OF EUT.....	6
5.2. DESCRIPTION OF AVAILABLE ANTENNAS.....	6
5.3. SOFTWARE AND FIRMWARE.....	6
5.4. MODIFICATIONS.....	6
5.5. WORST-CASE CONFIGURATION AND MODE.....	6
5.6. DESCRIPTION OF TEST SETUP.....	7
6. TEST AND MEASUREMENT EQUIPMENT.....	9
7. LIMITS AND RESULTS .....	10
7.1. 20dB & 99% BANDWIDTHS .....	10
7.2. DUTY CYCLE.....	13
7.3. TRANSMISSION TIME.....	19
7.4. RADIATED EMISSION TEST RESULTS.....	20
7.5. RX RADIATED SPURIOUS EMISSION .....	22
8. SETUP PHOTOS.....	23

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** 2GIG Technologies, Inc.  
200 Broadhollow Rd. Suite 207  
Melville, NY 11747.

**EUT DESCRIPTION:** 1047- 01 SECURITY TRANSMITTER

**MODEL:** 2GIG-TAKE- 319

**SERIAL NUMBER:** 3 and 4

**DATE TESTED:** MARCH 13 AND 17, 2009

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	PASS
INDUSTRY CANADA RSS-210 ISSUE 7	PASS

Compliance Certification Services, Inc. (CCS) tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by CCS based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:



THU CHAN  
EMC MANAGER  
COMPLIANCE CERTIFICATION SERVICES

Tested By:



THANH NGUYEN  
EMC ENGINEER  
COMPLIANCE CERTIFICATION SERVICES

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2003, FCC CFR 47 Part 2 and FCC CFR 47 Part 15, IC RSS-210 and IC RSS-212.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Power Line Conducted Emission	+/- 2.3 dB
Radiated Emission	+/- 3.4 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

<b>Equipment Type</b>	319.508 MHz Transmitter
<b>Fundamental Frequency</b>	319.508 MHz
<b>Power Source</b>	12VDC
<b>Transmitting Time</b>	Periodic $\leq$ 5 seconds
<b>Manufacturer</b>	Secure Wireless, Inc.

### 5.2. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an internal loop antenna, with -15 dBi gain.

### 5.3. SOFTWARE AND FIRMWARE

EUT is modified to transmit continuously.

### 5.4. MODIFICATIONS

No modifications were made during testing.

### 5.5. WORST-CASE CONFIGURATION AND MODE

The worst-case channel is determined by X, Y, and Z-axis. The highest measured output power was at Y-Axis.

## 5.6. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

N/A


### I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	DC	1	DC Plug	Unshielded	1.8m	N/A

### TEST SETUP

The EUT is stand-alone unit and is battery operated, and the AC/DC adapter is just for the testing purpose only.

**SETUP DIAGRAM FOR TESTS**





## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset	Cal Due
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C00996	4/20/2010
Spectrum Analyzer, 26.5 GHz	Agilent / HP	E4407B	C01101	7/27/2010
PreAmp	Sonoma	310N	N02891	3/31/2009
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01063	2/4/2010
Antenna, Bilog, 2 GHz	Sunol Sciences	JB1	C01011	1/14/2010
Antenna, Horn, 18 GHz	EMCO	3115	C00945	4/22/2009

## 7. LIMITS AND RESULTS

### 7.1. 20dB & 99% BANDWIDTHS

#### LIMITS

FCC §15.231 (c)

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

IC A1.1.3

For the purpose of Section A1.1, the 99% Bandwidth shall be no wider than 0.25% of the center frequency for devices operating between 70-900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency.

#### TEST PROCEDURE

ANSI C63.4

The transmitter output is connected to the spectrum analyzer.

20dB Bandwidth: The RBW is set to 100 KHz. The VBW is set to 300 KHz. The sweep time is coupled. Bandwidth is determined at the points 20 dB down from the modulated carrier.

99% Bandwidth: The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

#### RESULTS


20dB Bandwidth

Frequency (MHz)	20dB Bandwidth (KHz)	Limit (KHz)	Margin (KHz)
433.92	745	1084.8	-339.8


99% Bandwidth

Frequency (MHz)	99% Bandwidth (KHz)	Limit (KHz)	Margin (KHz)
433.92	71.59	1084.8	-1013.2

**20dB BANDWIDTH**



**99% BANDWIDTH**



## 7.2. DUTY CYCLE

### LIMITS

FCC §15.35 (c)

The measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer or radiated field strength. The RBW is set to 100 kHz and the VBW is set to 100 kHz. The sweep time is coupled and the span is set to 0 Hz. The number of pulses is measured and calculated in a 100 ms scan.


### CALCULATION

Average Reading = Peak Reading (dBuV/m) + 20log (Duty Cycle), Where Duty Cycle is (# of long pulses \* long pulse width) + (# of short pulses \* short pulse width) / 100 or T


### RESULTS

One Period (ms)	Long Pulse Width (ms)	# of Long Pulses	Long Pulse Width (ms)	# of Long Pulses	Short Width (ms)	# of Short Pulses	Duty Cycle	20*Log Duty Cycle (dB)
119.3	1.233	1	0.567	1	0.14	57	0.098	-20.19


**ONE PERIOD**



**LONG PULSE WIDTH**




**NUMBER OF LONG PULSES**






**SHORT PULSE WIDTH**



**NUMBER OF SHORT PULSES**



### 7.3. TRANSMISSION TIME

#### LIMITS

FCC §15.231 (a) (2)


IC A1.1.1 (b)

A transmitter activated automatically shall cease transmission within 5 seconds after activation.

#### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer or radiated field strength. The RBW is set to 100 kHz and the VBW is set to 100 kHz. The sweep time is set to 10 seconds and the span is set to 0 Hz.

#### RESULTS



### 7.4. RADIATED EMISSION TEST RESULTS

#### FUNDAMENTAL, HARMONICS AND TX SPURIOUS EMISSION (30 – 1000 MHz)



FCC, VCCI, CISPR, CE, AUSTEL, NZ  
 UL, CSA, TUV, BSMI, DHHS, NVLAP

47173 BENICIA STREET, FREMONT, CA 94538  
 PHONE: (510) 771-1000 FAX: (501) 661-0888

*Project #:* 09U12445  
*Report #:* 09U12445B Chamber  
*Date & Time:* 3/13/2009  
*Test Engr:* MENGISTU MEKURIA

*Company:* SECURE WIRELESS  
*EUT Description:* 1047-01 SECURITY TRANSMITTER  
*Test Configuration:* EUT only  
*Type of Test:* FCC 15.231  
*Mode of Operation:* Transmitting

M% = ((t1+t2+t3+...)/T) = 9.8%

Av Reading = Pk Reading + 20*log(M%)	
20 * log (M%) = -20.18 (Max=-20dB)	

Freq. (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Clos (dB)	Pre-amp (dB)	Pk Level (dBuV/m)	Av Level (dBuV/m)	Pk Limit FCC_B	Av Limit FCC_B	Pk Margin (dB)	Avg Margin (dB)	Pol (H/V)
319.508MHz Fundamental frequency												
EUT At X Position												
319.50	67.52	47.52	16.37	2.91	0.00	86.81	66.81	95.89	75.89	-9.08	-9.08	3mV
319.50	73.15	53.15	16.37	2.91	0.00	92.44	72.44	95.89	75.89	-3.45	-3.45	3mH
EUT At Y Position												
319.50	68.68	48.68	16.37	2.91	0.00	87.97	67.97	95.89	75.89	-7.92	-7.92	3mH
319.50	73.55	53.55	16.37	2.91	0.00	92.84	72.84	95.89	75.89	-3.05	-3.05	3mV
EUT At Z Position.												
319.50	67.07	47.07	16.37	2.91	0.00	86.35	66.35	95.89	75.89	-9.54	-9.54	3mV
319.50	71.62	51.62	16.37	2.91	0.00	90.91	70.91	95.89	75.89	-4.98	-4.98	3mH
Y-Position is the worst case												
639.00	52.44	32.44	22.28	4.40	27.81	51.31	31.31	75.89	55.89	-24.58	-24.58	3mV
639.00	61.03	41.03	22.28	4.40	27.81	59.90	39.90	75.89	55.89	-15.99	-15.99	3mH
957.00	59.59	39.59	22.28	4.40	27.81	58.46	38.46	75.89	55.89	-17.43	-17.43	3mV
957.00	57.49	37.49	22.28	4.40	27.81	56.36	36.36	75.89	55.89	-19.53	-19.53	3mH

**Note:** No other emissions were detected above system noise floor from 30 MHz to 1000 MHz.

**HARMONICS AND TX SPURIOUS EMISSIONS ABOVE 1GHz**

**High Frequency Measurement**  
 Compliance Certification Services, Fremont 5m Chamber

Company: SECURE WIRELESS  
 Project #: 09U12445  
 Date: 3/13/2003  
 Test Engineer: MENGISTU MEKURIA  
 Configuration: EUT AND AC ADAPTER  
 Mode: TX MODE

Test Equipment:

Horn 1-18GHz	Pre-amplifer 1-26GHz	Pre-amplifer 26-40GHz	Horn > 18GHz	Limit
T59; S/N: 3245 @3m	T145 Agilent 3008A0056			FCC 15.209

Hi Frequency Cables

3' cable 22807700	12' cable 22807600	20' cable 22807500	HPF	Reject Filter	Peak Measurements REW=VBW=1MHz Average Measurements Duty Cycle = -20dB
3' cable 22807700	12' cable 22807600	20' cable 22807500			

f	Dist	Read Pk	Read Avg.	AF	CL	Amp	D Corr	Filtr	Peak	Avg	Pk Lim	Avg Lim	Pk Mar	Avg Mar	Notes
GHz	(m)	dBuV	dBuV	dB/m	dB	dB	dB	dB	dBuV/m	dBuV/m	dBuV/m	dBuV/m	dB	dB	(V/H)
1.278	3.0	64.7	44.7	25.0	2.7	-35.9	0.0	0.0	56.4	36.4	74	54	-17.6	-17.6	V
1.598	3.0	63.2	43.2	26.1	3.0	-35.7	0.0	0.0	56.7	36.7	74	54	-17.3	-17.3	V
1.917	3.0	53.9	33.9	27.3	3.4	-35.5	0.0	0.0	49.1	29.1	74	54	-24.9	-24.9	V
2.237	3.0	57.9	37.9	28.0	3.7	-35.2	0.0	0.0	54.4	34.4	74	54	-19.6	-19.6	V
2.556	3.0	49.1	29.1	28.7	4.0	-35.1	0.0	0.0	46.7	26.7	74	54	-27.3	-27.3	V
2.876	3.0	49.4	29.4	29.7	4.2	-35.2	0.0	0.0	48.1	28.1	74	54	-25.9	-25.9	V
3.195	3.0	48.7	28.7	30.4	4.5	-35.1	0.0	0.0	48.6	28.6	74	54	-25.4	-25.4	V
3.515	3.0	48.8	28.8	31.1	4.8	-35.0	0.0	0.0	49.7	29.7	74	54	-24.3	-24.3	V
3.834	3.0	49.5	29.5	31.8	5.0	-34.8	0.0	0.0	51.5	31.5	74	54	-22.5	-22.5	V
1.278	3.0	64.4	44.4	25.0	2.7	-35.9	0.0	0.0	56.1	36.1	74	54	-17.9	-17.9	H
1.598	3.0	70.7	50.7	26.1	3.0	-35.7	0.0	0.0	64.2	44.2	74	54	-9.8	-9.8	H
1.917	3.0	59.6	39.6	27.3	3.4	-35.5	0.0	0.0	54.9	34.9	74	54	-19.1	-19.1	H
2.237	3.0	59.6	39.6	28.0	3.7	-35.2	0.0	0.0	56.1	36.1	74	54	-17.9	-17.9	H
2.556	3.0	52.4	32.4	28.7	4.0	-35.1	0.0	0.0	49.9	29.9	74	54	-24.1	-24.1	H
2.876	3.0	46.8	26.8	29.7	4.2	-35.2	0.0	0.0	45.4	25.4	74	54	-28.6	-28.6	H
3.195	3.0	47.5	27.5	30.4	4.5	-35.1	0.0	0.0	47.3	27.3	74	54	-26.7	-26.7	H
3.515	3.0	47.7	27.7	31.1	4.8	-35.0	0.0	0.0	48.6	28.6	74	54	-25.4	-25.4	H
3.834	3.0	48.8	28.8	31.8	5.0	-34.8	0.0	0.0	50.7	30.7	74	54	-23.3	-23.3	H

Rev. 11.10.08

f	Measurement Frequency	Amp	Preamp Gain	Avg Lim	Average Field Strength Limit
Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Pk Lim	Peak Field Strength Limit
Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Avg Mar	Margin vs. Average Limit
AF	Antenna Factor	Peak	Calculated Peak Field Strength	Pk Mar	Margin vs. Peak Limit
CL	Cable Loss	HPF	High Pass Filter		

## 7.5. RX RADIATED SPURIOUS EMISSION

### LIMITS

IC RSS-Gen Issue 2, section 7.2.3.2

All spurious emissions shall comply with the limits shown below:

Limits for radiated disturbance of Class B ITE at measuring distance of 3 m	
Frequency range (MHz)	Quasi-peak limits (dB $\mu$ V/m)
30 to 88	40
88 to 216	43.5
216 to 960	46
Above 960 MHz	54

Note: The lower limit shall apply at the transition frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to receive in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 5th harmonic is investigated with the transmitter set to the middle channel.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

### RESULTS


Not applicable, this EUT is transmitter only.

## 8. SETUP PHOTOS

### ANTENNA PORT



**RADIATED EMISSION FOR PORTABLE CONFIGURATION – X ORIENTATION**






**RADIATED EMISSION FOR PORTABLE CONFIGURATION – Y ORIENTATION**



**RADIATED EMISSION FOR PORTABLE CONFIGURATION – Z ORIENTATION**



**END OF REPORT**