



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03  
Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No. :** CQASZ20180700089E-02

**Applicant:** FUZHOU EMAX ELECTRONIC CO., LTD

**Address of Applicant:** Building #12-#16, CangShan Industrial Area, JuYuanZhou JinShan District, FuZhou, China.

**Manufacturer:** FUZHOU EMAX ELECTRONIC CO., LTD

**Address of Manufacturer:** Building #12-#16, CangShan Industrial Area, JuYuanZhou JinShan District, FuZhou, China.

**Equipment Under Test (EUT):**

**Product:** Smart Cooking Thermometer

**Model No.:** EM2255, SM55

**Test Model No.:** EM2255

**Brand Name:** N/A

**FCC ID:** WEC-EM2255

**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06

**Date of Test:** 2018-07-30 to 2018-08-02

**Date of Issue:** 2018-08-02

**Test Result :** PASS\*

**Tested By:**

*Martin Lee*

(Martin Lee)

**Reviewed By:**

*Jack Ai*

(Jack Ai)

**Approved By:**

*Jack Ai*

( Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20180700089E-02	Rev.01	Initial report	2018-08-02

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 SAR EVALUATION .....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	5
4.1.1 <i>Standard Requirement</i> .....	5
4.1.2 <i>Limits</i> .....	5
4.1.3 <i>EUT RF Exposure</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	FUZHOU EMAX ELECTRONIC CO., LTD
Address of Applicant:	Building #12-#16, CangShan Industrial Area, JuYuanZhou JinShan District, FuZhou, China.
Manufacturer:	FUZHOU EMAX ELECTRONIC CO., LTD
Address of Manufacturer:	Building #12-#16, CangShan Industrial Area, JuYuanZhou JinShan District, FuZhou, China.

#### 3.2 General Description of EUT

Product Name:	Smart Cooking Thermometer
Model No.:	EM2255, SM55
Test Model No.:	EM2255
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0
Modulation Type:	GFSK
Number of Channel:	40
Sample Type:	Portable production
Test Software of EUT:	CC2541_BLE-Device Control Panel (manufacturer declare )
Antenna Type:	Integral antenna
Antenna Gain:	2.0dBi
EUT Power Supply:	2*AA DC3V

Note:

All model: EM2255, SM55

Only the model EM2255 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 4.1.3 EUT RF Exposure

For BLE:

#### Measurement Data

GFSK mode	
Test channel	Peak Output Power (dBm)
Lowest	-8.44
Middle	-8.07
Highest	-7.53

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-8.44	-8.0±1	-7.0	0.200	0.06	3.0
Middle (2440MHz)	-8.07	-8.0±1	-7.0	0.200	0.06	
Highest (2480MHz)	-7.53	-8.0±1	-7.0	0.200	0.06	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20180700089E-01