




# RF EXPOSURE REPORT



Report No.: 18070771-FCC-H

Applicant	DASAN ELECTRON	
Product Name	Wireless Headset(Base)	
Model No.	DW-800B	
Serial No.	DW-800, X500, X500B	
Test Standard	FCC 2.1091	
Test Date	July 10 to September 05, 2018	
Issue Date	November 20, 2018	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Aaron Liang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	18070771-FCC-H
Page	3 of 9

This page has been left blank intentionally.

# CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....	8
6.1 APPLICABLE STANDARD.....	8
6.2 TEST RESULT .....	9

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
18070771-FCC-H	NONE	Original	September 05, 2018
18070771-FCC-H	V1	Updated the applicant name	November 13, 2018
18070771-FCC-H	V2	Updated the product name	November 20, 2018

## 2. Customer information

Applicant Name	DASAN ELECTRON CO., LTD.
Applicant Add	606, GODOWHADONG, KYUNGGI TECHONO PARK,1271-11, SA-DONG, ANSAN-SI, KYUNGGI-DO
Manufacturer	DASAN ELECTRON CO., LTD.
Manufacturer Add	606, GODOWHADONG, KYUNGGI TECHONO PARK,1271-11, SA-DONG, ANSAN-SI, KYUNGGI-DO

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Lab view of SIEMIC version 2.0

## 4. Equipment under Test (EUT) Information

Description of EUT:	Wireless Headset(Base)
Main Model:	DW-800B
Serial Model:	DW-800, X500, X500B
Date EUT received:	July 09, 2018
Test Date(s):	July 10 to August 26, 2018
Antenna Gain:	FP: -1.42dBi
Antenna Type:	DECT: Monopole antenna
Type of Modulation:	DECT:GFSK
Number of Channels:	DECT: 5CH
Input Power:	<p><b>Adapter:</b> Model: SK01G-0900050U INPUT: AC 100-240V, 50/60Hz,0.2A Max OUTPUT: 9V, 0.5A</p> <p><b>Battery:</b> Spec: LiPo 300mA</p>
Trade Name :	Freemate
RF Operating Frequency (ies):	DECT:1921.536 MHz~1928.448 MHz (Tx/Rx)
Port:	Please see the user' s manual
FCC ID:	WF2DW-800B



Test Report	18070771-FCC-H
Page	7 of 9

---

Hardware Version: Rev0.3

Software Version: Ver1.0

## 5. FCC §2.1091 - Maximum Permissible exposure (MPE)

### 6.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission' s guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density



## 6.2 Test Result

### FP:

Type	Frequency (MHz)	Duty Cycle	Conducted power (dBm)	Frame power (dBm)	Turn Up Power(dBm)	Antenna Gain (dBi)	E-field Strength (V/m) @ 20 cm	E-field Strength Limit (V/m)	Result
Power	1921.536	8.33%	14.15	3.356	3±1	-1.42	0.001	1	Pass
	1924.992	8.33%	13.94	3.146	3±1	-1.42	0.001	1	Pass
	1928.448	8.33%	13.78	2.986	3±1	-1.42	0.001	1	Pass

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For the antenna manufacturer provide only used limited to ERP/EIRP or radiated spurious emission test. The MPE evaluation as below:

Maximum output power at antenna input terminal: 4 (dBm)

Maximum output power at antenna input terminal: 2.511(mW)

Prediction distance: >20 (cm)

Predication frequency: 1921.536 (MHz) Low frequency

Antenna Gain (typical): -1.42(dBi)

Antenna Gain (typical): 0.721 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.0004(mW/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm<sup>2</sup>)

0.0004(mW/cm<sup>2</sup>) < 1 (mW/cm<sup>2</sup>)

**Result: Pass**